

JavaScript HTML DOM CSS

[Back to JS page](#)

Table of Contents

- [JavaScript HTML DOM CSS](#)
 - [Changing HTML Style](#)
 - [Example 1](#)
 - [Using Events](#)
 - [Example 2](#)
 - [More Examples](#)
 - [Example 3](#)
 - [Document](#)
 - [Reference](#)

Changing HTML Style

To change the style of an HTML element, use this syntax:

```
document.getElementById(id).style.property = new style
```

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript HTML DOM CSS</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Changing HTML Style</h4>
<p id="demo">This text will change color!</p>

<script>
document.getElementById("demo").style.color = "red";
</script>

</body>
</html>
```

Example 1

Result [View Example](#)

Using Events

The HTML DOM allows you to execute code when an event occurs. Events are generated by the browser when "things happen" to HTML elements.

You can change the style of an element when a user clicks a button:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript HTML DOM CSS</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Using Events</h4>
<p id="demo">Click the button to change style!</p>
<button type="button" onclick="document.getElementById('demo').style.fontSize='35px'">Click Me!<

</body>
</html>
```

Example 2

Result [View Example](#)

More Examples

You can change multiple style properties and make elements appear/disappear:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript HTML DOM CSS</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>More Examples</h4>
<p id="demo" style="display:block">This paragraph will disappear</p>

<button type="button" onclick="document.getElementById('demo').style.display='none'">Hide text</
<button type="button" onclick="document.getElementById('demo').style.display='block'">Show text<

</body>
</html>
```

Example 3

Result [View Example](#)

Document

Document in project

You can [Download PDF](#) file.

Reference

- [W3Schools JavaScript HTML DOM CSS](#)