

JavaScript Mouse Events

[Back to JS page](#)

Table of Contents

- [JavaScript Mouse Events](#)
 - [Mouseover and Mouseout](#)
 - [Example 1](#)
 - [Common Mouse Events](#)
 - [Mouse Position](#)
 - [Example 2](#)
 - [Document](#)
 - [Reference](#)

Mouseover and Mouseout

The `onmouseover` and `onmouseout` events can be used to trigger a function when the user hovers over or leaves an HTML element.

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Mouse Events</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Mouseover and Mouseout</h4>
<div onmouseover="mOver(this)" onmouseout="mOut(this)"
style="background-color:#D94A38;width:200px;height:50px;padding:40px;color:white;text-align:cent
Mouse Over Me
</div>

<script>
function mOver(obj) {
  obj.innerHTML = "Thank You"
}
function mOut(obj) {
  obj.innerHTML = "Mouse Over Me"
}
</script>

</body>
</html>
```

Example 1

Result [View Example](#)

Common Mouse Events

Here is a list of common mouse events:

Event	Description
<code>onclick</code>	The user clicks an element
<code>ondblclick</code>	The user double-clicks an element
<code>onmousedown</code>	A mouse button is pressed over an element
<code>onmouseup</code>	A mouse button is released over an element
<code>onmouseover</code>	The mouse pointer moves onto an element
<code>onmouseout</code>	The mouse pointer moves out of an element
<code>onmousemove</code>	The mouse pointer moves over an element
<code>onmouseenter</code>	Similar to <code>mouseover</code> but does not bubble

Mouse Position

You can get the mouse cursor position using `clientX` and `clientY` properties from the event object:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Mouse Events</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Mouse Position</h4>
<div onmousemove="getPosition(event)"
style="background-color:#D94A38;width:300px;height:150px;padding:20px;color:white;text-align:cen
Move mouse over this box
</div>
<p id="demo"></p>

<script>
function getPosition(event) {
  let x = event.clientX;
  let y = event.clientY;
  document.getElementById("demo").innerHTML = "Mouse position: X=" + x + ", Y=" + y;
}
</script>

</body>
</html>
```

Example 2

Result [View Example](#)

Document

Document in project

You can [Download PDF](#) file.

Reference

- [W3Schools JavaScript Mouse Events](#)