

# JavaScript HTML DOM Events

---

[Back to JS page](#)

## Table of Contents

- [JavaScript HTML DOM Events](#)
  - [Reacting to Events](#)
    - [Example 1](#)
  - [HTML Event Attributes](#)
    - [Example 2](#)
  - [Assign Events Using the HTML DOM](#)
    - [Example 3](#)
  - [The onload Event](#)
    - [Example 4](#)
  - [The oninput Event](#)
    - [Example 5](#)
  - [The onchange Event](#)
    - [Example 6](#)
  - [Document](#)
  - [Reference](#)

## Reacting to Events

---

A JavaScript can be executed when an event occurs, like when a user clicks on an HTML element.

To execute code when a user clicks on an element, add JavaScript code to an HTML event attribute:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript HTML DOM Events</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Reacting to Events</h4>
<button onclick="document.getElementById('demo').innerHTML=Date()">The time is?</button>
<p id="demo"></p>

</body>
</html>
```

## Example 1

---

Result [View Example](#)

## HTML Event Attributes

---

To assign events to HTML elements you can use event attributes like `onclick` , `onmouseover` , etc.

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript HTML DOM Events</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>HTML Event Attributes</h4>
<p>Click the button to display a message.</p>
<button onclick="displayDate()">Click me</button>
<p id="demo"></p>

<script>
function displayDate() {
    document.getElementById("demo").innerHTML = Date();
}
</script>

</body>
</html>
```

## Example 2

---

Result [View Example](#)

## Assign Events Using the HTML DOM

---

The HTML DOM allows you to assign events to HTML elements using JavaScript:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript HTML DOM Events</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Assign Events Using the HTML DOM</h4>
<button id="myBtn">Click me</button>
<p id="demo"></p>

<script>
document.getElementById("myBtn").onclick = function() {
    document.getElementById("demo").innerHTML = "Button clicked!";
};
</script>

</body>
</html>
```

## Example 3

---

Result [View Example](#)

## The onload Event

---

The `onload` event is often used to check the visitor's browser type and cookie version.

The `onload` event can be used to deal with cookies:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript HTML DOM Events</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>The onload Event</h4>
<p id="demo"></p>

<script>
window.onload = function() {
    document.getElementById("demo").innerHTML = "Page fully loaded!";
};
</script>

</body>
</html>
```

## Example 4

---

**Result** [View Example](#)

## The oninput Event

---

The `oninput` event fires when a user writes something in an input field:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript HTML DOM Events</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>The oninput Event</h4>
<p>Write something in the input field:</p>
<input type="text" id="myInput" oninput="myFunction()">
<p id="demo"></p>

<script>
function myFunction() {
  let x = document.getElementById("myInput").value;
  document.getElementById("demo").innerHTML = "You wrote: " + x;
}
</script>

</body>
</html>
```

## Example 5

---

**Result** [View Example](#)

## The onchange Event

---

The `onchange` event fires when a user changes the value of an input element:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript HTML DOM Events</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>The onchange Event</h4>
<p>Select a car:</p>
<select id="mySelect" onchange="myFunction()">
  <option value="Volvo">Volvo</option>
  <option value="BMW">BMW</option>
  <option value="Audi">Audi</option>
</select>
<p id="demo"></p>

<script>
function myFunction() {
  let x = document.getElementById("mySelect").value;
  document.getElementById("demo").innerHTML = "You selected: " + x;
}
</script>

</body>
</html>
```

## Example 6

---

Result [View Example](#)

## Document

---

Document in project

You can [Download PDF](#) file.

## Reference

---

- [W3Schools JavaScript HTML DOM Events](#)