

# JavaScript JSON Server

---

[Back to JS page](#)

## Table of Contents

- [JavaScript JSON Server](#)
  - [Loading JSON from a Server](#)
    - [Example 1](#)
  - [Loading a JSON Array](#)
    - [Example 2](#)
  - [Handling Errors](#)
    - [Example 3](#)
  - [Sending JSON](#)
    - [Example 4](#)
  - [Document](#)
  - [Reference](#)

## The fetch() Method

---

The `fetch()` method is used to send and receive data from a server.

It returns a Promise that resolves to a Response object.

The `response.json()` method parses the response body as JSON.

## Loading JSON from a Server

---

Use `fetch()` to load a JSON file from a server, then use `response.json()` to parse it:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript JSON Server</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Loading JSON from a Server</h4>
<p id="demo"></p>

<script>
fetch('https://jsonplaceholder.typicode.com/users/1')
  .then(response => response.json())
  .then(data => {
    document.getElementById("demo").innerHTML =
      "Name: " + data.name + "<br>" +
      "Email: " + data.email + "<br>" +
      "City: " + data.address.city;
  })
  .catch(error => {
    document.getElementById("demo").innerHTML = "Error: " + error.message;
  });
</script>

</body>
</html>
```

## Example 1

---

Result [View Example](#)

## Loading a JSON Array

---

You can also load a JSON array from a server:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript JSON Server</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Loading a JSON Array</h4>
<p id="demo"></p>

<script>
fetch('https://jsonplaceholder.typicode.com/users')
  .then(response => response.json())
  .then(data => {
    let text = "<ul>";
    for (let user of data) {
      text += "<li>" + user.name + " - " + user.email + "</li>";
    }
    text += "</ul>";
    document.getElementById("demo").innerHTML = text;
  })
  .catch(error => {
    document.getElementById("demo").innerHTML = "Error: " + error.message;
  });
</script>

</body>
</html>
```

## Example 2

---

Result [View Example](#)

## Handling Errors

---

Always handle errors when loading JSON from a server. Check the response status:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript JSON Server</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Handling Errors</h4>
<p id="demo"></p>

<script>
fetch('https://jsonplaceholder.typicode.com/users/nonexistent')
  .then(response => {
    if (!response.ok) {
      throw new Error("HTTP error! Status: " + response.status);
    }
    return response.json();
  })
  .then(data => {
    document.getElementById("demo").innerHTML = "Name: " + data.name;
  })
  .catch(error => {
    document.getElementById("demo").innerHTML = "Error: " + error.message;
  });
</script>

</body>
</html>
```

## Example 3

---

Result [View Example](#)

## Sending JSON

---

You can use `fetch()` with the `POST` method to send JSON data to a server:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript JSON Server</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Sending JSON</h4>
<p id="demo"></p>

<script>
const userData = {
  name: "John Doe",
  email: "john@example.com",
  username: "johndoe"
};

fetch('https://jsonplaceholder.typicode.com/users', {
  method: 'POST',
  headers: {
    'Content-Type': 'application/json'
  },
  body: JSON.stringify(userData)
})
  .then(response => response.json())
  .then(data => {
    document.getElementById("demo").innerHTML =
      "User created!<br>" +
      "ID: " + data.id + "<br>" +
      "Name: " + data.name + "<br>" +
      "Email: " + data.email;
  })
  .catch(error => {
    document.getElementById("demo").innerHTML = "Error: " + error.message;
  });
</script>

</body>
</html>
```

## Example 4

---

Result [View Example](#)

## Document

---

Document in project

You can [Download PDF](#) file.

## Reference

---

- [W3Schools JavaScript JSON Server](#)