

JavaScript HTMLCollection

[Back to JS page](#)

Table of Contents

- [JavaScript HTMLCollection](#)
 - [The HTMLCollection Object](#)
 - [Example 1](#)
 - [HTMLCollection Length](#)
 - [Example 2](#)
 - [Looping Through an HTMLCollection](#)
 - [Example 3](#)
 - [Document](#)
 - [Reference](#)

The HTMLCollection Object

An `HTMLCollection` is an array-like list of HTML elements.

Methods like `getElementsByName()` return an `HTMLCollection`.

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript HTMLCollection</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>The HTMLCollection Object</h4>

<p>First paragraph</p>
<p>Second paragraph</p>
<p>Third paragraph</p>

<p id="demo"></p>

<script>
const myCollection = document.getElementsByTagName("p");

document.getElementById("demo").innerHTML =
  "Number of <p> elements: " + myCollection.length + "<br>" +
  "First paragraph text: " + myCollection[0].innerHTML + "<br>" +
  "Second paragraph text: " + myCollection[1].innerHTML;
</script>

</body>
</html>
```

Example 1

Result [View Example](#)

HTMLCollection Length

The `length` property defines the number of elements in the HTMLCollection. You can use it to loop through the collection:

```

<!DOCTYPE html>
<html>
<body>

<h2>JavaScript HTMLCollection</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>HTMLCollection Length</h4>

<div id="list">
  <p>Apple</p>
  <p>Banana</p>
  <p>Orange</p>
  <p>Grape</p>
  <p>Mango</p>
</div>

<p id="demo"></p>

<script>
const collection = document.getElementById("list").getElementsByTagName("p");
let text = "Items (" + collection.length + "):<br>";
for (let i = 0; i < collection.length; i++) {
  text += (i + 1) + ". " + collection[i].innerHTML + "<br>";
}
document.getElementById("demo").innerHTML = text;
</script>

</body>
</html>

```

Example 2

Result [View Example](#)

Looping Through an HTMLCollection

You cannot use `forEach()` on an HTMLCollection directly. You must convert it to an array first, or use a `for` loop:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript HTMLCollection</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Looping Through an HTMLCollection</h4>

<div id="colors">
  <p class="item">Red</p>
  <p class="item">Green</p>
  <p class="item">Blue</p>
  <p class="item">Yellow</p>
</div>

<button onclick="changeColors()">Change Colors</button>
<p id="demo"></p>

<script>
function changeColors() {
  const items = document.getElementById("colors").getElementsByClassName("item");

  // Convert HTMLCollection to Array for using forEach
  const arr = Array.from(items);
  arr.forEach(function(item, index) {
    item.innerHTML += " (" + (index + 1) + ")";
  });

  document.getElementById("demo").innerHTML =
    "Modified " + items.length + " items using Array.from() + forEach()";
}
</script>

</body>
</html>
```

Example 3

Result [View Example](#)

Document

Document in project

You can [Download PDF](#) file.

Reference

- [W3Schools JavaScript HTMLCollection](#)