

JavaScript Window Location

[Back to JS page](#)

Table of Contents

- [JavaScript Window Location](#)
 - [Window Location Href](#)
 - [Example 1](#)
 - [Window Location Hostname](#)
 - [Example 2](#)
 - [Window Location Pathname](#)
 - [Example 3](#)
 - [Window Location Protocol](#)
 - [Example 4](#)
 - [Window Location Assign](#)
 - [Example 5](#)
 - [Document](#)
 - [Reference](#)

Window Location Href

The `window.location.href` property returns the URL of the current page:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Window Location</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Window Location Href</h4>
<p id="demo"></p>

<script>
document.getElementById("demo").innerHTML =
  "Page URL (href): " + window.location.href;
</script>

</body>
</html>
```

Example 1

Result [View Example](#)

Window Location Hostname

The `window.location.hostname` property returns the domain name of the web host:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Window Location</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Window Location Hostname</h4>
<p id="demo"></p>

<script>
document.getElementById("demo").innerHTML =
    "Page hostname: " + window.location.hostname;
</script>

</body>
</html>
```

Example 2

Result [View Example](#)

Window Location Pathname

The `window.location.pathname` property returns the pathname of the current page:

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Window Location</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Window Location Pathname</h4>
<p id="demo"></p>

<script>
document.getElementById("demo").innerHTML =
  "Page pathname: " + window.location.pathname;
</script>

</body>
</html>
```

Example 3

Result [View Example](#)

Window Location Protocol

The `window.location.protocol` property returns the web protocol of the page (http: or https:):

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Window Location</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Window Location Protocol</h4>
<p id="demo"></p>

<script>
document.getElementById("demo").innerHTML =
    "Page protocol: " + window.location.protocol;
</script>

</body>
</html>
```

Example 4

Result [View Example](#)

Window Location Assign

The `window.location.assign()` method loads a new document (navigates to a new URL):

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Window Location</h2>
<p>From w3schools.com, Experiment by Teeratus_R</p>

<h4>Window Location Assign</h4>
<p id="demo"></p>

<button onclick="showAllProperties()">Show All Location Properties</button>
<p id="demo2"></p>

<script>
function showAllProperties() {
  const loc = window.location;
  document.getElementById("demo2").innerHTML =
    "href: " + loc.href + "<br>" +
    "hostname: " + loc.hostname + "<br>" +
    "pathname: " + loc.pathname + "<br>" +
    "protocol: " + loc.protocol + "<br>" +
    "port: " + loc.port + "<br>" +
    "host: " + loc.host + "<br>" +
    "origin: " + loc.origin;
}
</script>

</body>
</html>
```

Example 5

Result [View Example](#)

Document

Document in project

You can [Download PDF](#) file.

Reference

- [W3Schools JavaScript Window Location](#)