

Gaussian Code Exercise

Read through the code below and fill out the TODOs. You'll find a cell at the end of the Jupyter notebook containing unit tests. After you've run the code cell with the Gaussian class, you can run the final cell to check that your code functions as expected.

This exercise includes a file called 'numbers.txt', which you can see if you click on the 'Jupyter' icon at the top of the workspace and then go into the folder titled 3.OOP_code_gaussian_class. The 'numbers.txt' file is read in by the `read_data_file()` method. There is also a solution in the 3.OOP_code_gaussian_class folder in a file called `answer.py`.

```
In [14]: import math
import matplotlib.pyplot as plt

class Gaussian():
    """ Gaussian distribution class for calculating and
    visualizing a Gaussian distribution.

    Attributes:
        mean (float) representing the mean value of the distribution
        stdev (float) representing the standard deviation of the distribution
        data_list (list of floats) a list of floats extracted from the data file

    """
    def __init__(self, mu = 0, sigma = 1):

        self.mean = mu
        self.stdev = sigma
        self.data = []

    def calculate_mean(self):

        """Method to calculate the mean of the data set.

        Args:
            None

        Returns:
            float: mean of the data set

        """

        #TODO: Calculate the mean of the data set. Remember that the data set is
        # Change the value of the mean attribute to be the mean of the data set
        # Return the mean of the data set
        average = sum(self.data) / len(self.data)
        self.mean = average
        return self.mean

    def calculate_stdev(self, sample=True):

        """Method to calculate the standard deviation of the data set.

        Args:
            sample (bool): whether the data represents a sample or population

        Returns:
            float: standard deviation of the data set

        """

        # TODO:
        # Calculate the standard deviation of the data set
```

```

#
#   The sample variable determines if the data set contains a sample or a population.
#   If sample = True, this means the data is a sample.
#   Keep the value of sample in mind for calculating the standard deviation.
#
#   Make sure to update self.stdev and return the standard deviation as well.

    if sample:
        n = len(self.data) - 1
    else:
        n = len(self.data)

    mean = self.mean
    sigma = 0

    for value in self.data:
        sigma += ((value - mean) ** 2)

    sigma = math.sqrt(sigma / n)
    self.stdev = sigma
    return self.stdev

def read_data_file(self, file_name, sample=True):
    """Method to read in data from a txt file. The txt file should have
    one number (float) per line. The numbers are stored in the data attribute.
    After reading in the file, the mean and standard deviation are calculated.

    Args:
        file_name (string): name of a file to read from

    Returns:
        None

    """

    # This code opens a data file and appends the data to a list called data_list
    with open(file_name) as file:
        data_list = []
        line = file.readline()
        while line:
            data_list.append(int(line))
            line = file.readline()
    file.close()

    # TODO:
    #   Update the self.data attribute with the data_list
    #   Update self.mean with the mean of the data_list.
    #   You can use the calculate_mean() method with self.calculate_mean()
    #   Update self.stdev with the standard deviation of the data_list. Use the
    #   calculate_stdev() method.
    self.data = data_list
    self.mean = self.calculate_mean()
    self.stdev = self.calculate_stdev(sample)

```

```

def plot_histogram(self):
    """Method to output a histogram of the instance variable data using
    matplotlib pyplot library.

    Args:
        None

    Returns:
        None
    """

    # TODO: Plot a histogram of the data_list using the matplotlib package.
    #       Be sure to label the x and y axes and also give the chart a title
    plt.hist(self.data)
    plt.title('Histogram of Data')
    plt.xlabel("data")
    plt.ylabel("count")


def pdf(self, x):
    """Probability density function calculator for the gaussian distribution

    Args:
        x (float): point for calculating the probability density function

    Returns:
        float: probability density function output
    """

    # TODO: Calculate the probability density function of the Gaussian distribution
    #       at the value x. You'll need to use self.stdev and self.mean to do this
    return (1.0 / (self.stdev * math.sqrt(2 * math.pi))) * math.exp(-0.5 * ((x - self.mean) / self.stdev)**2)


def plot_histogram_pdf(self, n_spaces = 50):

    """Method to plot the normalized histogram of the data and a plot of the
    probability density function along the same range

    Args:
        n_spaces (int): number of data points

    Returns:
        list: x values for the pdf plot
        list: y values for the pdf plot
    """

    #TODO: Nothing to do for this method. Try it out and see how it works.

    mu = self.mean
    sigma = self.stdev

    min_range = min(self.data)
    max_range = max(self.data)

```

```
# calculates the interval between x values
interval = 1.0 * (max_range - min_range) / n_spaces

x = []
y = []

# calculate the x values to visualize
for i in range(n_spaces):
    tmp = min_range + interval*i
    x.append(tmp)
    y.append(self.pdf(tmp))

# make the plots
fig, axes = plt.subplots(2, sharex=True)
fig.subplots_adjust(hspace=.5)
axes[0].hist(self.data, density=True)
axes[0].set_title('Normed Histogram of Data')
axes[0].set_ylabel('Density')

axes[1].plot(x, y)
axes[1].set_title('Normal Distribution for \n Sample Mean and Sample Std')
axes[0].set_ylabel('Density')
plt.show()

return x, y
```

```
In [15]: # Unit tests to check your solution

import unittest

class TestGaussianClass(unittest.TestCase):
    def setUp(self):
        self.gaussian = Gaussian(25, 2)

    def test_initialization(self):
        self.assertEqual(self.gaussian.mean, 25, 'incorrect mean')
        self.assertEqual(self.gaussian.stdev, 2, 'incorrect standard deviation')

    def test_pdf(self):
        self.assertEqual(round(self.gaussian.pdf(25), 5), 0.19947, \
            'pdf function does not give expected result')

    def test_meancalculation(self):
        self.gaussian.read_data_file('numbers.txt', True)
        self.assertEqual(self.gaussian.calculate_mean(), \
            sum(self.gaussian.data) / float(len(self.gaussian.data)), 'calculated me

    def test_stdevcalculation(self):
        self.gaussian.read_data_file('numbers.txt', True)
        self.assertEqual(round(self.gaussian.stdev, 2), 92.87, 'sample standard d
        self.gaussian.read_data_file('numbers.txt', False)
        self.assertEqual(round(self.gaussian.stdev, 2), 88.55, 'population standa

tests = TestGaussianClass()

tests_loaded = unittest.TestLoader().loadTestsFromModule(tests)

unittest.TextTestRunner().run(tests_loaded)
```

```
....
```

```
-----
Ran 4 tests in 0.010s
```

```
OK
```

```
Out[15]: <unittest.runner.TextTestResult run=4 errors=0 failures=0>
```

```
In [ ]:
```