

Fulllife XP 20W-50

Optimum Lubrication in Urban Traffic

PRODUCT DESCRIPTION

Fulllife XP 20W-50, is an engine oil which meets the lubrication needs of gasoline or diesel engines of passenger vehicles and light commercial vehicles.

APPLICATIONS

- It is suitable to use in gasoline or diesel engines of passenger vehicles and light commercial vehicles which recommended API SG/CF specification.

CHARACTERISTICS

- Its active cleaning feature controls forming of deposit and sludge, so keeps engine parts clean.
- Its maintains its lubrication even under extreme operating conditions due to its durable oil film strength.
- Its high oxidation stability maintains its protection until the next oil change.

PERFORMANCES

- API SG/CF

TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,886
Viscosity@ 40°C, mm ² /s	ASTM D 445	153,7
Viscosity@100°C, mm ² /s	ASTM D 445	17,4
Viscosity Index	ASTM D 2270	124
Flash Point, °C	ASTM D 92	246
Pour Point, °C	ASTM D 5950	-27
TBN, mgKOH/g	ASTM D 2896	6,5

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.