

### Fullmax 0W-20

## High Performance in Fuel Economy

#### PRODUCT DESCRIPTION

Fullmax 0W-20, is a synthetic engine oil which meets the performance requirements of new technology engines. It is especially suitable to use in gasoline or Ford and Renault diesel engines of passenger vehicles and light commercial vehicles. Its special formula provides effective engine cleanlines, superior engine protection and extreme fuel economy.

#### **APPLICATIONS**

- It is suitable to use in gasoline or diesel engines of passenger vehicles and light commercial vehicles.
- It is suitable to use in Ford vehicles which recommended WSS-M2C952-A1 specification.

### **CHARACTERISTICS**

- It provides excellent wear protection in new generation and high performance gasoline or diesel engines under all operating and driving conditions.
- It controls formation of deposit and sludge, so keeps the parts of engine clean and extends engine life.
- Its improved low viscosity property provides extreme fuel economy.
- Its superior thermal and oxidation stability maintains its performance during the long oil drain interval recommended by the engine manufacturers.

#### **PERFORMANCES**

- ACEA C5
- RENAULT RN17 FE

#### TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,841
Viscosity@ 40°C, mm²/s	ASTM D 445	39,4
Viscosity@100°C, mm²/s	ASTM D 445	8,1
Viscosity Index	ASTM D 2270	186
Flash Point, °C	ASTM D 92	226
Pour Point, °C	ASTM D 5950	-48
TBN, mgKOH/g	ASTM D 2896	7,6





1/2

opetfuchs.com.tr



# technical data sheet

#### **HEALTH AND SAFETY RECOMMENDATIONS**

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers spesifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.

OPET.TDS.0114/Rev.0/03.12.2019



Phone: +90 216 522 69 00 Fax : +90 216 522 69 90

teknikservisler@opetfuchs.com.tr opetfuchs.com.tr