Name: Hamza Zahoor

Enrollment: 01-135231-030

Class: BS IT(5B)

Lab Journal: Master Page

Code:

Site1.Master

```
<%@ Master Language="C#" AutoEventWireup="true" CodeBehind="Site1.master.cs" Inherits="WebApplication5.Site1" %>

<!DOCTYPE html>

<html>
<head runat="server">
    <title>Assign</title>
    <asp:ContentPlaceHolder ID="head" runat="server">
    </asp:ContentPlaceHolder>
</head>
<body>
    <form id="form1" runat="server">
        <!-- Navigation Bar -->
        <nav style="background-color: #f8f9fa; padding: 10px; font-family: Arial, sans-serif;">
            <a href="Default.aspx" style="margin-right: 15px; text-decoration: none; color: #007bff;">Home</a>
            <a href="About.aspx" style="margin-right: 15px; text-decoration: none; color: #007bff;">About</a>
```

```
            <a href="Contact.aspx" style="text-decoration: none; color:
#007bff;">Contact</a>

        </nav>


        <div style="padding:20px; font-family:'Lucida Sans', 'Lucida Sans Regular', 'Lucida
Grande', 'Lucida Sans Unicode', Geneva, Verdana, sans-serif">

            <h1>Table Calculator</h1>

            <asp:ContentPlaceHolder ID="ContentPlaceHolder1" runat="server">

            </asp:ContentPlaceHolder>

        </div>


        <!-- Footer -->

        <footer style="background-color: #f1f1f1; text-align: center; padding: 10px;
position: fixed; bottom: 0; width: 100%; font-family: Arial, sans-serif;">

            &copy; 2025 WebApplication5. All rights reserved.

        </footer>

    </form>

</body>

</html>
```

WebForm1.apsx.cs

```
using System;

using System.Collections.Generic;

using System.Linq;

using System.Reflection.Emit;

using System.Web;

using System.Web.UI;

using System.Web.UI.WebControls;
```

```csharp
namespace WebApplication5
{
    public partial class WebForm1 : System.Web.UI.Page
    {
        protected void Page_Load(object sender, EventArgs e)
        {


        }


        protected void TextBox1_TextChanged(object sender, EventArgs e)
        {
            // Your logic here (if any)
        }



        protected void Button1_Click(object sender, EventArgs e)
        {
            int a = int.Parse(TextBox1.Text);
            int b = int.Parse(TextBox2.Text);

            for (int i = 1; i <= b; i++)
            {
                var c = ($"<br>{a} x {i} = " + (a * i).ToString());
                Label1.Text += c;

            }
```

```
        }

    }
}
```