

Procedure Programming

Characters

Instructor: Jeeho Ryoo

Streams

All input and output is done with streams

Input stream

A sequence of bytes flowing into a program

Output stream

A sequence of bytes flowing out of a program

Standard Input/Output Streams

stdin stands for Standard Input

Keyboard, Scanner are standard input devices

Standard input is data going into a program

stdout stands for Standard output

Screen, printer are standard output device

Standard output is data going out from a computer

printf()

Output function

printf() prints the value given to the console

Built into the input output header file stdio.h

```
#include <stdio.h>  
int main()  
{  
    printf("Good Morning");  
    return 0;  
}
```

scanf()

Input function

Also built into the header file `stdio.h`

`scanf()` takes input from the user

Uses same format identifier `%d` as `printf()`

```
int x;  
scanf("%d", &x);
```

Note the **&** symbol, `scanf` requires a memory address (called address-of operator)

Format identifiers Console I/O

`%d` will scan or print an integer aka `int` (example: 5)

`%f` will scan or print a floating point aka `float` (example: 5.1)

`%c` will scan or print a character aka `char` (example: m)

`%s` will scan or print a char array aka `string` (example: george)

scanf() and printf() Example

```
#include <stdio.h>

int main()
{
    int x;
    printf("Enter a value...");
    scanf("%d", &x);
    printf( "\nYou entered: %d", x);
    return 0;
}
```

printf() and scanf() Strings Example

```
char s[20];  
printf("How are you doing?...");  
scanf("%s", s);  
printf( "\nYou entered: %s", s);  
return 0;
```

A string in scanf doesn't require the **&** because it's an array (discussed earlier)

Note even with strings whitespace is a delimiter by default

getchar()

Input function

Also built into the header file `stdio.h`

It reads one character

Example

```
char c;  
c = getchar();
```

fgets()

Input function

Reads up to and including a newline character (enter)

Takes in three arguments

A ***string***

Number of character to copy (***int***)

File type (in our case it's the standard input, ***stdin***)

```
fgets(str, 20, stdin);
```

fgets() Example

Write a program that prints a sentence to the console using fgets()


```
#include <stdio.h>
int main()
{
    char str[100];
    fgets(str, 100, stdin);
    printf( "\nYou entered: %s", str);
    return 0;
}
```

Input buffer

Holds the input data temporarily between the device and program

Once enter (newline) is pressed it signals the program to start executing data from the buffer

The program only retrieves the data that it needs , and leaves rest in buffer



fputs()

Output function

Simple string output

Takes two arguments

A **string**

File type (in our case it's the standard output, ***stdout***)

fputs(str, stdout); is equivalent to *printf("%s", str)*

fputs() Example

Write a program using fputs()

```
#include <stdio.h>
int main()
{
    char str[100];
    fputs("Input something\n", stdout);
    fgets(str, 100, stdin);
    fputs(str, stdout);
    return 0;
}
```

Characters in C

char is a one-byte data type capable of holding a character

Treated as an arithmetic integer type

(Usually) **unsigned**

May be used in arithmetic expressions

add, subtract, multiply, divide, etc.

Character constants

'a', 'b', 'c', ... 'z', '0', '1', ... '9', '+', '-',
, '=', '!', '~', etc, '\n', '\t', '\0', etc.

A-Z, a-z, 0-9 are *in order*, so that arithmetic can be done

Strings in C

Definition:— A *string* is a character array ending in '`\0`' — i.e.,

```
char s[256];  
char t[] = "This is an initialized  
string!";  
char *u = "This is another string!";
```

String constants are in double quotes
May contain any characters
Including `\`" and `\`'

String constants *may not* span lines
However, they may be concatenated — e.g.,
"Hello, " "World!\n" is the same as "Hello,
World!\n"

Strings in C (continued)

Let

```
char *u = "This  
is another  
string!";
```

Then

```
u[0] == 'T'  
u[1] == 'h'  
u[2] == 'i'  
...  
u[21] == 'g'  
u[22] == '!'  
u[23] == '\\0'
```

Support for Strings in C

Most string manipulation is done through functions in `<string.h>`

String functions *depend* upon final `'\0'`

So you don't have to count the characters!

Examples:–

`int strlen(char *s)` – returns length of string
Excluding final `'\0'`

`char* strcpy(char *s, char *ct)` – Copies
string `ct` to string `s`, return `s`

`s` must be big enough to hold contents of `ct`

`ct` may be smaller than `s`

Support for Strings in C (continued)

Examples (continued):—

int strcmp(char *s, char *t)

- lexically compares **s** and **t**, returns **<0** if **s < t**, **>0** if **s > t**, zero if **s** and **t** are identical

char* strcat(char *s, char *ct)

- Concatenates string **ct** to onto end of string **s**, returns **s**
- **s** must be big enough to hold contents of both strings!

Other string functions

strchr(), **strrchr()**, **strspn()**, **strcspn()**

strpbrk(), **strstr()**, **strtok()**, ...

String Conversion Functions in C

See <stdlib.h>

```
double atof(const char *s)
```

```
int atoi(const char *s)
```

```
long atol(const char *s)
```

```
double strtod(const char *s, char **endp)
```

```
long strtol(const char *s, char **endp, int  
base)
```

```
unsigned long strtoul(const char *s, char  
**endp, int base)
```

Dilemma

Question:—

If strings are arrays of characters, ...
and if arrays cannot be returned from functions, ...
how can we manipulate variable length strings and
pass them around our programs?

Answer:—

Use storage allocated in *The Heap*!

Definition — *The Heap*

A region of memory provided by most operating systems for allocating storage *not* in *Last in, First out* discipline

i.e., not a stack


Must be explicitly allocated *and* released

May be accessed *only* with pointers

Remember, an array is equivalent to a pointer

Many hazards to the C programmer

Static Data Allocation



Allocating Memory in The Heap

See `<stdlib.h>`

```
void *malloc(size_t size);
```

```
void free(void *ptr);
```

```
void *calloc(size_t nmemb, size_t size);
```

```
void *realloc(void *ptr, size_t size);
```

malloc() — allocates **size** bytes of memory from the heap and returns a pointer to it.

NULL pointer if allocation fails for any reason

free() — returns the chunk of memory pointed to by **ptr**
Must have been allocated by **malloc** or **calloc**

Allocating Memory in The Heap

See `<stdlib.h>`

```
void *malloc(size_t size);
```

```
void free(void *ptr);
```

```
void *calloc(size_t nmem, size_t size);
```

```
void *realloc(void *ptr, size_t size);
```

malloc() — allocates **size** bytes of memory from the heap and returns a pointer to it.

- NULL pointer if allocation fails for any reason

free() — returns the chunk of memory pointed to by **ptr**

- *Must* have been allocated by **malloc** or **calloc**

free() knows *size* of
chunk allocated by
malloc() or
calloc()

Notes

`calloc()` is just a variant of `malloc()`

`malloc()` is analogous to `new` in C++ and Java

- `new` in C++ actually calls `malloc()`

`free()` is analogous to `delete` in C++

- `delete` in C++ actually calls `free()`
- Java does not have `delete` — uses *garbage collection* to recover memory no longer in use

Typical usage of `malloc()` and `free()`

```
char *getTextFromSomewhere (...);
```

```
int main() {  
    char * txt;  
    ...;  
    txt = getTextFromSomewhere (...);  
    ...;  
    printf("The text is %s.", txt);  
    free(txt);  
}
```

Typical usage of `malloc()` and `free()`

`getTextFromSomewhere()`
creates a new string
using `malloc()`

```
char * getTextFromSomewhere(  
    char *t;  
    ...  
    t = malloc(stringLength);  
    ...  
    return t;  
}  
  
int main(){  
    char * txt;  
    ...;  
    txt = getTextFromSomewhere(...);  
    ...;  
    printf("The text is %s.", txt);  
    free(txt);  
}
```

Typical usage of `malloc()` and `free()`

```
char * getTextFromSomewhere(...) {  
    char *t;  
    ...  
    t = malloc(stringLength);  
    ...  
    return t;  
}
```

```
int main() {  
    char * txt;  
    ...;  
    txt = getTextFromSomewhere(...);  
    ...;  
    printf("The text is %s.", txt);  
    free(txt);  
}
```



Pointer to text is assigned to
`txt` in calling function

Usage of `malloc()` and `free()`

```
char * getTextFromSomewhere(...) {  
    char *t;  
    ...  
    t = malloc(stringLength);  
    ...  
    return t;  
}
```

```
int main() {  
    char * txt;  
    ...;  
    txt = getTextFromSomewhere(...);  
    ...;  
    printf("The text is: %s", txt);  
    free(txt);  
}
```

main() must remember to
free the storage pointed
to by **txt**

Definition – *Memory Leak*

The steady loss of available memory due to forgetting to `free()` everything that was `malloc`'ed.

- Bug-a-boo of most large C

If you “forget” the value of a pointer to a piece of `malloc`'ed memory, there is no way to find it again!

- Killing the program frees *all* memory!

String Manipulation in C

Almost all C programs that manipulate text do so with **malloc**'ed and **free**'d memory

No limit on size of string in C

Need to be aware of sizes of character arrays!

Need to remember to free storage when it is no longer needed

- *Before* forgetting pointer to that storage!

Input-Output Functions

printf(const char *format, ...)

- Format string may contain **%s** – inserts a string argument (i.e., **char ***) up to trailing '**\0**'

scanf(const char *format, ...)

- Format string may contain **%s** – scans a string into argument (i.e., **char ***) up to next “white space”
- Adds '**\0**'

Related functions

- **fprintf()**, **fscanf()** – to/from a file
- **sprintf()**, **sscanf()** – to/from a string

Example Hazard

```
char word[20];  
...;  
scanf("%s", word);
```

scanf will continue to scan characters from input until a space, tab, new-line, or **EOF** is detected

- An unbounded amount of input
- May overflow allocated character array
- Probable corruption of data!
- **scanf** adds trailing '**\0**'

Solution:

```
scanf("%19s", word);
```