



Video 2.10

Chris Murphy

Review

- Previously we saw how to use jQuery to select and modify DOM elements and add event listeners
- How else can we specify selectors and add event listeners?

- dog
- cat
- elephant
- bear

- dog
- cat
- elephant
- bear

- dog
- cat
- elephant
- bear

```
<html>
<head><script src="jquery.js"></script></head>
<body>
<ul>
<li>dog</li>
<li>cat</li>
<li>elephant</li>
<li>bear</li>
</ul>

<script>

$('li').mouseenter(function() {
    $(this).css('color', 'red');
    $(this).css('font-size', '120%');
});

$('li').mouseleave(function() {
    $(this).css('color', 'black');
    $(this).css('font-size', '100%');
});

</script>

</body>
</html>
```

```
<html>
<head><script src="jquery.js"></script></head>
<body>
<ul>
<li>dog</li>
<li>cat</li>
<li>elephant</li>
<li>bear</li>
</ul>

<script>

$('li').mouseenter(function() {
    $(this).css('color', 'red');
    $(this).css('font-size', '120%');
});

$('li').mouseleave(function() {
    $(this).css('color', 'black');
    $(this).css('font-size', '100%');
});

</script>

</body>
</html>
```

```
<html>
<head><script src="jquery.js"></script></head>
<body>
<ul>
<li>dog</li>
<li>cat</li>
<li>elephant</li>
<li>bear</li>
</ul>

<script>

$('li').mouseenter(function() {
    $(this).css('color', 'red');
    $(this).css('font-size', '120%');
});

$('li').mouseleave(function() {
    $(this).css('color', 'black');
    $(this).css('font-size', '100%');
});

</script>

</body>
</html>
```



```
<html>
<head><script src="jquery.js"></script></head>
<body>
<ul>
<li>dog</li>
<li>cat</li>
<li>elephant</li>
<li>bear</li>
</ul>

<script>

$('li').mouseenter(function() {
    $(this).css('color', 'red');
    $(this).css('font-size', '120%');
});

$('li').mouseleave(function() {
    $(this).css('color', 'black');
    $(this).css('font-size', '100%');
});

</script>

</body>
</html>
```

```
<html>
<head><script src="jquery.js"></script></head>
<body>
<ul>
<li>dog</li>
<li>cat</li>
<li>elephant</li>
<li>bear</li>
</ul>

<script>

$('li').mouseenter(function() {
    $(this).css('color', 'red');
    $(this).css('font-size', '120%');
});

$('li').mouseleave(function() {
    $(this).css('color', 'black');
    $(this).css('font-size', '100%');
});

</script>

</body>
</html>
```

```
<html>
<head><script src="jquery.js"></script></head>
<body>
<ul>
<li>dog</li>
<li>cat</li>
<li>elephant</li>
<li>bear</li>
</ul>

<script>

$('li').mouseenter(function() {
    $(this).css('color', 'red');
    $(this).css('font-size', '120%');
});

$('li').mouseleave(function() {
    $(this).css('color', 'black');
    $(this).css('font-size', '100%');
});

</script>

</body>
</html>
```

```
<html>
<head><script src="jquery.js"></script></head>
<body>
<ul>
<li>dog</li>
<li>cat</li>
<li>elephant</li>
<li>bear</li>
</ul>

<script>

$( 'li' ).mouseenter( function() {
    $(this).css('color', 'red');
    $(this).css('font-size', '120%');
});

$( 'li' ).mouseleave(function() {
    $(this).css('color', 'black');
    $(this).css('font-size', '100%');
});

</script>

</body>
</html>
```

```
<html>
<head><script src="jquery.js"></script></head>
<body>
<ul>
<li>dog</li>
<li>cat</li>
<li>elephant</li>
<li>bear</li>
</ul>

<script>

$( 'li' ).mouseenter(function() {
    $(this).css('color', 'red');
    $(this).css('font-size', '120%');
});

$( 'li' ).mouseleave(function() {
    $(this).css('color', 'black');
    $(this).css('font-size', '100%');
});

</script>

</body>
</html>
```

```
<html>
<head><script src="jquery.js"></script></head>
<body>
<ul>
<li>dog</li>
<li>cat</li>
<li>elephant</li>
<li>bear</li>
</ul>

<script>

$('li').mouseenter(function() {
    $(this).css('color', 'red');
    $(this).css('font-size', '120%');
});

$('li').mouseleave(function() {
    $(this).css('color', 'black');
    $(this).css('font-size', '100%');
});

</script>

</body>
</html>
```

```
<html>
<head><script src="jquery.js"></script></head>
<body>
<ul>
<li>dog</li>
<li>cat</li>
<li>elephant</li>
<li>bear</li>
</ul>

<script>

$('li').mouseenter(function() {
    $(this).css('color', 'red');
    $(this).css('font-size', '120%');
});

$('li').mouseleave(function() {
    $(this).css('color', 'black');
    $(this).css('font-size', '100%');
});

</script>

</body>
</html>
```

```
<html>
<head><script src="jquery.js"></script></head>
<body>
<ul>
<li>dog</li>
<li>cat</li>
<li>elephant</li>
<li>bear</li>
</ul>

<script>

$('li').mouseenter(function() {
    $(this).css('color', 'red');
    $(this).css('font-size', '120%');
});

$('li').mouseleave(function() {
    $(this).css('color', 'black');
    $(this).css('font-size', '100%');
});

</script>

</body>
</html>
```



```
<html>
<head><script src="jquery.js"></script></head>
<body>
<ul>
<li>dog</li>
<li>cat</li>
<li>elephant</li>
<li>bear</li>
</ul>

<script>

$('li').hover(
    function() {
        $(this).css('color', 'red');
        $(this).css('font-size', '120%');
    },
    function() {
        $(this).css('color', 'black');
        $(this).css('font-size', '100%');
    });

</script>

</body>
</html>
```

```
<html>
<head><script src="jquery.js"></script></head>
<body>
<ul>
<li>dog</li>
<li>cat</li>
<li>elephant</li>
<li>bear</li>
</ul>

<script>

$('li').hover(
  function() {
    $(this).css('color', 'red');
    $(this).css('font-size', '120%');
  },
  function() {
    $(this).css('color', 'black');
    $(this).css('font-size', '100%');
  });

</script>

</body>
</html>
```

```
<html>
<head><script src="jquery.js"></script></head>
<body>
<ul>
<li>dog</li>
<li>cat</li>
<li>elephant</li>
<li>bear</li>
</ul>

<script>
$('li').on({
  mouseenter: function() {
    $(this).css('color', 'red');
    $(this).css('font-size', '120%');
  },
  mouseleave: function() {
    $(this).css('color', 'black');
    $(this).css('font-size', '100%');
  },
  click: function() {
    $(this).css('background-color', 'yellow');
  }
});
</script>

</body>
</html>
```

```
<html>
<head><script src="jquery.js"></script></head>
<body>
<ul>
<li>dog</li>
<li>cat</li>
<li>elephant</li>
<li>bear</li>
</ul>

<script>
$('li').on({
  mouseenter: function() {
    $(this).css('color', 'red');
    $(this).css('font-size', '120%');
  },
  mouseleave: function() {
    $(this).css('color', 'black');
    $(this).css('font-size', '100%');
  },
  click: function() {
    $(this).css('background-color', 'yellow');
  }
});
</script>

</body>
</html>
```

```
<html>
<head><script src="jquery.js"></script></head>
<body>
<ul>
<li>dog</li>
<li>cat</li>
<li>elephant</li>
<li>bear</li>
</ul>

<script>
$( 'li' ).on({
  mouseenter: function() {
    $(this).css('color', 'red');
    $(this).css('font-size', '120%');
  },
  mouseleave: function() {
    $(this).css('color', 'black');
    $(this).css('font-size', '100%');
  },
  click: function() {
    $(this).css('background-color', 'yellow');
  }
});
</script>

</body>
</html>
```

- dog
- cat
- elephant
- bear
- canary
- eagle

```
<html>
<head><script src="jquery.js"></script></head>

<body>
<ul>
<li class="highlight">dog</li>
<li class="highlight">cat</li>
<li class="highlight">elephant</li>
<li class="highlight">bear</li>
</ul>

<ul>
<li>canary</li>
<li>eagle</li>
</ul>

<script>

$("li.highlight").on({
mouseenter: function() { . . . },
mouseleave: function() { . . . },
click: function() { . . . }
});

</script>

</body>
</html>
```

```
<html>
<head><script src="jquery.js"></script></head>

<body>
<ul>
<li class="highlight">dog</li>
<li class="highlight">cat</li>
<li class="highlight">elephant</li>
<li class="highlight">bear</li>
</ul>

<ul>
<li>canary</li>
<li>eagle</li>
</ul>

<script>

$("li.highlight").on({
mouseenter: function() { . . . },
mouseleave: function() { . . . },
click: function() { . . . }
});

</script>

</body>
</html>
```



```
<html>
<head><script src="jquery.js"></script></head>

<body>
<ul>
<li class="highlight">dog</li>
<li class="highlight">cat</li>
<li class="highlight">elephant</li>
<li class="highlight">bear</li>
</ul>

<ul>
<li>canary</li>
<li>eagle</li>
</ul>

<script>

$("li.highlight").on({
mouseenter: function() { . . . },
mouseleave: function() { . . . },
click: function() { . . . }
});

</script>

</body>
</html>
```

```
<html>
<head><script src="jquery.js"></script></head>

<body>
<ul>
<li class="highlight">dog</li>
<li class="highlight">cat</li>
<li class="highlight">elephant</li>
<li class="highlight">bear</li>
</ul>

<ul>
<li>canary</li>
<li>eagle</li>
</ul>

<script>

$("li.highlight").on({
mouseenter: function() { . . . },
mouseleave: function() { . . . },
click: function() { . . . }
});

</script>

</body>
</html>
```

```
<html>
<head><script src="jquery.js"></script></head>

<body>
<ul class="highlight">
<li>dog</li>
<li>cat</li>
<li>elephant</li>
<li>bear</li>
</ul>

<ul>
<li>canary</li>
<li>eagle</li>
</ul>

<script>

$("ul.highlight").find("li").on({
mouseenter: function() { . . . },
mouseleave: function() { . . . },
click: function() { . . . }
});

</script>

</body>
</html>
```

```
<html>
<head><script src="jquery.js"></script></head>

<body>
<ul class="highlight">
<li>dog</li>
<li>cat</li>
<li>elephant</li>
<li>bear</li>
</ul>

<ul>
<li>canary</li>
<li>eagle</li>
</ul>

<script>

$("ul.highlight").find("li").on({
mouseenter: function() { . . . },
mouseleave: function() { . . . },
click: function() { . . . }
});

</script>

</body>
</html>
```

```
<html>
<head><script src="jquery.js"></script></head>

<body>
<ul class="highlight">
<li>dog</li>
<li>cat</li>
<li>elephant</li>
<li>bear</li>
</ul>

<ul>
<li>canary</li>
<li>eagle</li>
</ul>

<script>

$("ul.highlight").find("li").on({
mouseenter: function() { . . . },
mouseleave: function() { . . . },
click: function() { . . . }
});

</script>

</body>
</html>
```

```
<html>
<head><script src="jquery.js"></script></head>

<body>
<ul class="highlight">
<li>dog</li>
<li>cat</li>
<li>elephant</li>
<li>bear</li>
</ul>

<ul>
<li>canary</li>
<li>eagle</li>
</ul>

<script>

$("ul.highlight").find("li").on({
mouseenter: function() { . . . },
mouseleave: function() { . . . },
click: function() { . . . }
});

</script>

</body>
</html>
```

```
<html>
<head><script src="jquery.js"></script></head>

<body>
<ul class="highlight">
<li>dog</li>
<li>cat</li>
<li>elephant</li>
<li>bear</li>
</ul>

<ul>
<li>canary</li>
<li>eagle</li>
</ul>

<script>

$("ul.highlight").find("li").on({
mouseenter: function() { . . . },
mouseleave: function() { . . . },
click: function() { . . . }
});

</script>

</body>
</html>
```

```
<html>
<head><script src="jquery.js"></script></head>

<body>
<ul class="highlight">
<li>dog</li>
<li>cat</li>
<li>elephant</li>
<li>bear</li>
</ul>

<ul>
<li>canary</li>
<li>eagle</li>
</ul>

<script>

$("ul.highlight").find("li").on({
mouseenter: function() { . . . },
mouseleave: function() { . . . },
click: function() { . . . }
});

</script>

</body>
</html>
```


Advanced Selectors

- `$ (someNodes) .find(selector)` will search *someNodes*' children for selector.

Advanced Selectors

- `$(someNodes).find(selector)` will search *someNodes*' children for selector.
- `$` selectors can be chained
 - `$("div.book")` selects the div with class="book"
 - `$("div, .book")` selects all divs **and** all elements with class="book"

Advanced Selectors

- `$(someNodes).find(selector)` will search *someNodes*' children for selector.
- `$` selectors can be chained
 - `$("div.book")` selects the div with class="book"
 - `$("div, .book")` selects all divs **and** all elements with class="book"
- `:` can be used to specify element properties
 - `$("p:hidden")` selects all `<p>` elements that are visually hidden

Advanced Selectors

- `$(someNodes).find(selector)` will search *someNodes*' children for selector.
- `$` selectors can be chained
 - `$("div.book")` selects the div with class="book"
 - `$("div, .book")` selects all divs **and** all elements with class="book"
- `:` can be used to specify element properties
 - `$("p:hidden")` selects all `<p>` elements that are visually hidden
- These selectors are all CSS selectors!
 - All other CSS selectors also work in `$`

Summary

- jQuery can be used to retrieve and modify DOM elements and add event listeners
- We can use advanced selectors and handlers to simplify functionality