



## Video 2.2

### Chris Murphy

# JavaScript Basics

---

- Like many other programming languages, JavaScript includes:
  - variables, arrays, and objects
  - loops and conditional statements
  - functions
- Even if you know Java, there are still some important differences
  - defining functions and objects
  - interacting with HTML

# Declaring a Variable

---

- The basic syntax for declaring any JavaScript variable is `var variableName = ...`

```
var age = 22;  
  
var name = 'Jane Doe';  
  
var isMale = false;
```

# Declaring a Variable

---

- The basic syntax for declaring any JavaScript variable is `var variableName = ...`

```
var age = 22;  
  
var name = 'Jane Doe';  
  
var isMale = false;
```

# Declaring a Variable

---

- The basic syntax for declaring any JavaScript variable is `var variableName = ...`

```
var age = 22;  
  
var name = 'Jane Doe' ;  
  
var isMale = false;
```

# Declaring a Variable

---

- The basic syntax for declaring any JavaScript variable is `var variableName = ...`

```
var age = 22;  
var name = 'Jane Doe';  
var isMale = false;
```

# Viewing a variable's value (1)

---

- If using a `<script>` section in a HTML file, or an external .js file, `document.write(var)` will display a variable's value in the HTML

```
My age is:  
<script>  
  var age = 12;  
  document.write(age);  
</script>
```

# Viewing a variable's value (1)

---

- If using a `<script>` section in a HTML file, or an external .js file, `document.write(var)` will display a variable's value in the HTML

```
My age is:  
<script>  
  var age = 12;  
  document.write(age);  
</script>
```



# Viewing a variable's value (1)

---

- If using a `<script>` section in a HTML file, or an external .js file, `document.write(var)` will display a variable's value in the HTML

```
My age is:  
<script>  
    var age = 12;  
    document.write(age);  
</script>
```

# Viewing a variable's value (1)

---

- If using a `<script>` section in a HTML file, or an external .js file, `document.write(var)` will display a variable's value in the HTML

```
My age is:  
<script>  
    var age = 12;  
    document.write(age);  
</script>
```

# Viewing a variable's value (1)

---

- If using a `<script>` section in a HTML file, or an external .js file, `document.write(var)` will display a variable's value in the HTML

```
My age is:  
<script>  
  var age = 12;  
  document.write(age);  
</script>
```

My age is: 12

# Viewing a variable's value (1)

---

- If using a `<script>` section in a HTML file, or an external .js file, `document.write(var)` will display a variable's value in the HTML

```
My age is:  
<script>  
  var age = 12;  
  document.write(age);  
</script>
```

My age is: 12

- However, this approach is discouraged
- We will see better alternatives later!

## Viewing a variable's value (2)

---

- You can also use `console.log(var)` to print a variable's value in the browser's JavaScript console

```
<script>  
  var age = 12;  
  console.log(age);  
</script>
```

## Viewing a variable's value (2)

---

- You can also use `console.log(var)` to print a variable's value in the browser's JavaScript console

```
<script>  
  var age = 12;  
  console.log(age);  
</script>
```

## Viewing a variable's value (2)

---

- You can also use `console.log(var)` to print a variable's value in the browser's JavaScript console

```
<script>  
  var age = 12;  
  console.log(age);  
</script>
```

## Viewing a variable's value (2)

---

- You can also use `console.log(var)` to print a variable's value in the browser's JavaScript console

```
<script>  
  var age = 12;  
  console.log(age) ;  
</script>
```



## Viewing a variable's value (2)

- You can also use `console.log(var)` to print a variable's value in the browser's JavaScript console

```
<script>
  var age = 12;
  console.log(age);
</script>
```



## Viewing a variable's value (2)

- You can also use `console.log(var)` to print a variable's value in the browser's JavaScript console

```
<script>
  var age = 12;
  console.log(age);
</script>
```



# Viewing a variable's value (3)

---

- Also, **alert** (*var*) will create a popup with the variable's value that appears on top of the browser

```
<script>  
  var age = 12;  
  alert(age);  
</script>
```

# Viewing a variable's value (3)

---

- Also, `alert(var)` will create a popup with the variable's value that appears on top of the browser

```
<script>  
  var age = 12;  
  alert(age);  
</script>
```

# Viewing a variable's value (3)

---

- Also, **alert** (*var*) will create a popup with the variable's value that appears on top of the browser

```
<script>  
  var age = 12;  
  alert (age);  
</script>
```

# Viewing a variable's value (3)

---

- Also, **alert** (*var*) will create a popup with the variable's value that appears on top of the browser

```
<script>  
  var age = 12;  
  alert(age) ;  
</script>
```

# Viewing a variable's value (3)

---

- Also, **alert** (*var*) will create a popup with the variable's value that appears on top of the browser

```
<script>  
  var age = 12;  
  alert(age);  
</script>
```

This page says:

12

OK

# Viewing a variable's value (3)

- Also, **alert** (*var*) will create a popup with the variable's value that appears on top of the browser

```
<script>
  var age = 12;
  alert(age);
</script>
```

This page says:

12

OK

- Last, if using the browser JavaScript console (REPL), just type the name of the variable

```
> var age = 12;
```



# Viewing a variable's value (3)

- Also, **alert** (*var*) will create a popup with the variable's value that appears on top of the browser

```
<script>
  var age = 12;
  alert(age);
</script>
```

This page says:

12

OK

- Last, if using the browser JavaScript console (REPL), just type the name of the variable

```
> var age = 12;
> age
```

# Viewing a variable's value (3)

- Also, `alert(var)` will create a popup with the variable's value that appears on top of the browser

```
<script>
  var age = 12;
  alert(age);
</script>
```

This page says:

12

OK

- Last, if using the browser JavaScript console (REPL), just type the name of the variable

```
> var age = 12
> age
12
```

# Changing a variable's type

---

- The type of each variable does not need to be specified and can be changed at any time.

```
var id = 33.2;  
  
id = 'secret';
```

# Changing a variable's type

---

- The type of each variable does not need to be specified and can be changed at any time.

```
var id = 33.2;  
  
id = 'secret';
```

# Changing a variable's type

---

- The type of each variable does not need to be specified and can be changed at any time.

```
var id = 33.2;  
  
id = 'secret';
```

# Primitive Types

---

Type	Example values
Number	5, 1.25, 1.1e5, +Infinity, -Infinity, NaN

# Primitive Types

---

Type	Example values
Number	5, 1.25, 1.1e5, +Infinity, -Infinity, NaN
String	'hello'

# Primitive Types

---

Type	Example values
Number	5, 1.25, 1.1e5, +Infinity, -Infinity, NaN
String	'hello'
Boolean	true, false



# Primitive Types

---

Type	Example values
Number	5, 1.25, 1.1e5, +Infinity, -Infinity, NaN
String	'hello'
Boolean	true, false
Null	null

# Primitive Types

---

Type	Example values
Number	5, 1.25, 1.1e5, +Infinity, -Infinity, NaN
String	'hello'
Boolean	true, false
Null	null
Undefined	undefined

# Numbers

---

- All JavaScript numbers are stored using floating-point notation
  - i.e. 5 is stored internally as 0.5e1
- `+infinity` represents all numbers greater than `Number.MAX_VALUE` (around  $10^{308}$ )
- `-infinity` represents all numbers less than `Number.MIN_VALUE` (around  $10^{-324}$ )
- `NaN` represents any non-number value
  - `Number('tree')` would return `NaN`

# Number Operations

---

- Basic arithmetic (+, -, \*, /, %) can be used on JavaScript numbers
- Precedence will follow MDAS unless parentheses are used
- ++ and -- can be used to increment/decrement JavaScript numbers

```
var a = 4;  
a++; // a = 5  
var c = a - 3; // 2  
var d = c + 3 * a; // 17  
var e = ( c + 3 ) * a; // 25
```

# Strings

---

- JavaScript strings are series of 16-bit unsigned integers, each integer representing a character
- Convention is to use single quotes for strings unless single quotes exist within the string
  - `'I am a dolphin'` vs. `"I'm a dolphin"`
- Escape characters use backslash: `'\n \t \\'`
- All JavaScript strings are immutable
  - Any manipulation results in a new string

# String Functions

---

- `+` or `.concat(otherString)` can be used to concatenate strings (add them together)

```
var firstName = 'John';  
var lastName = 'doe';
```

# String Functions

---

- `+` or `.concat(otherString)` can be used to concatenate strings (add them together)

```
var firstName = 'John';  
var lastName = 'doe';  
  
var fullName= firstName.concat(' ', lastName); // 'John doe'
```

# String Functions

---

- `+` or `.concat(otherString)` can be used to concatenate strings (add them together)

```
var firstName = 'John';  
var lastName = 'doe';  
  
var fullName= firstName.concat(' ', lastName); // 'John doe'  
var greeting = 'HELLO, ' + fullName;
```



# String Functions

---

- `+` or `.concat(otherString)` can be used to concatenate strings (add them together)
- `.toUpperCase()` and `.toLowerCase()` change the case of every character in a string

```
var firstName = 'John';  
var lastName = 'doe';  
  
var fullName= firstName.concat(' ', lastName); // 'John doe'  
var greeting = 'HELLO, ' + fullName;  
  
console.log(greeting.toUpperCase());           // 'HELLO, JOHN DOE'  
console.log(greeting.toLowerCase());           // 'hello, john doe'
```

# String Functions

---

- `+` or `.concat(otherString)` can be used to concatenate strings (add them together)
- `.toUpperCase()` and `.toLowerCase()` change the case of every character in a string
- `var.length` gets the length of a string

```
var firstName = 'John';  
var lastName = 'doe';  
  
var fullName= firstName.concat(' ', lastName); // 'John doe'  
var greeting = 'HELLO, ' + fullName;  
  
console.log(greeting.toUpperCase());           // 'HELLO, JOHN DOE'  
console.log(greeting.toLowerCase());           // 'hello, john doe'  
  
console.log(greeting.length);                  // 15
```

# Booleans

---

- Booleans are logical values that can only be `true` or `false`
- Any value can be used as a boolean in JavaScript
  - “Falsy” values: `null`, `undefined`, `0`, `NaN`, `''`
  - “Truthy” values: `'cow'`, `'false'`, `5`, etc...
- Any variable type can become a boolean when used with logical operators

# Null and Undefined

---

- **Null** is a value that can be assigned to variables to represent “no value”

```
var occupation = null;  
console.log(occupation); // null
```

# Null and Undefined

---

- **Null** is a value that can be assigned to variables to represent “no value”

```
var occupation = null;  
console.log(occupation); // null
```

- **Undefined** means that a variable was declared but no value has been assigned

```
var salary;  
console.log(salary); // undefined
```

# Summary

---

- JavaScript variables do not need to have their types specified when they are declared
- Variable types are allowed to change
- Five primitive types: number, string, boolean, null, undefined