

1 point

1. For many of the questions in this quiz, you will need to have completed the **Calculating the Shape of a Perimeter** programming exercise, using the **ProgrammingAssignmentRunner BlueJ Project on DukeLearnToProgram.com**: <http://www.dukelearntoprogram.com/course2/files.php>.

What is the perimeter of the shape made from the file **datatest1.txt** whose contents are shown below (just give to two decimal places)?

-3,3

-4,-3

4,-2

6,5

30.64

1 point

2. What is the average length of a side in the shape made from the file **datatest4.txt** whose contents are shown below (just give to two decimal places)?

-3, 9

-8, 7

-12, 4

-6, -2

-4, -6

2, -8

6, -5

10, -3

8, 5

4, 8

5.94

1 point

3. What is the longest side in the shape made from the file **datatest1.txt** whose contents are shown below (just give to two decimal places)?

-3,3

-4,-3

4,-2

6,5

9.21

1 point

4. What is the largest perimeter of a shape made from the shapes in files **dataset1.txt**, **dataset2.txt**, **dataset3.txt**, **dataset4.txt**, **dataset5.txt**, and **dataset6.txt** (just give to two decimal places)?

62.65

1 point

5. What is the name of the file that has the shape with the largest perimeter from the four files **example1.txt**, **example2.txt**, **example3.txt** and **example4.txt**?

☐ example1.txt

☐ example2.txt

☒ example3.txt

☐ example4.txt

1 point

6. The method `getNumPoints` returns the number of points in a Shape `s`.

Which one of the following is NOT a correct implementation of `getNumPoints`?

☐

```
1 public int getNumPoints (Shape s) {  
2     int count = 0;  
3     for (Point p : s.getPoints()) {  
4         int newPoint = 1;  
5         count = count + newPoint;  
6     }  
7     return count;  
8 }
```

☒

```
1 public int getNumPoints (Shape s) {  
2     int count = 0;  
3     for (Point p : s.getPoints()) {  
4         count = count + count;  
5     }  
6     return count;  
7 }
```

☐

```
1 public int getNumPoints (Shape s) {  
2     int count = 0;  
3     int newPoint = 1;  
4     for (Point p : s.getPoints()) {  
5         count = count + newPoint;  
6     }  
7     return count;  
8 }
```

☐

```
1 public int getNumPoints (Shape s) {  
2     int count = 0;  
3     for (Point p : s.getPoints()) {  
4         count = count + 1;  
5     }  
6     return count;  
7 }
```

1 point

7. Consider the following code for the function `mysteryShape` that has one parameter a Shape `s` and calls the function `getNumPoints` from the assignment.

```
1 public double mysteryShape (Shape s) {  
2     double tmp = 0;  
3     for (Point p : s.getPoints()) {  
4  
5         if (p.getX() > 0) {  
6  
7             if (p.getY() < 0) {  
8                 tmp = tmp + 1;  
9             }  
10        }  
11    }  
12    return tmp / getNumPoints(s);  
13 }  
14  
15
```

Which one of the following best describes the purpose of this function?

☐

The function computes the **sum** of those points from the Shape `s` that have a **positive X** and a **negative Y**.

☐

The function computes the **sum** of those points from the Shape `s` that have a **positive X** or a **negative Y**.

☐

The function computes the **percentage** of those points from the Shape `s` that have a **positive X** or a **negative Y**.

☒

The function computes the **percentage** of those points from the Shape `s` that have a **positive X** and a **negative Y**.

☒ I, **Ning Zheng**, understand that submitting work that isn't my own may result in permanent failure of this course or deactivation of my Coursera account.

[Learn more about Coursera's Honor Code](#)

Submit Quiz