Source code

```
import java.util.ArrayList;
import java.util.Collections;
import java.util.Scanner;

public class Test{

   public static void main(String[] args) {
      /*System.out.println("Hello World!");*/
      System.out.println("\n**************************************\n");
      System.out.println("\tWelcome to TheDesk \n");
      System.out.println("**************************************");
      optionsSelection();

   }
   private static void optionsSelection() {
      String[] arr = {"1. I wish to review my expenditure",
            "2. I wish to add my expenditure",
            "3. I wish to delete my expenditure",
            "4. I wish to sort the expenditures",
            "5. I wish to search for a particular expenditure",
            "6. Close the application"
      };
      int[] arr1 = {1,2,3,4,5,6};
      int  slen = arr1.length;
      for(int i=0; i<slen;i++){
         System.out.println(arr[i]);
         // display the all the Strings mentioned in the String array
      }
      ArrayList<Integer> arrlist = new ArrayList<Integer>();
      ArrayList<Integer> expenses = new ArrayList<Integer>();
      expenses.add(1000);
      expenses.add(2300);
      expenses.add(45000);
      expenses.add(32000);
      expenses.add(110);
      expenses.addAll(arrlist);
      System.out.println("\nEnter your choice:\t");
      Scanner sc = new Scanner(System.in);
      int options;
      do {
      options= sc.nextInt();
            switch (options){
               case 1:
                  System.out.println("Your saved expenses are listed below: \n");
                  System.out.println(expenses+"\n");
```

Source code

```
                break;
            case 2:
                System.out.println("Enter the value to add your Expense: \n");
                int value = sc.nextInt();
                expenses.add(value);
                System.out.println("Your value is updated\n");
                expenses.addAll(arrlist);
                System.out.println(expenses+"\n");
                break;
            case 3:
                System.out.println("You are about the delete all your expenses! \nConfirm again by
selecting the same option...\n");
                int con_choice = sc.nextInt();
                if(con_choice==options){
                     expenses.clear();
                   System.out.println(expenses+"\n");
                   System.out.println("All your expenses are erased!\n");
                } else {
                   System.out.println("Oops... try again!");
                }

                break;
            case 4:
                sortExpenses(expenses);

                break;
            case 5:
                searchExpenses(expenses);
                break;
            case 6:
                closeApp();
                break;
            default:
                System.out.println("You have made an invalid choice!");
                break;
          }
      }
 while (options != 6);
      }

   private static void closeApp() {
      System.out.println("Closing your application... \nThank you!");
         }
   private static void searchExpenses(ArrayList<Integer> arrayList) {
```

Source code

```
        int leng = arrayList.size();
        System.out.println("Enter the expense you need to search:\t");
        //Complete the method
        Scanner sc = new Scanner(System.in);
        int num = sc.nextInt();
        boolean ans = arrayList.contains(num);
if (ans)
System.out.println("The list contains the expense");
else
System.out.println("The list does not contains the expense");


    }
    private static void sortExpenses(ArrayList<Integer> arrayList) {
        int arrlength =  arrayList.size();
       //Complete the method. The expenses should be sorted in ascending order.
        Collections.sort(arrayList);
        System.out.println(arrayList);

    }
}
```