

GeeksforGeeks

A computer science portal for geeks

Placements

Practice

GATE CS

IDE

Q&A

GeeksQuiz

Login/Register

Permutations of a given string using STL

A permutation, also called an “arrangement number” or “order”, is a rearrangement of the elements of an ordered list S into a one-to-one correspondence with S itself. A string of length n has $n!$ permutation.

Source: [Mathword](#)


Below are the permutations of string ABC.

ABC ACB BAC BCA CBA CAB

We have discussed C implementation to print all permutations of a given string using backtracking [here](#). In this post, C++ implementation using STL is discussed.

Method 1 (Using rotate())

`std::rotate` function rotates elements of a vector/string such that the passed middle element becomes first. For example, if we call rotate for “ABCD” with middle as second element, the string becomes “BCDA” and if we again call rotate with middle as second element, the string becomes “CDAB”. Refer [this](#) for a sample program.



Recursion Tree for all permutations of string "ABC"

Below is C++ implementation.

```

// C++ program to print all permutations with
// duplicates allowed using rotate() in STL
#include <bits/stdc++.h>
using namespace std;

// Function to print permutations of string str,
// out is used to store permutations one by one
void permute(string str, string out)
{
    // When size of str becomes 0, out has a
    // permutation (length of out is n)
    if (str.size() == 0)
    {
        cout << out << endl;
        return;
    }

    // One by one move all characters at
    // the beginning of out (or result)
    for (int i = 0; i < str.size(); i++)
    {
        // Remove first character from str and
        // add it to out
        permute(str.substr(1), out + str[0]);

        // Rotate string in a way second character
        // moves to the beginning.
        rotate(str.begin(), str.begin() + 1, str.end());
    }
}

// Driver code
int main()
{

```

```
string str = "ABC";
permute(str, "");
return 0;
}
```

[Run on IDE](#)

Output :

```
ABC
ACB
BCA
BAC
CAB
CBA
```

Method 2 (using next_permute())

We can use `next_permute()` that modifies a string so that it stores lexicographically next permutation. If current string is lexicographically largest, i.e., "CBA", then `next_permute()` returns false.

We first sort the string, so that it is converted to lexicographically smallest permutation. Then we one by one call `next_permutation` until it returns false.

```
// C++ program to print all permutations with
// duplicates allowed using next_permute()
#include <bits/stdc++.h>
using namespace std;

// Function to print permutations of string str
// using next_permute()
void permute(string str)
{
    // Sort the string in lexicographically
    // ascending order
    sort(str.begin(), str.end());

    // Keep printing next permutation while there
    // is next permutation
    do {
        cout << str << endl;
    } while (next_permutation(str.begin(), str.end()));
}

// Driver code
int main()
{
    string str = "CBA";
    permute(str);
    return 0;
}
```

[Run on IDE](#)

Output :

```
ABC
ACB
```

BCA
BAC
CAB
CBA

Note that the second method always prints permutations in lexicographically sorted order irrespective of input string.

This article is contributed by **Aditya Goel**. If you like GeeksforGeeks and would like to contribute, you can also write an article and mail your article to contribute@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above

Company Wise Coding Practice Topic Wise Coding Practice

3 Comments Category: Strings Tags: STL

Related Posts:

- Check if string follows order of characters defined by a pattern or not | Set 3
- Check if string follows order of characters defined by a pattern or not | Set 2
- Find k'th character of decrypted string
- **Minimum Cost To Make Two Strings Identical**
- Find all strings that match specific pattern in a dictionary
- Check if string follows order of characters defined by a pattern or not | Set 1
- Find longest palindrome formed by removing or shuffling chars from string
- Calculate sum of all numbers present in a string

(Login to Rate and Mark)

4.1

Average Difficulty : 4.1/5.0
Based on 9 vote(s)

☐
☐

Add to TODO List

Mark as DONE

Writing code in comment? Please use code.geeksforgeeks.org, generate link and share the link here.

3 Comments

GeeksforGeeks

 Tejas Joshi ▾ Recommend 1  Share

Sort by Newest ▾



Join the discussion...

**AllergicToBitches** • 3 months ago

Another C++ implementation using std::string without backtracking

<http://ideone.com/IATWDo>

Using std::prev_permutation -

<http://ideone.com/aF5bT9>

^ | ▾ • Reply • Share ›

**Denish Thummar** • 3 months ago





This will also print repeated permutation if input contains repeated characters.

^ | ▾ • Reply • Share ›

**sudhir Tiwari** • 4 months ago

what about complexity???

1 ^ | ▾ • Reply • Share ›

 Subscribe  Add Disqus to your site  Add Disqus  Add  Privacy

@geeksforgeeks, Some rights reserved

[Contact Us!](#)[About Us!](#)[Advertise with us!](#)