

INDEX

| Sr. No | Practical Aim | Signature |
|--------|--|-----------|
| 1 | Creating Data Model using Cassandra. | |
| 2 | Conversion from different formats to HOURS format. a. Text delimited csv format. b. XML c. JSON d. MySQL Database e. Picture (JPEG) f. Video g. Audio | |
| 3 | Utilities and Auditing | |
| 4 | Retrieving Data | |
| 5 | Assessing Data | |
| 6 | Processing Data | |
| 7 | Transforming Data | |
| 8 | Organizing Data | |
| 9 | Generating Reports | |
| 10 | Data Visualization with Power BI | |


Practical 1:

Creating Data Model using Cassandra.

Go to Cassandra directory

C:\apache-cassandra-3.11.4\bin

Run Cassandra.bat file



Open C:\apache-cassandra-3.11.4\bin\cqlsh.py with python 2.7 and run

Creating a Keyspace using Cqlsh

Create keyspace keyspace1 with replication = {,,class“:“SimpleStratergy“, „replication_factor“: 3};

Use keyspace1;

A screenshot of a terminal window titled "Python 2.7.10 Shell". The window shows the following text:
Connected to Test Cluster at 127.0.0.1:9042.
[cqlsh 5.0.1 | Cassandra 3.11.4 | CQL spec 3.4.
4 | Native protocol v4]
Use HELP for help.
cqlsh> use keyspace1;
cqlsh:keyspace1>
Ln: 13 Col: 17

Create table dept (dept_id int PRIMARY KEY, dept_name text, dept_loc text);

Create table emp (emp_id int PRIMARY KEY, emp_name text, dept_id int, email text, phone text);

Insert into dept (dept_id, dept_name, dept_loc) values (1001, 'Accounts', 'Mumbai'); Insert into dept (dept_id, dept_name, dept_loc) values (1002, 'Marketing', 'Delhi'); Insert into dept (dept_id, dept_name, dept_loc) values (1003, 'HR', 'Chennai');

Insert into emp (emp_id, emp_name, dept_id, email, phone) values (1001, 'ABCD', 1001,'abcd@company.com', '1122334455');

Insert into emp (emp_id, emp_name, dept_id, email, phone) values (1002, 'DEFG', 1001,'defg@company.com', '2233445566');

Insert into emp (emp_id, emp_name, dept_id, email, phone) values (1003, 'GHIJ', 1002,

```
'ghij@company.com', '3344556677');
Insert into emp ( emp_id, emp_name, dept_id, email, phone ) values (1004, 'JKLM',
1002,'jklm@company.com', '4455667788');
Insert into emp ( emp_id, emp_name, dept_id, email, phone ) values (1005, 'MNOP',
1003,'mnop@company.com', '5566778899');
Insert into emp ( emp_id, emp_name, dept_id, email, phone ) values (1006, 'MNOP',
1003,'mnop@company.com', '5566778844');
```

```
cqlsh:keyspace1> select * from emp;
+-----+-----+-----+-----+
| emp_id | dept_id | email      | emp_name | phone
+-----+-----+-----+-----+
| 1006   | 1003    | mnop@company.com | MNOP     | 5566778844
| 1004   | 1002    | jklm@company.com | JKLM     | 4455667788
| 1005   | 1003    | mnop@company.com | MNOP     | 5566778899
| 1001   | 1001    | abcd@company.com | ABCD     | 1122334455
| 1003   | 1002    | ghij@company.com | GHIJ     | 3344556677
| 1002   | 1001    | defg@company.com | DEFG     | 2233445566
+-----+-----+-----+-----+
(6 rows)

cqlsh:keyspace1> select * from dept;
+-----+-----+-----+
| dept_id | dept_loc | dept_name
+-----+-----+-----+
| 1001    | Mumbai   | Accounts
| 1003    | Chennai  | HR
| 1002    | Delhi    | Marketing
+-----+-----+-----+
(3 rows)
```

```
update dept set dept_name='Human Resource' where dept_id=1003;
```

```
cqlsh:keyspace1> select * from dept;
+-----+-----+-----+
| dept_id | dept_loc | dept_name
+-----+-----+-----+
| 1001    | Mumbai   | Accounts
| 1003    | Chennai  | Human Resource
| 1002    | Delhi    | Marketing
+-----+-----+-----+
(3 rows)
```

```
cqlsh:keyspace1> delete from emp where emp_id=1006;
cqlsh:keyspace1> select * from emp;
+-----+-----+-----+-----+
| emp_id | dept_id | email      | emp_name | phone
+-----+-----+-----+-----+
| 1004   | 1002    | jklm@company.com | JKLM     | 4455667788
| 1005   | 1003    | mnop@company.com | MNOP     | 5566778899
| 1001   | 1001    | abcd@company.com | ABCD     | 1122334455
| 1003   | 1002    | ghij@company.com | GHIJ     | 3344556677
| 1002   | 1001    | defg@company.com | DEFG     | 2233445566
+-----+-----+-----+-----+
(5 rows)
```

Practical 2:

Write Python / R Program to convert from the following formats to HORUS format:

A. Text delimited CSV to HORUS format.

Code

```
# Utility Start CSV to HORUS =====
# Standard Tools
import pandas as pd
# Input Agreement =====
sInputFileName='C:/VKHCG/05-DS/9999-
Data/Country_Code.csv'
InputData=pd.read_csv(sInputFileName,encoding="latin-1")
print('Input Data Values =====')
print(InputData)
print('=====') # Processing Rules
=====
ProcessData=InputData
# Remove columns ISO-2-Code and ISO-3-CODE
ProcessData.drop('ISO-2-CODE',
axis=1,inplace=True)ProcessData.drop('ISO-3-
Code', axis=1,inplace=True) # Rename Country
and ISO-M49
ProcessData.rename(columns={'Country': 'CountryName'},
inplace=True) ProcessData.rename(columns={'ISO-M49':
'CountryNumber'}, inplace=True)# Set new Index
ProcessData.set_index('CountryNumber',
inplace=True)# Sort data by CurrencyNumber
ProcessData.sort_values('CountryName', axis=0, ascending=False,
inplace=True)print('Process Data Values
=====') print(ProcessData)
print('=====') # Output Agreement
=====
OutputData=ProcessData
sOutputFileName='C:/VKHCG/05-DS/9999-Data/HORUS-CSV-
Country.csv'OutputData.to_csv(sOutputFileName, index = False)
print('CSV to HORUS - Done')
# Utility done =====
```

OUTPUT :-

| Input Data Volume | | | | | |
|------------------------|-----------------------------|-----|------|-----|--|
| 0 | AEGON LIFE | 5.7 | REF | 4 | |
| 1 | AXA LIFE INSURANCE | 5.8 | ALL | 2.9 | |
| 2 | AXA LIFE | 6.1 | AT&T | 1.8 | |
| 3 | ELIANA LIFE | 6.2 | CIA | 1.2 | |
| 4 | INTERSTATE INSURANCE | 6.3 | EDM | 1.0 | |
| 5 | INTERSTATE INSURANCE | 6.4 | ETL | 1.1 | |
| 6 | WILLIS AND FULTON INSURANCE | 6.5 | HLF | 0.7 | |
| 7 | WILLIS AND FULTON INSURANCE | 6.6 | HPI | 1.0 | |
| 8 | WILLIS AND FULTON INSURANCE | 6.7 | YAH | 0.7 | |
| 9 | WILLIS AND FULTON INSURANCE | 6.8 | ZIMB | 0.8 | |
| 10 | WILLIS AND FULTON INSURANCE | 6.9 | ZPE | 1.0 | |
| [40 rows omitted] | | | | | |
| Previous Data Volume | | | | | |
| [40 rows omitted] | | | | | |
| 0 | AXA LIFE INSURANCE | 5.8 | ALL | 2.9 | |
| 1 | AXA LIFE | 6.1 | AT&T | 1.8 | |
| 2 | ELIANA LIFE | 6.2 | CIA | 1.2 | |
| 3 | INTERSTATE INSURANCE | 6.3 | EDM | 1.0 | |
| 4 | INTERSTATE INSURANCE | 6.4 | ETL | 1.1 | |
| 5 | WILLIS AND FULTON INSURANCE | 6.5 | HLF | 0.7 | |
| 6 | WILLIS AND FULTON INSURANCE | 6.6 | HPI | 1.0 | |
| 7 | WILLIS AND FULTON INSURANCE | 6.7 | YAH | 0.7 | |
| 8 | WILLIS AND FULTON INSURANCE | 6.8 | ZIMB | 0.8 | |
| 9 | WILLIS AND FULTON INSURANCE | 6.9 | ZPE | 1.0 | |
| [40 rows omitted] | | | | | |
| CSV file loaded = True | | | | | |
| END | | | | | |

B. XML to HORUS Format

Code :-

```
# Utility Start XML to HORUS =====
# Standard Tools
import pandas as pd
import xml.etree.ElementTree as ET
def df2xml(data):
    header = data.columns
    root = ET.Element('root')
    for row in range(data.shape[0]):
        entry = ET.SubElement(root,'entry')
        for index in range(data.shape[1]):
            schild=str(header[index])
            child = ET.SubElement(entry, schild)
            if str(data[schild][row]) != 'nan':
                child.text = str(data[schild][row])
            else:
                child.text = 'n/a'
            entry.append(child)
        result = ET.tostring(root)
    return result
def xml2df(xml_data):
    root = ET.XML(xml_data)
    all_records = []
    for i, child in enumerate(root):
        record = { }
        for subchild in child:
            record[subchild.tag] = subchild.text
        all_records.append(record)
    return pd.DataFrame(all_records)
```

```
sInputFileName='C:/VKHCG/05-DS/9999-Data/Country_Code.xml'
InputData = open(sInputFileName).read()
print('=====')
print('Input Data Values =====')
print('=====')
print(InputData)
print('=====')
#=====
#
# Processing Rules =====
#=====
#
ProcessDataXML=InputData
# XML to Data Frame
ProcessData=xml2df(ProcessDataXML)
# Remove columns ISO-2-Code and ISO-3-CODE
ProcessData.drop('ISO-2-CODE', axis=1,inplace=True)
ProcessData.drop('ISO-3-Code', axis=1,inplace=True)
# Rename Country and ISO-M49
ProcessData.rename(columns={'Country': 'CountryName'}, inplace=True)
ProcessData.rename(columns={'ISO-M49': 'CountryNumber'}, inplace=True)
# Set new Index
ProcessData.set_index('CountryNumber', inplace=True)
# Sort data by CurrencyNumber
ProcessData.sort_values('CountryName', axis=0, ascending=False, inplace=True)
print('=====')
print('Process Data Values =====')
print('=====')
print(ProcessData)
print('=====')
OutputData=ProcessData
sOutputFileName='C:/VKHCG/05-DS/9999-Data/HORUS-XML-Country.csv'
OutputData.to_csv(sOutputFileName, index = False)
print('=====')
print('XML to HORUS - Done')
print('=====')
# Utility done =====
```

Output:

```
----- RESTART: C:\VKHCG\05-DS\9999-Data\XML2HORUS.py -----
----- Input Data Values -----
Squeezed text (385 lines).

----- Process Data Values -----
CountryName
CountryNumber
716 Zimbabwe
894 Zambia
887 Yemen
732 Western Sahara
876 Wallis and Futuna Islands
...
16 American Samoa
12 Algeria
5 Albania
248 Aland Islands
4 Afghanistan

[247 rows x 1 columns]

----- XML to HORUS - Done -----
>>>
```

C. JSON to HORUS Format

Code:

```
# Utility Start JSON to HORUS =====
# Standard Tools
#=====
#
# import pandas as pd
# Input Agreement =====
sInputFileName='C:/VKHCG/05-DS/9999-Data/Country_Code.json'
InputData=pd.read_json(sInputFileName, orient='index', encoding="latin-1")
print('Input Data Values =====')
print(InputData)
print('=====')
# Processing Rules =====
ProcessData=InputData
# Remove columns ISO-2-Code and ISO-3-CODE
ProcessData.drop('ISO-2-CODE', axis=1,inplace=True)
ProcessData.drop('ISO-3-Code', axis=1,inplace=True)
# Rename Country and ISO-M49
ProcessData.rename(columns={'Country': 'CountryName'}, inplace=True)
```

```

ProcessData.rename(columns={'ISO-M49': 'CountryNumber'}, inplace=True)
# Set new Index
ProcessData.set_index('CountryNumber', inplace=True)
# Sort data by CurrencyNumber
ProcessData.sort_values('CountryName', axis=0, ascending=False, inplace=True)
print('Process Data Values =====')
print(ProcessData)
print('=====')
# Output Agreement =====
OutputData=ProcessData
sOutputFileName='c:/VKHCG/05-DS/9999-Data/HORUS-JSON-Country.csv'
OutputData.to_csv(sOutputFileName, index = False)
print('JSON to HORUS - Done')
# Utility done =====

```

Output:

```

>>> RESTART: C:\VKHCG\05-DS\9999-Data\JSON2HORUS.py
Input Data Values
   Country ISO-2-Code ISO-3-Code ISO-M49
0  Afghanistan      AF      AFG       4
1  Aland Islands     AX      ALA      248
10  Argentina       AR      ARG       32
100  Hungary        HU      HUN      348
101  Iceland         IS      ISL      352
...
25  Guyana          GY      GUY      328
36  Haiti            HT      HTI      332
97  Beard and McDonald Islands  HM      HMD      334
98  Holy See(Vatican City State) VA      VAT      336
99  Honduras        HN      HND      340
[247 rows x 4 columns]

Process Data Values
   CountryName
CountryNumber
716      Zimbabwe
594      Zambia
887      Yemen
732      Western Sahara
876      Wallis and Futuna Islands
...
16      American Samoa
12      Algeria
8      Albania
248      Aland Islands
4      Afghanistan
[247 rows x 1 columns]

JSON to HORUS - Done
>>>

```

D. MySql Database to HORUS Format Code:

```

# Utility Start Database to HORUS =====
# Standard Tools
#=====

import pandas as pd
import sqlite3 as sq
# Input Agreement =====

sInputFileName='C:/VKHCG/05-DS/9999-Data/utility.db'

```

```
sInputTable='Country_Code'

conn = sq.connect(sInputFileName)
sSQL='select * FROM ' + sInputTable + ';'
InputData=pd.read_sql_query(sSQL, conn)
print('Input Data Values =====')

print(InputData)
print('=====')
# Processing Rules =====
ProcessData=InputData

# Remove columns ISO-2-Code and ISO-3-CODE
ProcessData.drop('ISO-2-CODE', axis=1,inplace=True)
ProcessData.drop('ISO-3-Code', axis=1,inplace=True)
# Rename Country and ISO-M49
ProcessData.rename(columns={'Country': 'CountryName'}, inplace=True)
ProcessData.rename(columns={'ISO-M49': 'CountryNumber'}, inplace=True)
# Set new Index
ProcessData.set_index('CountryNumber', inplace=True)
# Sort data by CurrencyNumber
ProcessData.sort_values('CountryName', axis=0, ascending=False, inplace=True)
print('Process Data Values =====')
print(ProcessData)
print('=====')
# Output Agreement =====
OutputData=ProcessData

sOutputFileName='C:/VKHCG/05-DS/9999-Data/HORUS-CSV-Country.csv'
OutputData.to_csv(sOutputFileName, index = False)
print('Database to HORUS - Done')

# Utility done =====
```

Output:

| ===== RESTART: C:\VKHCG\05-DS\9999-Data\DATABASE3HORUS.py ===== | | | | |
|---|-----------------------------|------------|--------|----|
| Input Data Values ===== | | | | |
| Index | Country ISO-3-Code | ISO-3-Code | ISO-HH | |
| 0 | Afghanistan | AFG | AFG | AF |
| 1 | Aland Islands | ALA | ALA | AA |
| 2 | Albania | ALB | ALB | AL |
| 3 | Algeria | DZA | DZA | DZ |
| 4 | Angola | AGO | AGO | AO |
| .. | ... | ... | ... | .. |
| 281 | Maldives and Future Islands | MV | MVF | MF |
| 282 | Marshall Islands | MH | MHD | MJ |
| 283 | Tunisia | TUN | TUN | TT |
| 284 | Tanzania | TZA | TZA | TA |
| 285 | Zimbabwe | ZWE | ZWE | ZJ |
| 286 | ... | ... | ... | .. |

[247 rows x 5 columns]

| ===== STOCKER Data Values ===== | | |
|---------------------------------|-------|-----------------------------|
| CountryNumber | Label | CountryName |
| 710 | 116 | Zimbabwe |
| 899 | 249 | Zambia |
| 887 | 248 | Tunisia |
| 732 | 249 | Republik Tahiti |
| 976 | 492 | Maldives and Future Islands |

E. Picture (JPEG) to HORUS Format Code:

```
# Utility Start Picture to HORUS =====
# Standard Tools
#=====
=
from scipy.misc import imread
import pandas as pd
import matplotlib.pyplot as plt
import numpy as np
# Input Agreement =====
sInputFileName='C:/VKHCG/05-DS/9999-Data/Angus.jpg'
InputData = imread(sInputFileName, flatten=False, mode='RGBA')
print('Input Data Values =====')
print('X: ',InputData.shape[0])
print('Y: ',InputData.shape[1])
print('RGBA: ', InputData.shape[2])
print('=====')
# Processing Rules =====
ProcessRawData=InputData.flatten()
y=InputData.shape[2] + 2
x=int(ProcessRawData.shape[0]/y)
ProcessData=pd.DataFrame(np.reshape(ProcessRawData, (x, y)))
sColumns= ['XAxis','YAxis','Red', 'Green', 'Blue','Alpha']
ProcessData.columns=sColumns
ProcessData.index.names =[ID]
print('Rows: ',ProcessData.shape[0])
print('Columns :',ProcessData.shape[1])
```

```
print('=====')  
print('Process Data Values =====')  
print('=====')  
plt.imshow(InputData)  
plt.show()  
print('=====')  
# Output Agreement =====  
OutputData=ProcessData  
print('Storing File')  
sOutputFileName='C:/VKHCG/05-DS/9999-Data/HORUS-Picture.csv'  
OutputData.to_csv(sOutputFileName, index = False)  
print('=====')  
print('Picture to HORUS - Done')  
print('=====')
```

Output:



F. Video to HORUS Format

Code:

Movie to Frames

```
# Utility Start Movie to HORUS (Part 1) =====
# Standard Tools
#
#=====
import os
import shutil
import cv2
#
#=====
sInputFileName='C:/VKHCG/05-DS/9999-Data/dog.mp4'
sDataBaseDir='C:/VKHCG/05-DS/9999-Data/temp'
if os.path.exists(sDataBaseDir):
    shutil.rmtree(sDataBaseDir)
if not os.path.exists(sDataBaseDir):
```

```

os.makedirs(sDataBaseDir)
print('=====')
print('Start Movie to Frames')
print('=====')
vidcap = cv2.VideoCapture(sInputFileName)
success,image = vidcap.read()
count = 0
while success:
    success,image = vidcap.read()
    sFrame=sDataBaseDir + str('/dog-frame-' + str(format(count, '04d')))+ '.jpg'
    print('Extracted: ', sFrame)
    cv2.imwrite(sFrame, image)
    if os.path.getsize(sFrame) == 0:
        count += -1
        os.remove(sFrame)
        print('Removed: ', sFrame)
    if cv2.waitKey(10) == 27: # exit if Escape is hit
        break
    count += 1
print('=====')
print('Generated : ', count, ' Frames')
print('=====')
print('Movie to Frames HORUS - Done')
print('=====')
# Utility done =====

```

```

>>> -----
----- RESTART: C:\VKHCG\05-DS\9999-Data\MOVIE2HORUSFrame.py -----
----- Start Movie to Frames -----
Extracted: C:/VKHCG/05-DS/9999-Data/temp/dog-frame-0000.jpg
Extracted: C:/VKHCG/05-DS/9999-Data/temp/dog-frame-0001.jpg
Extracted: C:/VKHCG/05-DS/9999-Data/temp/dog-frame-0002.jpg
Extracted: C:/VKHCG/05-DS/9999-Data/temp/dog-frame-0003.jpg
Extracted: C:/VKHCG/05-DS/9999-Data/temp/dog-frame-0004.jpg
Extracted: C:/VKHCG/05-DS/9999-Data/temp/dog-frame-0005.jpg
Extracted: C:/VKHCG/05-DS/9999-Data/temp/dog-frame-0006.jpg
Extracted: C:/VKHCG/05-DS/9999-Data/temp/dog-frame-0007.jpg
Extracted: C:/VKHCG/05-DS/9999-Data/temp/dog-frame-0008.jpg
Extracted: C:/VKHCG/05-DS/9999-Data/temp/dog-frame-0009.jpg
Extracted: C:/VKHCG/05-DS/9999-Data/temp/dog-frame-0010.jpg
Extracted: C:/VKHCG/05-DS/9999-Data/temp/dog-frame-0099.jpg
Extracted: C:/VKHCG/05-DS/9999-Data/temp/dog-frame-0100.jpg
Extracted: C:/VKHCG/05-DS/9999-Data/temp/dog-frame-0101.jpg
-----
Generated : 101  Frames
-----
Movie to Frames HORUS - Done
----->>> |

```

Now frames are created and need to load them into HORUS.

Frames to Horus

```
# Utility Start Movie to HORUS (Part 2) =====
# Standard Tools
#=====
from scipy.misc import imread
import pandas as pd
import matplotlib.pyplot as plt
import numpy as np
import os
# Input Agreement =====
sDataBaseDir='C:/VKHCG/05-DS/9999-Data/temp'
f=0
for file in os.listdir(sDataBaseDir):
if file.endswith(".jpg"):
f += 1
sInputFileName=os.path.join(sDataBaseDir, file)
print('Process : ', sInputFileName)
InputData = imread(sInputFileName, flatten=False, mode='RGBA')
print('Input Data Values =====')
print('X: ',InputData.shape[0])
print('Y: ',InputData.shape[1])
print('RGB: ', InputData.shape[2])
print('=====')
# Processing Rules =====
ProcessRawData=InputData.flatten()
y=InputData.shape[2] + 2
x=int(ProcessRawData.shape[0]/y)
ProcessFrameData=pd.DataFrame(np.reshape(ProcessRawData, (x, y)))
ProcessFrameData['Frame']=file
print('=====')
print('Process Data Values =====')
print('=====')
plt.imshow(InputData)
plt.show()
if f == 1:
ProcessData=ProcessFrameData
else:
ProcessData=ProcessData.append(ProcessFrameData)
if f > 0:
sColumns= ['XAxis','YAxis','Red', 'Green', 'Blue','Alpha','FrameName']
ProcessData.columns=sColumns
print('=====')
ProcessFrameData.index.names =[ID']
print('Rows: ',ProcessData.shape[0])
print('Columns :',ProcessData.shape[1])
```

```

print('=====')
# Output Agreement =====
OutputData=ProcessData
print('Storing File')
sOutputFileName='C:/VKHCG/05-DS/9999-Data/HORUS-Movie-Frame.csv'
OutputData.to_csv(sOutputFileName, index = False)
print('=====')
print('Processed ; ', f,' frames')
print('=====')
print('Movie to HORUS - Done')
print('=====')

```

Output:

```

=====
Rows: 15667200
Columns : 7
=====
Storing File
=====
Processed ; 102 frames
=====
Movie to HORUS - Done
=====
```



dog-frame-0000.jpeg



dog-frame-0001.jpeg

Check the files from C:\VKHCG\05-DS\9999-Data\temp
The movie clip is converted into 102 picture frames and then to HORUS format

G. Audio to HORUS Format

Code:

```

# Utility Start Audio to HORUS =====
# Standard Tools
#=====
=
```

```

from scipy.io import wavfile
import pandas as pd
import matplotlib.pyplot as plt
import numpy as np
#=====
=
def show_info(aname, a,r):
    print ('.....')
    print ("Audio:", aname)
    print ('.....')
    print ("Rate:", r)
    print ('.....')
    print ("shape:", a.shape)
    print ("dtype:", a.dtype)
    print ("min, max:", a.min(), a.max())
    print ('.....')
    plot_info(aname, a,r)
#=====

=
def plot_info(aname, a,r):
    sTitle= 'Signal Wave - ' + aname + ' at ' + str(r) + 'hz'
    plt.title(sTitle)
    sLegend=[]
    for c in range(a.shape[1]):
        sLabel = 'Ch' + str(c+1)
        sLegend=sLegend+[str(c+1)]
        plt.plot(a[:,c], label=sLabel)
    plt.legend(sLegend)
    plt.show()
#=====

=
sInputFileName='C:/VKHCG/05-DS/9999-Data/2ch-sound.wav'
print('=====')
print('Processing : ', sInputFileName)
print('=====')
InputRate, InputData = wavfile.read(sInputFileName)
show_info("2 channel", InputData,InputRate)
ProcessData=pd.DataFrame(InputData)
sColumns= ['Ch1','Ch2']
ProcessData.columns=sColumns
OutputData=ProcessData
sOutputFileName='C:/VKHCG/05-DS/9999-Data/HORUS-Audio-2ch.csv'
OutputData.to_csv(sOutputFileName, index = False)
#=====

=
sInputFileName='C:/VKHCG/05-DS/9999-Data/4ch-sound.wav'
print('=====')


```

```

print('Processing : ', sInputFileName)
print('=====')
InputRate, InputData = wavfile.read(sInputFileName)
show_info("4 channel", InputData, InputRate)
ProcessData=pd.DataFrame(InputData)
sColumns= ['Ch1','Ch2','Ch3', 'Ch4']
ProcessData.columns=sColumns
OutputData=ProcessData
sOutputFileName='C:/VKHCG/05-DS/9999-Data/HORUS-Audio-4ch.csv'
OutputData.to_csv(sOutputFileName, index = False)
#=====
=
sInputFileName='C:/VKHCG/05-DS/9999-Data/6ch-sound.wav'
print('=====')
print('Processing : ', sInputFileName)
print('=====')
InputRate, InputData = wavfile.read(sInputFileName)
show_info("6 channel", InputData, InputRate)
ProcessData=pd.DataFrame(InputData)
sColumns= ['Ch1','Ch2','Ch3', 'Ch4', 'Ch5','Ch6']
ProcessData.columns=sColumns
OutputData=ProcessData
sOutputFileName='C:/VKHCG/05-DS/9999-Data/HORUS-Audio-6ch.csv'
OutputData.to_csv(sOutputFileName, index = False)
#=====
=
sInputFileName='C:/VKHCG/05-DS/9999-Data/8ch-sound.wav'
print('=====')
print('Processing : ', sInputFileName)
print('=====')
InputRate, InputData = wavfile.read(sInputFileName)
show_info("8 channel", InputData, InputRate)
ProcessData=pd.DataFrame(InputData)
sColumns= ['Ch1','Ch2','Ch3', 'Ch4', 'Ch5','Ch6','Ch7','Ch8']
ProcessData.columns=sColumns
OutputData=ProcessData
sOutputFileName='C:/VKHCG/05-DS/9999-Data/HORUS-Audio-8ch.csv'
OutputData.to_csv(sOutputFileName, index = False)
print('=====')
print('Audio to HORUS - Done')

```

Output:



Practical 3

Utilities and Auditing

A. Fixers Utilities:

Fixers enable your solution to take your existing data and fix a specific quality issue.

```
#----- Program to Demonstrate Fixers utilities -----
```

```
import string
```

```
import datetime as dt
```

1 Removing leading or lagging spaces from a data entry

```
print('#1 Removing leading or lagging spaces from a data entry');
```

```
baddata = " Data Science with too many spaces is bad!!! "
```

```
print('>',baddata,'<')
```

```
cleandata=baddata.strip()
```

```
print('>',cleandata,'<')
```

2 Removing nonprintable characters from a data entry

```
print('#2 Removing nonprintable characters from a data entry')
```

```
printable = set(string.printable)
```

```
baddata = "Data\x00Science with\x02 funny characters is \x10bad!!!"
```

```
cleandata=".join(filter(lambda x: x in string.printable,baddata))
```

```
print('Bad Data : ',baddata);
```

```
print('Clean Data : ',cleandata)
```

3 Reformatting data entry to match specific formatting criteria.

```
# Convert YYYY/MM/DD to DD Month YYYY
```

```
print('# 3 Reformatting data entry to match specific formatting criteria.')
```

```
baddate = dt.date(2019, 10, 31)
```

```
baddata=format(baddate,'%Y-%m-%d')
```

```
gooddate = dt.datetime.strptime(baddata,'%Y-%m-%d')
```

```
gooddata=format(gooddate,'%d %B %Y')
```

```
print('Bad Data : ',baddata)
```

```
print('Good Data : ',gooddata)
```

Output:

```
>>>
=====
      RESTART: C:/Users/User/Desktop/u1.py
=====
#1 Removing leading or lagging spaces from a data entry
> Data Science with too many spaces is bad!!! <
> Data Science with too many spaces is bad!!! <
#2 Removing nonprintable characters from a data entry
Bad Data : Data Science with funny characters is \tbad!!!
Clean Data : DataScience with funny characters is bad!!!
# 3 Reformatting data entry to match specific formatting criteria.
Bad Data : 2019-10-31
Good Data : 31 October 2019
>>> |
```


Ln: 72 Col: 4

B. Data Binning or Bucketing

Binning is a data preprocessing technique used to reduce the effects of minor observation errors. Statistical data binning is a way to group a number of more or less continuous values into a smaller number of “bins.”

Code :

```
import numpy as np
import matplotlib.mlab as mlab
import matplotlib.pyplot as plt
import scipy.stats as stats
np.random.seed(0)
# example data
mu = 90 # mean of distribution
sigma = 25 # standard deviation of distribution
x = mu + sigma * np.random.randn(5000)
num_bins = 25
fig, ax = plt.subplots()
# the histogram of the data
n, bins, patches = ax.hist(x, num_bins, density=1)
# add a 'best fit' line
y = stats.norm.pdf(bins, mu, sigma)
# mlab.normpdf(bins, mu, sigma)
ax.plot(bins, y, '--')
ax.set_xlabel('Example Data')
ax.set_ylabel('Probability density')
sTitle=r'Histogram '+ str(len(x)) +' entries into ' + str(num_bins) + ' Bins: $\mu=' + str(mu) + '$, $\sigma=' + str(sigma) + '$'
ax.set_title(sTitle)
fig.tight_layout()
sPathFig='C:/VKHCG/05-DS/4000-UL/0200-DU/DU-Histogram.png'
fig.savefig(sPathFig)
plt.show()
```

Output:

C. Averaging of Data

The use of averaging of features value enables the reduction of data volumes in a control fashion to improve effective data processing.

C:/VKHCG/05-DS/4000-UL/0200-DU/DU-Mean.py

Code:

```
import pandas as pd
#####
InputFileName='IP_DATA_CORE.csv'
OutputFileName='Retrieve_Router_Location.csv'
Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ')
```

```

print('#####')
sFileName=Base + '/01-Vermeulen/00-RawData/' + InputFileName
print('Loading :',sFileName)
IP_DATA_ALL=pd.read_csv(sFileName,header=0,low_memory=False,
usecols=['Country','Place Name','Latitude','Longitude'], encoding="latin-1")
IP_DATA_ALL.rename(columns={'Place Name': 'Place_Name'}, inplace=True)
AllData=IP_DATA_ALL[['Country', 'Place_Name','Latitude']]
print(AllData)
MeanData=AllData.groupby(['Country', 'Place_Name'])['Latitude'].mean()
print(MeanData)
#####

```

Output:

```

>>> RESTART: C:\VKHCG\05-DS\4000-UL\0200-DU\DU-Mean.py
#####
Working base : C:/VKHCG using
#####
Loading : C:/VKHCG/01-Vermeulen/00-RawData/IP_DATA_CORE.csv
   Country Place_Name  Latitude
0       US  New York    40.7528
1       US  New York    40.7528
2       US  New York    40.7528
3       US  New York    40.7528
4       US  New York    40.7528
...
3557     DE    Munich    48.0915
3558     DE    Munich    48.1833
3559     DE    Munich    48.1000
3560     DE    Munich    48.1480
3561     DE    Munich    48.1480
[3562 rows x 3 columns]
   Country Place_Name  Latitude
DE    Munich    48.143223
GB    London    51.509406
US    New York   40.747044
Name: Latitude, dtype: float64
#####

```

Outlier Detection

Outliers are data that is so different from the rest of the data in the data set that it may be caused by an error in the data source. There is a technique called outlier detection that, with good data science, will identify these outliers.

C:\VKHCG\05-DS\4000-UL\0200-DU\DU-Outliers.py

Code:

```

#####
# -*- coding: utf-8 -*-
#####
import pandas as pd
#####
InputFileName='IP_DATA_CORE.csv'
OutputFileName='Retrieve_Router_Location.csv'
Base='C:/VKHCG'
print('#####')
print('Working Base :',Base)
print('#####')
sFileName=Base + '/01-Vermeulen/00-RawData/' + InputFileName
print('Loading :',sFileName)
IP_DATA_ALL=pd.read_csv(sFileName,header=0,low_memory=False,
usecols=['Country','Place Name','Latitude','Longitude'], encoding="latin-1")
IP_DATA_ALL.rename(columns={'Place Name': 'Place_Name'}, inplace=True)
LondonData=IP_DATA_ALL.loc[IP_DATA_ALL['Place_Name']=='London']
AllData=LondonData[['Country', 'Place_Name','Latitude']]
print('All Data')
print(AllData)
#####

```

```

MeanData=AllData.groupby(['Country', 'Place_Name'])['Latitude'].mean()
StdData=AllData.groupby(['Country', 'Place_Name'])['Latitude'].std()
print('Outliers')
UpperBound=float(MeanData+StdData)
print('Higher than ', UpperBound)
OutliersHigher=AllData[AllData.Latitude>UpperBound]
print(OutliersHigher)
LowerBound=float(MeanData-StdData)
print('Lower than ', LowerBound)
OutliersLower=AllData[AllData.Latitude<LowerBound]
print(OutliersLower)
print('Not Outliers')
OutliersNot=AllData[(AllData.Latitude>=LowerBound) &
(AllData.Latitude<=UpperBound)]
print(OutliersNot)
#####

```

Output:

```

===== RESTART: C:\VKHCG\05-DS\4000-UL\0200-DU\DU-Outliers.py
=====
#####
Working Base : C:/VKHCG
#####
Loading : C:/VKHCG/01-Vermeulen/00-RawData/IP_DATA_CORE.csv
All Data
Country Place_Name Latitude
1910 GB London 51.5130
1911 GB London 51.5508
1912 GB London 51.5649
1913 GB London 51.5895
1914 GB London 51.5232
... ...
[1502 rows x 3 columns]
Outliers
Higher than 51.51263550786781
Country Place_Name Latitude
1910 GB London 51.5130

```

Output:

```

===== RESTART: C:\VKHCG\05-DS\4000-UL\0200-DU\DU-Outliers.py
=====
#####
Working Base : C:/VKHCG
#####
Loading : C:/VKHCG/01-Vermeulen/00-RawData/IP_DATA_CORE.csv
All Data
Country Place_Name Latitude
1910 GB London 51.5130
1911 GB London 51.5508
1912 GB London 51.5649
1913 GB London 51.5895
1914 GB London 51.5232
... ...

```

[1502 rows x 3 columns]

Outliers

Higher than 51.51263550786781

Country Place_Name Latitude

1910 GB London 51.5130

D. Logging

Write a Python / R program for basic logging in data science.

C:\VKHCG\77-Yoke\Yoke_Logging.py

Code:

```
import sys
import os
import logging
import uuid
import shutil
import time
#####
Base='C:/VKHCG'
#####
sCompanies=['01-Vermeulen','02-Krennwallner','03-Hillman','04-Clark']
sLayers=['01-Retrieve','02-Assess','03-Process','04-Transform','05-Organise','06-Report']
sLevels=['debug','info','warning','error']
for sCompany in sCompanies:
    sFileDir=Base + '/' + sCompany
    if not os.path.exists(sFileDir):
        os.makedirs(sFileDir)
    for sLayer in sLayers:
        log sFileDir):
        shutil.rmtree(sFileDir)
        time.sleep(2)
    if not os.path.exists(sFileDir):
        os.makedirs(sFileDir)
        skey=str(uuid.uuid4())
    sLogFile=Base + '/' + sCompany + '/' + sLayer + '/Logging/Logging_' + skey + '.log'
    print('Set up:',sLogFile)
# set up logging to file - see previous section for more details
logging.basicConfig(level=logging.DEBUG,
format='%(asctime)s %(name)-12s %(levelname)-8s %(message)s',
datefmt='%m-%d %H:%M',
filename=sLogFile,
filemode='w')
# define a Handler which writes INFO messages or higher to the sys.stderr
console = logging.StreamHandler()
console.setLevel(logging.INFO)
# set a format which is simpler for console use
formatter = logging.Formatter('%(name)-12s: %(levelname)-8s %(message)s')
# tell the handler to use this format
console.setFormatter(formatter)
# add the handler to the root logger
logging.getLogger().addHandler(console)
```

```
# Now, we can log to the root logger, or any other logger. First the root...
logging.info('Practical Data Science is fun!.')
for sLevel in sLevels:
    sApp='Application-' + sCompany + '-' + sLayer + '-' + sLevel
    logger = logging.getLogger(sApp)
    if sLevel == 'debug':
        logger.debug('Practical Data Science logged a debugging message.')
    if sLevel == 'info':
        logger.info('Practical Data Science logged information message.')
    if sLevel == 'warning':
        logger.warning('Practical Data Science logged a warning message.')
    if sLevel == 'error':
        logger.error('Practical Data Science logged an error message.')
#
```

Output:

```
>>>
=====
RESTART: C:\VKHCG\77-Yoke\Yoke_Logging.py =====
Set up: C:/VKHCG/01-Vermeulen/01-Retrieve/Logging/Logging_61705603-bb6e-47f0-b5a
9-23d42e267311.log
root      : INFO    Practical Data Science is fun!.
Aplication-01-Vermeulen-01-Retrieve-info: INFO    Practical Data Science lo
d information message.
Aplication-01-Vermeulen-01-Retrieve-warning: WARNING  Practical Data Science lo
gged a warning message.
Aplication-01-Vermeulen-01-Retrieve-error: ERROR    Practical Data Science log
ed an error message.
Set up: C:/VKHCG/01-Vermeulen/02-Assess/Logging/Logging_a7fecb9b-4d40-474e-bc2d-
994958d85194.log
```

Practical 4

A. Perform the following data processing using R.

Use R-Studio for the following:

```
>library(readr)
Warning message: package „readr“ was built under R version 3.4.4
Load a table named IP_DATA_ALL.csv.
>IP_DATA_ALL <- read_csv("C:/VKHCG/01-Vermeulen/00-
RawData/IP_DATA_ALL.csv")
Parsed with column specification:
cols(
  ID = col_double(),
  Country = col_character(),
  `Place Name` = col_character(),
  `Post Code` = col_double(),
  Latitude = col_double(),
  Longitude = col_double(),
  `First IP Number` = col_double(),
  `Last IP Number` = col_double()
)
>View(IP_DATA_ALL)
>spec(IP_DATA_ALL)
cols(
  ID = col_double(),
  Country = col_character(),
  `Place Name` = col_character(),
  `Post Code` = col_double(),
  Latitude = col_double(),
  Longitude = col_double(),
  `First IP Number` = col_double(),
  `Last IP Number` = col_double()
)
```

This informs you that you have the following eight columns:

- ID of type integer
- Place name of type character
- Post code of type character
- Latitude of type numeric double
- Longitude of type numeric double
- First IP number of type integer
- Last IP number of type integer

```
>library(tibble)
```

```
>set_tidy_names(IP_DATA_ALL, syntactic = TRUE, quiet = FALSE)
```

New names:

Place Name -> Place.Name

Post Code -> Post.Code

First IP Number -> First.IP.Number

Last IP Number -> Last.IP.Number

This informs you that four of the field names are not valid and suggests new field names that are valid. You can fix any detected invalid column names by executing

```
IP_DATA_ALL_FIX=set_tidy_names(IP_DATA_ALL, syntactic = TRUE, quiet = TRUE)
```

By using command View(IP_DATA_ALL_FIX), you can check that you have fixed the columns. The new table IP_DATA_ALL_FIX.csv will fix the invalid column names with valid names.

```
>sapply(IP_DATA_ALL_FIX, typeof)
ID Country Place.Name Post.Code Latitude
"double" "character" "character" "double" "double"
Longitude First.IP.Number Last.IP.Number
"double" "double" "double"
>library(data.table)
>hist_country=data.table(Country=unique(IP_DATA_ALL_FIX[is.na(IP_DATA_ALL_FIX
['Country'])] == 0, ]$Country))
>setorder(hist_country,'Country')
>hist_country_with_id=rowid_to_column(hist_country, var = "RowIDCountry")
>View(hist_country_fix)
>IP_DATA_COUNTRY_FREQ=data.table(with(IP_DATA_ALL_FIX, table(Country)))
>View(IP_DATA_COUNTRY_FREQ)
```

| | Country | N |
|---|---------|------|
| 2 | GB | 1502 |
| 3 | US | 1383 |
| 1 | DE | 677 |

- The two biggest subset volumes are from the US and GB.
- The US has just over four times the data as GB.

```
hist_latitude =data.table(Latitude=unique(IP_DATA_ALL_FIX
[is.na(IP_DATA_ALL_with_ID ['Latitude'])] == 0, ]$Latitude))
setkeyv(hist_latitude, 'Latitude')
setorder(hist_latitude)
hist_latitude_with_id=rowid_to_column(hist_latitude, var = "RowID")
View(hist_latitude_with_id)
IP_DATA_Latitude_FREQ=data.table(with(IP_DATA_ALL_FIX,table(Latitude)))
View(IP_DATA_Latitude_FREQ)
```

- The two biggest data volumes are from latitudes 51.5092 and 40.6888.
- The spread appears to be nearly equal between the top-two latitudes.

```
>sapply(IP_DATA_ALL_FIX[, 'Latitude'], min, na.rm=TRUE)
Latitude 40.6888
```

What does this tell you?

Fact: The range of latitude for the Northern Hemisphere is from 0 to 90. So, if you do not have any latitudes farther south than 40.6888, you can improve your retrieve routine.

```
>sapply(IP_DATA_ALL_FIX[, 'Country'], min, na.rm=TRUE)
Country "DE"
```

Minimum business frequency is from DE – Denmark.

```
>sapply(IP_DATA_ALL_FIX[, 'Latitude'], max, na.rm=TRUE)
Latitude
```

```

51.5895
>sapply(IP_DATA_ALL_FIX[, 'Country'], max, na.rm=TRUE)
Country
"US"
The result is 51.5895. What does this tell you?
Fact: The range in latitude for the Northern Hemisphere is from 0 to 90. So, if you do not have any latitudes more northerly than 51.5895, you can improve your retrieve routine.
>sapply(IP_DATA_ALL_FIX [, 'Latitude'], mean, na.rm=TRUE)
Latitude
46.69097
>sapply(IP_DATA_ALL_FIX [, 'Latitude'], median, na.rm=TRUE)
Latitude
48.15
>sapply(IP_DATA_ALL_FIX [, 'Latitude'], range, na.rm=TRUE)
Latitude
[1] 40.6888
[2] 51.5895
>sapply(IP_DATA_ALL_FIX [, 'Latitude'], quantile, na.rm=TRUE)
Latitude
0% 40.6888
25% 40.7588
50% 48.1500
75% 51.5092
100% 51.5895
>sapply(IP_DATA_ALL_FIX [, 'Latitude'], sd, na.rm=TRUE)
Latitude
4.890387
>sapply(IP_DATA_ALL_FIX [, 'Longitude'], sd, na.rm=TRUE)
Longitude
38.01702

```

B. Program to retrieve different attributes of data.

```

##### C:\ VKHCG\01-Vermeulen\01-Retrieve\Retrive_IP_DATA_ALL.py#####
import sys
import os
import pandas as pd
#####
Base='C:/VKHCG'
#####
sFileName=Base + '/01-Vermeulen/00-RawData/IP_DATA_ALL.csv'
print('Loading :',sFileName)
IP_DATA_ALL=pd.read_csv(sFileName,header=0,low_memory=False, encoding="latin-1")
#####
sFileDir=Base + '/01-Vermeulen/01-Retrieve/01-EDS/02-Python'
if not os.path.exists(sFileDir):
    os.makedirs(sFileDir)
print('Rows:', IP_DATA_ALL.shape[0])
print('Columns:', IP_DATA_ALL.shape[1])
print('### Raw Data Set #####')
for i in range(0,len(IP_DATA_ALL.columns)):
    print(IP_DATA_ALL.columns[i],type(IP_DATA_ALL.columns[i]))

```

```

print('### Fixed Data Set #####')
IP_DATA_ALL_FIX=IP_DATA_ALL
for i in range(0,len(IP_DATA_ALL.columns)):
    cNameOld=IP_DATA_ALL_FIX.columns[i] + ''
    cNameNew=cNameOld.strip().replace(" ", ".")
    IP_DATA_ALL_FIX.columns.values[i] = cNameNew
print(IP_DATA_ALL.columns[i],type(IP_DATA_ALL.columns[i]))
#####
#print(IP_DATA_ALL_FIX.head())
#####
print('Fixed Data Set with ID')
IP_DATA_ALL_with_ID=IP_DATA_ALL_FIX
IP_DATA_ALL_with_ID.index.names = ['RowID']
#print(IP_DATA_ALL_with_ID.head())
sFileName2=sFileDir + '/Retrieve_IP_DATA.csv'
IP_DATA_ALL_with_ID.to_csv(sFileName2, index = True, encoding="latin-1")
#####
print('### Done!! #####')
#####

```

Output:

```

Python 3.7.4 Shell
File Edit Shell Debug Options Window Help
>>>
===== RESTART: C:\VKHCG\01-Vermeulen\01-Retrieve\Retrieve-IP_DATA_ALL.py =====
Loading : C:/VKHCG/01-Vermeulen/00-RawData/IP_DATA_ALL.csv
Rows: 3562
Columns: 8
### Raw Data Set #####
ID <class 'str'>
Country <class 'str'>
Place Name <class 'str'>
Post Code <class 'str'>
Latitude <class 'str'>
Longitude <class 'str'>
First IP Number <class 'str'>
Last IP Number <class 'str'>
### Fixed Data Set #####
ID <class 'str'>
Country <class 'str'>
Place.Name <class 'str'>
Post.Code <class 'str'>
Latitude <class 'str'>
Longitude <class 'str'>
First.IP.Number <class 'str'>
Last.IP.Number <class 'str'>
Fixed Data Set with ID
### Done!! #####
>>>
Ln: 494 Col: 22

```

C. Data Pattern

To determine a pattern of the data values, Replace all alphabet values with an uppercase case *A*, all numbers with an uppercase *N*, and replace any spaces with a lowercase letter *b* and all other unknown characters with a lowercase *u*. As a result, “Good Book 101” becomes “AAAAbAAAAbNNNu.” This pattern creation is beneficial for designing any specific assess rules. This pattern view of data is a quick way to identify common patterns or determine standard layouts.

```

library(readr)
library(data.table)
FileName=paste0('c:/VKHCG/01-Vermeulen/00-RawData/IP_DATA_ALL.csv')
IP_DATA_ALL <- read_csv(FileName)
hist_country=data.table(Country=unique(IP_DATA_ALL$Country))
pattern_country=data.table(Country=hist_country$Country,

```

```

PatternCountry=hist_country$Country
oldchar=c(letters,LETTERS)
newchar=replicate(length(oldchar),"A")
for (r in seq(nrow(pattern_country))){
  s=pattern_country[r,]$PatternCountry;
  for (c in seq(length(oldchar)))){
    s=chartr(oldchar[c],newchar[c],s)
  };
  for (n in seq(0,9,1)){
    s=chartr(as.character(n),"N",s)
  };
  s=chartr(" ","b",s)
  s=chartr(".", "u",s)
  pattern_country[r,]$PatternCountry=s;
};
View(pattern_country)

```

| | Country | PatternCountry |
|---|---------|----------------|
| 1 | US | AA |
| 2 | DE | AA |
| 3 | GB | AA |

Example 2: This is a common use of patterns to separate common standards and structures. Pattern can be loaded in separate retrieve procedures. If the same two patterns, NNNNuNNuNN and uuNNuNNuNN, are found, you can send NNNNuNNuNN directly to be converted into a date, while uuNNuNNuNN goes through a quality-improvement process to then route back to the same queue as NNNNuNNuNN, once it complies.

```

library(readr)
library(data.table)
Base='C:/VKHCG'
FileName=paste0(Base,'/01-Vermeulen/00-RawData/IP_DATA_ALL.csv')
IP_DATA_ALL <- read_csv(FileName)
hist_latitude=data.table(Latitude=unique(IP_DATA_ALL$Latitude))
pattern_latitude=data.table(latitude=hist_latitude$Latitude,
  Patternlatitude=as.character(hist_latitude$Latitude))
oldchar=c(letters,LETTERS)
newchar=replicate(length(oldchar),"A")
for (r in seq(nrow(pattern_latitude))){
  s=pattern_latitude[r,]$Patternlatitude;
  for (c in seq(length(oldchar)))){
    s=chartr(oldchar[c],newchar[c],s)
  };
  for (n in seq(0,9,1)){
    s=chartr(as.character(n),"N",s)
  };
  s=chartr(" ","b",s)
  s=chartr("+","u",s)
  s=chartr("-","u",s)
}

```

```

s=chartr(".", "u", s)
pattern_latitude[r,]$Patternlatitude=s;
};
setorder(pattern_latitude,latitude)
View(pattern_latitude[1:3])

```

| | latitude | Patternlatitude |
|---|----------|-----------------|
| 1 | 40.6888 | NNuNNNN |
| 2 | 40.7038 | NNuNNNN |
| 3 | 40.7055 | NNuNNNN |

D. Loading IP_DATA_ALL:

This data set contains all the IP address allocations in the world. It will help you to locate your customers when interacting with them online.

Create a new Python script file and save it as Retrieve-IP_DATA_ALL.py in directory C:\VKHCG\01-Vermeulen\01-Retrieve.

```

#####
#-*- coding: utf-8 -*-
#####
import sys
import os
import pandas as pd
#####
Base='C:/VKHCG'
#####
sFileName=Base + '/01-Vermeulen/00-RawData/IP_DATA_ALL.csv'
print('Loading :',sFileName)
IP_DATA_ALL=pd.read_csv(sFileName,header=0,low_memory=False, encoding="latin-1")
#####
sFileDir=Base + '/01-Vermeulen/01-Retrieve/01-EDS/02-Python'
if not os.path.exists(sFileDir):
    os.makedirs(sFileDir)
print('Rows:', IP_DATA_ALL.shape[0])
print('Columns:', IP_DATA_ALL.shape[1])
print('## Raw Data Set #####')
for i in range(0,len(IP_DATA_ALL.columns)):
    print(IP_DATA_ALL.columns[i],type(IP_DATA_ALL.columns[i]))
print('## Fixed Data Set #####')
IP_DATA_ALL_FIX=IP_DATA_ALL
for i in range(0,len(IP_DATA_ALL.columns)):
    cNameOld=IP_DATA_ALL_FIX.columns[i] + ''
    cNameNew=cNameOld.strip().replace(" ", ".")
    IP_DATA_ALL_FIX.columns.values[i] = cNameNew
print(IP_DATA_ALL.columns[i],type(IP_DATA_ALL.columns[i]))
#print(IP_DATA_ALL_FIX.head())
print('Fixed Data Set with ID')

```

```

IP_DATA_ALL_with_ID=IP_DATA_ALL_FIX
IP_DATA_ALL_with_ID.index.names = ['RowID']
#print(IP_DATA_ALL_with_ID.head())
sFileName2=sFileDir + '/Retrieve_IP_DATA.csv'
IP_DATA_ALL_with_ID.to_csv(sFileName2, index = True, encoding="latin-1")
#####
print('### Done!! #####')
#####
>>>
===== RESTART: C:\VKHCG\01-Vermeulen\01-Retrieve\Retrieve-IP_DATA_ALL.py =====
Loading : C:/VKHCG/01-Vermeulen/00-RawData/IP_DATA_ALL.csv
Rows: 3562
Columns: 8
### Raw Data Set #####
ID <class 'str'>
Country <class 'str'>
Place Name <class 'str'>
Post Code <class 'str'>
Latitude <class 'str'>
Longitude <class 'str'>
First IP Number <class 'str'>
Last IP Number <class 'str'>
### Fixed Data Set #####
ID <class 'str'>
Country <class 'str'>
Place.Name <class 'str'>
Post.Code <class 'str'>
Latitude <class 'str'>
Longitude <class 'str'>
First.IP.Number <class 'str'>
Last.IP.Number <class 'str'>
Fixed Data Set with ID
### Done!! #####
>>>

```

Start your Python editor and create a text file named Retrieve-IP_Routing.py in directory.
C:\VKHCG\01-Vermeulen\01-Retrieve.

```

#####
# -*- coding: utf-8 -*-
#####
import sys
import os
import pandas as pd
from math import radians, cos, sin, asin, sqrt
#####
def haversine(lon1, lat1, lon2, lat2, stype):
"""

Calculate the great circle distance between two points
on the earth (specified in decimal degrees)
"""

# convert decimal degrees to radians
lon1, lat1, lon2, lat2 = map(radians, [lon1, lat1, lon2, lat2])
# haversine formula
dlon = lon2 - lon1
dlat = lat2 - lat1
a = sin(dlat/2)**2 + cos(lat1) * cos(lat2) * sin(dlon/2)**2
c = 2 * asin(sqrt(a))
if stype == 'km':

```

```

r = 6371 # Radius of earth in kilometers
else:
    r = 3956 # Radius of earth in miles
    d=round(c * r,3)
    return d
#####
Base='C:/VKHCG'
#####
sFileName=Base + '/01-Vermeulen/00-RawData/IP_DATA_CORE.csv'
print('Loading :',sFileName)
IP_DATA_ALL=pd.read_csv(sFileName,header=0,low_memory=False,
usecols=['Country','Place Name','Latitude','Longitude'], encoding="latin-1")
#####
sFileDir=Base + '/01-Vermeulen/01-Retrieve/01-EDS/02-Python'
if not os.path.exists(sFileDir):
    os.makedirs(sFileDir)
#####
IP_DATA = IP_DATA_ALL.drop_duplicates(subset=None, keep='first', inplace=False)
IP_DATA.rename(columns={'Place Name': 'Place_Name'}, inplace=True)
IP_DATA1 = IP_DATA
IP_DATA1.insert(0, 'K', 1)
IP_DATA2 = IP_DATA1
#####
print(IP_DATA1.shape)
#####
IP_CROSS=pd.merge(right=IP_DATA1, left=IP_DATA2, on='K')
IP_CROSS.drop('K', axis=1, inplace=True)
IP_CROSS.rename(columns={'Longitude_x': 'Longitude_from', 'Longitude_y':
'Longitude_to'}, inplace=True)
IP_CROSS.rename(columns={'Latitude_x': 'Latitude_from', 'Latitude_y': 'Latitude_to'},
inplace=True)
IP_CROSS.rename(columns={'Place_Name_x': 'Place_Name_from', 'Place_Name_y':
'Place_Name_to'}, inplace=True)
IP_CROSS.rename(columns={'Country_x': 'Country_from', 'Country_y': 'Country_to'},
inplace=True)
#####
IP_CROSS['DistanceBetweenKilometers'] = IP_CROSS.apply(lambda row:
haversine(
row['Longitude_from'],
row['Latitude_from'],
row['Longitude_to'],
row['Latitude_to'],
'km')
,axis=1)
#####
IP_CROSS['DistanceBetweenMiles'] = IP_CROSS.apply(lambda row:
haversine(
row['Longitude_from'],
row['Latitude_from'],
row['Longitude_to'],
row['Latitude_to'],
'miles')
,axis=1)

```

```

print(IP_CROSS.shape)
sFileName2=sFileDir + '/Retrieve_IP_Routing.csv'
IP_CROSS.to_csv(sFileName2, index = False, encoding="latin-1")
#####
print('### Done!! #####')
#####

```

Output:

See the file named Retrieve_IP_Routing.csv in C:\VKHCG\01-Vermeulen\01-Retrieve\01-EDS\02-Python.

| 1 | Country_from | Place_Name_from | Latitude_from | Longitude_from | Country_to | Place_Name_to | Latitude_to | Longitude_to | DistanceBetweenKilometers | DistanceBetweenMiles |
|----|--------------|-----------------|---------------|----------------|------------|---------------|-------------|--------------|---------------------------|----------------------|
| 2 | US | New York | 40.7528 | -73.9725 | US | New York | 40.7528 | -73.9725 | 0 | 0 |
| 3 | US | New York | 40.7528 | -73.9725 | US | New York | 40.7214 | -74.0052 | 4.448 | 2.762 |
| 4 | US | New York | 40.7528 | -73.9725 | US | New York | 40.7662 | -73.9862 | 1.885 | 1.17 |
| 5 | US | New York | 40.7528 | -73.9725 | US | New York | 40.7449 | -73.9782 | 1.001 | 0.622 |
| 6 | US | New York | 40.7528 | -73.9725 | US | New York | 40.7605 | -73.9933 | 1.95 | 1.211 |
| 7 | US | New York | 40.7528 | -73.9725 | US | New York | 40.7588 | -73.968 | 0.767 | 0.476 |
| 8 | US | New York | 40.7528 | -73.9725 | US | New York | 40.7637 | -73.9727 | 1.212 | 0.753 |
| 9 | US | New York | 40.7528 | -73.9725 | US | New York | 40.7553 | -73.9924 | 1.699 | 1.055 |
| 10 | US | New York | 40.7528 | -73.9725 | US | New York | 40.7308 | -73.9975 | 3.228 | 2.004 |
| 11 | US | New York | 40.7528 | -73.9725 | US | New York | 40.7694 | -73.9609 | 2.088 | 1.297 |

Total Records: 22501

So, the distance between a router in New York (40.7528, -73.9725) to another router in New York (40.7214, -74.0052) is 4.448 kilometers, or 2.762 miles.

Building a Diagram for the Scheduling of Jobs

Start your Python editor and create a text file named Retrieve-Router-Location.py in directory.

C:\VKHCG\01-Vermeulen\01-Retrieve.

```

##### Retrieve-Router-Location.py #####
# -*- coding: utf-8 -*-
#####
import sys
import os
import pandas as pd
#####
InputFileName='IP_DATA_CORE.csv'
OutputFileName='Retrieve_Router_Location.csv'
#####
Base='C:/VKHCG'
#####
sFileName=Base + '/01-Vermeulen/00-RawData/' + InputFileName
print('Loading :',sFileName)
IP_DATA_ALL=pd.read_csv(sFileName,header=0,low_memory=False,
usecols=['Country','Place Name','Latitude','Longitude'], encoding="latin-1")
#####
IP_DATA_ALL.rename(columns={'Place Name': 'Place_Name'}, inplace=True)
#####
sFileDir=Base + '/01-Vermeulen/01-Retrieve/01-EDS/02-Python'

```

```

if not os.path.exists(sFileDir):
    os.makedirs(sFileDir)
ROUTERLOC = IP_DATA_ALL.drop_duplicates(subset=None, keep='first', inplace=False)
print('Rows :',ROUTERLOC.shape[0])
print('Columns :',ROUTERLOC.shape[1])
sFileName2=sFileDir + '/' + OutputFileName
ROUTERLOC.to_csv(sFileName2, index = False, encoding="latin-1")
#####
print('## Done!! #####')
#####

```

Output:

```

>>>
=====
RESTART: C:\VKHCG\01-Vermeulen\01-Retrieve\Retrieve-Router-Location.py ===
Loading : C:/VKHCG/01-Vermeulen/00-RawData/IP_DATA_CORE.csv
Rows : 150
Columns : 4
## Done!! #####

```

See the file named Retrieve_Router_Location.csv in
C:\VKHCG\01-Vermeulen\01-Retrieve\01-EDS\02-Python.

| 1 | Country | Place_Name | Latitude | Longitude |
|----|---------|------------|----------|-----------|
| 2 | US | New York | 40.7528 | -73.9725 |
| 3 | US | New York | 40.7214 | -74.0052 |
| 4 | US | New York | 40.7662 | -73.9862 |
| 5 | US | New York | 40.7449 | -73.9782 |
| 6 | US | New York | 40.7605 | -73.9933 |
| 7 | US | New York | 40.7588 | -73.968 |
| 8 | US | New York | 40.7637 | -73.9727 |
| 9 | US | New York | 40.7553 | -73.9924 |
| 10 | US | New York | 40.7308 | -73.9975 |

Krennwallner AG

The company has two main jobs in need of your attention:

- *Picking content for billboards*: I will guide you through the data science required to pick advertisements for each billboard in the company.
- *Understanding your online visitor data*: I will guide you through the evaluation of the web traffic to the billboard's online web servers.

Picking Content for Billboards

Start your Python editor and create a text file named Retrieve-DE-Billboard-Locations.py in directory.

```

C:\VKHCG\02-Krennwallner\01-Retrieve.
#####
# Retrieve-DE-Billboard-Locations.py #####
# -*- coding: utf-8 -*-
#####
import sys
import os
import pandas as pd
#####

```

```

InputFileName='DE_Billboard_Locations.csv'
OutputFileName='Retrieve_DE_Billboard_Locations.csv'
Company='02-Krennwallner'
#####
Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
#####
Base='C:/VKHCG'
sFileName=Base + '/' + Company + '/00-RawData/' + InputFileName
print('Loading :',sFileName)
IP_DATA_ALL=pd.read_csv(sFileName,header=0,low_memory=False,
usecols=['Country','PlaceName','Latitude','Longitude'])
IP_DATA_ALL.rename(columns={'PlaceName': 'Place_Name'}, inplace=True)
#####
sFileDir=Base + '/' + Company + '/01-Retrieve/01-EDS/02-Python'
if not os.path.exists(sFileDir):
    os.makedirs(sFileDir)
ROUTERLOC = IP_DATA_ALL.drop_duplicates(subset=None, keep='first', inplace=False)
print('Rows :',ROUTERLOC.shape[0])
print('Columns :',ROUTERLOC.shape[1])
sFileName2=sFileDir + '/' + OutputFileName
ROUTERLOC.to_csv(sFileName2, index = False)
#####
print('## Done!! #####')
#####

```

>>>

```

RESTART: C:\VKHCG\02-Krennwallner\01-Retrieve\Retrieve-DE-Billboard-Locations.py
#####
Working Base : C:/VKHCG  using  win32
#####
Loading : C:/VKHCG/02-Krennwallner/00-RawData/DE_Billboard_Locations.csv
Rows : 8873
Columns : 4
## Done!! #####

```

See the file named Retrieve_Router_Location.csv in
C:\VKHCG\02-Krennwallner\01-Retrieve\01-EDS\02-Python.

| 1 | Country | Place_Name | Latitude | Longitude |
|----|---------|------------|----------|-----------|
| 2 | US | New York | 40.7528 | -73.9725 |
| 3 | US | New York | 40.7214 | -74.0052 |
| 4 | US | New York | 40.7662 | -73.9862 |
| 5 | US | New York | 40.7449 | -73.9782 |
| 6 | US | New York | 40.7605 | -73.9933 |
| 7 | US | New York | 40.7588 | -73.968 |
| 8 | US | New York | 40.7637 | -73.9727 |
| 9 | US | New York | 40.7553 | -73.9924 |
| 10 | US | New York | 40.7308 | -73.9975 |

Understanding Your Online Visitor Data

Let's retrieve the visitor data for the billboard we have in Germany.

Several times it was found that common and important information is buried somewhere in the company's various data sources. Investigating any direct suppliers or consumers' upstream or downstream data sources attached to the specific business process is necessary. That is part of your skills that you are applying to data science. Numerous insightful fragments of information was found in the data sources surrounding a customer's business processes.

Start your Python editor and create a file named Retrieve-Online-Visitor.py in directory C:\VKHCG\02-Krennwallner\01-Retrieve.

```
#####
# -*- coding: utf-8 -*-
#####
import sys
import os
import pandas as pd
import gzip as gz
#####
InputFileName='IP_DATA_ALL.csv'
OutputFileName='Retrieve_Online_Visitor'
CompanyIn= '01-Vermeulen'
CompanyOut= '02-Krennwallner'
#####
Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
#####
Base='C:/VKHCG'
sFileName=Base + '/' + CompanyIn + '/00-RawData/' + InputFileName
print('Loading :',sFileName)
IP_DATA_ALL=pd.read_csv(sFileName,header=0,low_memory=False,
usecols=['Country','Place Name','Latitude','Longitude','First IP Number','Last IP Number'])
IP_DATA_ALL.rename(columns={'Place Name': 'Place_Name'}, inplace=True)
IP_DATA_ALL.rename(columns={'First IP Number': 'First_IP_Number'}, inplace=True)
IP_DATA_ALL.rename(columns={'Last IP Number': 'Last_IP_Number'}, inplace=True)
#####
sFileDir=Base + '/' + CompanyOut + '/01-Retrieve/01-EDS/02-Python'
if not os.path.exists(sFileDir):
```

```

os.makedirs(sFileDir)
visitordata = IP_DATA_ALL.drop_duplicates(subset=None, keep='first', inplace=False)
visitordata10=visitordata.head(10)
print('Rows :',visitordata.shape[0])
print('Columns :',visitordata.shape[1])
print('Export CSV')
sFileName2=sFileDir + '/' + OutputFileName + '.csv'
visitordata.to_csv(sFileName2, index = False)
print('Store All:',sFileName2)
sFileName3=sFileDir + '/' + OutputFileName + '_10.csv'
visitordata10.to_csv(sFileName3, index = False)
print('Store 10:',sFileName3)
of Commerce 2019 – 20
print('Loading :,sFileName)
IP_DATA_ALL=pd.read_csv(sFileName,header=0,low_memory=False,
usecols=['Country','Place Name','Latitude','Longitude','First IP Number','Last IP Number'])
IP_DATA_ALL.rename(columns={'Place Name': 'Place_Name'}, inplace=True)
IP_DATA_ALL.rename(columns={'First IP Number': 'First_IP_Number'}, inplace=True)
IP_DATA_ALL.rename(columns={'Last IP Number': 'Last_IP_Number'}, inplace=True)
#####
sFileDir=Base + '/' + CompanyOut + '/01-Retrieve/01-EDS/02-Python'
if not os.path.exists(sFileDir):
os.makedirs(sFileDir)
visitordata = IP_DATA_ALL.drop_duplicates(subset=None, keep='first', inplace=False)
visitordata10=visitordata.head(10)
print('Rows :,visitordata.shape[0])
print('Columns :,visitordata.shape[1])
print('Export CSV')
sFileName2=sFileDir + '/' + OutputFileName + '.csv'
visitordata.to_csv(sFileName2, index = False)
print('Store All:',sFileName2)
sFileName3=sFileDir + '/' + OutputFileName + '_10.csv'
visitordata10.to_csv(sFileName3, index = False)
print('Store 10:',sFileName3)
for z in ['gzip', 'bz2', 'xz']:
if z == 'gzip':
sFileName4=sFileName2 + '.gz'
else:
sFileName4=sFileName2 + '.' + z
visitordata.to_csv(sFileName4, index = False, compression=z)
print('Store :,sFileName4)
#####
print('Export JSON')
for sOrient in ['split','records','index', 'columns','values','table']:
sFileName2=sFileDir + '/' + OutputFileName + '_' + sOrient + '.json'
visitordata.to_json(sFileName2,orient=sOrient,force_ascii=True)
print('Store All:',sFileName2)
sFileName3=sFileDir + '/' + OutputFileName + '_10_' + sOrient + '.json'
visitordata10.to_json(sFileName3,orient=sOrient,force_ascii=True)
print('Store 10:',sFileName3)
sFileName4=sFileName2 + '.gz'
file_in = open(sFileName2, 'rb')
file_out = gz.open(sFileName4, 'wb')

```

```

file_out.writelines(file_in)
file_in.close()
file_out.close()
print('Store GZIP All:',sFileName4)
sFileName5=sFileDir + '/' + OutputFileName + '_' + sOrient + '_UnGZip.json'
file_in = gz.open(sFileName4, 'rb')
file_out = open(sFileName5, 'wb')
file_out.writelines(file_in)
file_in.close()
file_out.close()
print('Store UnGZIP All:',sFileName5)
#####
print('## Done!! #####')
#####

```

Output:

```

== RESTART: C:\VKHCG\02-Krennwallner\01-Retrieve\Retrieve-Online-Visitor.py ==
#####
Working Base : C:/VKHCG using win32
#####
Loading : C:/VKHCG/01-Vermeulen/00-RawData/IP_DATA_ALL.csv
Rows : 3562
Columns : 6
Export CSV
Store All: C:/VKHCG/02-Krennwallner/01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor.csv
Store 10: C:/VKHCG/02-Krennwallner/01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor_10.csv
Store : C:/VKHCG/02-Krennwallner/01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor.csv.gz
Store : C:/VKHCG/02-Krennwallner/01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor.csv.bz2
Store : C:/VKHCG/02-Krennwallner/01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor.csv.xz
Export JSON
Store All: C:/VKHCG/02-Krennwallner/01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor_split.json
Store 10: C:/VKHCG/02-Krennwallner/01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor_10_split.json
Store GZIP All: C:/VKHCG/02-Krennwallner/01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor_split.json.gz
Store UnGZIP All: C:/VKHCG/02-Krennwallner/01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor_split_UngZip.json
Store All: C:/VKHCG/02-Krennwallner/01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor_records.json
Store 10: C:/VKHCG/02-Krennwallner/01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor_10_records.json
Store GZIP All: C:/VKHCG/02-Krennwallner/01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor_records.json.gz
Store UnGZIP All: C:/VKHCG/02-Krennwallner/01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor_records_UngZip.json
Store All: C:/VKHCG/02-Krennwallner/01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor_index.json
Store 10: C:/VKHCG/02-Krennwallner/01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor_10_index.json
Store GZIP All: C:/VKHCG/02-Krennwallner/01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor_index.json.gz
Store UnGZIP All: C:/VKHCG/02-Krennwallner/01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor_index_UngZip.json
Store All: C:/VKHCG/02-Krennwallner/01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor_columns.json
Store 10: C:/VKHCG/02-Krennwallner/01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor_10_columns.json
Store GZIP All: C:/VKHCG/02-Krennwallner/01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor_columns.json.gz
Store UnGZIP All: C:/VKHCG/02-Krennwallner/01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor_columns_UngZip.json
Store All: C:/VKHCG/02-Krennwallner/01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor_values.json

```

See the file named Retrieve_Online_Visitor.csv in
C:\VKHCG\02-Krennwallner\01-Retrieve\01-EDS\02-Python

| | A | B | C | D | E | F |
|----|---------|------------|----------|-----------|-----------------|----------------|
| 1 | Country | Place_Name | Latitude | Longitude | First_IP_Number | Last_IP_Number |
| 2 | US | New York | 40.6888 | -74.0203 | 400887248 | 400887263 |
| 3 | US | New York | 40.6888 | -74.0203 | 400904512 | 400904543 |
| 4 | US | New York | 40.6888 | -74.0203 | 401402080 | 401402095 |
| 5 | US | New York | 40.6888 | -74.0203 | 402261072 | 402261087 |
| 6 | US | New York | 40.6888 | -74.0203 | 402288032 | 402288047 |
| 7 | US | New York | 40.6888 | -74.0203 | 641892352 | 641900543 |
| 8 | US | New York | 40.6888 | -74.0203 | 644464896 | 644465151 |
| 9 | US | New York | 40.6888 | -74.0203 | 758770912 | 758770927 |
| 10 | US | New York | 40.6888 | -74.0203 | 1075972352 | 1075975167 |

You can also see the following JSON files of only ten records.

XML processing.

Start Python editor and create a file named Retrieve-Online-Visitor-XML.py indirectory C:\VKHCG\02-Krennwallner\01-Retrieve.

```
#####
# -*- coding: utf-8 -*-
#####
import sys
import os
import pandas as pd
import xml.etree.ElementTree as ET
#####
def df2xml(data):
    header = data.columns
    root = ET.Element('root')
    for row in range(data.shape[0]):
        entry = ET.SubElement(root,'entry')
        for index in range(data.shape[1]):
            schild=str(header[index])
            child = ET.SubElement(entry, schild)
            if str(data[schild][row]) != 'nan':
                child.text = str(data[schild][row])
            else:
                child.text = 'n/a'
            entry.append(child)
        result = ET.tostring(root)
    return result
#####
def xml2df(xml_data):
    root = ET.XML(xml_data)
    all_records = []
    for i, child in enumerate(root):
        record = { }
        for subchild in child:
            record[subchild.tag] = subchild.text
        all_records.append(record)
```

```


return pd.DataFrame(all_records)
#####
InputFileName='IP_DATA_ALL.csv'
OutputFileName='Retrieve_Online_Visitor.xml'
CompanyIn= '01-Vermeulen'
CompanyOut= '02-Krennwallner'
#####
if sys.platform == 'linux':
    Base=os.path.expanduser('~') + '/VKHCG'
else:
    Base='C:/VKHCG'
#####
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
#####
sFileName=Base + '/' + CompanyIn + '00-RawData/' + InputFileName
print('Loading :',sFileName)
IP_DATA_ALL=pd.read_csv(sFileName,header=0,low_memory=False)
IP_DATA_ALL.rename(columns={'Place Name': 'Place_Name'}, inplace=True)
IP_DATA_ALL.rename(columns={'First IP Number': 'First_IP_Number'}, inplace=True)
IP_DATA_ALL.rename(columns={'Last IP Number': 'Last_IP_Number'}, inplace=True)
IP_DATA_ALL.rename(columns={'Post Code': 'Post_Code'}, inplace=True)
#####
sFileDir=Base + '/' + CompanyOut + '01-Retrieve/01-EDS/02-Python'
if not os.path.exists(sFileDir):
    os.makedirs(sFileDir)
visitorodata = IP_DATA_ALL.head(10000)
print('Original Subset Data Frame')
print('Rows :',visitorodata.shape[0])
print('Columns :',visitorodata.shape[1])
print(visitorodata)
print('Export XML')
sXML=df2xml(visitorodata)
sFileName=sFileDir + '/' + OutputFileName
file_out = open(sFileName, 'wb')
file_out.write(sXML)
file_out.close()
print('Store XML:',sFileName)
xml_data = open(sFileName).read()
unxmlrawdata=xml2df(xml_data)
print('Raw XML Data Frame')
print('Rows :',unxmlrawdata.shape[0])
print('Columns :',unxmlrawdata.shape[1])
print(unxmlrawdata)
unxmldata = unxmlrawdata.drop_duplicates(subset=None, keep='first', inplace=False)
print('Deduplicated XML Data Frame')
print('Rows :',unxmldata.shape[0])
print('Columns :',unxmldata.shape[1])
print(unxmldata)
#print('### Done!! #####')

```

Output:

See a file named Retrieve_Online_Visitor.xml in
 C:\VKHCG\02-Krennwallner\01-Retrieve\01-EDS\02-Python.

This enables you to deliver XML format data as part of the retrieve step.



| Computer > Local Disk (C:) > VKHCG > 02-Krennwallner > 01-Retrieve > 01-EDS > 02-Python | | | | | |
|---|-------------------------------------|--------------------|----------------|------------|--|
| | | Open | Burn | New folder | |
| Writ | Name | Date modified | Type | Size | |
| esktop | Retrieve_Online_Visitor.csv | 10/21/2019 6:55 PM | XZ File | 22 KB | |
| wnloads | Retrieve_Online_Visitor | 10/21/2019 7:07 PM | XML Document | 1,715 KB | |
| cent Places | Retrieve_Online_Visitor_values.json | 10/21/2019 6:55 PM | WinRAR archive | 34 KB | |
| | Retrieve_Online_Visitor.table.json | 10/21/2019 6:55 PM | WinRAR archive | 40 KB | |

```
Working Base : C:/VKHCG using win32
#####
Loading : C:/VKHCG/01-Vermeulen/00-RawData/IP_DATA_ALL.csv
Original Subset Data Frame
Rows : 3562
Columns : 8
ID Country Place_Name ... Longitude First_IP_Number Last_IP_Number
0 1 US New York ... -73.9725 204276480 204276735
1 2 US New York ... -73.9725 301984864 301985791
2 3 US New York ... -73.9725 404678736 404679039
3 4 US New York ... -73.9725 411592704 411592959
4 5 US New York ... -73.9725 416784384 416784639
...
3557 3558 DE Munich ... 11.5392 1591269504 1591269631
3558 3559 DE Munich ... 11.7500 1558374784 1558374911
3559 3560 DE Munich ... 11.4667 1480845312 1480845439
3560 3561 DE Munich ... 11.7434 1480596992 1480597503
3561 3562 DE Munich ... 11.7434 1558418432 1558418943
[3562 rows x 8 columns]
Export XML
Store XML: C:/VKHCG/02-Krennwallner/01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor.xml
Raw XML Data Frame
Rows : 3562
Columns : 8
ID Country Place_Name ... Longitude First_IP_Number Last_IP_Number
0 1 US New York ... -73.9725 204276480 204276735
1 2 US New York ... -73.9725 301984864 301985791
2 3 US New York ... -73.9725 404678736 404679039
3 4 US New York ... -73.9725 411592704 411592959
4 5 US New York ... -73.9725 416784384 416784639
...
3557 3558 DE Munich ... 11.5392 1591269504 1591269631
3558 3559 DE Munich ... 11.75 1558374784 1558374911
3559 3560 DE Munich ... 11.4667 1480845312 1480845439
3560 3561 DE Munich ... 11.7434 1480596992 1480597503
3561 3562 DE Munich ... 11.7434 1558418432 1558418943
[3562 rows x 8 columns]
Deduplicated XML Data Frame
Rows : 3562
Columns : 8
ID Country Place_Name ... Longitude First_IP_Number Last_IP_Number
0 1 US New York ... -73.9725 204276480 204276735
1 2 US New York ... -73.9725 301984864 301985791
2 3 US New York ... -73.9725 404678736 404679039
3 4 US New York ... -73.9725 411592704 411592959
4 5 US New York ... -73.9725 416784384 416784639
...
3557 3558 DE Munich ... 11.5392 1591269504 1591269631
3558 3559 DE Munich ... 11.75 1558374784 1558374911
3559 3560 DE Munich ... 11.4667 1480845312 1480845439
3560 3561 DE Munich ... 11.7434 1480596992 1480597503
3561 3562 DE Munich ... 11.7434 1558418432 1558418943
[3562 rows x 8 columns]
>>>
```



C:\VKHCG\02-Krennwallner\01-Retrieve\01-EDS\...

```
- <root>
  - <entry>
    <ID>1</ID>
    <ID>1</ID>
    <Country>US</Country>
    <Country>US</Country>
    <Place_Name>New York</Place_Name>
    <Place_Name>New York</Place_Name>
    <Post_Code>10017</Post_Code>
    <Post_Code>10017</Post_Code>
    <Latitude>40.7528</Latitude>
    <Latitude>40.7528</Latitude>
    <Longitude>-73.9725</Longitude>
    <Longitude>-73.9725</Longitude>
    <First_IP_Number>204276480</First_IP_Number>
    <First_IP_Number>204276480</First_IP_Number>
    <Last_IP_Number>204276735</Last_IP_Number>
    <Last_IP_Number>204276735</Last_IP_Number>
  </entry>
```

Hillman Ltd

Start your Python editor and create a file named Retrieve-Incoterm-EXW.py in directory C:\VKHCG\03-Hillman\01-Retrieve.

```
import os
import sys
import pandas as pd
IncoTerm='EXW'
InputFileName='Incoterm_2010.csv'
OutputFileName='Retrieve_Incoterm_' + IncoTerm + '_RuleSet.csv'
Company='03-Hillman'
#####
Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
sFileDir=Base + '/' + Company + '/01-Retrieve/01-EDS/02-Python'
if not os.path.exists(sFileDir):
    os.makedirs(sFileDir)
#####
### Import Incoterms
#####
sFileName=Base + '/' + Company + '/00-RawData/' + InputFileName
print('#####')
print('Loading :',sFileName)
IncotermGrid=pd.read_csv(sFileName,header=0,low_memory=False)
IncotermRule=IncotermGrid[IncotermGrid.Shipping_Term == IncoTerm]
print('Rows :',IncotermRule.shape[0])
print('Columns :',IncotermRule.shape[1])
print('#####')
print(IncotermRule)
sFileName=sFileDir + '/' + OutputFileName
IncotermRule.to_csv(sFileName, index = False)
print('## Done!! #####')
```

Output

See the file named Retrieve_Incoterm_EXW.csv in C:\VKHCG\03-Hillman\01-Retrieve\01-EDS\02-Python. Open this file,

```

>>>
===== RESTART: C:\VKHCG\03-Hillman\01-Retrieve\Retrieve-Incoterms-EXW.py =====
#####
Working Base : C:/VKHCG using win32
#####
Loading : C:/VKHCG/03-Hillman/00-RawData/Incoterm_2010.csv
Rows : 1
Columns : 9
#####
    Shipping_Term Seller Carrier Port_From ... Port_To Terminal Named_Place Buyer
0          EXW   Seller   Buyer     Buyer ...     Buyer     Buyer      Buyer  Buyer
[1 rows x 9 columns]
### Done!! #####

```

FCA—Free Carrier (Named Place of Delivery)

```

import os
import sys
import pandas as pd
#####
IncoTerm='FCA'
InputFileName='Incoterm_2010.csv'
OutputFileName='Retrieve_Incoterms_' + IncoTerm + '_RuleSet.csv'
Company='03-Hillman'
#####
Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
#####
sFileDir=Base + '/' + Company + '/01-Retrieve/01-EDS/02-Python'
if not os.path.exists(sFileDir):
os.makedirs(sFileDir)
#####
### Import Incoterms
#####
sFileName=Base + '/' + Company + '/00-RawData/' + InputFileName
print('#####')
print('Loading :',sFileName)
IncotermGrid=pd.read_csv(sFileName,header=0,low_memory=False)
IncotermRule=IncotermGrid[IncotermGrid.Shipping_Term == IncoTerm]
print('Rows :',IncotermRule.shape[0])
print('Columns :',IncotermRule.shape[1])
print('#####')
print(IncotermRule)
sFileName=sFileDir + '/' + OutputFileName
IncotermRule.to_csv(sFileName, index = False)
print('## Done!! #####')

```

Output:

```

>>>
===== RESTART: C:\VKHCG\03-Hillman\01-Retrieve\Retrieve-Incoterm-FCA.py =====
#####
Working Base : C:/VKHCG using win32
#####
Loading : C:/VKHCG/03-Hillman/00-RawData/Incoterm_2010.csv
Rows : 1
Columns : 9
#####
   Shipping_Term Seller Carrier Port_From ... Port_To Terminal Named_Place Buyer
1          FCA    Seller   Seller     Buyer ...     Buyer     Buyer      Buyer  Buyer
[1 rows x 9 columns]
### Done!! #####

```

CPT—Carriage Paid To (Named Place of Destination)

C:\VKHCG\03-Hillman\01-Retrieve.

CIP—Carriage and Insurance Paid To (Named Place of Destination) DAT—Delivered at Terminal (Named Terminal at Port or Place of Destination)

DAP—Delivered at Place (Named Place of Destination)

DDP—Delivered Duty Paid (Named Place of Destination)

By this term, the seller is responsible for delivering the goods to the named place in the country of the buyer and pays all costs in bringing the goods to the destination, including import duties and taxes. The seller is not responsible for unloading. This term places the maximum obligations on the seller and minimum obligations on the buyer. No risk or responsibility is transferred to the buyer until delivery of the goods at the named place of destination.

Possible Shipping Routes

There are numerous potential shipping routes available to the company. The retrieve step can generate the potential set, by using a route combination generator. This will give you a set of routes, but it is highly unlikely that you will ship along all of them. It is simply a population of routes that can be used by the data science to find the optimum solution.

Start your Python editor and create a file named Retrieve-Warehouse-Incoterm-Chains.py in directory C:\VKHCG\03-Hillman\01-Retrieve.

Adopt New Shipping Containers

Adopting the best packing option for shipping in containers will require that I introduce a new concept. Shipping of containers is based on a concept reducing the packaging you use down to an optimum set of sizes having the following requirements:

- The product must fit within the box formed by the four sides of a cube.
- The product can be secured using packing foam, which will fill any void volume in the packaging.
- Packaging must fit in shipping containers with zero space gaps.

• Containers can only hold product that is shipped to a single warehouse, shop, or customer.

Start your Python editor and create a text file named Retrieve-Container-Plan.py in directory . C:\VKHCG\03-Hillman\01-Retrieve.

***** Replace pd.DataFrame.from_items with pd.DataFrame.from_dict**

```

import sys
import os
import pandas as pd
#####
ContainerFileName='Retrieve_Container.csv'
BoxFileName='Retrieve_Box.csv'
ProductFileName='Retrieve_Product.csv'
Company='03-Hillman'
#####
Base='C:/VKHCG'

```

```

#####
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
#####
sFileDir=Base + '/' + Company + '/01-Retrieve/01-EDS/02-Python'
if not os.path.exists(sFileDir):
    os.makedirs(sFileDir)
#####
### Create the Containers
#####
containerLength=range(1,21)
containerWidth=range(1,10)
containerHeighth=range(1,6)
containerStep=1
c=0
for l in containerLength:
    for w in containerWidth:
        for h in containerHeighth:
            containerVolume=(l/containerStep)*(w/containerStep)*(h/containerStep)
            c=c+1
            ContainerLine=[['ShipType', ['Container']],
            ('UnitNumber', ('C'+format(c,"06d"))),
            ('Length',(format(round(l,3)," .4f"))),
            ('Width',(format(round(w,3)," .4f"))),
            ('Height',(format(round(h,3)," .4f"))),
            ('ContainerVolume',(format(round(containerVolume,6)," .6f")))]
            if c==1:
                ContainerFrame = pd.DataFrame.from_dict(ContainerLine)
            else:
                ContainerRow = pd.DataFrame.from_dict(ContainerLine)
                ContainerFrame = ContainerFrame.append(ContainerRow)
                ContainerFrame.index.name = 'IDNumber'
            print('#####')
            print('## Container')
            print('#####')
            print('Rows :',ContainerFrame.shape[0])
            print('Columns :',ContainerFrame.shape[1])
            print('#####')
#####
sFileContainerName=sFileDir + '/' + ContainerFileName
ContainerFrame.to_csv(sFileContainerName, index = False)
#####
## Create valid Boxes with packing foam
#####
boxLength=range(1,21)
boxWidth=range(1,21)
boxHeighth=range(1,21)
packThick=range(0,6)
boxStep=10
b=0
for l in boxLength:
    for w in boxWidth:

```

```

for h in boxHeighth:
for t in packThick:
    boxVolume=round((l/boxStep)*(w/boxStep)*(h/boxStep),6)
    productVolume=round(((l-t)/boxStep)*((w-t)/boxStep)*((h-t)/boxStep),6)
    if productVolume > 0:
        b=b+1
        BoxLine=[('ShipType', ['Box']),
                  ('UnitNumber', ('B'+format(b,"06d"))),
                  ('Length',(format(round(l/10,6),"6f"))),
                  ('Width',(format(round(w/10,6),"6f"))),
                  ('Height',(format(round(h/10,6),"6f"))),
                  ('Thickness',(format(round(t/5,6),"6f"))),
                  ('BoxVolume',(format(round(boxVolume,9),"9f"))),
                  ('ProductVolume',(format(round(productVolume,9),"9f")))]
        if b==1:
            BoxFrame = pd.DataFrame.from_dict(BoxLine)
        else:
            BoxRow = pd.DataFrame.from_dict(BoxLine)
            BoxFrame = BoxFrame.append(BoxRow)
            BoxFrame.index.name = 'IDNumber'
            print('#####')
            print('## Box')
            print('#####')
            print('Rows :',BoxFrame.shape[0])
            print('Columns :',BoxFrame.shape[1])
            print('#####')
            #####
            sFileBoxName=sFileDir + '/' + BoxFileName
            BoxFrame.to_csv(sFileBoxName, index = False)
            #####
            ## Create valid Product
            #####
            productLength=range(1,21)
            productWidth=range(1,21)
            productHeighth=range(1,21)
            productStep=10
            p=0
            for l in productLength:
                for w in productWidth:
                    for h in productHeighth:
                        productVolume=round((l/productStep)*(w/productStep)*(h/productStep),6)
                        if productVolume > 0:
                            p=p+1
                            ProductLine=[('ShipType', ['Product']),
                                         ('UnitNumber', ('P'+format(p,"06d"))),
                                         ('Length',(format(round(l/10,6),"6f"))),
                                         ('Width',(format(round(w/10,6),"6f"))),
                                         ('Height',(format(round(h/10,6),"6f"))),
                                         ('ProductVolume',(format(round(productVolume,9),"9f")))]
                            if p==1:
                                ProductFrame = pd.DataFrame.from_dict(ProductLine)
                            else:
                                ProductRow = pd.DataFrame.from_dict(ProductLine)

```

```

ProductFrame = ProductFrame.append(ProductRow)
BoxFrame.index.name = 'IDNumber'
print('#####')
print('## Product')
print('#####')
print('Rows :',ProductFrame.shape[0])
print('Columns :',ProductFrame.shape[1])
print('#####')
#####
sFileProductName=sFileDir + '/' + ProductFileName
ProductFrame.to_csv(sFileProductName, index = False)
#####
#####
print('## Done!! #####')
#####

```

Output:

```

Python 3.7.4 Shell
File Edit Shell Debug Options Window Help
==== RESTART: C:\VKHCG\03-Hillman\01-Retrieve\Retrieve-Container-Plan.py ====
#####
Working Base : C:/VKHCG using win32
#####
## Container
#####
Rows : 5400
Columns : 2
#####
## Box
#####
Rows : 275880
Columns : 2
#####
## Product
#####
Rows : 48000
Columns : 2
#####
## Done!! #####
>>>
Ln: 58 Col: 4

```

Your second simulation is the cardboard boxes for the packing of the products. The requirement is for boxes having a dimension of 100 centimeters × 100 centimeters × 100 centimeters to 2.1 meters × 2.1 meters × 2.1 meters. You can also use between zero and 600 centimeters of packing foam to secure any product in the box.

See the container data file Retrieve_Container.csv and Retrieve_Box.csv in C:\VKHCG\03-Hillman\01-Retrieve\01-EDS\02-Python.

Create a Delivery Route

The model enables you to generate a complex routing plan for the shipping routes of the company. Start your Python editor and create a text file named Retrieve-Route-Plan.py in directory .

C:\VKHCG\03-Hillman\01-Retrieve.

```

import os
import sys
import pandas as pd
from geopy.distance import vincenty
#####
InputFileName='GB_Postcode_Warehouse.csv'
OutputFileName='Retrieve_GB_Warehouse.csv'
Company='03-Hillman'
#####

```

```

Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
#####
sFileDir=Base + '/' + Company + '/01-Retrieve/01-EDS/02-Python'
if not os.path.exists(sFileDir):
    os.makedirs(sFileDir)
#####
sFileName=Base + '/' + Company + '/00-RawData/' + InputFileName
print('#####')
print('Loading :',sFileName)
Warehouse=pd.read_csv(sFileName,header=0,low_memory=False)
WarehouseClean=Warehouse[Warehouse.latitude != 0]
WarehouseGood=WarehouseClean[WarehouseClean.longitude != 0]
WarehouseGood.drop_duplicates(subset='postcode', keep='first', inplace=True)
WarehouseGood.sort_values(by='postcode', ascending=1)
#####
sFileName=sFileDir + '/' + OutputFileName
WarehouseGood.to_csv(sFileName, index = False)
WarehouseLoop = WarehouseGood.head(20)
for i in range(0,WarehouseLoop.shape[0]):
    print('Run :',i,' =====>>>>>>',WarehouseLoop['postcode'][i])
    WarehouseHold = WarehouseGood.head(10000)
    WarehouseHold['Transaction']=WarehouseHold.apply(lambda row:
    'WH-to-WH'
    ,axis=1)
    OutputLoopName='Retrieve_Route_' + 'WH-' + WarehouseLoop['postcode'][i] + '_Route.csv'
    WarehouseHold['Seller']=WarehouseHold.apply(lambda row:
    'WH-' + WarehouseLoop['postcode'][i]
    ,axis=1)
    WarehouseHold['Seller_Latitude']=WarehouseHold.apply(lambda row:
    WarehouseHold['latitude'][i],axis=1)
    WarehouseHold['Seller_Longitude']=WarehouseHold.apply(lambda row:
    WarehouseLoop['longitude'][i],axis=1)
    WarehouseHold['Buyer']=WarehouseHold.apply(lambda row:
    'WH-' + row['postcode'],axis=1)
    WarehouseHold['Buyer_Latitude']=WarehouseHold.apply(lambda row:
    row['latitude'],axis=1)
    WarehouseHold['Buyer_Longitude']=WarehouseHold.apply(lambda row:
    row['longitude'],axis=1)
    WarehouseHold['Distance']=WarehouseHold.apply(lambda row: round(
    vincenty((WarehouseLoop['latitude'][i],WarehouseLoop['longitude'][i]),
    (row['latitude'],row['longitude'])).miles,6),axis=1)
    WarehouseHold.drop('id', axis=1, inplace=True)
    WarehouseHold.drop('postcode', axis=1, inplace=True)
    WarehouseHold.drop('latitude', axis=1, inplace=True)
    WarehouseHold.drop('longitude', axis=1, inplace=True)
#####
sFileLoopName=sFileDir + '/' + OutputLoopName
WarehouseHold.to_csv(sFileLoopName, index = False)
#####
print('## Done!! #####')

```

```
#####
#####
```

Output:

```
===== RESTART: C:\VKHCG\03-Hillman\01-Retrieve\Retrieve-Route-Plan.py =====
#####
Working Base : C:/VKHCG using win32
#####
#####
Loading : C:/VKHCG/03-Hillman/00-RawData/GB_Postcode_Warehouse.csv
Run : 0 =====>>>>>> AB10
Run : 1 =====>>>>>>> AB11
Run : 2 =====>>>>>>> AB12
Run : 3 =====>>>>>>> AB13
Run : 4 =====>>>>>>> AB14
Run : 5 =====>>>>>>> AB15
Run : 6 =====>>>>>>> AB16
Run : 7 =====>>>>>>> AB21
Run : 8 =====>>>>>>> AB22
Run : 9 =====>>>>>>> AB23
Run : 10 =====>>>>>>> AB24
Run : 19 =====>>>>>>> AB37
### Done!! #####
>>>
```

See the collection of files similar in format to Retrieve_Route_WH-AB11_Route.csv in C:\VKHCG\03-Hillman\01-Retrieve\01-EDS\02-Python.

| 1 | Transaction | Seller | Seller_Latitude | Seller_Longitude | Buyer | Buyer_Latitude | Buyer_Longitude | Distance |
|---|-------------|---------|-----------------|------------------|---------|----------------|-----------------|----------|
| 2 | WH-to-WH | WH-AB11 | 57.13875 | -2.09089 | WH-AB10 | 57.13514 | -2.11731 | 1.024915 |
| 3 | WH-to-WH | WH-AB11 | 57.13875 | -2.09089 | WH-AB11 | 57.13875 | -2.09089 | 0 |
| 4 | WH-to-WH | WH-AB11 | 57.13875 | -2.09089 | WH-AB12 | 57.101 | -2.1106 | 2.715503 |
| 5 | WH-to-WH | WH-AB11 | 57.13875 | -2.09089 | WH-AB13 | 57.10801 | -2.23776 | 5.922893 |

Global Post Codes

Open RStudio and use R to process the following R script:

Retrieve-Postcode-Global.r

```
library(readr)
All_Countries <- read_delim("C:/VKHCG/03-Hillman/00-RawData/All_Countries.txt",
"\t", col_names = FALSE,
col_types = cols(
X12 = col_skip(),
X6 = col_skip(),
X7 = col_skip(),
X8 = col_skip(),
X9 = col_skip(),
na = "null", trim_ws = TRUE)
write.csv(All_Countries,
file = "C:/VKHCG/03-Hillman/01-Retrieve/01-EDS/01-R/Retrieve_All_Countries.csv")
```

Output:

The program will successfully uploaded a new file named Retrieve_All_Countries.csv, after removing column No. 6, 7, 8, 9 and 12 from All_Countries.txt

| | A | B | C | D | E | F | G | H |
|----|----|----|-------|---|-------|----|----------|----------|
| 1 | | X1 | X2 | X3 | X4 | X5 | X10 | X11 |
| 2 | 1 | x1 | x2 | x3 | x4 | x5 | x10 | x11 |
| 3 | 2 | AD | AD100 | Canillo | | | 42.5833 | 1.6667 |
| 4 | 3 | AD | AD200 | Encamp | | | 42.5333 | 1.6333 |
| 5 | 4 | AD | AD300 | Ordino | | | 42.6 | 1.55 |
| 6 | 5 | AD | AD400 | La Massana | | | 42.5667 | 1.4833 |
| 7 | 6 | AD | AD500 | Andorra la Vella | | | 42.5 | 1.5 |
| 8 | 7 | AD | AD600 | Sant Julià de Lòria | | | 42.4667 | 1.5 |
| 9 | 8 | AD | AD700 | Escaldes-Engordany | | | 42.5 | 1.5667 |
| 10 | 9 | AR | 3636 | POZO CERCADO (EL CHORRO (F), DPTO. RIVADAVIA (S)) | Salta | A | -23.4933 | -61.9267 |
| 11 | 10 | AR | 4123 | LAS SALADAS | Salta | A | -25.7833 | -64.5 |

Clark Ltd

Clark is the financial powerhouse of the group. It must process all the money-related data sources.

Forex-The first financial duty of the company is to perform any foreign exchange trading.

Forex Base Data-Previously, you found a single data source (Euro_ExchangeRates.csv) for forex rates in Clark. Earlier in the chapter, I helped you to create the load, as part of your R processing.

The relevant file is Retrieve_Retrieve_Euro_ExchangeRates.csv in directory

C:\ VKHCG\04-Clark\01-Retrieve\01-EDS\01-R. So, that data is ready.

Financials - Clark generates the financial statements for all the group's companies.

Financial Base Data - You found a single data source (Profit_And_Loss.csv) in Clark for financials and, as mentioned previously, a single data source (Euro_ExchangeRates.csv) for forex rates. The file relevant file is Retrieve_Profit_And_Loss.csv in directory

C:\VKHCG\04-Clark\01-Retrieve\01-EDS\01-R.

Person Base Data

Start Python editor and create a file named Retrieve-PersonData.py in directory .

C:\VKHCG\04-Clark\01-Retrieve.

```
#####
# -*- coding: utf-8 -*-
import sys
import os
import shutil
import zipfile
import pandas as pd
Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
Company='04-Clark'
ZIPFiles=['Data_female-names','Data_male-names','Data_last-names']
for ZIPFile in ZIPFiles:
    InputZIPFile=Base+'/'+Company+'/00-RawData/' + ZIPFile + '.zip'
    OutputDir=Base+'/'+Company+'/01-Retrieve/01-EDS/02-Python/' + ZIPFile
    OutputFile=Base+'/'+Company+'/01-Retrieve/01-EDS/02-Python/Retrieve-' + ZIPFile+'.csv'
    zip_file = zipfile.ZipFile(InputZIPFile, 'r')
    zip_file.extractall(OutputDir)
    zip_file.close()
t=0
```

```

for dirname, dirnames, filenames in os.walk(OutputDir):
    for filename in filenames:
        sCSVFile = dirname + '/' + filename
        t=t+1
        if t==1:
            NameRawData=pd.read_csv(sCSVFile,header=None,low_memory=False)
            NameData=NameRawData
        else:
            NameRawData=pd.read_csv(sCSVFile,header=None,low_memory=False)
            NameData=NameData.append(NameRawData)
            NameData.rename(columns={0 : 'NameValues'},inplace=True)
            NameData.to_csv(OutputFile, index = False)
            shutil.rmtree(OutputDir)
        print('Process: ',InputZIPFile)
        print('### Done!! #####')
This generates three files named
Retrieve-Data_female-names.csv
Retrieve-Data_male-names.csv
Retrieve-Data_last-names.csv

```

```

Python 3.7.4 Shell
File Edit Shell Debug Options Window Help
>>>
===== RESTART: C:/VKHCG/04-Clark/01-Retrieve/Retrieve-PersonData.py =====
#####
Working Base : C:/VKHCG using win32
#####
Process: C:/VKHCG/04-Clark/00-RawData/Data_female-names.zip
Process: C:/VKHCG/04-Clark/00-RawData/Data_male-names.zip
Process: C:/VKHCG/04-Clark/00-RawData/Data_last-names.zip
### Done!! #####
>>> |
Ln: 419 Col: 4

```

Connecting to other Data Sources

A. Program to connect to different data sources.

SQLite:

```

# -*- coding: utf-8 -*-
import sqlite3 as sq
import pandas as pd
Base='C:/VKHCG'
sDatabaseName=Base + '/01-Vermeulen/00-RawData/SQLite/vermeulen.db'
conn = sq.connect(sDatabaseName)
sFileName='C:/VKHCG/01-Vermeulen/01-Retrieve/01-EDS/02-
Python/Retrieve_IP_DATA.csv'
print('Loading :',sFileName)
IP_DATA_ALL_FIX=pd.read_csv(sFileName,header=0,low_memory=False)
IP_DATA_ALL_FIX.index.names = ['RowIDCSV']
sTable='IP_DATA_ALL'
print('Storing :',sDatabaseName,' Table:',sTable)
IP_DATA_ALL_FIX.to_sql(sTable, conn, if_exists="replace")
print('Loading :',sDatabaseName,' Table:',sTable)
TestData=pd.read_sql_query("select * from IP_DATA_ALL;", conn)

```

```

print('#####')
print('## Data Values')
print('#####')
print(TestData)
print('#####')
print('## Data Profile')
print('#####')
print('Rows :', TestData.shape[0])
print('Columns :', TestData.shape[1])
print('#####')
print('## Done!! #####')

```

The screenshot shows a Python 3.7.4 Shell window. The code reads data from a SQLite database and prints it to the console. The output includes the connection details, the data values, and the data profile.

```

Python 3.7.4 Shell
File Edit Shell Debug Options Window Help
>>>
= RESTART: C:/VKHCG/03-Hillman/01-Retrieve/Retrieve-IP_DATA_ALL_2_SQLite.py =
Loading : C:/VKHCG/01-Vermeulen/01-Retrieve/01-EDS/02-Python/Retrieve_IP_DATA.csv
Storing : C:/VKHCG/01-Vermeulen/00-RawData/SQLite/vermeulen.db Table: IP_DATA_ALL
Loading : C:/VKHCG/01-Vermeulen/00-RawData/SQLite/vermeulen.db Table: IP_DATA_ALL
#####
## Data Values
#####
   RowIDCSV  RowID     ID ... Longitude First.IP.Number Last.IP.Number
0          0      0    1 ... -73.9725  204276480    204276735
1          1      1    2 ... -73.9725  301984864    301985791
2          2      2    3 ... -73.9725  404678736    404679039
3          3      3    4 ... -73.9725  411592704    411592959
4          4      4    5 ... -73.9725  416784384    416784639
...
3557      3557  3557  3558 ... 11.5392  1591269504  1591269631
3558      3558  3558  3559 ... 11.7500  1558374784  1558374911
3559      3559  3559  3560 ... 11.4667  1480845312  1480845439
3560      3560  3560  3561 ... 11.7434  1480596992  1480597503
3561      3561  3561  3562 ... 11.7434  1558418432  1558418943
[3562 rows x 10 columns]
#####
## Data Profile
#####
Rows : 3562
Columns : 10
#####
## Done!! #####
>>> | Ln: 107 Col: 4

```

MySQL:

Open MySql

Create a database “DataScience”

Create a python file and add the following code:

```

##### Connection With MySQL #####
import mysql.connector
conn = mysql.connector.connect(host='localhost',
                                database='DataScience',
                                user='root',
                                password='root')
conn.connect()
if(conn.is_connected()):
    print('##### Connection With MySql Established Successfully ##### ')
else:
    print('Not Connected -- Check Connection Properites')

```

The screenshot shows a terminal window with the command `mysqlconnection.py` being run. It prints the connection details and a success message.

```

>>>
RESTART: C:/Users/User/AppData/Local/Programs/Python/Python37-32/mysqlconnection.py
##### Connection With MySql Established Successfully #####
>>>

```

Microsoft Excel

```
#####
##### Retrieve-Country-Currency.py
#####
# -*- coding: utf-8 -*-
#####
import os
import pandas as pd
#####
Base='C:/VKHCG'
#####
sFileDir=Base + '/01-Vermeulen/01-Retrieve/01-EDS/02-Python'
#if not os.path.exists(sFileDir):
#os.makedirs(sFileDir)
#####
CurrencyRawData = pd.read_excel('C:/VKHCG/01-Vermeulen/00-
RawData/Country_Currency.xlsx')
sColumns = ['Country or territory', 'Currency', 'ISO-4217']
CurrencyData = CurrencyRawData[sColumns]
CurrencyData.rename(columns={'Country or territory': 'Country', 'ISO-4217':
'CurrencyCode'}, inplace=True)
CurrencyData.dropna(subset=['Currency'],inplace=True)
CurrencyData['Country'] = CurrencyData['Country'].map(lambda x: x.strip())
CurrencyData['Currency'] = CurrencyData['Currency'].map(lambda x:
x.strip())
CurrencyData['CurrencyCode'] = CurrencyData['CurrencyCode'].map(lambda x:
x.strip())
print(CurrencyData)
print('~~~~~ Data from Excel Sheet Retrieved Successfully ~~~~~ ')
#####
sFileName=sFileDir + '/Retrieve-Country-Currency.csv'
CurrencyData.to_csv(sFileName, index = False)
#####
```

OUTPUT:

| | Country | Currency | CurrencyCode |
|-----|----------------------------|----------------------|--------------|
| 1 | Afghanistan | Afghan afghani | AFN |
| 2 | Akrotiri and Dhekelia (UK) | European euro | EUR |
| 3 | Aland Islands (Finland) | European euro | EUR |
| 4 | Albania | Albanian lek | ALL |
| 5 | Algeria | Algerian dinar | DZD |
| .. | ... | ... | ... |
| 271 | Wake Island (USA) | United States dollar | USD |
| 272 | Wallis and Futuna (France) | CFP franc | XPF |
| 274 | Yemen | Yemeni rial | YER |
| 276 | Zambia | Zambian kwacha | ZMW |
| 277 | Zimbabwe | United States dollar | USD |

[253 rows x 3 columns]

~~~~~ Data from Excel Sheet Retrieved Successfully ~~~~~

>>> |

## PRACTICAL 05

### Assessing Data

#### Assess Superstep

Data quality refers to the condition of a set of qualitative or quantitative variables. Data quality is a multidimensional measurement of the acceptability of specific data sets. In business, data quality is measured to determine whether data can be used as a basis for reliable intelligence extraction for supporting organizational decisions. Data profiling involves observing in your data sources all the viewpoints that the information offers. The main goal is to determine if individual viewpoints are accurate and complete. The Assess superstep determines what additional processing to apply to the entries that are noncompliant.

#### Errors

Typically, one of four things can be done with an error to the data.

1. Accept the Error
2. Reject the Error
3. Correct the Error
4. Create a Default Value

A. Perform error management on the given data using pandas package.

Python pandas package enables several automatic error-management features. File Location:

C:\VKHCG\01-Vermeulen\02-Assess

Missing Values in Pandas:

- i. Drop the Columns Where All Elements Are Missing Values

|    | A  | B      | C      | D      | E      | F      | G      | H      |
|----|----|--------|--------|--------|--------|--------|--------|--------|
| 1  | ID | FieldA | FieldB | FieldC | FieldD | FieldE | FieldF | FieldG |
| 2  | 1  | Good   | Better | Best   | 1024   |        | 10241  | 1      |
| 3  | 2  | Good   |        | Best   | 512    |        | 5121   | 2      |
| 4  | 3  | Good   | Better |        | 256    |        | 256    | 3      |
| 5  | 4  | Good   | Better | Best   |        |        | 211    | 4      |
| 6  | 5  | Good   | Better |        | 64     |        | 6411   | 5      |
| 7  | 6  | Good   |        | Best   | 32     |        | 32     | 6      |
| 8  | 7  |        | Better | Best   | 16     |        | 1611   | 7      |
| 9  | 8  |        |        | Best   | 8      |        | 8111   | 8      |
| 10 | 9  |        |        |        | 4      |        | 41     | 9      |
| 11 | 10 | A      | B      | C      | 2      |        | 21111  | 10     |
| 12 |    |        |        |        |        |        |        | 11     |
| 13 | 10 | Good   | Better | Best   | 1024   |        | 102411 | 12     |
| 14 | 10 | Good   |        | Best   | 512    |        | 512    | 13     |
| 15 | 10 | Good   | Better |        | 256    |        | 2256   | 14     |
| 16 | 10 | Good   | Better | Best   |        |        |        | 15     |
| 17 | 10 | Good   | Better |        | 64     |        | 164    | 16     |
| 18 | 10 | Good   |        | Best   | 32     |        | 32     | 17     |
| 19 | 10 |        | Better | Best   | 16     |        |        | 18     |
| 20 | 10 |        |        | Best   | 8      |        |        | 19     |
| 21 | 10 |        |        |        | 4      |        | 4      | 20     |
| 22 | 10 | A      | B      | C      | 2      |        | 111    | 21     |

Code :

```
##### Assess-Good-Bad-01.py#####
# -*- coding: utf-8 -*-
#####
#
import sys
import os
import pandas as pd
#####
# Base='C:/VKHCG'
#####
# print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
#####
#
sInputFileName='Good-or-Bad.csv'
sOutputFileName='Good-or-Bad-01.csv'Company='01-Vermeulen'
#####
# Base='C:/VKHCG'
#####
#
sFileDir=Base + '/' + Company + '/02-Assess/01-EDS/02-Python'if not
os.path.exists(sFileDir):
os.makedirs(sFileDir)
#####
### Import Warehouse
#####
#
sFileName=Base + '/' + Company + '/00-RawData/' + sInputFileNameprint('Loading
:',sFileName) RawData=pd.read_csv(sFileName,header=0)
print('#####')
print('## Raw Data Values')
print('#####')
print(RawData)
print('#####')
#
print('## Data Profile')
print('#####')
print('Rows :',RawData.shape[0])
print('Columns :',RawData.shape[1])
print('#####')
#####
#
sFileName=sFileDir + '/' + sInputFileNameRawData.to_csv(sFileName, index = False)
#####
#
TestData=RawData.dropna(axis=1, how='all')
#####
#
print('#####')
print('## Test Data Values')
print('#####')
print(TestData)
print('#####')
```

```

#')
print('## Data Profile')
print('#####')
print('Rows :',TestData.shape[0])
print('Columns :',TestData.shape[1])
print('#####')
#####
sFileName=sFileDir + '/' + sOutputFileName
TestData.to_csv(sFileName, index = False)
#####
print('#####')
print('## Done!! #####')
print('#####')
#####
#####
Output:
>>>
===== RESTART: C:\VKHCG\01-Vermeulen\02-Assess\Assess-Good-Bad-01.py
=====
#####
#####
#####
Working Base : C:/VKHCG using
win32
#####
#####
Loading : C:/VKHCG/01-Vermeulen/00-RawData/Good-or-Bad.csv
#####
## Raw Data Values
#####
#####
ID FieldA FieldB FieldC FieldD FieldE
FieldF FieldG0 1.0 Good Better Best 1024.0
NaN 10241.0 1
1 2.0 Good NaN Best 512.0 NaN 5121.0 2
2 3.0 Good Better NaN 256.0 NaN 256.0 3
3 4.0 Good Better Best NaN NaN 211.0 4
4 5.0 Good Better NaN 64.0 NaN 6411.0 5
5 6.0 Good NaN Best 32.0 NaN 32.0 6
6 7.0 NaN Better Best 16.0 NaN 1611.0 7
7 8.0 NaN NaN Best 8.0 NaN 8111.0 8
8 9.0 NaN NaN NaN 4.0 NaN 41.0 9
9 10.0 A B C 2.0 NaN 21111.0 10
10 NaN NaN NaN NaN NaN NaN 11
11 10.0 Good Better Best 1024.0 NaN 102411.0 12
12 10.0 Good NaN Best 512.0 NaN 512.0 13
13 10.0 Good Better NaN 256.0 NaN 1256.0 14
14 10.0 Good Better Best NaN NaN NaN 15
15 10.0 Good Better NaN 64.0 NaN 164.0 16
16 10.0 Good NaN Best 32.0 NaN 322.0 17
17 10.0 NaN Better Best 16.0 NaN 163.0 18
18 10.0 NaN NaN Best 8.0 NaN 844.0 19

```



```
print('## Test Data Values')
print('#####')
print(TestData)
print('#####')
#')
print('## Data Profile')
print('#####')
print('Rows :',TestData.shape[0])
print('Columns :',TestData.shape[1])
print('#####')
#####
sFileName=sFileDir + '/' + sOutputFileName
TestData.to_csv(sFileName, index = False)
#####
print('#####')
print('## Done!! #####')
print('#####')
#####
#####
#####
>>>
===== RESTART: C:\VKHCG\01-Vermeulen\02-Assess\Assess-Good-Bad-02.py
=====
Working Base : C:/VKHCG using win32#####
Loading : C:/VKHCG/01-Vermeulen/00-RawData/Good-or-Bad.csv#####
## Raw Data Values #####
ID FieldA FieldB FieldC FieldD FieldE FieldF FieldG0 1.0 Good Better Best 1024.0 NaN
10241.0 1
1 2.0 Good NaN Best 512.0 NaN 5121.0 2#####
## Data Profile #####
Rows : 21
Columns : 8 #####
## Test Data Values #####
FieldG0 1
1 2 #####
## Data Profile #####
Rows : 21
Columns : 1 #####
### Done!! #####
>>>
iii. Keep Only the Rows That Contain a Maximum of Two Missing Values
##### Assess-Good-Bad-03.py #####
# -*- coding: utf-8 -*-
#####
import sys
import os
import pandas as pd
#####
sInputFileName='Good-or-Bad.csv' sOutputFileName='Good-or-Bad-03.csv' Company='01-Vermeulen' Base='C:/VKHCG'
#####
print('#####')
```

```

print('Working Base :',Base, ' using Windows ~~~~')
print('#####
sFileDir=Base + '/' + Company + '/02-Assess/01-EDS/02-Python'if not
os.path.exists(sFileDir):
os.makedirs(sFileDir)
#####
### Import Warehouse
#####
sFileName=Base + '/' + Company + '/00-RawData/' + sInputFileNameprint('Loading
:',sFileName) RawData=pd.read_csv(sFileName,header=0)
print('#####
print('## Raw Data Values') print('#####
print(RawData) print('#####

```

```

print('## Data Profile') print('#####
print('Rows :,RawData.shape[0]) print('Columns :,RawData.shape[1])
print('#####
sFileName=sFileDir + '/' + sInputFileNameRawData.to_csv(sFileName, index = False)
#####
TestData=RawData.dropna(thresh=2) print('#####
print('## Test Data Values') print('#####
print(TestData) print('#####
print('## Data Profile') print('#####
print('Rows :,TestData.shape[0]) print('Columns :,TestData.shape[1])
print('#####
sFileName=sFileDir + '/' + sOutputFileNameTestData.to_csv(sFileName, index = False)
#####
print('#####
print('## Done!! #####') print('#####

```

**Before**

| A  | B       | C      | D      | E      | F      | G      | H      |
|----|---------|--------|--------|--------|--------|--------|--------|
| 1  | ID      | FieldA | FieldB | FieldC | FieldD | FieldE | FieldF |
| 2  | 3 Good  | Better | Best   | 1024   | 10040  | 1      |        |
| 3  | 2 Good  | Better | Best   | 512    | 5020   | 2      |        |
| 4  | 3 Good  | Better | Best   | 256    | 256    | 3      |        |
| 5  | 4 Good  | Better | Best   | 128    | 128    | 4      |        |
| 6  | 5 Good  | Better | Best   | 64     | 6415   | 5      |        |
| 7  | 6 Good  | Better | Best   | 32     | 32     | 6      |        |
| 8  | 7       | Better | Best   | 16     | 1615   | 7      |        |
| 9  | 8       | Best   | Best   | 8      | 8113   | 8      |        |
| 10 | 9       |        | Best   | 4      | 41     | 9      |        |
| 11 | 10 A    | B      | C      | 2      | 21111  | 10     |        |
| 12 |         |        |        |        | 11     |        |        |
| 13 | 10 Good | Better | Best   | 1024   | 100411 | 12     |        |
| 14 | 10 Good | Best   | Best   | 512    | 512    | 13     |        |
| 15 | 10 Good | Better | Best   | 256    | 1256   | 14     |        |
| 16 | 10 Good | Better | Best   | 128    | 128    | 15     |        |
| 17 | 10 Good | Better | Best   | 64     | 64     | 16     |        |
| 18 | 10 Good | Best   | Best   | 32     | 32     | 17     |        |
| 19 | 10      | Better | Best   | 16     | 16     | 18     |        |
| 20 | 10      | Best   | Best   | 8      | 8      | 19     |        |
| 21 | 10      |        | Best   | 4      | 4      | 20     |        |
| 22 | 10 A    | B      | C      | 2      | 21111  | 21     |        |

**After**

| A  | B       | C      | D      | E      | F      | G      | H      |
|----|---------|--------|--------|--------|--------|--------|--------|
| 1  | ID      | FieldA | FieldB | FieldC | FieldD | FieldE | FieldF |
| 2  | 1 Good  | Better | Best   | 1024   | 10041  | 1      |        |
| 3  | 2 Good  | Better | Best   | 512    | 512    | 2      |        |
| 4  | 3 Good  | Better | Best   | 256    | 256    | 3      |        |
| 5  | 4 Good  | Better | Best   | 128    | 128    | 4      |        |
| 6  | 5 Good  | Better | Best   | 64     | 6411   | 5      |        |
| 7  | 6 Good  | Better | Best   | 32     | 32     | 6      |        |
| 8  | 7       | Better | Best   | 16     | 1613   | 7      |        |
| 9  | 8       | Best   | Best   | 8      | 8111   | 8      |        |
| 10 | 9       |        | Best   | 4      | 41     | 9      |        |
| 11 | 10 A    | B      | C      | 2      | 21111  | 10     |        |
| 12 | 10 Good | Better | Best   | 1024   | 202411 | 12     |        |
| 13 | 10 Good | Best   | Best   | 512    | 512    | 13     |        |
| 14 | 10 Good | Better | Best   | 256    | 1256   | 14     |        |
| 15 | 10 Good | Better | Best   | 128    | 128    | 15     |        |
| 16 | 10 Good | Better | Best   | 64     | 164    | 16     |        |
| 17 | 10 Good | Best   | Best   | 32     | 322    | 17     |        |
| 18 | 10      | Better | Best   | 16     | 163    | 18     |        |
| 19 | 10      | Best   | Best   | 8      | 848    | 19     |        |
| 20 | 10      |        | Best   | 4      | 4555   | 20     |        |
| 21 | 10 A    | B      | C      | 2      | 21111  | 21     |        |

Row with more than two missing values got deleted.

The next step along the route is to generate a full network routing solution for the company, to resolve the data issues in the retrieve data.

B. Write Python / R program to create the network routing diagram from the givendata onrouters.

```
#####
Assess-Network-Routing-Company.py #####
import sys
import os
```

```

import pandas as pd
#####
pd.options.mode.chained_assignment = None

```

```

#####
Base='C:/VKHCG'
#####
print('#####')
print('Working Base :',Base, ' using Windows')
print('#####')
#####
sInputFileName1='01-Retrieve/01-EDS/01-R/Retrieve_Country_Code.csv'
sInputFileName2='01-Retrieve/01-EDS/02-Python/Retrieve_Router_Location.csv'
sInputFileName3='01-Retrieve/01-EDS/01-R/Retrieve_IP_DATA.csv'
#####
sOutputFileName='Assess-Network-Routing-Company.csv'Company='01-Vermeulen'
#####
#####
### Import Country Data
#####
sFileName=Base + '/' + Company + '/' + sInputFileName1
print('#####')
print('Loading :,sFileName) print('#####')
CountryData=pd.read_csv(sFileName,header=0,low_memory=False, encoding="latin-1")
print('Loaded Country:',CountryData.columns.values)
print('#####')
#####
## Assess Country Data
#####
print('#####')
print('Changed :,CountryData.columns.values) CountryData.rename(columns={'Country':
'Country_Name'}, inplace=True) CountryData.rename(columns={'ISO-2-CODE':
'Country_Code'}, inplace=True) CountryData.drop('ISO-M49', axis=1, inplace=True)

CountryData.drop('ISO-3-Code', axis=1, inplace=True)CountryData.drop('RowID', axis=1,
inplace=True) print('To :,CountryData.columns.values)
print('#####')
#####
### Import Company Data
#####
sFileName=Base + '/' + Company + '/' + sInputFileName2
print('#####')
print('Loading :,sFileName) print('#####')
CompanyData=pd.read_csv(sFileName,header=0,low_memory=False, encoding="latin-1")
print('Loaded Company :,CompanyData.columns.values)
print('#####')
#####
## Assess Company Data
#####
print('#####')
print('Changed :,CompanyData.columns.values) CompanyData.rename(columns={'Country':
'Country_Code'}, inplace=True)print('To :,CompanyData.columns.values)
print('#####')
#####
### Import Customer Data
#####
sFileName=Base + '/' + Company + '/' + sInputFileName3
print('#####')

```

```

print('Loading :',sFileName) print('#####')
CustomerRawData=pd.read_csv(sFileName,header=0,low_memory=False,encoding="latin-1")

print('#####')

print('Loaded Customer :',CustomerRawData.columns.values)
print('#####')
#####
CustomerData=CustomerRawData.dropna(axis=0, how='any')
print('#####')
print('Remove Blank Country Code')

print('Reduce Rows from', CustomerRawData.shape[0], ' to ', CustomerData.shape[0])
print('#####')
#####
print('#####')
print('Changed :',CustomerData.columns.values) CustomerData.rename(columns={'Country': 'Country_Code'}, inplace=True) print('To :',CustomerData.columns.values)
print('#####')
#####
print('#####')
print('Merge Company and Country Data')
print('#####')
CompanyNetworkData=pd.merge(CompanyName,
CountryData, how='inner', on='Country_Code'
) #####
print('#####')
print('Change ',CompanyNetworkData.columns.values)for i in
CompanyName.columns.values: j='Company_ '+i
CompanyName.rename(columns={i: j}, inplace=True)print('To ',
CompanyName.columns.values)

print('#####')
#####
#####
sFileDir=Base + '/' + Company + '/02-Assess/01-EDS/02-Python'if not
os.path.exists(sFileDir):
os.makedirs(sFileDir)
#####
sFileName=sFileDir + '/' + sOutputFileName print('#####')
print('Storing :', sFileName) print('#####')
CompanyNetworkData.to_csv(sFileName, index = False, encoding="latin-1")
print('## Done!! #####')

```

**Output:**

Go to C:\VKHCG\01-Vermeulen\02-Assess\01-EDS\02-Python folder and open

Assess-Network-Routing-Company.csv

| A | B           | C                  | D                | E                 |
|---|-------------|--------------------|------------------|-------------------|
| 1 | Any_Country | Company_Place_Name | Company_Latitude | Company_Longitude |
| 2 | US          | New York           | 40.7528          | -73.9725          |
| 3 | US          | New York           | 40.7214          | -74.0052          |
| 4 | US          | New York           | 40.7662          | -73.9862          |
| 5 | US          | New York           | 40.7449          | -73.9782          |
| 6 | US          | New York           | 40.7605          | -73.9933          |
| 7 | US          | New York           | 40.7588          | -73.968           |
| 8 | US          | New York           | 40.7637          | -73.9727          |
| 9 | US          | New York           | 40.7553          | -73.9924          |

Next, Access the the customers location using network router location.

```
#####Assess-Network-Routing-Customer.py
import sys
import os
import pandas as pd
#####
#
pd.options.mode.chained_assignment = None
#####
# Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')

#####
sInputFileName=Base+'01-Vermeulen/02-Assess/01-EDS/02-Python/Assess-
Network_Routing-Customer.csv'
#####
sOutputFileName='Assess-Network-Routing-
Customer.gml'Company='01-Vermeulen'
#####
### Import Country Data
#####
#
sFileName=sInputFileName
print('#####')
print('Loading :',sFileName)
print('#####')
CustomerData=pd.read_csv(sFileName,header=0,low_memory=False,
encoding="latin-1") print('Loaded Country:',CustomerData.columns.values)
print('#####')
print(CustomerData.head())
print('#####')
#') print('## Done!!
#####
print('#####')
#')
```

## Output

### Assess-Network-Routing-Customer.csv

| 1  | 2            | 3                 | 4                 | 5                  | 6                     |
|----|--------------|-------------------|-------------------|--------------------|-----------------------|
| 1  | Key_Customer | Customer_Place_No | Customer_Latitude | Customer_Longitude | Customer_Country_Name |
| 2  | GW           | Gaborone          | -24.9484          | 25.9118            | Botswana              |
| 3  | GW           | Hanotswifi        | -21.3863          | 27.5963            | Botswana              |
| 4  | GW           | Miar              | -19.9833          | 23.4363            | Botswana              |
| 5  | GW           | Molepolole        | -24.4163          | 25.5363            | Botswana              |
| 6  | NE           | Namley            | 15.5397           | 2.1187             | Niger                 |
| 7  | MZ           | Maputo            | -25.9853          | 32.5853            | Mozambique            |
| 8  | MZ           | Tete              | -16.1564          | 31.5867            | Mozambique            |
| 9  | MZ           | Quelimane         | -17.8708          | 30.6863            | Mozambique            |
| 10 | MZ           | Chimba            | -19.3164          | 31.4813            | Mozambique            |
| 11 | MZ           | Matola            | -25.9823          | 32.4593            | Mozambique            |
| 12 | MZ           | Pemba             | -12.9608          | 40.5078            | Mozambique            |
| 13 | MZ           | Lichinga          | -13.3128          | 35.2406            | Mozambique            |
| 14 | MZ           | Musse             | -21.8593          | 30.3473            | Mozambique            |
| 15 | MZ           | Chibuto           | -24.6963          | 33.5308            | Mozambique            |
| 16 | MZ           | Russano Garcia    | -25.4403          | 31.9853            | Mozambique            |
| 17 | GH           | Tema              | 5.4187            | -0.1187            | Ghana                 |
| 18 | GH           | Kumasi            | 6.6833            | -1.8187            | Ghana                 |
| 19 | GH           | Takoradi          | 4.8833            | -1.75              | Ghana                 |
| 20 | GH           | Akroso            | 5.39              | -0.2187            | Ghana                 |

#####

### Assess-Network-Routing-Node.py

```
#####
import sys
import os
import pandas as pd
#####
#
pd.options.mode.chained_assignment = None
#####
# Base='C:/VKHCG'
#####
# print('#####')
print('Working Base :',Base, ' using ',sys.platform)
print('#####')
#####
#
sInputFileName='01-Retrieve/01-EDS/02-Python/Retrieve_IP_DATA.csv'
#####
sOutputFileName='Assess-Network-Routing-
Node.csv'Company='01-Vermeulen'
```

```

#####
### Import IP Data
#####
#
sFileName=Base + '/' + Company + '/' + sInputFileName
print('#####')
print('Loading :,sFileName)
print('#####')
IPData=pd.read_csv(sFileName,header=0,low_memory=False,
encoding="latin-1") print('Loaded IP :, IPData.columns.values)
print('#####')
#####
#### print('#####')
print('Changed
:',IPData.columns.values)
IPData.drop('RowID', axis=1,
inplace=True)IPData.drop('ID',
axis=1, inplace=True)
IPData.rename(columns={'Country': 'Country_Code'},
inplace=True) IPData.rename(columns={'Place.Name':
'Place_Name'}, inplace=True)
IPData.rename(columns={'Post.Code': 'Post_Code'}, inplace=True)
IPData.rename(columns={'First.IP.Number': 'First_IP_Number'},
inplace=True) IPData.rename(columns={'Last.IP.Number':
'Last_IP_Number'}, inplace=True)print('To
:',IPData.columns.values)
print('#####')
#####
#### print('#####')
print('Change
',IPData.columns.values)for i in
IPData.columns.values:
j='Node_'+i
IPData.rename(columns={i: j},
inplace=True)print('To ',
IPData.columns.values)
print('#####')
#####
sFileDir=Base + '/' + Company + '/02-Assess/01-
EDS/02-Python'if not os.path.exists(sFileDir):
os.makedirs(sFileDir)
sFileName=sFileDir + '/' + sOutputFileName
print('#####')
print('Storing :, sFileName)
print('#####')
IPData.to_csv(sFileName, index = False, encoding="latin-1")
#####
print('#####')
print('## Done!! #####')
print('#####') ####
Output:
C:/VKHCG/01-Vermeulen/02-Assess/01-EDS/02-Python/Assess-Network-Routing_Node.csv

```

**Output:**  
**C:\VKHCG\01-Vermeulen\02-Assess\01-EDS\02-Python\Assess-Network-Routing-Node.csv**

| A  | B                 | C               | D              | E             | F              | G                                              |
|----|-------------------|-----------------|----------------|---------------|----------------|------------------------------------------------|
| 1  | Node_Country_Code | Node_Place_Name | Node_Post_Code | Node_Latitude | Node_Longitude | node_code, first_IP_Asnobi Node_Last_IP_Number |
| 2  | BW                | Gablonz         | -24.6864       | 25.9118       | 682763056      | 682791567                                      |
| 3  | BW                | Gablonz         | -24.6868       | 25.9118       | 682763056      | 682791169                                      |
| 4  | BW                | Gablonz         | -24.6864       | 25.9118       | 682763056      | 682790911                                      |
| 5  | BW                | Gablonz         | -24.6864       | 25.9118       | 682763056      | 682790988                                      |
| 6  | BW                | Gablonz         | -24.6864       | 25.9118       | 682763056      | 682790979                                      |
| 7  | BW                | Gablonz         | -24.6864       | 25.9118       | 682763056      | 6827905315                                     |
| 8  | BW                | Gablonz         | -24.6864       | 25.9118       | 682763056      | 682790527                                      |
| 9  | BW                | Gablonz         | -24.6864       | 25.9118       | 682763056      | 682790440                                      |
| 10 | BW                | Gablonz         | -24.6864       | 25.9118       | 682763056      | 682790447                                      |
| 11 | BW                | Gablonz         | -24.6868       | 25.9118       | 700418782      | 700418919                                      |
| 12 | BW                | Gablonz         | -24.6868       | 25.9118       | 700418782      | 700418927                                      |
| 13 | BW                | Gablonz         | -24.6868       | 25.9118       | 700418782      | 700418939                                      |
| 14 | BW                | Gablonz         | -24.6868       | 25.9118       | 700418782      | 700418967                                      |
| 15 | BW                | Gablonz         | -24.6868       | 25.9118       | 700418782      | 1463487743                                     |
| 16 | BW                | Gablonz         | -24.6868       | 25.9118       | 700418782      | 1764209279                                     |
| 17 | NE                | Niarbyl         | 15.5567        | -3.1389       | 699811036      | 699811039                                      |
| 18 | NE                | Niarbyl         | 15.5567        | -3.1389       | 699811036      | 699811039                                      |
| 19 | NE                | Niarbyl         | 15.5567        | -3.1389       | 699811036      | 699811039                                      |
| 20 | NE                | Niarbyl         | 15.5567        | -3.1389       | 701203486      | 701203711                                      |
| 21 | NE                | Niarbyl         | 15.5567        | -3.1389       | 701203486      | 701203711                                      |
| 22 | NE                | Niarbyl         | 15.5567        | -3.1389       | 701203486      | 701203711                                      |
| 23 | NE                | Niarbyl         | 15.5567        | -3.1389       | 701203486      | 701203711                                      |
| 24 | MZ                | Mazurini        | -25.9905       | 32.5892       | 692839459      | 692839459                                      |
| 25 | MZ                | Mazurini        | -25.9905       | 32.5892       | 692839459      | 692839459                                      |

### Directed Acyclic Graph (DAG)

A directed acyclic graph is a specific graph that only has one path through the graph.

c. Write a Python / R program to build directed acyclic graph.

Open your python editor and create a file named Assess-DAG-Location.py in directory C:\VKHCG\01-Vermeulen\02-Assess

```
#####
#####
import networkx as nx

import matplotlib.pyplot
as plt
import sys
import os

import pandas as pd
#####
# Base='C:/VKHCG'
#####
# print('#####')
print('Working Base :',Base, ' using ',sys.platform)
print('#####')
#####
#
sInputFileName='01-Retrieve/01-EDS/02-
Python/Retrieve_Router_Location.csv' sOutputFileName1='Assess-
DAG-Company-Country.png' sOutputFileName2='Assess-DAG-
Company-Country-Place.png'
Company='01-Vermeulen'
#####
#
### Import Company Data
```

```

#####
sFileName=Base + '/' + Company + '/' + sInputFileName
print('#####')
print('Loading :',sFileName)
print('#####')
CompanyData=pd.read_csv(sFileName,header=0,low_memory=False,
encoding="latin-1")print('Loaded Company :',CompanyData.columns.values)
print('#####')
#####
##
print(CompanyData)
print('#####')
print('Rows : ',CompanyData.shape[0])
print('#####')
#####
#####
G1=nx.DiGrap
h()
G2=nx.DiGrap
h()
#####

for i in
range(CompanyData.shape[0]):
G1.add_node(CompanyData['Coun
try'][i])
sPlaceName= CompanyData['Place_Name'][i] + '-' +
CompanyData['Country'][i]G2.add_node(sPlaceName)
print('#####')

for n1 in G1.nodes():

for n2 in G1.nodes():

if n1 != n2:

print('Link :',n1,' to ', n2)
G1.add_edge(n1,n2)
print('#####')
print('#####')
print("Nodes of
graph: ")
print(G1.nodes())
print("Edges of
graph: ")

```

```

print(G1.edges())
print('#####')
#####
sFileDir=Base + '/' + Company + '/02-Assess/01-EDS/02-Python'if not
os.path.exists(sFileDir):
os.makedirs(sFileDir)
#####
sFileName=sFileDir + '/' + sOutputFileName1 print('#####')
print('Storing :, sFileName) print('#####')
nx.draw(G1,pos=nx.spectral_layout(G1),nodecolor='r',edge_color='g',
with_labels=True,node_size=8000, font_size=12)
plt.savefig(sFileName) # save as png plt.show() # display
#####
print('#####')
for n1 in G2.nodes():

for n2 in G2.nodes():

if n1 != n2:

print('Link :,n1, ' to ', n2)G2.add_edge(n1,n2)
print('#####') print('#####')
print("Nodes of graph: ")print(G2.nodes()) print("Edges of graph: ")print(G2.edges())
print('#####')
#####

```

```

sFileDir=Base + '/' + Company + '/02-Assess/01-EDS/02-Python'if not
os.path.exists(sFileDir):
os.makedirs(sFileDir)
#####
sFileName=sFileDir + '/' + sOutputFileName2 print('#####')
print('Storing :, sFileName) print('#####')
nx.draw(G2,pos=nx.spectral_layout(G2),nodecolor='r',edge_color='b',
with_labels=True,node_size=8000, font_size=12)
plt.savefig(sFileName) # save as png plt.show() # display
#####


```

Output: #####  
Rows : 150 #####  
Link : US to DELink : US to GBLink : DE to USLink : DE to GBLink : GB to USLink : GB  
to DE  
#####  
Nodes of graph:

['US', 'DE', 'GB']

Edges of graph:

[('US', 'DE'), ('US', 'GB'), ('DE', 'US'), ('DE', 'GB'), ('GB', 'US'), ('GB', 'DE')]  
#####




Open your Python editor and create a file named Assess-DAG-GPS.py in directory C:\VKHCG\01-Vermeulen\02-Assess.

```

import networkx as nx
import matplotlib.pyplot as plt
import sys
import os
import pandas as pd
Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
sInputFileName='01-Retrieve/01-EDS/02-Python/Retrieve_Router_Location.csv'
sOutputFileName='Assess-DAG-Company-GPS.png'
Company='01-Vermeulen'## Import Company Data
sFileName=Base + '/' + Company + '/' + sInputFileName
print('#####')
print('Loading :',sFileName) print('#####')
CompanyData=pd.read_csv(sFileName,header=0,low_memory=False, encoding="latin-1")
print('Loaded Company :',CompanyData.columns.values)
print('#####')
print(CompanyData) print('#####')
print('Rows : ',CompanyData.shape[0]) print('#####')
G=nx.Graph()
for i in range(CompanyData.shape[0]): nLatitude=round(CompanyData['Latitude'][i],2)
nLongitude=round(CompanyData['Longitude'][i],2)
if nLatitude < 0:
    sLatitude = str(nLatitude*-1) + ' S'
else:
    sLatitude = str(nLatitude) + ' N'
if nLongitude < 0:
    sLongitude = str(nLongitude*-1) + ' W'
else:
    sLongitude = str(nLongitude) + ' E'
sGPS= sLatitude + '-' + sLongitude
G.add_node(sGPS)
print('#####')
for n1 in G.nodes():

    for n2 in G.nodes():
        if n1 != n2:
            print('Link :',n1, ' to ', n2)
            G.add_edge(n1,n2)
print('#####')
print('#####')
print("Nodes of graph: ") print(G.number_of_nodes())
print("Edges of graph: ")
print(G.number_of_edges())
print('#####')
Output:
```

```
==== RESTART: C:\VKHCG\01-Vermeulen\02-Assess\Assess-DAG-GPS-unsmoothed.py
=====
#####
#####
Working Base : C:/VKHCG using win32#####
Loading : C:/VKHCG/01-Vermeulen/01-Retrieve/01-EDS/02-
Python/Retrieve_Router_Location.csv #####
Loaded Company : ['Country' 'Place_Name' 'Latitude' 'Longitude']
#####
Country Place_Name Latitude Longitude0 US New York 40.7528 -73.9725
```



1 US New York 40.7214 -74.0052

D. Write a Python / R program to pick the content for Bill Boards from the givendata.

## Picking Content for Billboards

The basic process required is to combine two sets of data and then calculate the number of visitors per day from the range of IP addresses that access the billboards in Germany.

Bill Board Location: Rows -  
8873 Access Visitors: Rows  
- 75999

Access Location Record: Rows – 1,81,235

Open Python editor and create a file named Assess-DE-

Billboard.py in directory C:\VKHCG\02-Krennwallner\02-Assess

Assess-DE-Billboard.py

```
import sys
```

```
import os
```

```
import sqlite3 as sq
```

```
import pandas as pd
```

```
#####
#Base='C:/VKHCG' print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
#####
sInputFileName1='01-Retrieve/01-EDS/02-Python/Retrieve_DE_Billboard_Locations.csv'
sInputFileName2='01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor.csv'
sOutputFileName='Assess-DE-Billboard-Visitor.csv'
Company='02-Krennwallner'
```

```

#####
sDataBaseDir=Base + '/' + Company + '/02-Assess/SQLite'if not os.path.exists(sDataBaseDir):
os.makedirs(sDataBaseDir)
#####
sDatabaseName=sDataBaseDir + '/krennwallner.db'conn = sq.connect(sDatabaseName)
#####
### Import Billboard Data
#####
sFileName=Base + '/' + Company + '/' + sInputFileName1
print('#####')
print('Loading :,sFileName) print('#####')
BillboardRawData=pd.read_csv(sFileName,header=0,low_memory=False, encoding="latin- 1")
BillboardRawData.drop_duplicates(subset=None, keep='first', inplace=True)
BillboardData=BillboardRawData
print('Loaded Company :,BillboardData.columns.values)
print('#####')
#####
print('#####')
sTable='Assess_BillboardData'
print('Storing :,sDatabaseName,' Table:,sTable) BillboardData.to_sql(sTable, conn,
if_exists="replace")print('#####')
#####
print(BillboardData.head()) print('#####')
print('Rows :,BillboardData.shape[0]) print('#####')
#####
### Import Billboard Data
#####
sFileName=Base + '/' + Company + '/' + sInputFileName2
print('#####')
print('Loading :,sFileName) print('#####')
VisitorRawData=pd.read_csv(sFileName,header=0,low_memory=False, encoding="latin-1")
VisitorRawData.drop_duplicates(subset=None, keep='first', inplace=True)
VisitorData=VisitorRawData[VisitorRawData.Country=='DE']
print('Loaded Company :,VisitorData.columns.values)
print('#####')
#####
print('#####')
sTable='Assess_VisitorData'
print('Storing :,sDatabaseName,' Table:,sTable)

VisitorData.to_sql(sTable, conn, if_exists="replace") print('#####')
#####
print(VisitorData.head()) print('#####')
print('Rows :,VisitorData.shape[0]) print('#####')
#####
print('#####')
sTable='Assess_BillboardVisitorData' print('Loading :,sDatabaseName,' Table:,sTable)
sSQL="select distinct"
sSQL=sSQL+ " A.Country AS BillboardCountry," sSQL=sSQL+ " A.Place_Name AS
BillboardPlaceName," sSQL=sSQL+ " A.Latitude AS BillboardLatitude, " sSQL=sSQL+
A.Longitude AS BillboardLongitude," sSQL=sSQL+ " B.Country AS VisitorCountry,"
sSQL=sSQL+ " B.Place_Name AS VisitorPlaceName," sSQL=sSQL+ " B.Latitude AS
VisitorLatitude, " sSQL=sSQL+ " B.Longitude AS VisitorLongitude,"
sSQL=sSQL+ " (B.Last_IP_Number - B.First_IP_Number) * 365.25 * 24 * 12 AS

```

```

VisitorYearRate"
sSQL=sSQL+ " from"
sSQL=sSQL+ " Assess_BillboardData as A"sSQL=sSQL+ " JOIN "
sSQL=sSQL+ " Assess_VisitorData as B"sSQL=sSQL+ " ON "
sSQL=sSQL+ " A.Country = B.Country"sSQL=sSQL+ " AND "
sSQL=sSQL+ " A.Place_Name = B.Place_Name;"
BillboardVistorsData=pd.read_sql_query(sSQL, conn) print('#####')
#####
print('#####')
sTable='Assess_BillboardVistorsData' print('Storing :,sDatabaseName,'Table:',sTable)
BillboardVistorsData.to_sql(sTable, conn, if_exists="replace") print('#####')
#####
print(BillboardVistorsData.head()) print('#####')
print('Rows : ',BillboardVistorsData.shape[0]) print('#####')
#####
sFileDir=Base + '/' + Company + '/02-Assess/01-EDS/02-Python'if not
os.path.exists(sFileDir):
os.makedirs(sFileDir)
#####
print('#####')
print('Storing :, sFileName) print('#####')
sFileName=sFileDir + '/' + sOutputFileName BillboardVistorsData.to_csv(sFileName, index
= False) print('#####')
#####
print('#####') print('###')
Done!! #####

```

**Output:**

C:\VKHCG\02-Krennwallner\01-Retrieve\01-EDS\02-Python\Retrieve\_Online\_Visitor.csv  
containing, 10,48,576(Ten lack Forty Eight Thousand Five Hundred and Seventy Six  
rows.

| A       | B          | C        | D         | E               | F              |
|---------|------------|----------|-----------|-----------------|----------------|
| Country | Place_Name | Latitude | Longitude | First_IP_Number | Last_IP_Number |
| 2       | BW         | -24.6494 | 25.9119   | 692791056       | 692791567      |
| 2       | BW         | -24.6494 | 25.9119   | 6927911824      | 692791103      |
| 2       | BW         | -24.6494 | 25.9119   | 692790956       | 6927909311     |
| 1048556 | NL         | 52.3556  | 4.9136    | 385939968       | 385940479      |
| 1048557 | NL         | 52.3556  | 4.9136    | 385940128       | 385940153      |
| 1048558 | NL         | 52.3556  | 4.9136    | 385957680       | 3859561093     |
| 1048559 | NL         | 52.3556  | 4.9136    | 386003200       | 3860033867     |
| 1048560 | NL         | 52.3556  | 4.9136    | 386013360       | 386013671      |
| 1048561 | NL         | 52.3556  | 4.9136    | 386013184       | 386013095      |
| 1048562 | NL         | 52.3556  | 4.9136    | 386013725       | 3860135467     |
| 1048563 | NL         | 52.3556  | 4.9136    | 386020352       | 386021375      |
| 1048564 | NL         | 52.3556  | 4.9136    | 386035712       | 3860359807     |
| 1048565 | NL         | 52.3556  | 4.9136    | 386050208       | 3860506479     |
| 1048566 | NL         | 52.3556  | 4.9136    | 386073344       | 3860731998     |
| 1048567 | NL         | 52.3556  | 4.9136    | 386074112       | 386074623      |
| 1048568 | NL         | 52.3556  | 4.9136    | 386079410       | 386079671      |
| 1048569 | NL         | 52.3556  | 4.9136    | 386095612       | 386095853      |
| 1048570 | NL         | 52.3556  | 4.9136    | 386105610       | 386109017      |
| 1048571 | NL         | 52.3556  | 4.9136    | 386109440       | 3861133338     |
| 1048572 | NL         | 52.3556  | 4.9136    | 386191350       | 386195455      |
| 1048573 | NL         | 52.3556  | 4.9136    | 386201600       | 386201338      |
| 1048574 | NL         | 52.3556  | 4.9136    | 386215936       | 386220031      |
| 1048575 | NL         | 52.3556  | 4.9136    | 386221224       | 386223319      |
| 1048576 | NL         | 52.3556  | 4.9136    | 386244608       | 386244605      |

SQLite Visitor's Database

C:/VKHCG/02-Krennwallner/02-Assess/SQLite/krennwallner.db Table: BillboardCountry  
BillboardPlaceName ... VisitorLongitude VisitorYearRate 0 DE  
Lake ... 8.5667 26823960.0  
1 DE Horb ... 8.6833 26823960.0

2 DE Horb ... 8.6833 53753112.0

3 DE Horb ... 8.6833 107611416.0

4 DE Horb ... 8.6833 13359384.0

| A      | B                | C                  | D            | E             | F           | G                | H          | I           |                 |
|--------|------------------|--------------------|--------------|---------------|-------------|------------------|------------|-------------|-----------------|
| #      | BillboardCountry | BillboardPlaceName | billboardLat | billboardLong | isPortCount | VisitorPlaceName | visitorLat | visitorLong | visitorYearRate |
| 1      |                  |                    |              |               |             |                  |            |             |                 |
| 2      | DE               | Lake               | 51.7633      | 8.5667        | DE          | Lake             | 51.7633    | 8.5667      | 26823990        |
| 3      | DE               | Horb               | 48.4333      | 8.6833        | DE          | Horb             | 48.4333    | 8.6833      | 26823990        |
| 4      | DE               | Horb               | 48.4333      | 8.6833        | DE          | Horb             | 48.4333    | 8.6833      | 53751112        |
| 5      | DE               | Horb               | 48.4333      | 8.6833        | DE          | Horb             | 48.4333    | 8.6833      | 107611438       |
| 6      | DE               | Horb               | 48.4333      | 8.6833        | DE          | Horb             | 48.4333    | 8.6833      | 13359384        |
| 7      | DE               | Horb               | 48.4333      | 8.6833        | DE          | Horb             | 48.4333    | 8.6754      | 26823990        |
| 8      | DE               | Horb               | 48.4333      | 8.6833        | DE          | Horb             | 48.4333    | 8.6754      | 53751112        |
| 9      | DE               | Handenberg         | 51.1         | 7.7133        | DE          | Handenberg       | 51.1       | 7.7133      | 26823990        |
| 103221 | DE               | Frankfurt          | 50.1327      | 8.7668        | DE          | Frankfurt        | 50.1167    | 8.6833      | 1157112         |
| 103222 | DE               | Frankfurt          | 50.1327      | 8.7668        | DE          | Frankfurt        | 50.1167    | 8.6833      | 24299152        |
| 103223 | DE               | Frankfurt          | 50.1327      | 8.7668        | DE          | Frankfurt        | 50.1167    | 8.6833      | 907769968       |
| 103224 | DE               | Frankfurt          | 50.1327      | 8.7668        | DE          | Frankfurt        | 50.1172    | 8.7281      | 53751112        |
| 103225 | DE               | Frankfurt          | 50.1327      | 8.7668        | DE          | Frankfurt        | 50.1172    | 8.7281      | 26823990        |
| 103226 | DE               | Frankfurt          | 50.1327      | 8.7668        | DE          | Frankfurt        | 50.1172    | 8.7281      | 107611438       |
| 103227 | DE               | Frankfurt          | 50.1327      | 8.7668        | DE          | Frankfurt        | 50.1172    | 8.7281      | 1577880         |
| 103228 | DE               | Frankfurt          | 50.1327      | 8.7668        | DE          | Frankfurt        | 50.1184    | 8.6095      | 15642455        |
| 103229 | DE               | Frankfurt          | 50.1327      | 8.7668        | DE          | Frankfurt        | 50.1184    | 8.6095      | 10634776        |
| 103230 | DE               | Frankfurt          | 50.1327      | 8.7668        | DE          | Frankfurt        | 50.1319    | 8.6833      | 736344          |
| 103231 | DE               | Frankfurt          | 50.1327      | 8.7668        | DE          | Frankfurt        | 50.1319    | 8.6833      | 0               |
| 103232 | DE               | Frankfurt          | 50.1327      | 8.7668        | DE          | Frankfurt        | 50.1327    | 8.7668      | 736344          |
| 103233 | DE               | Frankfurt          | 50.1327      | 8.7668        | DE          | Frankfurt        | 50.1492    | 8.7097      | 172336536       |
| 103234 | DE               | Frankfurt          | 50.1327      | 8.7668        | DE          | Frankfurt        | 50.1492    | 8.7097      | 480761240       |
| 103235 | DE               | Frankfurt          | 50.1327      | 8.7668        | DE          | Frankfurt        | 50.1528    | 8.7445      | 26823990        |
| 103236 | DE               | Frankfurt          | 50.1327      | 8.7668        | DE          | Frankfurt        | 50.1878    | 8.6632      | 1577880         |

E. Write a Python / R program to generate GML file from the given csv file. Understanding Your Online Visitor Data

Online visitors have to be mapped to their closest billboard, to ensure we understand where and what they can access.

Open your Python editor and create a file called Assess-Billboard\_2\_Visitor.py in directory

```
C:\VKHCG\02-Krennwallner\02-Assess. import networkx as nx
import sys
import os
import sqlite3 as sq
import pandas as pd
from geopy.distance import vincenty
#####
# Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
#####
#
Company='02-Krennwallner' sTable='Assess_BillboardVisitorData'
sOutputFileName='Assess-DE-Billboard-Visitor.gml'
#####
sDataBaseDir=Base + '/' + Company + '/02-Assess/SQLite'if not os.path.exists(sDataBaseDir):
os.makedirs(sDataBaseDir)
#####
sDatabaseName=sDataBaseDir + '/krennwallner.db'conn = sq.connect(sDatabaseName)
#####
print('#####')
print('Loading :,sDatabaseName, Table:,sTable)sSQL="select "
sSQL=sSQL+ " A.BillboardCountry," sSQL=sSQL+ " A.BillboardPlaceName,"
sSQL=sSQL+ " ROUND(A.BillboardLatitude,3) AS
BillboardLatitude, " sSQL=sSQL+
ROUND(A.BillboardLongitude,3) AS BillboardLongitude,"
sSQL=sSQL+ " (CASE WHEN A.BillboardLatitude < 0 THEN
" sSQL=sSQL+ " 'S' || ROUND(ABS(A.BillboardLatitude),3)"
sSQL=sSQL+ " ELSE "
sSQL=sSQL+ " 'N' ||
```

```

ROUND(ABS(A.BillboardLatitude),3)"
sSQL=sSQL+ " END ) AS sBillboardLatitude,"
sSQL=sSQL+ " (CASE WHEN A.BillboardLongitude < 0
THEN "sSQL=sSQL+ " 'W' ||
ROUND(ABS(A.BillboardLongitude),3)" sSQL=sSQL+
"ELSE "
sSQL=sSQL+ " 'E' ||
ROUND(ABS(A.BillboardLongitude),3)"
sSQL=sSQL+ " END ) AS sBillboardLongitude,"
sSQL=sSQL+ " A.VisitorCountry,"
sSQL=sSQL+ " A.VisitorPlaceName,"
sSQL=sSQL+ " ROUND(A.VisitorLatitude,3) AS
VisitorLatitude, " sSQL=sSQL+
"ROUND(A.VisitorLongitude,3) AS VisitorLongitude,"
sSQL=sSQL+ " (CASE WHEN A.VisitorLatitude < 0
THEN " sSQL=sSQL+ " 'S' ||
ROUND(ABS(A.VisitorLatitude),3)" sSQL=sSQL+
"ELSE "
sSQL=sSQL+ " 'N'
||ROUND(ABS(A.VisitorLatitude),3)"
sSQL=sSQL+ " END ) AS sVisitorLatitude,"
sSQL=sSQL+ " (CASE WHEN A.VisitorLongitude < 0
THEN "sSQL=sSQL+ " 'W' ||
ROUND(ABS(A.VisitorLongitude),3)" sSQL=sSQL+
"ELSE "
sSQL=sSQL+ " 'E' ||
ROUND(ABS(A.VisitorLongitude),3)"
sSQL=sSQL+ " END ) AS sVisitorLongitude,"
sSQL=sSQL+ " A.VisitorYearRate"
sSQL=sSQL+ " from"
sSQL=sSQL+ " Assess_BillboardVistorsData AS A;"
BillboardVistorsData=pd.read_sql_query(sSQL, conn)

print('#####')
BillboardVistorsData['Distance']=BillboardVistorsData.apply(lambda row:round(
vincenty((row['BillboardLatitude'],row['BillboardLongitude']),
(row['VisitorLatitude'],row['VisitorLongitude'])).miles
,4)
,axis=1) #####
G=nx.Graph() #####
for i in range(BillboardVistorsData.shape[0]):
sNode0='MediaHub-' + BillboardVistorsData['BillboardCountry'][i]sNode1='B-' +
BillboardVistorsData['sBillboardLatitude'][i] + '-' sNode1=sNode1 +
BillboardVistorsData['sBillboardLongitude'][i] G.add_node(sNode1,
Nodetype='Billboard', Country=BillboardVistorsData['BillboardCountry'][i],
PlaceName=BillboardVistorsData['BillboardPlaceName'][i],
Latitude=round(BillboardVistorsData['BillboardLatitude'][i],3),
Longitude=round(BillboardVistorsData['BillboardLongitude'][i],3))sNode2='M-' +
BillboardVistorsData['sVisitorLatitude'][i] + '-' sNode2=sNode2 +
BillboardVistorsData['sVisitorLongitude'][i] G.add_node(sNode2,
Nodetype='Mobile', Country=BillboardVistorsData['VisitorCountry'][i],
PlaceName=BillboardVistorsData['VisitorPlaceName'][i],
Latitude=round(BillboardVistorsData['VisitorLatitude'][i],3),
Longitude=round(BillboardVistorsData['VisitorLongitude'][i],3))print('Link Media Hub

```

```

:',sNode0,' to Billboard : ', sNode1) G.add_edge(sNode0,sNode1)
print('Link Post Code :',sNode1,' to GPS : ', sNode2)
G.add_edge(sNode1,sNode2,distance=round(BillboardVistorsData['Distance'][i]))
#####
print('#####')
print("Nodes    of    graph:    ",nx.number_of_nodes(G))   print("Edges    of    graph:
",nx.number_of_edges(G))print('#####')
#####
sFileDir=Base + '/' + Company + '/02-Assess/01-EDS/02-Python'if not
os.path.exists(sFileDir):
os.makedirs(sFileDir)
#####
sFileName=sFileDir + '/' + sOutputFileName print('#####')
print('Storing :', sFileName) print('#####')
nx.write_gml(G,sFileName) sFileName=sFileName +'.gz'nx.write_gml(G,sFileName)
#####
print('#####') print('###
Done!! #####')
#####
Output:
This will produce a set of demonstrated values onscreen, plus a graph data file

```

named Assess-DE-Billboard-Visitor.gml.

(It takes a long time to complete the process, after completion the gml file can be viewed intext editor)

Hence, we have applied formulae to extract features, such as the distance between the billboard and the visitor.

Planning an Event for Top-Ten Customers

Open Python editor and create a file named Assess-Visitors.py in directory C:\VKHCG\02-Krennwallner\02-Assess

```
#####
#####
import sys
import os
import sqlite3 as sq
import pandas as pd
from pandas.io import sql
#####
# Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
#####
#
Company='02-Krennwallner'
sInputFileName='01-Retrieve/01-EDS/02-Python/Retrieve_Online_Visitor.csv'
#####
sDataBaseDir=Base + '/' + Company + '/02-Assess/SQLite'if not os.path.exists(sDataBaseDir):
os.makedirs(sDataBaseDir)
#####
sDatabaseName=sDataBaseDir + '/krennwallner.db'conn = sq.connect(sDatabaseName)
#####
### Import Country Data #####
sFileName=Base + '/' + Company + '/' + sInputFileName
print('#####')
print('Loading :',sFileName) print('#####')
VisitorRawData=pd.read_csv(sFileName,header=0,
low_memory=False, encoding="latin-1", skip_blank_lines=True)
VisitorRawData.drop_duplicates(subset=None, keep='first', inplace=True)
VisitorData=VisitorRawData
print('Loaded Company :',VisitorData.columns.values)
print('#####')
#####
print('#####')
sTable='Assess_Visitor'
print('Storing :',sDatabaseName,' Table:',sTable) VisitorData.to_sql(sTable, conn,
if_exists="replace") print('#####')
#####
print(VisitorData.head()) print('#####')
print('Rows : ',VisitorData.shape[0]) print('#####')
```

```

#####
print('#####')
sView='Assess_Visitor_UseIt'
print('Creating :',sDatabaseName,' View:',sView)sSQL="DROP VIEW IF EXISTS " + sView
+ ","
sql.execute(sSQL,conn)
sSQL="CREATE VIEW " + sView + " AS"sSQL=sSQL+ " SELECT"
sSQL=sSQL+ " A.Country," sSQL=sSQL+ " A.Place_Name,"sSQL=sSQL+ " A.Latitude,"
sSQL=sSQL+ " A.Longitude,"
sSQL=sSQL+ " (A.Last_IP_Number - A.First_IP_Number) AS UsesIt"sSQL=sSQL+ "
FROM"
sSQL=sSQL+ " Assess_Visitor as A"sSQL=sSQL+ " WHERE"
sSQL=sSQL+ " Country is not null"sSQL=sSQL+ " AND"
sSQL=sSQL+ " Place_Name is not null;"sql.execute(sSQL,conn)
#####
print('#####')
sView='Assess_Total_Visitors_Location' print('Creating :',sDatabaseName,' View:',sView)
sSQL="DROP VIEW IF EXISTS " + sView + ";"
sql.execute(sSQL,conn)
sSQL="CREATE VIEW " + sView + " AS"sSQL=sSQL+ " SELECT"
sSQL=sSQL+ " Country," sSQL=sSQL+ " Place_Name,"
sSQL=sSQL+ " SUM(UsesIt) AS TotalUsesIt"sSQL=sSQL+ " FROM"
sSQL=sSQL+ " Assess_Visitor_UseIt"sSQL=sSQL+ " GROUP BY"
sSQL=sSQL+ " Country," sSQL=sSQL+ " Place_Name"sSQL=sSQL+ " ORDER BY"
sSQL=sSQL+ " TotalUsesIt DESC"sSQL=sSQL+ " LIMIT 10;"
sql.execute(sSQL,conn)
#####
print('#####')
sView='Assess_Total_Visitors_GPS'
print('Creating :',sDatabaseName,'
View:',sView)sSQL="DROP VIEW IF
EXISTS " + sView + ";"
sql.execute(sSQL,conn)
sSQL="CREATE VIEW " + sView +
" AS"sSQL=sSQL+ " SELECT"
sSQL=sSQL+ " Latitude,"
sSQL=sSQL+ " Longitude,"
sSQL=sSQL+ " SUM(UsesIt) AS
TotalUsesIt"sSQL=sSQL+ " FROM"
sSQL=sSQL+
Assess_Visitor_UseIt"
sSQL=sSQL+ " GROUP BY"
sSQL=sSQL+ " Latitude,"
sSQL=sSQL+ " Longitude"

sSQL=sSQL+ " ORDER BY"
sSQL=sSQL+ " TotalUsesIt
DESC"sSQL=sSQL+ " LIMIT
10;"
sql.execute(sSQL,conn)
#####
##
sTables=['Assess_Total_Visitors_Location',

```

```
'Assess_Total_Visitors_GPS'] for sTable in sTables:
print('#####')
print('Loading :',sDatabaseName,' Table:',sTable)sSQL=" SELECT "
sSQL=sSQL+ " *" sSQL=sSQL+ " FROM"
sSQL=sSQL+ " " + sTable + ";" TopData=pd.read_sql_query(sSQL, conn)
print('#####')
print(TopData) print('#####')
print('#####')
print('Rows : ',TopData.shape[0]) print('#####')
##### print('###')
Done!! #####
```

Output:

| CustomerID | CustomerName | TotalVisitors |
|------------|--------------|---------------|
| 1          | CM           | 981.2195      |
| 2          | DR           | 336.82181     |
| 3          | ED           | 334.72427     |
| 4          | EP           | 334.04799     |
| 5          | ES           | 258.81951     |
| 6          | EV           | 273.81347     |
| 7          | EW           | 274.60164     |
| 8          | EW           | 172.70034     |
| 9          | EW           | 237.87441     |
| 10         | EW           | 209.63931     |

| Latitude | Longitude | TotalVisitors |
|----------|-----------|---------------|
| 39.95903 | -122.3893 | 313.39700     |
| 39.95903 | -122.3826 | 332.51464     |
| 39.95903 | -122.3877 | 224.73421     |
| 39.9427  | 119.58771 | 214.29772     |
| 39.9427  | 119.58508 | 119.71653     |
| 40.2346  | 119.5828  | 148.96438     |
| 40.1755  | -74.2746  | 140.61373     |
| 40.2023  | -83.2763  | 147.71213     |
| 40.1971  | -78.4253  | 107.61024     |
| 39.9373  | -127.3849 | 147.61006     |

F. Write a Python / R program to plan the locations of the warehouses from the given data.

#### Planning the Locations of the Warehouses

Planning the location of the warehouses requires the assessment of the GPS locations of these warehouses against the requirements for Hillman's logistics needs.

Open your editor and create a file named Assess-Warehouse-Address.py in directory C:\VKHCG\03-Hillman\02-Assess.

```
##### Assess-Warehouse-Address.py ##### import os
import pandas as pd
from geopy.geocoders import Nominatimgeolocator = Nominatim()
#####
InputDir='01-Retrieve/01-EDS/01-R'
```

```

InputFileName='Retrieve_GB_Postcode_Warehouse.csv'EDSDir='02-Assess/01-EDS'
OutputDir=EDSDir + '/02-Python' OutputFileName='Assess_GB_Warehouse_Address.csv'
Company='03-Hillman'
#####
Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using Windows')
print('#####')
#####
sFileDir=Base + '/' + Company + '/' + EDSDir if not os.path.exists(sFileDir):
os.makedirs(sFileDir)
#####
sFileDir=Base + '/' + Company + '/' + OutputDir if not os.path.exists(sFileDir):
os.makedirs(sFileDir)
#####
sFileName=Base + '/' + Company + '/' + InputDir + '/' + InputFileName
print('#####')
print('Loading :',sFileName)
Warehouse=pd.read_csv(sFileName,header=0,low_memory=False)
Warehouse.sort_values(by='postcode', ascending=1)
#####
## Limited to 10 due to service limit on Address Service.
#####
WarehouseGoodHead=Warehouse[Warehouse.latitude != 0].head(5)
WarehouseGoodTail=Warehouse[Warehouse.latitude != 0].tail(5)
#####
WarehouseGoodHead['Warehouse_Point']=WarehouseGoodHead.apply(lambda row:
(str(row['latitude'])+','+str(row['longitude'])))
,axis=1) WarehouseGoodHead['Warehouse_Address']=WarehouseGoodHead.apply(lambda row:
geolocator.reverse(row['Warehouse_Point']).address
,axis=1)
WarehouseGoodHead.drop('Warehouse_Point', axis=1, inplace=True)
WarehouseGoodHead.drop('id', axis=1, inplace=True) WarehouseGoodHead.drop('postcode',
axis=1, inplace=True)
#####
WarehouseGoodTail['Warehouse_Point']=WarehouseGoodTail.apply(lambda row:
(str(row['latitude'])+','+str(row['longitude'])))
,axis=1) WarehouseGoodTail['Warehouse_Address']=WarehouseGoodTail.apply(lambda row:
geolocator.reverse(row['Warehouse_Point']).address
,axis=1)
WarehouseGoodTail.drop('Warehouse_Point', axis=1, inplace=True)
WarehouseGoodTail.drop('id', axis=1, inplace=True) WarehouseGoodTail.drop('postcode',
axis=1, inplace=True)
#####
WarehouseGood=WarehouseGoodHead.append(WarehouseGoodTail, ignore_index=True)
print(WarehouseGood)
#####
sFileName=sFileDir + '/' + OutputFileName
WarehouseGood.to_csv(sFileName, index = False)
#####
print('### Done!! #####')
#####

```

**Output:**

```
#####
Working Base : C:/VKHCG using Windows
#####
#####
Loading : C:/VKHCG/03-Hillman/01-Retrieve/01-EDS/01-R/Retrieve_GB_Postcode_Warehouse.csv
    latitude longitude                                         Warehouse_Address
0  57.135140 -2.117310  35, Broomhill Road, Broomhill, Aberdeen, Aberd...
1  57.138750 -2.090890  South Esplanade West, Torry, Aberdeen, Aberdes...
2  57.101000 -2.110600  A92, Cove and Altens, Aberdeen, Aberdeen City, ...
3  57.108010 -2.237760  Colthill Circle, Milltimber, Countesswells, Ab...
4  57.100760 -2.270730  Johnston Gardens East, Peterculter, South Last...
5  53.837717 -1.780013  HM Revenue and Customs, Riverside Estate, Temp...
6  53.794470 -1.766539  Listerhills Road Norcroft Street, Listerhills ...
7  51.518556 -0.714794  Sorting Office, Stafferton Way, Fishery, Maide...
8  54.890923 -2.943847  Royal Mail (Delivery Office), Junction Street, ...
9  57.481338 -4.223951  Inverness Sorting & Delivery Office, Strothers...
### Done!! #####
>>> |
```

```
if not os.path.exists(sFileDir):
os.makedirs(sFileDir)
#####
sFileName=Base + '/' + Company + '/' + InputDir + '/' + InputFileName print('#####')
print('Loading :',sFileName) Warehouse=pd.read_csv(sFileName,header=0,low_memory=False, encoding="latin-1")
#####
sColumns={'X1' : 'Country','X2' : 'PostCode',
'X3' : 'PlaceName',
'X4' : 'AreaName',
'X5' : 'AreaCode',
'X10' : 'Latitude',
'X11' : 'Longitude'} Warehouse.rename(columns=sColumns,inplace=True)
WarehouseGood=Warehouse
#####
sFileName=sFileDir + '/' + OutputFileName WarehouseGood.to_csv(sFileName, index = False) #####
print('### Done!! #####')
#####
This will produce a set of demonstrated values onscreen, plus a graph data file named Assess_All_Warehouse.csv.
```

## Output:

```
>>>
===== RESTART: C:\VKHCG\03-Hillman\02-Assess\Assess-Warehouse-Global.py =====
#####
Working Base : C:/VKHCG using win32
#####
Loading : C:/VKHCG/03-Hillman/01-Retrieve/01-EDS/01-R/Retrieve_All_Countries.csv
### Done!! #####
>>>
```

Open Assess0\_All\_Warehouse.csv from C:\VKHCG\03-Hillman\02-Assess\01-EDS\02-Python

| A     | B          | C       | D        | E                   | F              | G        | H        |           |
|-------|------------|---------|----------|---------------------|----------------|----------|----------|-----------|
| 1     | Unnamed: 0 | Country | PostCode | PlaceName           | AreaName       | AreaCode | Latitude | Longitude |
| 2     | 1          | AD      | AD100    | Canillo             |                |          | 42.5835  | 1.6667    |
| 3     | 2          | AD      | AD200    | Encamp              |                |          | 42.5335  | 1.6333    |
| 4     | 3          | AD      | AD300    | Ordino              |                |          | 42.6     | 1.55      |
| 5     | 4          | AD      | AD400    | La Massana          |                |          | 42.5667  | 1.4833    |
| 6     | 5          | AD      | AD500    | Andorra la Vella    |                |          | 42.5     | 1.5       |
| 31621 | 31620      | AT      | 4925     | Gumpeling           | Oberösterreich | 4        | 48.1555  | 13.4802   |
| 31622 | 31621      | AT      | 4925     | Windischhub         | Oberösterreich | 4        | 48.1555  | 13.4802   |
| 31623 | 31622      | AT      | 4926     | Obereselbach        | Oberösterreich | 4        | 48.1917  | 13.5784   |
| 31624 | 31623      | AT      | 4926     | Jetzing             | Oberösterreich | 4        | 48.1555  | 13.4802   |
| 31625 | 31624      | AT      | 4926     | Pilgersham          | Oberösterreich | 4        | 48.1772  | 13.5855   |
| 31626 | 31625      | AT      | 4926     | Grausgrub           | Oberösterreich | 4        | 48.1555  | 13.4802   |
| 31627 | 31626      | AT      | 4926     | Auerenkirchen am Ha | Oberösterreich | 4        | 48.1828  | 13.577    |
| 31628 | 31627      | AT      | 4926     | Stocket             | Oberösterreich | 4        | 48.1555  | 13.4802   |
| 31629 | 31628      | AT      | 4926     | Baching             | Oberösterreich | 4        | 48.1555  | 13.4802   |
| 31630 | 31629      | AT      | 4926     | Kern                | Oberösterreich | 4        | 48.1555  | 13.4802   |
| 31631 | 31630      | AT      | 4926     | Manaberg            | Oberösterreich | 4        | 48.1555  | 13.4802   |
| 31632 | 31631      | AT      | 4926     | Untereselbach       | Oberösterreich | 4        | 48.1555  | 13.4802   |
| 31633 | 31632      | AT      | 4926     | Hattig              | Oberösterreich | 4        | 48.1555  | 13.4802   |
| 31634 | 31633      | AT      | 4926     | Unering             | Oberösterreich | 4        | 48.1555  | 13.4802   |
| 31635 | 31634      | AT      | 4926     | Kleinbach           | Oberösterreich | 4        | 48.1555  | 13.4802   |
| 31636 | 31635      | AT      | 4926     | Lehen               | Oberösterreich | 4        | 48.1555  | 13.4802   |
| 31637 | 31636      | AT      | 4926     | Hof                 | Oberösterreich | 4        | 48.1555  | 13.4802   |
| 31638 | 31637      | AT      | 4931     | Großweifendorf      | Oberösterreich | 4        | 48.15    | 13.3333   |
| 31639 | 31638      | AT      | 4931     | Neulendt            | Oberösterreich | 4        | 48.1897  | 13.3521   |

H. Using the given data, write a Python / R program to plan the shipping routes for best-fit international logistics.

Hillman requires an international logistics solution to support all the required shipping routes.

Open Python editor and create a file named Assess-Best-Fit-Logistics.py in directory

C:\VKHCG\03-Hillman\02-Assess

```
import sys
import os
import pandas as pd
import networkx as nx
from geopy.distance import vincenty
import sqlite3 as sq
from pandas.io import sql
#####
if sys.platform == 'linux': Base=os.path.expanduser('~') + '/VKHCG' else:
Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
#####
Company='03-Hillman'
InputDir='01-Retrieve/01-EDS/01-R' InputFileName='Retrieve_All_Countries.csv'
EDSDir='02-Assess/01-EDS'
```

```

OutputDir=EDSDir + '/02-Python' OutputFileName='Assess_Best_Logistics.gml'
#####
sFileDir=Base + '/' + Company + '/' + EDSDir if not os.path.exists(sFileDir):
    os.makedirs(sFileDir)
sql.execute(sSQL,conn)
sSQL="CREATE VIEW " + sView + " AS"
sSQL+= " SELECT DISTINCT"
sSQL+= " S.Country AS SourceCountry," + " S.Latitude AS"
sSQL+= " SourceLatitude," + " S.Longitude AS SourceLongitude," + " SSQL+= "
T.Country AS TargetCountry," + " T.Latitude AS TargetLatitude," + " TSQL+= "
" T.Longitude AS TargetLongitude" + " FROM"
sSQL+= " Assess_RoutePointsCountry AS S" + "SQL+= "
sSQL+= " Assess_RoutePointsCountry AS T" + "SQL+= "
" WHERE S.Country <> "
T.Country" + "SQL+= "
" AND"
sSQL+= " S.Country in ('GB','DE','BE','AU','US','IN")" + "SQL+= "
" AND"
sSQL+= " T.Country in ('GB','DE','BE','AU','US','IN');"
sql.execute(sSQL,conn)
print('#####')
print('Loading :,' + sDatabaseName + ',' + sView) + "SQL=" "SELECT"
sSQL+= " *" + "SQL+= "
" FROM" + "SQL+= "
" " + sView + ";" + "SQL+= "
RouteCountries=pd.read_sql_query(sSQL, conn)
RouteCountries['Distance']=RouteCountries.apply(lambda row:round(
    vincenty((row['SourceLatitude'],row['SourceLongitude']),
    (row['TargetLatitude'],row['TargetLongitude']))).miles,4),axis=1)
print(RouteCountries.head(5))
#####
### Fit Country to Post Code
#####
print('#####')
sView='Assess_RoutePostCode'
print('Creating :,' + sDatabaseName + ',' + sView) + "SQL=" "DROP VIEW IF EXISTS " + sView
+ "SQL+= "
";" + "SQL+= "
sql.execute(sSQL,conn)
sSQL="CREATE VIEW " + sView + " AS"
sSQL+= " SELECT DISTINCT"
sSQL+= " S.Country AS SourceCountry," + " S.Latitude AS"
sSQL+= " SourceLatitude," + " S.Longitude AS SourceLongitude," + " SSQL+= "
T.Country AS TargetCountry," + " T.PostCode AS TargetPostCode," + "SQL+= "
sSQL+= " T.Latitude AS TargetLatitude," + " SSQL+= "
" T.Longitude AS"
TargetLongitude" + "SQL+= "
" FROM"
sSQL+= " Assess_RoutePointsCountry AS S"
"SQL+= "
" ,"
sSQL+= " Assess_RoutePointsPostCode AS T" + "SQL+= "
" WHERE S.Country ="
T.Country" + "SQL+= "
" AND"
sSQL+= " S.Country in ('GB','DE','BE','AU','US','IN")" + "SQL+= "
" AND"
sSQL+= " T.Country in ('GB','DE','BE','AU','US','IN');"
sql.execute(sSQL,conn)
print('#####')
print('Loading :,' + sDatabaseName + ',' + sView) + "SQL=" "SELECT"
sSQL+= " *" + "SQL+= "
" FROM" + "SQL+= "
" " + sView + ";" + "SQL+= "
RoutePostCode=pd.read_sql_query(sSQL, conn)
RoutePostCode['Distance']=RoutePostCode.apply(lambda row: round(
    vincenty((row['SourceLatitude'],row['SourceLongitude']),
    (row['TargetLatitude'],row['TargetLongitude']))).miles
    ,4)
    ,axis=1)
print(RoutePostCode.head(5))
#####

```

```

### Fit Post Code to Place Name
#####
print('#####')
sView='Assess_RoutePlaceName'
print('Creating :',sDatabaseName,' View:',sView) sSQL="DROP VIEW IF EXISTS " + sView
+ ";" 
sql.execute(sSQL,conn)
sSQL="CREATE VIEW " + sView + " AS" sSQL=sSQL+ " SELECT DISTINCT"
sSQL=sSQL+ " S.Country AS SourceCountry," sSQL=sSQL+ " S.PostCode AS
SourcePostCode," sSQL=sSQL+ " S.Latitude AS SourceLatitude," sSQL=sSQL+ "
S.Longitude AS SourceLongitude," sSQL=sSQL+ " T.Country AS TargetCountry,"
sSQL=sSQL+ " T.PostCode AS TargetPostCode," sSQL=sSQL+ " T.PlaceName AS
TargetPlaceName,"sSQL=sSQL+ " T.Latitude AS TargetLatitude," sSQL=sSQL+ "
T.Longitude AS TargetLongitude" sSQL=sSQL+ " FROM"
sSQL=sSQL+ " Assess_RoutePointsPostCode AS S"sSQL=sSQL+ " ,"
sSQL=sSQL+ " Assess_RoutePointsPLaceName AS T"sSQL=sSQL+ " WHERE"
sSQL=sSQL+ " S.Country = T.Country" sSQL=sSQL+ " AND"
sSQL=sSQL+ " S.PostCode = T.PostCode"sSQL=sSQL+ " AND"
sSQL=sSQL+ " S.Country in ('GB','DE','BE','AU','US','IN")sSQL=sSQL+ " AND"
sSQL=sSQL+ " T.Country in ('GB','DE','BE','AU','US','IN');"
sql.execute(sSQL,conn) print('#####')
print('Loading :,sDatabaseName,' Table:,sView)

sSQL=" SELECT " sSQL=sSQL+ " *" sSQL=sSQL+ " FROM" sSQL=sSQL+ " " + sView +
";"
RoutePlaceName=pd.read_sql_query(sSQL, conn)
RoutePlaceName['Distance']=RoutePlaceName.apply(lambda row: round(
vincenty((row['SourceLatitude'],row['SourceLongitude']),
(row['TargetLatitude'],row['TargetLongitude']))).miles
,4)
, axis=1) print(RoutePlaceName.head(5))
#####
G=nx.Graph() #####
print('Countries:',RouteCountries.shape) for i in range(RouteCountries.shape[0]):
sNode0='C-' + RouteCountries['SourceCountry'][i]G.add_node(sNode0,
Nodetype='Country', Country=RouteCountries['SourceCountry'][i],
Latitude=round(RouteCountries['SourceLatitude'][i],4),
Longitude=round(RouteCountries['SourceLongitude'][i],4))sNode1='C-' +
RouteCountries['TargetCountry'][i] G.add_node(sNode1,
Nodetype='Country', Country=RouteCountries['TargetCountry'][i],
Latitude=round(RouteCountries['TargetLatitude'][i],4),
Longitude=round(RouteCountries['TargetLongitude'][i],4))
G.add_edge(sNode0,sNode1,distance=round(RouteCountries['Distance'][i],3))
#print(sNode0,sNode1)
#####
print('Post Code:',RoutePostCode.shape) for i in range(RoutePostCode.shape[0]):
sNode0='C-' + RoutePostCode['SourceCountry'][i]G.add_node(sNode0,
Nodetype='Country', Country=RoutePostCode['SourceCountry'][i],
Latitude=round(RoutePostCode['SourceLatitude'][i],4),
Longitude=round(RoutePostCode['SourceLongitude'][i],4))
sNode1='P-' + RoutePostCode['TargetPostCode'][i] + '-' + RoutePostCode['TargetCountry'][i]
G.add_node(sNode1,
Nodetype='PostCode', Country=RoutePostCode['TargetCountry'][i],
PostCode=RoutePostCode['TargetPostCode'][i],

```

```

Latitude=round(RoutePostCode['TargetLatitude'][i],4),
Longitude=round(RoutePostCode['TargetLongitude'][i],4))
G.add_edge(sNode0,sNode1,distance=round(RoutePostCode['Distance'][i],3))
#print(sNode0,sNode1)
#####
print('Place Name:',RoutePlaceName.shape) for i in range(RoutePlaceName.shape[0]):
sNode0='P-' + RoutePlaceName['TargetPostCode'][i] + '-'sNode0=sNode0 +
RoutePlaceName['TargetCountry'][i] G.add_node(sNode0,
Nodetype='PostCode',


Country=RoutePlaceName['SourceCountry'][i],
PostCode=RoutePlaceName['TargetPostCode'][i],
Latitude=round(RoutePlaceName['SourceLatitude'][i],4),
Longitude=round(RoutePlaceName['SourceLongitude'][i],4)) sNode1=sNode1 +
RoutePlaceName['TargetPostCode'][i] + '-'sNode1=sNode1 +
RoutePlaceName['TargetCountry'][i] G.add_node(sNode1,
Nodetype='PlaceName', Country=RoutePlaceName['TargetCountry'][i],
PostCode=RoutePlaceName['TargetPostCode'][i],
PlaceName=RoutePlaceName['TargetPlaceName'][i],
Latitude=round(RoutePlaceName['TargetLatitude'][i],4),
Longitude=round(RoutePlaceName['TargetLongitude'][i],4))
G.add_edge(sNode0,sNode1,distance=round(RoutePlaceName['Distance'][i],3))
#print(sNode0,sNode1)
#####
sFileName=sFileDir + '/' + OutputFileName print('#####')
print('Storing :, sFileName) print('#####')
nx.write_gml(G,sFileName) sFileName=sFileName +'.gz'nx.write_gml(G,sFileName)
#####
print('#####')
print('Path:', nx.shortest_path(G,source='P-SW1-GB',target='P-01001-US',weight='distance'))
print('Path length:', nx.shortest_path_length(G,source='P-SW1-GB',target='P-01001-
US',weight='distance')) print('Path length (1):', nx.shortest_path_length(G,source='P-SW1-
GB',target='C-GB',weight='distance')) print('Path length (2):',
nx.shortest_path_length(G,source='C-GB',target='C-US',weight='distance')) print('Path length
(3):', nx.shortest_path_length(G,source='C-US',target='P-01001-US',weight='distance'))
print('#####')
print('Routes from P-SW1-GB < 2: ', nx.single_source_shortest_path(G,source='P-SW1-GB'
,cutoff=1)) print('Routes from P-01001-US < 2: ',
nx.single_source_shortest_path(G,source='P-01001-US',cutoff=1))
print('#####')
#####
print('#####')
print('Vacuum Database')sSQL="VACUUM;" sql.execute(sSQL,conn) print('#####')
#####
print('### Done!! #####')
#####
Output:

```

You can now query features out of a graph, such as shortage paths between locations and paths from a given location, using Assess\_Best\_Logistics.gml with appropriate application.

I. Write a Python / R program to decide the best packing option to ship in container from the given data.

Hillman wants to introduce new shipping containers into its logistics strategy. This program will go through a process of assessing the possible container sizes. This example introduces

features with ranges or tolerances. Open Python editor and create a file named Assess-Shipping-Containers.py in directory C:\VKHCG\03-Hillman\02-Assessimport sys  
import os  
import pandas as pdimport sqlite3 as sq

```

from pandas.io import sql
#####
Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
#####
Company='03-Hillman'
InputDir='01-Retrieve/01-EDS/02-Python' InputFileName1='Retrieve_Product.csv'
InputFileName2='Retrieve_Box.csv' InputFileName3='Retrieve_Container.csv' EDSDir='02-Assess/01-EDS' OutputDir=EDSDir + '/02-Python'
OutputFileName='Assess_Shipping_Containers.csv'
#####
sFileDir=Base + '/' + Company + '/' + EDSDirif not os.path.exists(sFileDir):
os.makedirs(sFileDir)
#####
sFileDir=Base + '/' + Company + '/' + OutputDirif not os.path.exists(sFileDir):
os.makedirs(sFileDir)
#####
sDataBaseDir=Base + '/' + Company + '/02-Assess/SQLite'if not os.path.exists(sDataBaseDir):
os.makedirs(sDataBaseDir)
#####
sDatabaseName=sDataBaseDir + '/hillman.db' conn = sq.connect(sDatabaseName)
#####
#####
### Import Product Data
#####
sFileName=Base + '/' + Company + '/' + InputDir + '/' + InputFileName1 print('#####')
print('Loading :',sFileName) ProductRawData=pd.read_csv(sFileName,header=0,
low_memory=False,encoding="latin-1"
)
ProductRawData.drop_duplicates(subset=None, keep='first', inplace=True)
ProductRawData.index.name = 'IDNumber'
ProductData=ProductRawData[ProductRawData.Length <= 0.5].head(10) print('Loaded
Product :,ProductData.columns.values) print('#####')
#####
print('#####')
sTable='Assess_Product'
print('Storing :,sDatabaseName, Table:,sTable) ProductData.to_sql(sTable, conn,
if_exists="replace") print('#####')
#####
print(ProductData.head()) print('#####')

```

```

print('Rows : ',ProductData.shape[0]) print('#####')
#####
#####
### Import Box Data
#####
sFileName=Base + '/' + Company + '/' + InputDir + '/' + InputFileName2print('#####')
print('Loading :',sFileName) BoxRawData=pd.read_csv(sFileName,header=0,
low_memory=False,encoding="latin-1"
)
BoxRawData.drop_duplicates(subset=None, keep='first', inplace=True) BoxRawData.index.name
= 'IDNumber' BoxData=BoxRawData[BoxRawData.Length <= 1].head(1000) print('Loaded
Product :,BoxData.columns.values) print('#####')
#####
print('#####')
sTable='Assess_Box'
print('Storing :,sDatabaseName,' Table:',sTable) BoxData.to_sql(sTable, conn,
if_exists="replace") print('#####')
#####
print(BoxData.head()) print('#####')
print('Rows : ',BoxData.shape[0]) print('#####')
#####
#####
### Import Container Data
#####
sFileName=Base + '/' + Company + '/' + InputDir + '/' + InputFileName3print('#####')
print('Loading :,sFileName) ContainerRawData=pd.read_csv(sFileName,header=0,
low_memory=False,encoding="latin-1"
)
ContainerRawData.drop_duplicates(subset=None, keep='first', inplace=True)
ContainerRawData.index.name = 'IDNumber'
ContainerData=ContainerRawData[ContainerRawData.Length <= 2].head(10)print('Loaded
Product :,ContainerData.columns.values) print('#####')
#####
print('#####')
sTable='Assess_Container'
print('Storing :,sDatabaseName,' Table:',sTable) BoxData.to_sql(sTable, conn,
if_exists="replace") print('#####')
#####
print(ContainerData.head()) print('#####')

print('Rows : ',ContainerData.shape[0]) print('#####')
#####
#####
### Fit Product in Box
#####
print('#####')
sView='Assess_Product_in_Box'
print('Creating :,sDatabaseName,' View:',sView)sSQL="DROP VIEW IF EXISTS " + sView
+ ","
sql.execute(sSQL,conn)
sSQL="CREATE VIEW " + sView + " AS"sSQL=sSQL+ " SELECT"
sSQL=sSQL+ " P.UnitNumber AS ProductNumber," sSQL=sSQL+ " B.UnitNumber AS
BoxNumber," sSQL=sSQL+ " (B.Thickness * 1000) AS PackSafeCode,"

```

```

sSQL=sSQL+ " (B.BoxVolume - P.ProductVolume) AS PackFoamVolume,"
sSQL=sSQL+ " ((B.Length*10) * (B.Width*10) * (B.Height*10)) * 167 AS
Air_Dimensional_Weight," sSQL=sSQL+ " ((B.Length*10) * (B.Width*10) * (B.Height*10))
* 333 AS Road_Dimensional_Weight,"sSQL=sSQL+ " ((B.Length*10) * (B.Width*10) *
(B.Height*10)) * 1000 AS Sea_Dimensional_Weight,"sSQL=sSQL+ " P.Length AS
Product_Length,"
sSQL=sSQL+ " P.Width AS Product_Width," sSQL=sSQL+ " P.Height AS Product_Height,"
sSQL=sSQL+ " P.ProductVolume AS Product_cm_Volume,"
sSQL=sSQL+ " ((P.Length*10) * (P.Width*10) * (P.Height*10)) AS Product_ccm_Volume,"
sSQL=sSQL+ " (B.Thickness * 0.95) AS Minimum_Pack_Foam,"
sSQL=sSQL+ " (B.Thickness * 1.05) AS Maximum_Pack_Foam,"
sSQL=sSQL+ " B.Length - (B.Thickness * 1.10) AS Minimum_Product_Box_Length,"
sSQL=sSQL+ " B.Length - (B.Thickness * 0.95) AS Maximum_Product_Box_Length,"
sSQL=sSQL+ " B.Width - (B.Thickness * 1.10) AS Minimum_Product_Box_Width,"
sSQL=sSQL+ " B.Width - (B.Thickness * 0.95) AS Maximum_Product_Box_Width,"
sSQL=sSQL+ " B.Height - (B.Thickness * 1.10) AS Minimum_Product_Box_Height,"
sSQL=sSQL+ " B.Height - (B.Thickness * 0.95) AS Maximum_Product_Box_Height,"
sSQL=sSQL+ " B.Length AS Box_Length,"
sSQL=sSQL+ " B.Width AS Box_Width," sSQL=sSQL+ " B.Height AS Box_Height,"
sSQL=sSQL+ " B.BoxVolume AS Box_cm_Volume,"
sSQL=sSQL+ " ((B.Length*10) * (B.Width*10) * (B.Height*10)) AS Box_ccm_Volume,"
sSQL=sSQL+ " (2 * B.Length * B.Width) + (2 * B.Length * B.Height) + (2 * B.Width *
B.Height) AS Box_sqm_Area,"
sSQL=sSQL+ " ((B.Length*10) * (B.Width*10) * (B.Height*10)) * 3.5 AS
Box_A_Max_Kg_Weight,"sSQL=sSQL+ " ((B.Length*10) * (B.Width*10) * (B.Height*10))
* 7.7 AS Box_B_Max_Kg_Weight," sSQL=sSQL+ " ((B.Length*10) * (B.Width*10) *
(B.Height*10)) * 10.0 AS Box_C_Max_Kg_Weight"sSQL=sSQL+ " FROM"
sSQL=sSQL+ " Assess_Product as P"sSQL=sSQL+ " ,"
sSQL=sSQL+ " Assess_Box as B"sSQL=sSQL+ " WHERE"
sSQL=sSQL+ " P.Length >= (B.Length - (B.Thickness * 1.10))"sSQL=sSQL+ " AND"
sSQL=sSQL+ " P.Width >= (B.Width - (B.Thickness * 1.10))"sSQL=sSQL+ " AND"
sSQL=sSQL+ " P.Height >= (B.Height - (B.Thickness * 1.10))"sSQL=sSQL+ " AND"
sSQL=sSQL+ " P.Length <= (B.Length - (B.Thickness * 0.95))"sSQL=sSQL+ " AND"

sSQL=sSQL+ " P.Width <= (B.Width - (B.Thickness * 0.95))"sSQL=sSQL+ " AND"
sSQL=sSQL+ " P.Height <= (B.Height - (B.Thickness * 0.95))"sSQL=sSQL+ " AND"
sSQL=sSQL+ " (B.Height - B.Thickness) >= 0"sSQL=sSQL+ " AND"
sSQL=sSQL+ " (B.Width - B.Thickness) >= 0"sSQL=sSQL+ " AND"
sSQL=sSQL+ " (B.Height - B.Thickness) >= 0"sSQL=sSQL+ " AND"
sSQL=sSQL+ " B.BoxVolume >= P.ProductVolume;"sql.execute(sSQL,conn)
### Fit Box in Pallet
#####
t=0
for l in range(2,8):
    for w in range(2,8):
        for h in range(4):
            t += 1
PalletLine=[('IDNumber',[t]),
            ('ShipType', ['Pallet']),
            ('UnitNumber', ('L-'+format(t,"06d"))),
            ('Box_per_Length',(format(2**l,"4d"))),
            ('Box_per_Width',(format(2**w,"4d"))),
            ('Box_per_Height',(format(2**h,"4d")))]if t==1:

```

```

PalletFrame = pd.DataFrame.from_items(PalletLine) else:
PalletRow = pd.DataFrame.from_items(PalletLine) PalletFrame =
PalletFrame.append(PalletRow) PalletFrame.set_index(['IDNumber'], inplace=True)
#####
PalletFrame.head() print('#####')
print('Rows : ', PalletFrame.shape[0]) print('#####')
#####
### Fit Box on Pallet
#####
print('#####')
sView='Assess_Box_on_Pallet'
print('Creating :',sDatabaseName,' View:',sView)sSQL="DROP VIEW IF EXISTS " + sView
+ ";"
sql.execute(sSQL,conn)
sSQL="CREATE VIEW " + sView + " AS"sSQL=sSQL+ " SELECT DISTINCT"
sSQL=sSQL+ " P.UnitNumber AS PalletNumber,"sSQL=sSQL+ " B.UnitNumber AS
BoxNumber,"
sSQL=sSQL+ " round(B.Length*P.Box_per_Length,3) AS Pallet_Length,"sSQL=sSQL+ "
round(B.Width*P.Box_per_Width,3) AS Pallet_Width," sSQL=sSQL+ "
round(B.Height*P.Box_per_Height,3) AS Pallet_Height,"
sSQL=sSQL+ " P.Box_per_Length * P.Box_per_Width * P.Box_per_Height AS Pallet_Boxes"
sSQL=sSQL+ " FROM"
sSQL=sSQL+ " Assess_Box as B"sSQL=sSQL+ ","
sSQL=sSQL+ " Assess_Pallet as P"
sSQL=sSQL+ " WHERE"
sSQL=sSQL+ " round(B.Length*P.Box_per_Length,3) <= 20"sSQL=sSQL+ " AND"
sSQL=sSQL+ " round(B.Width*P.Box_per_Width,3) <= 9"sSQL=sSQL+ " AND"
sSQL=sSQL+ " round(B.Height*P.Box_per_Height,3) <= 5;" sql.execute(sSQL,conn)
#####
sTables=['Assess_Product_in_Box','Assess_Box_on_Pallet'] for sTable in sTables:
print('#####')
print('Loading :',sDatabaseName,' Table:',sTable)sSQL=" SELECT "
sSQL=sSQL+ " *" sSQL=sSQL+ " FROM"
sSQL=sSQL+ " " + sTable + ";" SnapShotData=pd.read_sql_query(sSQL, conn)
print('#####')
sTableOut=sTable + '_SnapShot'
print('Storing :',sDatabaseName,' Table:',sTable) SnapShotData.to_sql(sTableOut, conn,
if_exists="replace") print('#####')
#####
### Fit Pallet in Container
#####
sTables=['Length','Width','Height']for sTable in sTables:
sView='Assess_Pallet_in_Container_' + sTable print('Creating :',sDatabaseName,'
View:',sView)sSQL="DROP VIEW IF EXISTS " + sView + ";"
sql.execute(sSQL,conn)
sSQL="CREATE VIEW " + sView + " AS"sSQL=sSQL+ " SELECT DISTINCT"
sSQL=sSQL+ " C.UnitNumber AS ContainerNumber,"sSQL=sSQL+ " P.PalletNumber,"
sSQL=sSQL+ " P.BoxNumber,"
sSQL=sSQL+ " round(C." + sTable + "/P.Pallet_" + sTable + ",0)"sSQL=sSQL+ " AS
Pallet_per_" + sTable + ","
sSQL=sSQL+ " round(C." + sTable + "/P.Pallet_" + sTable + ",0)" sSQL=sSQL+ " *
P.Pallet_Boxes AS Pallet_" + sTable + "_Boxes,"sSQL=sSQL+ " P.Pallet_Boxes"
sSQL=sSQL+ " FROM"

```

```

sSQL=sSQL+ " Assess_Container as C"sSQL=sSQL+ ","
sSQL=sSQL+ " Assess_Box_on_Pallet_SnapShot as P"sSQL=sSQL+ " WHERE"
sSQL=sSQL+ " round(C.Length/P.Pallet_Length,0) > 0"sSQL=sSQL+ " AND"
sSQL=sSQL+ " round(C.Width/P.Pallet_Width,0) > 0"sSQL=sSQL+ " AND"
sSQL=sSQL+ " round(C.Height/P.Pallet_Height,0) > 0;"sql.execute(sSQL,conn)
print('#####')
print('Loading :,sDatabaseName,' Table:',sView)sSQL=" SELECT "
sSQL=sSQL+ " *"

sSQL=sSQL+ " FROM" sSQL=sSQL+ " " + sView + ";"
SnapShotData=pd.read_sql_query(sSQL, conn) print('#####')
sTableOut= sView + '_SnapShot'
print('Storing :,sDatabaseName,' Table:',sTableOut) SnapShotData.to_sql(sTableOut, conn,
if_exists="replace") print('#####')
#####
print('#####')
sView='Assess_Pallet_in_Container' print('Creating :,sDatabaseName,' View:',sView)
sSQL="DROP VIEW IF EXISTS " + sView + ";"
sql.execute(sSQL,conn)
sSQL="CREATE VIEW " + sView + " AS"sSQL=sSQL+ " SELECT"
sSQL=sSQL+ " CL.ContainerNumber,"sSQL=sSQL+ " CL.PalletNumber," sSQL=sSQL+ "
CL.BoxNumber,"
sSQL=sSQL+ " CL.Pallet_Boxes AS Boxes_per_Pallet,"sSQL=sSQL+ "
CL.Pallet_per_Length,"
sSQL=sSQL+ " CW.Pallet_per_Width,"sSQL=sSQL+ " CH.Pallet_per_Height,"
sSQL=sSQL+ " CL.Pallet_Length_Boxes * CW.Pallet_Width_Boxes *
CH.Pallet_Height_Boxes ASContainer_Boxes"
sSQL=sSQL+ " FROM"
sSQL=sSQL+ " Assess_Pallet_in_Container_Length_SnapShot as CL"sSQL=sSQL+ " JOIN"
sSQL=sSQL+ " Assess_Pallet_in_Container_Width_SnapShot as CW"sSQL=sSQL+ " ON"
sSQL=sSQL+ " CL.ContainerNumber = CW.ContainerNumber"sSQL=sSQL+ " AND"
sSQL=sSQL+ " CL.PalletNumber = CW.PalletNumber"sSQL=sSQL+ " AND"
sSQL=sSQL+ " CL.BoxNumber = CW.BoxNumber"sSQL=sSQL+ " JOIN"
sSQL=sSQL+ " Assess_Pallet_in_Container_Height_SnapShot as CH" sSQL=sSQL+ " ON"
sSQL=sSQL+ " CL.ContainerNumber = CH.ContainerNumber"sSQL=sSQL+ " AND"
sSQL=sSQL+ " CL.PalletNumber = CH.PalletNumber"sSQL=sSQL+ " AND"
sSQL=sSQL+ " CL.BoxNumber = CH.BoxNumber;"sql.execute(sSQL,conn)
#####
sTables=['Assess_Product_in_Box','Assess_Pallet_in_Container'] for sTable in sTables:
print('#####')
print('Loading :,sDatabaseName,' Table:',sTable)sSQL=" SELECT "
sSQL=sSQL+ " *" sSQL=sSQL+ " FROM"
sSQL=sSQL+ " " + sTable + ";" PackData=pd.read_sql_query(sSQL, conn)
print('#####')
print(PackData)

print('#####') print('#####')
print('Rows : ',PackData.shape[0]) print('#####')
sFileName=sFileDir + '/' + sTable + '.csv' print(sFileName) PackData.to_csv(sFileName,
index = False)
print('## Done!! #####')
#####

```

```

Python 3.7.4 Shell
File Edit View Insert Cell Help
***** STARTING C:\VKHCG\03-Hillman\02-Assess\Assess-Shipping-Containers.py ****
Working Base = C:\VKHCG using win32
*****
Loading : C:\VKHCG\03-Hillman\01-Retrieve\01-EDS\02-Python\Retrieve_Product.csv
Loaded Product : 5 * SkuType "UnitNumber" "Length" "Width" "Height" "ProductVolume"
*****
***** Loading : C:\VKHCG\03-Hillman\02-Assess\SQLite\hillman.db : Table: Assess_Product
***** SkuType UnitNumber Length Width Height ProductVolume
IDNumber
0  product  2000001  0.1  0.1  0.1  0.001
1  product  2000002  0.1  0.1  0.2  0.002
2  product  2000003  0.1  0.1  0.3  0.003
3  product  2000004  0.1  0.1  0.4  0.004
4  product  2000005  0.1  0.1  0.5  0.005
*****
Rows = 5
*****
Loading : C:\VKHCG\03-Hillman\01-Retrieve\01-EDS\02-Python\Retrieve_Boxes.csv
Loaded Product : 5 * SkuType "UnitNumber" "Length" "Width" "Height" "ProductVolume"
"ProductVolume" * ProductVolume *
*****

```

J. Write a Python program to create a delivery route using the given data. Creating a Delivery Route

Hillman requires the complete grid plan of the delivery routes for the company, to ensure the suppliers, warehouses, shops, and customers can be reached by its new strategy. This new plan will enable the optimum routes between suppliers, warehouses, shops, and customers.

Open Python editor and create a file named Assess-Shipping-Routes.py in directory C:\VKHCG\03-Hillman\02-Assess.

```

#####
import sys
import os
import pandas as pd
import sqlite3 as sq
from pandas.io import sql
import networkx as nx
from geopy.distance import vincenty
#####
nMax=3 nMaxPath=10 nSet=False nVSet=False
#####
Base='C:/VKHCG'
#####
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
#####
Company='03-Hillman' InputDir1='01-Retrieve/01-EDS/01-R'
InputDir2='01-Retrieve/01-EDS/02-Python'

InputFileName1='Retrieve_GB_Postcode_Warehouse.csv'
InputFileName2='Retrieve_GB_Postcodes_Shops.csv' EDSDir='02-Assess/01-EDS'
OutputDir=EDSDir + '/02-Python' OutputFileName1='Assess_Shipping_Routes.gml'
OutputFileName2='Assess_Shipping_Routes.txt'
#####
sFileDir=Base + '/' + Company + '/' + EDSDir if not os.path.exists(sFileDir):
os.makedirs(sFileDir)
#####
sFileDir=Base + '/' + Company + '/' + OutputDir if not os.path.exists(sFileDir):
os.makedirs(sFileDir)
#####
sDataBaseDir=Base + '/' + Company + '/02-Assess/SQLite' if not os.path.exists(sDataBaseDir):
os.makedirs(sDataBaseDir)
```

```

#####
sDatabaseName=sDataBaseDir + '/hillman.db' conn = sq.connect(sDatabaseName)
#####
#####
### Import Warehouse Data
#####
sFileName=Base + '/' + Company + '/' + InputDir1 + '/' + InputFileName1 print('#####')
print('Loading :,sFileName) WarehouseRawData=pd.read_csv(sFileName,header=0,
low_memory=False,encoding="latin-1"
)
WarehouseRawData.drop_duplicates(subset=None, keep='first', inplace=True)
WarehouseRawData.index.name = 'IDNumber'
WarehouseData=WarehouseRawData.head(nMax)
WarehouseData=WarehouseData.append(WarehouseRawData.tail(nMax))
WarehouseData=WarehouseData.append(WarehouseRawData[WarehouseRawData.postcode=
='KA13']) if nSet==True:
WarehouseData=WarehouseData.append(WarehouseRawData[WarehouseRawData.postcode=='S
W1W']) WarehouseData.drop_duplicates(subset=None, keep='first', inplace=True)
print('Loaded Warehouses :,WarehouseData.columns.values)
print('#####')
#####
print('#####')
sTable='Assess_Warehouse_UK'
print('Storing :,sDatabaseName, Table:',sTable) WarehouseData.to_sql(sTable, conn,
if_exists="replace") print('#####')
#####
print(WarehouseData.head()) print('#####')
print('Rows :,WarehouseData.shape[0]) print('#####')
#####
### Import Shop Data

#####
sFileName=Base + '/' + Company + '/' + InputDir1 + '/' + InputFileName2 print('#####')
print('Loading :,sFileName) ShopRawData=pd.read_csv(sFileName,header=0,
low_memory=False,encoding="latin-1"
)
ShopRawData.drop_duplicates(subset=None, keep='first', inplace=True)
ShopRawData.index.name = 'IDNumber'
ShopData=ShopRawData
print('Loaded Shops :,ShopData.columns.values)
print('#####')
#####
print('#####')
sTable='Assess_Shop_UK'
print('Storing :,sDatabaseName, Table:',sTable) ShopData.to_sql(sTable, conn,
if_exists="replace") print('#####')
#####
print(ShopData.head()) print('#####')
print('Rows :,ShopData.shape[0]) print('#####')
#####
### Connect HQ
#####
print('#####')

```

```

sView='Assess_HQ'
print('Creating :',sDatabaseName,' View:',sView)sSQL="DROP VIEW IF EXISTS " + sView
+ ","
sql.execute(sSQL,conn)
sSQL="CREATE VIEW " + sView + " AS"sSQL=sSQL+ " SELECT"
sSQL=sSQL+ " W.postcode AS HQ_PostCode," sSQL=sSQL+ " 'HQ-' || W.postcode AS
HQ_Name," sSQL=sSQL+ " round(W.latitude,6) AS HQ_Latitude," sSQL=sSQL+ "
round(W.longitude,6) AS HQ_Longitude"sSQL=sSQL+ " FROM"
sSQL=sSQL+ " Assess_Warehouse_UK as W"sSQL=sSQL+ " WHERE"
sSQL=sSQL+ " TRIM(W.postcode) in ('KA13','SW1W');"
sql.execute(sSQL,conn)
#####
### Connect Warehouses
#####
print('#####')
sView='Assess_Warehouse'
print('Creating :',sDatabaseName,' View:',sView)sSQL="DROP VIEW IF EXISTS " + sView
+ ","
sql.execute(sSQL,conn)
sSQL="CREATE VIEW " + sView + " AS"sSQL=sSQL+ " SELECT"
sSQL=sSQL+ " W.postcode AS Warehouse_PostCode," sSQL=sSQL+ " 'WH-' || W.postcode
AS Warehouse_Name,"

sSQL=sSQL+ " round(W.latitude,6) AS Warehouse_Latitude," sSQL=sSQL+ "
round(W.longitude,6) AS Warehouse_Longitude"sSQL=sSQL+ " FROM"
sSQL=sSQL+ " Assess_Warehouse_UK as W;"sql.execute(sSQL,conn)
#####
### Connect Warehouse to Shops by PostCode
#####
print('#####')
sView='Assess_Shop'
print('Creating :',sDatabaseName,' View:',sView)sSQL="DROP VIEW IF EXISTS " + sView
+ ","
sql.execute(sSQL,conn)
sSQL="CREATE VIEW " + sView + " AS"sSQL=sSQL+ " SELECT"
sSQL=sSQL+ " TRIM(S.postcode) AS Shop_PostCode,"
sSQL=sSQL+ " 'SP-' || TRIM(S.FirstCode) || '-' || TRIM(S.SecondCode) AS Shop_Name,"
sSQL=sSQL+ " TRIM(S.FirstCode) AS Warehouse_PostCode,"
sSQL=sSQL+ " round(S.latitude,6) AS Shop_Latitude," sSQL=sSQL+ " round(S.longitude,6)
AS Shop_Longitude"sSQL=sSQL+ " FROM"
sSQL=sSQL+ " Assess_Warehouse_UK as W"sSQL=sSQL+ " JOIN"
sSQL=sSQL+ " Assess_Shop_UK as S"sSQL=sSQL+ " ON"
sSQL=sSQL+ " TRIM(W.postcode) = TRIM(S.FirstCode);" sql.execute(sSQL,conn)
#####
G=nx.Graph() #####
print('#####')
sTable = 'Assess_HQ'
print('Loading :',sDatabaseName,' Table:',sTable)sSQL=" SELECT DISTINCT"
sSQL=sSQL+ " *" sSQL=sSQL+ " FROM"
sSQL=sSQL+ " " + sTable + ";" RouteData=pd.read_sql_query(sSQL, conn)
print('#####')
#####

```

```

print(RouteData.head()) print('#####')
print('HQ Rows : ',RouteData.shape[0]) print('#####')
#####
for i in range(RouteData.shape[0]): sNode0=RouteData['HQ_Name'][i]G.add_node(sNode0,
Nodetype='HQ',
PostCode=RouteData['HQ_PostCode'][i], Latitude=round(RouteData['HQ_Latitude'][i],6),
Longitude=round(RouteData['HQ_Longitude'][i],6))
#####
print('#####')
sTable = 'Assess_Warehouse'

print('Loading :',sDatabaseName,' Table:',sTable)sSQL=" SELECT DISTINCT"
sSQL=sSQL+ " *" sSQL=sSQL+ " FROM"
sSQL=sSQL+ " " + sTable + ";" RouteData=pd.read_sql_query(sSQL, conn)
print('#####')
#####
print(RouteData.head()) print('#####')
print('Warehouse Rows : ',RouteData.shape[0]) print('#####')
for i in range(RouteData.shape[0]): sNode0=RouteData['Warehouse_Name'][i]
G.add_node(sNode0, Nodetype='Warehouse',
PostCode=RouteData['Warehouse_PostCode'][i],
Latitude=round(RouteData['Warehouse_Latitude'][i],6),
Longitude=round(RouteData['Warehouse_Longitude'][i],6))print('#####')
sTable = 'Assess_Shop'
print('Loading :',sDatabaseName,' Table:',sTable)sSQL=" SELECT DISTINCT"
sSQL=sSQL+ " *" sSQL=sSQL+ " FROM"
sSQL=sSQL+ " " + sTable + ";" RouteData=pd.read_sql_query(sSQL, conn)
print('#####')
print(RouteData.head()) print('#####')
print('Shop Rows : ',RouteData.shape[0]) print('#####')
for i in range(RouteData.shape[0]): sNode0=RouteData['Shop_Name'][i]G.add_node(sNode0,
Nodetype='Shop',
PostCode=RouteData['Shop_PostCode'][i],
WarehousePostCode=RouteData['Warehouse_PostCode'][i],
Latitude=round(RouteData['Shop_Latitude'][i],6),
Longitude=round(RouteData['Shop_Longitude'][i],6))
#####
## Create Edges
#####
print('#####')
print('Loading Edges') print('#####')
for sNode0 in nx.nodes_iter(G):for sNode1 in nx.nodes_iter(G):
if G.node[sNode0]['Nodetype']=='HQ' and \G.node[sNode1]['Nodetype']=='HQ' and \ sNode0
!= sNode1:
distancemeters=round(\ vincenty(\ (\ G.node[sNode0]['Latitude'],\
G.node[sNode0]['Longitude'])\
),\ (\

G.node[sNode1]['Latitude'],\ G.node[sNode1]['Longitude'])\
).meters\
,0)
distancemiles=round(\ vincenty(\ (\ G.node[sNode0]['Latitude'],\
G.node[sNode0]['Longitude'])\

```

```

),\(\ G.node[sNode1]['Latitude']\ ,\ G.node[sNode1]['Longitude']\ )\
).miles\
,3)
if distancemiles >= 0.05:
cost = round(150+(distancemiles * 2.5),6)vehicle='V001'
else:
cost = round(2+(distancemiles * 0.10),6)vehicle='ForkLift'
G.add_edge(sNode0,sNode1,DistanceMeters=distancemeters, \ DistanceMiles=distancemiles, \
Cost=cost,Vehicle=vehicle)if nVSet==True:
print('Edge-H-H:',sNode0,' to ', sNode1, \ ' Distance:',distancemeters,'meters',\
distancemiles,'miles','Cost', cost,'Vehicle',vehicle)if G.node[sNode0]['Nodetype']=='HQ' and \
G.node[sNode1]['Nodetype']=='Warehouse' and \sNode0 != sNode1:
distancemeters=round(\ vincenty(\ (\ G.node[sNode0]['Latitude'],\
G.node[sNode0]['Longitude']\ \
),\(\ G.node[sNode1]['Latitude']\ ,\ G.node[sNode1]['Longitude']\ )\
).meters\
,0)
distancemiles=round(\ vincenty(\ (\ G.node[sNode0]['Latitude'],\
G.node[sNode0]['Longitude']\ \
),\(\ G.node[sNode1]['Latitude']\ ,\ G.node[sNode1]['Longitude']\ )\
).miles\
,3)
if distancemiles >= 10:
cost = round(50+(distancemiles * 2),6)vehicle='V002'
else:
cost = round(5+(distancemiles * 1.5),6)vehicle='V003'
if distancemiles <= 50: G.add_edge(sNode0,sNode1,DistanceMeters=distancemeters, \
DistanceMiles=distancemiles, \
Cost=cost,Vehicle=vehicle)if nVSet==True:
print('Edge-H-W:',sNode0,' to ', sNode1, \ ' Distance:',distancemeters,'meters',\
distancemiles,'miles','Cost', cost,'Vehicle',vehicle)if nSet==True and \
G.node[sNode0]['Nodetype']=='Warehouse' and \G.node[sNode1]['Nodetype']=='Warehouse' \
and \sNode0 != sNode1:
distancemeters=round(\ vincenty(\ \
(\ G.node[sNode0]['Latitude'],\ G.node[sNode0]['Longitude']\ \
),\(\ G.node[sNode1]['Latitude']\ ,\ G.node[sNode1]['Longitude']\ )\
).meters\
,0)
distancemiles=round(\ vincenty(\ (\ G.node[sNode0]['Latitude'],\
G.node[sNode0]['Longitude']\ \
),\(\ G.node[sNode1]['Latitude']\ ,\ G.node[sNode1]['Longitude']\ )\
).miles\
,3)
if distancemiles >= 10:
cost = round(50+(distancemiles * 1.10),6)vehicle='V004'
else:
cost = round(5+(distancemiles * 1.05),6)vehicle='V005'
if distancemiles <= 20: G.add_edge(sNode0,sNode1,DistanceMeters=distancemeters, \
DistanceMiles=distancemiles, \
Cost=cost,Vehicle=vehicle)if nVSet==True:
print('Edge-W-W:',sNode0,' to ', sNode1, \ ' Distance:',distancemeters,'meters',\

```

```

distancemiles,'miles','Cost', cost,'Vehicle',vehicle) if G.node[sNode0]['Nodetype']=='Warehouse'
and \G.node[sNode1]['Nodetype']=='Shop' and \
G.node[sNode0]['PostCode']==G.node[sNode1]['WarehousePostCode'] and \ sNode0 != sNode1:
distancemeters=round(\ vincenty(\ (\ G.node[sNode0]['Latitude'],\
G.node[sNode0]['Longitude'])\
),\ (\ G.node[sNode1]['Latitude'],\ ,\ G.node[sNode1]['Longitude'])\
).meters\
,0)
distancemiles=round(
vincenty(\(
G.node[sNode0]['Latitude'],\ G.node[sNode0]['Longitude']\
),\ (\ G.node[sNode1]['Latitude'],\ ,\ G.node[sNode1]['Longitude'])\
).miles\
,3)
if distancemiles >= 10:
cost = round(50+(distancemiles * 1.50),6)vehicle='V006'
else:
cost = round(5+(distancemiles * 0.75),6)vehicle='V007'
if distancemiles <= 10: G.add_edge(sNode0,sNode1,DistanceMeters=distancemeters, \
DistanceMiles=distancemiles, \
Cost=cost,Vehicle=vehicle)if nVSet==True:
print('Edge-W-S:',sNode0,' to ', sNode1, '\' Distance:',distancemeters,'meters',\
distancemiles,'miles','Cost', cost,'Vehicle',vehicle)if nSet==True and \
G.node[sNode0]['Nodetype']=='Shop' and \ G.node[sNode1]['Nodetype']=='Shop' and \
G.node[sNode0]['WarehousePostCode']==G.node[sNode1]['WarehousePostCode'] and \ sNode0 \
!= sNode1:
distancemeters=round(\ vincenty(\ (\ G.node[sNode0]['Latitude'],\
G.node[sNode0]['Longitude'])\
),\ (\ G.node[sNode1]['Latitude'],\ ,\ G.node[sNode1]['Longitude'])\
).meters\
,0)
distancemiles=round(\ vincenty(\ (\ G.node[sNode0]['Latitude'],\
G.node[sNode0]['Longitude'])\
),\ (\ G.node[sNode1]['Latitude'],\ ,\ G.node[sNode1]['Longitude'])\
).miles\
,3)
if distancemiles >= 0.05:
cost = round(5+(distancemiles * 0.5),6)vehicle='V008'
else:
cost = round(1+(distancemiles * 0.1),6)vehicle='V009'
if distancemiles <= 0.075: G.add_edge(sNode0,sNode1,DistanceMeters=distancemeters, \
DistanceMiles=distancemiles, \
Cost=cost,Vehicle=vehicle)

if nVSet==True:
print('Edge-S-S:',sNode0,' to ', sNode1, '\' Distance:',distancemeters,'meters',\
distancemiles,'miles','Cost', cost,'Vehicle',vehicle)if nSet==True and \
G.node[sNode0]['Nodetype']=='Shop' and \ G.node[sNode1]['Nodetype']=='Shop' and \
G.node[sNode0]['WarehousePostCode']!=G.node[sNode1]['WarehousePostCode'] and \ sNode0 != \
sNode1:
distancemeters=round(\ vincenty(\ (\ G.node[sNode0]['Latitude'],\
G.node[sNode0]['Longitude'])\

```

```

),\(\ G.node[sNode1]['Latitude']\,\,\,\ G.node[sNode1]['Longitude']\ )\)
).meters\
,0)
distancemiles=round(\ vincenty(\ (\ G.node[sNode0]['Latitude'],\
G.node[sNode0]['Longitude']\,
),\(\ G.node[sNode1]['Latitude']\,\,\,\ G.node[sNode1]['Longitude']\ )\)
).miles\
,3)
cost = round(1+distancemiles * 0.1),6)vehicle='V010'
if distancemiles <= 0.025: G.add_edge(sNode0,sNode1,DistanceMeters=distancemeters, \
DistanceMiles=distancemiles, \
Cost=cost,Vehicle=vehicle)if nVSet==True:
print('Edge-S-S:',sNode0,' to ', sNode1, '\ Distance:',distancemeters,'meters',\
distancemiles,'miles','Cost', cost,'Vehicle',vehicle)sFileName=sFileDir + '/' +
OutputFileName1 print('#####')
print('Storing :, sFileName) print('#####')
nx.write_gml(G,sFileName) sFileName=sFileName +'.gz' nx.write_gml(G,sFileName)
print('Nodes:',nx.number_of_nodes(G)) print('Edges:',nx.number_of_edges(G))
sFileName=sFileDir + '/' + OutputFileName2 print('#####')
print('Storing :, sFileName) print('#####')
## Create Paths print('#####')
print('Loading Paths') print('#####')
f = open(sFileName,'w')l=0
sline = 'ID|Cost|StartAt|EndAt|Path|Measure'if nVSet==True: print ('0', sline) f.write(sline+
'\n')
for sNode0 in nx.nodes_iter(G):
for sNode1 in nx.nodes_iter(G):
if sNode0 != sNode1 and \
nx.has_path(G, sNode0, sNode1)==True and \nx.shortest_path_length(G, \
source=sNode0, \target=sNode1, \
weight='DistanceMiles') < nMaxPath:l+=1
sID='{:0f}'.format(l)
spat = ','.join(nx.shortest_path(G, \source=sNode0, \
target=sNode1, \ weight='DistanceMiles')) slength= '{:.6f}'.format(
nx.shortest_path_length(G, \source=sNode0, \ target=sNode1, \ weight='DistanceMiles'))
sline = sID + "|"DistanceMiles"|" + sNode0 + "||" \
+ sNode1 + "||" + spat + "||" + slengthif nVSet==True: print (sline) f.write(sline + '\n')
l+=1
sID='{:0f}'.format(l)
spat = ','.join(nx.shortest_path(G, \source=sNode0, \
target=sNode1, \ weight='DistanceMeters')) slength= '{:.6f}'.format(
nx.shortest_path_length(G, \source=sNode0, \ target=sNode1, \ weight='DistanceMeters'))
sline = sID + "|"DistanceMeters"|" + sNode0 + "||" \
+ sNode1 + "||" + spat + "||" + slengthif nVSet==True: print (sline) f.write(sline + '\n')
l+=1
sID='{:0f}'.format(l)
spat = ','.join(nx.shortest_path(G, \source=sNode0, \
target=sNode1, \weight='Cost'))
slength= '{:.6f}'.format(\ nx.shortest_path_length(G, \source=sNode0, \ target=sNode1, \
weight='Cost'))
sline = sID + "|Cost"|" + sNode0 + "||" + sNode1 + "||" + spat + "||" + slengthif \
nVSet==True: print (sline) f.write(sline + '\n')

```

```

f.close() print('Nodes:',nx.number_of_nodes(G))print('Edges:',nx.number_of_edges(G))
print('Paths:',SID) print('#####')
print('Vacuum Database')sSQL="VACUUM;"
sql.execute(sSQL,conn) print('#####')
print('## Done!! #####')

```

| IDNumber | id   | postcode | latitude | longitude |
|----------|------|----------|----------|-----------|
| 0        | 2    | AB10     | 57.13514 | -2.11731  |
| 1        | 3    | AB11     | 57.13875 | -2.08089  |
| 2        | 4    | AB12     | 57.10100 | -2.11060  |
| 3000     | 3003 | PA80     | 0.00000  | 0.00000   |
| 3001     | 3004 | L80      | 0.00000  | 0.00000   |

Rows : 7

#####

Loading : C:/VKHCG/03-Hillman/01-Retrieve/01-EDS/01-R/Retrieve\_GB\_Postcode\_Warehouse.csv  
Loaded Warehouses : ['id', 'postcode', 'latitude', 'longitude']  
#####

Storing : C:/VKHCG/03-Hillman/02-Assess/SQLite/hillman.db Table: Assess\_Warehouse\_UK  
#####

## Clark Ltd

Clark Ltd is the accountancy company that handles everything related to the VKHCG's finances and personnel. Let's investigate Clark with new knowledge.

K. Write a Python program to create Simple forex trading planner from the givendata.

### Simple Forex Trading Planner

Clark requires the assessment of the group's forex data, for processing and data quality issues. I will guide you through an example of a forex solution.

Open your Python editor and create a file named Assess-Forex.py in directory C:\VKHCG\04-Clark\02-Assess.

```

#####
import sys
import os
import sqlite3 as sq
import pandas as pd
#####
Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
#####
Company='04-Clark'
sInputFileName1='01-Vermeulen/01-Retrieve/01-EDS/02-Python/Retrieve-Country-Currency.csv'
sInputFileName2='04-Clark/01-Retrieve/01-EDS/01-R/Retrieve_Euro_EchangeRates.csv'
#####
sDataBaseDir=Base + '/' + Company + '/02-Assess/SQLite' if not os.path.exists(sDataBaseDir):
os.makedirs(sDataBaseDir)
#####
sDatabaseName=sDataBaseDir + '/clark.db'

```

```

conn = sq.connect(sDatabaseName)
#####
### Import Country Data
#####
sFileName1=Base + '/' + sInputFileName1 print('#####')
print('Loading :',sFileName1) print('#####')
CountryRawData=pd.read_csv(sFileName1,header=0,low_memory=False, encoding="latin-1")
CountryRawData.drop_duplicates(subset=None, keep='first', inplace=True)
CountryData=CountryRawData
print('Loaded Company :',CountryData.columns.values)
print('#####')
#####
print('#####')
sTable='Assess_Country'
print('Storing :',sDatabaseName,' Table:',sTable) CountryData.to_sql(sTable, conn,
if_exists="replace") print('#####')
#####
print(CountryData.head()) print('#####')
print('Rows : ',CountryData.shape[0]) print('#####')
#####
### Import Forex Data
#####
sFileName2=Base + '/' + sInputFileName2 print('#####')
print('Loading :',sFileName2) print('#####')
ForexRawData=pd.read_csv(sFileName2,header=0,low_memory=False, encoding="latin-1")
ForexRawData.drop_duplicates(subset=None, keep='first', inplace=True)
ForexData=ForexRawData.head(5)
print('Loaded Company :',ForexData.columns.values)
print('#####')
#####
print('#####')
sTable='Assess_Forex'
print('Storing :',sDatabaseName,' Table:',sTable) ForexData.to_sql(sTable, conn,
if_exists="replace") print('#####')
#####
print(ForexData.head()) print('#####')
print('Rows : ',ForexData.shape[0]) print('#####')
#####
print('#####')
sTable='Assess_Forex'
print('Loading :',sDatabaseName,' Table:',sTable)sSQL="select distinct"
sSQL=sSQL+ " A.CodeIn"sSQL=sSQL+ " from"
sSQL=sSQL+ " Assess_Forex as A;" CodeData=pd.read_sql_query(sSQL, conn)

```

```

print('#####')
#####
for c in range(CodeData.shape[0]):
print('#####')
sTable='Assess_Forex & 2x Country > ' + CodeData['CodeIn'][c] print('Loading
:',sDatabaseName,' Table:',sTable)
sSQL="select distinct" sSQL=sSQL+ " A.Date," sSQL=sSQL+ " A.CodeIn,"
sSQL=sSQL+ " B.Country as CountryIn," sSQL=sSQL+ " B.Currency as CurrencyNameIn,"
sSQL=sSQL+ " A.CodeOut,"
sSQL=sSQL+ " C.Country as CountryOut," sSQL=sSQL+ " C.Currency as
CurrencyNameOut," sSQL=sSQL+ " A.Rate"
sSQL=sSQL+ " from" sSQL=sSQL+ " Assess_Forex as A" sSQL=sSQL+ " JOIN"
sSQL=sSQL+ " Assess_Country as B" sSQL=sSQL+ " ON A.CodeIn = B.CurrencyCode"
sSQL=sSQL+ " JOIN"
sSQL=sSQL+ " Assess_Country as C" sSQL=sSQL+ " ON A.CodeOut = C.CurrencyCode"
sSQL=sSQL+ " WHERE"
sSQL=sSQL+ " A.CodeIn ='" + CodeData['CodeIn'][c] + "';"
ForexData=pd.read_sql_query(sSQL, conn).head(1000) print('#####')
print(ForexData) print('#####')
sTable='Assess_Forex_' + CodeData['CodeIn'][c] print('Storing :,sDatabaseName,'
Table:',sTable) ForexData.to_sql(sTable, conn, if_exists="replace") print('#####')
print('#####')
print('Rows : ',ForexData.shape[0]) print('#####')
#####
print('###')
Done!! #####
#####
Output:

```

This will produce a set of demonstrated values onscreen by removing duplicate records and other related dataprocessing.

L. Write a Python program to process the balance sheet to ensure that only good data is processing.Financials

Clark requires you to process the balance sheet for the VKHCG group companies. Go through a sample balancesheet data assessment, to ensure that only the good data is processed.

Open Python editor and create a file named Assess-Financials.py in directoryC:\VKHCG\04-Clark\02-Assess.

```

import sys import os
import sqlite3 as sq import pandas as pd
if sys.platform == 'linux': Base=os.path.expanduser('~') + '/VKHCG' else:
Base='C:/VKHCG'

print('#####')
print('Working Base :,Base, ' using ', sys.platform)
print('#####')
Company='04-Clark'
sInputFileName='01-Retrieve/01-EDS/01-R/Retrieve_Profit_And_Loss.csv'
sDataBaseDir=Base + '/' + Company + '/02-Assess/SQLite'
if not os.path.exists(sDataBaseDir):
os.makedirs(sDataBaseDir) sDatabaseName=sDataBaseDir + '/clark.db' conn =
sq.connect(sDatabaseName)
### Import Financial Data
sFileName=Base + '/' + Company + '/' + sInputFileName
print('#####')
print('Loading :,sFileName) print('#####')

```

```

FinancialRawData=pd.read_csv(sFileName,header=0,low_memory=False, encoding="latin-1")
FinancialData=FinancialRawData
print('Loaded Company :',FinancialData.columns.values)
print('#####') print('#####')
sTable='Assess-Financials'
print('Storing :,sDatabaseName,' Table:',sTable) FinancialData.to_sql(sTable, conn,
if_exists="replace") print('#####')
print(FinancialData.head()) print('#####')
print('Rows :,FinancialData.shape[0]) print('#####')
print('## Done!! #####')
Write a Python program to store all master records for the financial calendarFinancial
Calendar
Clark stores all the master records for the financial calendar. So we import thecalendar from
the retrieve step“sdata storage.
Open Python editor and create a file named Assess-Calendar.py in directory C:\VKHCG\04-
Clark\02-Assess.
#####
import sys
import os
import sqlite3 as sq
import pandas as pd
#####
if sys.platform == 'linux': Base=os.path.expanduser('~') + '/VKHCG' else:
Base='C:/VKHCG' print('#####')
print('Working Base :,Base, ' using ', sys.platform)
print('#####')
#####
Company='04-Clark'
#####
sDataBaseDirIn=Base + '/' + Company + '/01-Retrieve/SQLite' if not
os.path.exists(sDataBaseDirIn): os.makedirs(sDataBaseDirIn)
sDatabaseNameIn=sDataBaseDirIn + '/clark.db'
connIn = sq.connect(sDatabaseNameIn)

#####
sDataBaseDirOut=Base + '/' + Company + '/01-Retrieve/SQLite' if not
os.path.exists(sDataBaseDirOut): os.makedirs(sDataBaseDirOut)
sDatabaseNameOut=sDataBaseDirOut + '/clark.db'
connOut = sq.connect(sDatabaseNameOut)
#####
sTableIn='Retrieve_Date'
sSQL='select * FROM ' + sTableIn + ';' print('#####')
sTableOut='Assess_Time'
print('Loading :,sDatabaseNameIn,' Table:',sTableIn) dateRawData=pd.read_sql_query(sSQL,
connIn) dateData=dateRawData
#####
print('#####')
print('Load Rows :,dateRawData.shape[0], ' records')
print('#####')
dateData.drop_duplicates(subset='FinDate', keep='first', inplace=True)
#####
print('#####')
sTableOut='Assess_Date'
print('Storing :,sDatabaseNameOut,' Table:',sTableOut) dateData.to_sql(sTableOut, connOut,
if_exists="replace") print('#####')

```

```

#####
print('#####')
print('Store Rows : ',dateData.shape[0], ' records')
print('#####')
#####
sTableIn='Retrieve_Time'
sSQL='select * FROM ' + sTableIn + ';' print('#####')
sTableOut='Assess_Time'
print('Loading : ',sDatabaseNameIn,' Table:',sTableIn) timeRawData=pd.read_sql_query(sSQL,
connIn) timeData=timeRawData
#####
print('#####')
print('Load Rows : ',timeData.shape[0], ' records')
print('#####')
timeData.drop_duplicates(subset=None, keep='first', inplace=True)
#####
print('#####')
sTableOut='Assess_Time'
print('Storing : ',sDatabaseNameOut,' Table:',sTableOut) timeData.to_sql(sTableOut, connOut,
if_exists="replace") print('#####')
#####
print('#####')
print('Store Rows : ',timeData.shape[0], ' records')
print('#####')
#####
print('#####') print('###')
Done!! #####
#####

```

```

Python 3.7.4 Shell
File Edit Shell Debug Option Window Help
Type "help", "copyright", "credits" or "license()" for more information.
>>>
----- RESTART: C:\VKHCG\04-Clark\02-Assess\Assess-Calendar.py -----
#####
Working Base : C:/VKHCG using Win32
#####
Loading : C:/VKHCG/04-Clark/01-Retrieve/SQLite/clark.db Table: Retrieve_Date
#####
Load Rows : 50406 records
#####
Storing : C:/VKHCG/04-Clark/01-Retrieve/SQLite/clark.db Table: Assess_Date
#####
Store Rows : 43830 records
#####
Loading : C:/VKHCG/04-Clark/01-Retrieve/SQLite/clark.db Table: Retrieve_Time
#####
Load Rows : 7196 records
#####
Storing : C:/VKHCG/04-Clark/01-Retrieve/SQLite/clark.db Table: Assess_Time
#####
Store Rows : 1440 records
#####
### Done!! #####
>>> | L: 31 Col: 4

```

M. Write a Python program to generate payroll from the given data.

People

Clark Ltd generates the payroll, so it holds all the staff records. Clark also handles all payments to suppliers and receives payments from customers' details on all companies.

Open Python editor and create a file named Assess-People.py in directory C:\VKHCG\04-Clark\02-Assess.

```
#####
import sys
import os
#####
import sqlite3 as sq
import pandas as pd
#####
Base='C:/VKHCG'
print('#####')

print('Working Base :',Base, ' using ', sys.platform)
print('#####')
#####
Company='04-Clark'

sInputFileName1='01-Retrieve/01-EDS/02-Python/Retrieve-Data_female-names.csv'
sInputFileName2='01-Retrieve/01-EDS/02-Python/Retrieve-Data_male-names.csv'

sInputFileName3='01-Retrieve/01-EDS/02-Python/Retrieve-Data_last-names.csv'
sOutputFileName1='Assess-Staff.csv'
sOutputFileName2='Assess-Customers.csv'
#####
sDataBaseDir=Base + '/' + Company + '/02-Assess/SQLite' if not os.path.exists(sDataBaseDir):
os.makedirs(sDataBaseDir)
#####
sDatabaseName=sDataBaseDir + '/clark.db' conn = sq.connect(sDatabaseName)
#####

### Import Female Data
#####
sFileName=Base + '/' + Company + '/' + sInputFileName1
print('#####')
print('Loading :',sFileName) print('#####')
print(sFileName)

FemaleRawData=pd.read_csv(sFileName,header=0,low_memory=False, encoding="latin-1")
FemaleRawData.rename(columns={'NameValues' : 'FirstName'},inplace=True)
FemaleRawData.drop_duplicates(subset=None, keep='first', inplace=True)
FemaleData=FemaleRawData.sample(100)
print('#####')
#####
print('#####')
sTable='Assess_FemaleName'

print('Storing :',sDatabaseName,' Table:',sTable) FemaleData.to_sql(sTable, conn,
if_exists="replace") print('#####') print('#####')
print('Rows : ',FemaleData.shape[0], ' records') print('#####')
```

```
#####
```

### ### Import Male Data

```
sFileName=Base + '/' + Company + '/' + sInputFileName2
print('#####')
print('Loading :',sFileName) print('#####')
MaleRawData=pd.read_csv(sFileName,header=0,low_memory=False, encoding="latin-1")
MaleRawData.rename(columns={'NameValues' : 'FirstName'},inplace=True)
MaleRawData.drop_duplicates(subset=None, keep='first', inplace=True)
MaleData=MaleRawData.sample(100)
print('#####')
```

```
sTable='Assess_MaleName'
```

```
print('Storing :',sDatabaseName,' Table:',sTable) MaleData.to_sql(sTable, conn,
if_exists="replace") print('#####')
#####
print('#####')
print('Rows : ',MaleData.shape[0], ' records') print('#####')
#####
### Import Surname Data
```

```
sFileName=Base + '/' + Company + '/' + sInputFileName3
print('#####')
print('Loading :',sFileName) print('#####')
SurnameRawData=pd.read_csv(sFileName,header=0,low_memory=False, encoding="latin-1")
SurnameRawData.rename(columns={'NameValues' : 'LastName'},inplace=True)
SurnameRawData.drop_duplicates(subset=None, keep='first', inplace=True)
SurnameData=SurnameRawData.sample(200)
print('#####')
```

```
sTable='Assess_Surname'
```

```
print('Storing :',sDatabaseName,' Table:',sTable)
```

```
SurnameData.to_sql(sTable, conn, if_exists="replace")print('#####')
print('#####')
print('Rows : ',SurnameData.shape[0], ' records')
print('#####') print('#####')
sTable='Assess_FemaleName & Assess_MaleName'print('Loading :',sDatabaseName,'
Table:',sTable) sSQL="select distinct"
sSQL=sSQL+ " A.FirstName," sSQL=sSQL+ " 'Female' as Gender"sSQL=sSQL+ " from"
sSQL=sSQL+ " Assess_FemaleName as A"sSQL=sSQL+ " UNION"
sSQL=sSQL+ " select distinct" sSQL=sSQL+ " A.FirstName," sSQL=sSQL+ " 'Male' as
Gender"sSQL=sSQL+ " from"
sSQL=sSQL+ " Assess_MaleName as A;" FirstNameData=pd.read_sql_query(sSQL, conn)
print('#####')
#####
#print('#####')
sTable='Assess_FirstName'
```

```
print('Storing :',sDatabaseName,' Table:',sTable) FirstNameData.to_sql(sTable, conn,
if_exists="replace") print('#####')
```

```
#####
#####
print('#####')
sTable='Assess_FirstName x2 & Assess_Surname' print('Loading :',sDatabaseName,'
Table:',sTable)


sSQL="select distinct" sSQL=sSQL+ " A.FirstName,"
sSQL=sSQL+ " B.FirstName AS SecondName,"sSQL=sSQL+ " C.LastName,"
sSQL=sSQL+ " A.Gender" sSQL=sSQL+ " from"
sSQL=sSQL+ " Assess_FirstName as A"sSQL=sSQL+ ","
sSQL=sSQL+ " Assess_FirstName as B"sSQL=sSQL+ ","
sSQL=sSQL+ " Assess_Surname as C"sSQL=sSQL+ " WHERE"
sSQL=sSQL+ " A.Gender = B.Gender" sSQL=sSQL+ " AND"
sSQL=sSQL+ " A.FirstName <> B.FirstName;" PeopleRawData=pd.read_sql_query(sSQL,
conn)People1Data=PeopleRawData.sample(10000) sTable='Assess_FirstName &
Assess_Surname' print('Loading :',sDatabaseName,' Table:',sTable)sSQL="select distinct"
sSQL=sSQL+ " A.FirstName," sSQL=sSQL+ " " AS SecondName,"sSQL=sSQL+ "
B.LastName," sSQL=sSQL+ " A.Gender" sSQL=sSQL+ " from"
sSQL=sSQL+ " Assess_FirstName as A"sSQL=sSQL+ ","
sSQL=sSQL+ " Assess_Surname as B;" PeopleRawData=pd.read_sql_query(sSQL, conn)
People2Data=PeopleRawData.sample(10000) PeopleData=People1Data.append(People2Data)
print(PeopleData)

print('#####') #print('#####')
sTable='Assess_People'

print('Storing :',sDatabaseName,' Table:',sTable) PeopleData.to_sql(sTable, conn,
if_exists="replace") print('#####')
sFileDir=Base + '/' + Company + '/02-Assess/01-EDS/02-Python' if not
os.path.exists(sFileDir):
    os.makedirs(sFileDir) sOutputFileName = sTable+'.csv'
sFileName=sFileDir + '/' + sOutputFileName print('#####')
print('Storing :', sFileName) print('#####')
PeopleData.to_csv(sFileName, index = False) print('#####')
##### print('###
Done!! #####')
##### OUTPUT:
```

#### OUTPUT:

```
Python 3.7.6 |Anaconda, Inc.| (default, Jan  4 2020, 19:50:29) [MSC v.1916 64 bit (AMD64)]
Type "help", "copyright", "credits" or "license" for more information.
RESTART: C:\VKHCG\04-Clark\02-Assess\Assess-People.py
#####
Loading : C:/VKHCG/04-Clark/01-Retrieve/01-EDS/02-Python/Retrieve-Data_female-names.csv
C:/VKHCG/04-Clark/01-Retrieve/01-EDS/02-Python/Retrieve-Data_female-names.csv
Storing : C:/VKHCG/04-Clark/02-Assess/SQLite/clark.db Table: Assess_FemaleName
Rows : 100 records
Loading : C:/VKHCG/04-Clark/01-Retrieve/01-EDS/02-Python/Retrieve-Data_male-names.csv
Storing : C:/VKHCG/04-Clark/02-Assess/SQLite/clark.db Table: Assess_MaleName
Rows : 100 records
Loading : C:/VKHCG/04-Clark/01-Retrieve/01-EDS/02-Python/Retrieve-Data_last-names.csv
Storing : C:/VKHCG/04-Clark/02-Assess/SQLite/clark.db Table: Assess_Surname
Rows : 200 records
Loading : C:/VKHCG/04-Clark/02-Assess/SQLite/clark.db Table: Assess_FemaleName & Assess_MaleName
Storing : C:/VKHCG/04-Clark/02-Assess/SQLite/clark.db Table: Assess_FirstName
Loading : C:/VKHCG/04-Clark/02-Assess/SQLite/clark.db Table: Assess_FirstName x2 & Assess_Surname
Loading : C:/VKHCG/04-Clark/02-Assess/SQLite/clark.db Table: Assess_FirstName & Assess_Surname
FirstName SecondName LastName Gender
247156 Miguel Efren Ortega Male
3466902 Tommye Coretta Roberts Female
3336436 Stan Xavier Costa Male
1151796 Faviola Gene Heard Female
093614 Dorene Joelle Mccloud Female
...
...
...
31958 Santiago Crook Male
32635 Shaunte Ferreira Female
2436 Bernie Dubose Male
39951 Zoraida Cherry Female
7702 Dannie Foret Male
[20000 rows x 4 columns]
Storing : C:/VKHCG/04-Clark/02-Assess/SQLite/clark.db Table: Assess_People
Storing : C:/VKHCG/04-Clark/02-Assess/01-EDS/02-Python/Assess_People.csv
#####
#####
```



## Practical 6: Processing Data

### A. Build the time hub, links, and satellites.

Open your Python editor and create a file named Process\_Time.py. Save it into directory C:\VKHCG\01-Vermeulen\03-Process.

```
import sys
import os
from datetime import datetime
from datetime import timedelta
from pytz import timezone, all_timezones
import pandas as pd
import sqlite3 as sq
from pandas.io import sql
import uuid
pd.options.mode.chained_assignment = None
if sys.platform == 'linux':
    Base = os.path.expanduser('~') + '/VKHCG'
else:
    Base = 'C:/VKHCG'
print('#####')
print('Working Base :', Base, ' using ', sys.platform)
print('#####')
Company = '01-Vermeulen'
InputDir = '00-RawData'
InputFileName = 'VehicleData.csv'
sDataBaseDir = Base + '/' + Company + '/03-Process/SQLite'
if not os.path.exists(sDataBaseDir):
    os.makedirs(sDataBaseDir)
#####
sDatabaseName = sDataBaseDir + '/Hillman.db'
conn1 = sq.connect(sDatabaseName)
#####
sDataVaultDir = Base + '/88-DV'
if not os.path.exists(sDataVaultDir):
    os.makedirs(sDataVaultDir)
sDatabaseName = sDataVaultDir + '/datavault.db'
conn2 = sq.connect(sDatabaseName)
base = datetime(2018, 1, 1, 0, 0, 0)
numUnits = 10 * 365 * 24
date_list = [base - timedelta(hours=x) for x in range(0, numUnits)]
t = 0
for i in date_list:
    now_utc = i.replace(tzinfo=timezone('UTC'))
    sDateTime = now_utc.strftime("%Y-%m-%d %H:%M:%S")
    print(sDateTime)
    sDateTimeKey = sDateTime.replace('-', '.').replace(':', '-')
    t += 1
    IDNumber = str(uuid.uuid4())
    TimeLine = [
        ('ZoneBaseKey', ['UTC']),
        ('IDNumber', [IDNumber]),
        ('nDateTimeValue', [now_utc]),
        ('DateTimeValue', [sDateTime]),
        ('DateTimeKey', [sDateTimeKey])
    ]
    if t == 1:
        TimeFrame = pd.DataFrame.from_items(TimeLine)
    else:
        TimeRow = pd.DataFrame.from_items(TimeLine)
        TimeFrame = TimeFrame.append(TimeRow)
    #####
TimeHub = TimeFrame[['IDNumber', 'ZoneBaseKey', 'DateTimeKey', 'DateTimeValue']]
TimeHubIndex = TimeHub.set_index(['IDNumber'], inplace=False)
TimeFrame.set_index(['IDNumber'], inplace=True)
sTable = 'Process-Time'
print('Storing :', sDatabaseName, ' Table:', sTable)
TimeHubIndex.to_sql(sTable, conn1, if_exists="replace")
sTable = 'Hub-Time'
print('Storing :', sDatabaseName, ' Table:', sTable)
TimeHubIndex.to_sql(sTable, conn2, if_exists="replace")
active_timezones = all_timezones
z = 0
for zone in active_timezones:
    t = 0
    for j in range(TimeFrame.shape[0]):
        now_date = TimeFrame['nDateTimeValue'][j]
        DateTimeKey = TimeFrame['DateTimeKey'][j]
        now_utc = now_date.replace(tzinfo=timezone('UTC'))
        sDateTime = now_utc.strftime("%Y-%m-%d %H:%M:%S")
        TimeLine = [
            ('ZoneBaseKey', [zone]),
            ('IDNumber', [IDNumber]),
            ('nDateTimeValue', [now_utc]),
            ('DateTimeValue', [sDateTime]),
            ('DateTimeKey', [sDateTimeKey])
        ]
        if t == 1:
            TimeFrame = pd.DataFrame.from_items(TimeLine)
        else:
            TimeRow = pd.DataFrame.from_items(TimeLine)
            TimeFrame = TimeFrame.append(TimeRow)
        #####
    TimeHubIndex = TimeHub.set_index(['IDNumber'], inplace=False)
    TimeFrame.set_index(['IDNumber'], inplace=True)
    sTable = 'Process-Time'
    print('Storing :', sDatabaseName, ' Table:', sTable)
    TimeHubIndex.to_sql(sTable, conn1, if_exists="replace")
    sTable = 'Hub-Time'
    print('Storing :', sDatabaseName, ' Table:', sTable)
    TimeHubIndex.to_sql(sTable, conn2, if_exists="replace")
    active_timezones = all_timezones
    z = 0
```

```
%m-%d %H:%M:%S") now_zone = now_utc.astimezone(timezone(zone))
sZoneDateTime=now_zone.strftime("%Y-%m-%d %H:%M:%S") print(sZoneDateTime)
t+=1 z+=1
IDZoneNumber=str(uuid.uuid4()) TimeZoneLine=[('ZoneBaseKey', ['UTC']),
('IDZoneNumber', [IDZoneNumber]), ('DateTimeKey', [DateTimeKey]),
('UTCDateTimeValue', [sDateTime]), ('Zone', [zone]),
('DateTimeValue', [sZoneDateTime])] if t==1:
TimeZoneFrame = pd.DataFrame.from_items(TimeZoneLine) else:
TimeZoneRow = pd.DataFrame.from_items(TimeZoneLine) TimeZoneFrame =
TimeZoneFrame.append(TimeZoneRow)
TimeZoneFrameIndex=TimeZoneFrame.set_index(['IDZoneNumber'],inplace=False)
sZone=zone.replace('/','-').replace(' ','')
sTable = 'Process-Time-'+sZone
print('Storing :',sDatabaseName,' Table:',sTable) TimeZoneFrameIndex.to_sql(sTable, conn1,
if_exists="replace") sTable = 'Satellite-Time-'+sZone
print('Storing :',sDatabaseName,' Table:',sTable) TimeZoneFrameIndex.to_sql(sTable, conn2,
if_exists="replace") print('#####')
print('Vacuum Databases') sSQL="VACUUM;" sql.execute(sSQL,conn1)sql.execute(sSQL,conn2)
```

print('#####')  
print('## Done!! #####')

You have built your first hub and satellites for time in the data vault.

The data vault has been built in directory ..\VKHCG\88-DV\datavault.db. You can access it with your SQLitetools

Golden Nominal

A golden nominal record is a single person's record, with distinctive references for use by all systems. This gives

the system a single view of the person. I use first name, other names, last name, and birth date as my golden nominal. The data we have in the assess directory requires a birth date to become a golden nominal. The program will generate a golden nominal using our sample data set.

Open your Python editor and create a file called Process-People.py in the .. C:\VKHCG\04-Clark\03-Process directory.

```
#####
#####
import sys
import os
import sqlite3 as sq
import pandas as pd
from pandas.io import sql
from datetime import datetime, timedelta
from pytz import timezone, all_timezones
from random import randint
import uuid
if sys.platform == 'linux':
    Base=os.path.expanduser('~') + '/VKHCG'
else:
    Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
Company='04-Clark'
sInputFileName='02-Assess/01-EDS/02-Python/Assess_People.csv'
sDataBaseDir=Base + '/' + Company + '/03-Process/SQLite'
if not os.path.exists(sDataBaseDir): os.makedirs(sDataBaseDir)
```

```

sDatabaseName=sDataBaseDir + '/clark.db' conn1 = sq.connect(sDatabaseName)
sDataVaultDir=Base + '/88-DV'
if not os.path.exists(sDataBaseDir): os.makedirs(sDataBaseDir)
sDatabaseName=sDataVaultDir + '/datavault.db' conn2 = sq.connect(sDatabaseName)
### Import Female Data
sFileName=Base + '/' + Company + '/' + sInputFileName
print('#####')
print('Loading :',sFileName) print('#####')
print(sFileName)
RawData=pd.read_csv(sFileName,header=0,low_memory=False, encoding="latin-1")
RawData.drop_duplicates(subset=None, keep='first', inplace=True)
start_date = datetime(1900,1,1,0,0,0)
start_date_utc=start_date.replace(tzinfo=timezone('UTC')) HoursBirth=100*365*24
RawData['BirthDateUTC']=RawData.apply(lambda row: (start_date_utc +
timedelta(hours=randint(0, HoursBirth)))
,axis=1)

zonemax=len(all_timezones)-1 RawData['TimeZone']=RawData.apply(lambda row:
(all_timezones[randint(0, zonemax)])
,axis=1) RawData['BirthDateISO']=RawData.apply(lambda row:
row["BirthDateUTC"].astimezone(timezone(row['TimeZone'])))
,axis=1) RawData['BirthDateKey']=RawData.apply(lambda row:
row["BirthDateUTC"].strftime("%Y-%m-%d %H:%M:%S"))
,axis=1) RawData['BirthDate']=RawData.apply(lambda row:
row["BirthDateISO"].strftime("%Y-%m-%d %H:%M:%S"))
,axis=1) RawData['PersonID']=RawData.apply(lambda row:
str(uuid.uuid4()))
,axis=1) Data=RawData.copy()
Data.drop('BirthDateUTC', axis=1,inplace=True) Data.drop('BirthDateISO',
axis=1,inplace=True) indexed_data = Data.set_index(['PersonID'])
print('#####') print('#####')
sTable='Process_Person'
print('Storing :',sDatabaseName,' Table:',sTable) indexed_data.to_sql(sTable, conn1,
if_exists="replace") print('#####')
PersonHubRaw=Data[['PersonID','FirstName','SecondName','LastName','BirthDateKey']]
PersonHubRaw['PersonHubID']=RawData.apply(lambda row:
str(uuid.uuid4()))
,axis=1) PersonHub=PersonHubRaw.drop_duplicates(subset=None, \ keep='first',\
inplace=False)
indexed_PersonHub = PersonHub.set_index(['PersonHubID'])sTable = 'Hub-Person'
print('Storing :',sDatabaseName,' Table:',sTable) indexed_PersonHub.to_sql(sTable, conn2,
if_exists="replace")
PersonSatelliteGenderRaw=Data[['PersonID','FirstName','SecondName','LastName'\ ,
'BirthDateKey','Gender']]
PersonSatelliteGenderRaw['PersonSatelliteID']=RawData.apply(lambda row: str(uuid.uuid4()))
,axis=1) PersonSatelliteGender=PersonSatelliteGenderRaw.drop_duplicates(subset=None, \
keep='first', \
inplace=False)
indexed_PersonSatelliteGender = PersonSatelliteGender.set_index(['PersonSatelliteID'])
sTable = 'Satellite-Person-Gender'
print('Storing :',sDatabaseName,' Table:',sTable)
indexed_PersonSatelliteGender.to_sql(sTable, conn2, if_exists="replace")
#####

```

```

PersonSatelliteBirthdayRaw=Data[['PersonID','FirstName','SecondName','LastName',\
'BirthDateKey','TimeZone','BirthDate']]
PersonSatelliteBirthdayRaw['PersonSatelliteID']=RawData.apply(lambda row:
str(uuid.uuid4()))
, axis=1) PersonSatelliteBirthday=PersonSatelliteBirthdayRaw.drop_duplicates(subset=None, \
keep='first',\ inplace=False)
indexed_PersonSatelliteBirthday = PersonSatelliteBirthday.set_index(['PersonSatelliteID'])
sTable = 'Satellite-Person-Names'
print('Storing :',sDatabaseName,' Table:',sTable) indexed_PersonSatelliteBirthday.to_sql(sTable,
conn2, if_exists="replace") sFileDir=Base + '/' + Company + '/03-Process/01-EDS/02-Python'
if not os.path.exists(sFileDir):
os.makedirs(sFileDir) sOutputFileName = sTable + '.csv'
sFileName=sFileDir + '/' + sOutputFileName print('#####')
print('Storing :', sFileName) print('#####')
RawData.to_csv(sFileName, index = False) print('#####')
print('#####')
print('Vacuum Databases') sSQL="VACUUM;"
sql.execute(sSQL,conn1) sql.execute(sSQL,conn2) print('#####')
print('## Done!! #####')

```

Output :

It will apply golden nominal rules by assuming nobody born before January 1, 1900, droping to two ISOcomplex

date time structures, as the code does not translate into SQLite's data types and saves your new golden nominal to a CSV file.

Load the person into the data vault

```

=====
RESTART: C:\VKHCG\04-Clark\03-Process\Process-People.py =====
Working Base : C:/VKHCG using win32
Loading : C:/VKHCG/04-Clark/02-Assess/01-EDS/02-Python/Assess_People.csv C:/VKHCG/04-
Clark/02-Assess/01-EDS/02-Python/Assess_People.csv
Storing : C:/VKHCG/88-DV/datavault.db Table: Process_Person
Storing : C:/VKHCG/88-DV/datavault.db Table: Satellite-Person-GenderStoring :
C:/VKHCG/88-DV/datavault.db Table: Satellite-Person-Names
Storing : C:/VKHCG/04-Clark/03-Process/01-EDS/02-Python/Satellite-Person-Names.csv
Vacuum Databases
#####
## Done!! #####

```

Vehicles

The international classification of vehicles is a complex process. There are standards, but these are notuniversally

applied or similar between groups or countries.

Let's load the vehicle data for Hillman Ltd into the data vault, as we will need it later. Create a new file namedProcess-Vehicle-Logistics.py in the Python editor in directory ..\VKHCG\03-Hillman\03-Process.

```

# -*- coding: utf-8 -*-
import sys
import os
import pandas as pd
import sqlite3 as sq
from pandas.io import sq
pd.options.mode.chained_assignment = None
if sys.platform == 'linux':
    Base=os.path.expanduser('~') + '/VKHCG'

```

```

else:
Base='C:/VKHCG' print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
Company='03-Hillman' InputDir='00-RawData' InputFileName='VehicleData.csv'
sDataBaseDir=Base + '/' + Company + '/03-Process/SQLite'if not
os.path.exists(sDataBaseDir):
os.makedirs(sDataBaseDir) sDatabaseName=sDataBaseDir + '/Hillman.db'conn1 =
sq.connect(sDatabaseName) sDataVaultDir=Base + '/88-DV'
if not os.path.exists(sDataBaseDir):
os.makedirs(sDataBaseDir) sDatabaseName=sDataVaultDir + '/datavault.db'conn2 =
sq.connect(sDatabaseName)
sFileName=Base + '/' + Company + '/' + InputDir + '/' + InputFileNameprint('#####')
print('Loading :,sFileName) VehicleRaw=pd.read_csv(sFileName,header=0,low_memory=False,
encoding="latin-1") sTable='Process_Vehicles'
print('Storing :,sDatabaseName,' Table:',sTable) VehicleRaw.to_sql(sTable, conn1,
if_exists="replace") VehicleRawKey=VehicleRaw[['Make','Model']].copy()
VehicleKey=VehicleRawKey.drop_duplicates()
VehicleKey['ObjectKey']=VehicleKey.apply(lambda row:
str('+' + str(row['Make']).strip().replace(' ','-').replace('/', '-').lower() +
')-' + (str(row['Model']).strip().replace(' ','-').replace('/', '-').lower())
+')')
, axis=1) VehicleKey['ObjectType']=VehicleKey.apply(lambda row:
'vehicle'
, axis=1) VehicleKey['ObjectUUID']=VehicleKey.apply(lambda row: str(uuid.uuid4())
, axis=1)
### Vehicle Hub#
VehicleHub=VehicleKey[['ObjectType','ObjectKey','ObjectUUID']].copy()
VehicleHub.index.name='ObjectHubID'
sTable = 'Hub-Object-Vehicle'
print('Storing :,sDatabaseName,' Table:',sTable) VehicleHub.to_sql(sTable, conn2,
if_exists="replace") ### Vehicle Satellite
#
VehicleSatellite=VehicleKey[['ObjectType','ObjectKey','ObjectUUID','Make','Model']].copy()
VehicleSatellite.index.name='ObjectSatelliteID'
sTable = 'Satellite-Object-Make-Model' print('Storing :,sDatabaseName,' Table:',sTable)
VehicleSatellite.to_sql(sTable, conn2, if_exists="replace")### Vehicle Dimension
sView='Dim-Object'
print('Storing :,sDatabaseName,' View:',sView) sSQL="CREATE VIEW IF NOT EXISTS ["
+sView + "] AS"


sSQL=sSQL+ " SELECT DISTINCT"
sSQL=sSQL+ " H.ObjectType,"
sSQL=sSQL+ " H.ObjectKey AS VehicleKey," sSQL=sSQL+ " TRIM(S.Make) AS
VehicleMake," sSQL=sSQL+ " TRIM(S.Model) AS VehicleModel"sSQL=sSQL+ " FROM"
sSQL=sSQL+ " [Hub-Object-Vehicle] AS H"sSQL=sSQL+ " JOIN"
sSQL=sSQL+ " [Satellite-Object-Make-Model] AS S"sSQL=sSQL+ " ON"
sSQL=sSQL+ " H.ObjectType=S.ObjectType"sSQL=sSQL+ " AND"
sSQL=sSQL+ " H.ObjectUUID=S.ObjectUUID;"sql.execute(sSQL,conn2)
print('#####')
print('Loading :,sDatabaseName,' Table:',sView)sSQL=" SELECT DISTINCT"
sSQL=sSQL+ " VehicleMake," sSQL=sSQL+ " VehicleModel" sSQL=sSQL+ " FROM"

```

```

sSQL=sSQL+ "[" + sView + "]"
sSQL=sSQL+ " ORDER BY"
sSQL=sSQL+ " VehicleMake"
sSQL=sSQL+ " AND"
sSQL=sSQL+ " VehicleMake;" DimObjectData=pd.read_sql_query(sSQL, conn2)
DimObjectData.index.name='ObjectDimID'
DimObjectData.sort_values(['VehicleMake','VehicleModel'],inplace=True, ascending=True)
print('#####
print(DimObjectData)
#####
#####
print('#####
print('Vacuum Databases') sSQL="VACUUM;"
sql.execute(sSQL,conn1) sql.execute(sSQL,conn2) print('#####
#####
conn1.close()conn2.close()
#####
##### #print('#####
Done!! #####")
#####

```



## Human-Environment Interaction

In the Python editor, open a new file named Process\_Location.py in directory ..\VKHCG\01-Vermeulen\03-Process.

```
import sys
import os
import pandas as pd
import sqlite3 as sq
from pandas.io import sql
import uuid
Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
Company='01-Vermeulen' InputAssessGraphName='Assess_All_Animals.gml'
EDSAssessDir='02-Assess/01-EDS' InputAssessDir=EDSAssessDir + '/02-Python'
sFileAssessDir=Base + '/' + Company + '/' + InputAssessDir
if not os.path.exists(sFileAssessDir):
    os.makedirs(sFileAssessDir)

sDataBaseDir=Base + '/' + Company + '/03-Process/SQLite'
if not os.path.exists(sDataBaseDir):
    os.makedirs(sDataBaseDir)
sDatabaseName=sDataBaseDir + '/Vermeulen.db'
conn1 = sq.connect(sDatabaseName)
sDataVaultDir=Base + '/88-DV'
if not os.path.exists(sDataVaultDir):
    os.makedirs(sDataVaultDir)
sDatabaseName=sDataVaultDir + '/datavault.db'
conn2 = sq.connect(sDatabaseName)

t=0 tMax=360*180
for Longitude in range(-180,180,10):
    for Latitude in range(-90,90,10):
        t+=1
        IDNumber=str(uuid.uuid4())
        LocationName='L'+format(round(Longitude,3)*1000, '+07d') + \
            '+'+format(round(Latitude,3)*1000, '+07d')
        print('Create:',t,' of ',tMax,':',LocationName)
        LocationLine=[('ObjectBaseKey', ['GPS']), ('IDNumber', [IDNumber]),
                      ('LocationNumber', [str(t)]), ('LocationName', [LocationName]), ('Longitude', [Longitude]),
                      ('Latitude', [Latitude])]
        if t==1:
            LocationFrame = pd.DataFrame.from_items(LocationLine)
        else:
            LocationRow = pd.DataFrame.from_items(LocationLine)
            LocationFrame = LocationFrame.append(LocationRow)
        LocationHubIndex=LocationFrame.set_index(['IDNumber'], inplace=False)
        sTable = 'Process-Location'
        print('Storing :',sDatabaseName, ' Table:',sTable)
        LocationHubIndex.to_sql(sTable, conn1, if_exists="replace")
sTable = 'Hub-Location'
```

```

print('Storing :',sDatabaseName,' Table:',sTable)
LocationHubIndex.to_sql(sTable, conn2, if_exists="replace")
print('#####')
print('Vacuum Databases')
sSQL="VACUUM;"
sql.execute(sSQL,conn1)
sql.execute(sSQL,conn2)
print('#####')
print('## Done!!')
#####

```

```

Python 3.7.4 Shell
File Edit Shell Options Window Help
Create: 645 of 64800 : L+170000--050000
Create: 646 of 64800 : L+170000--060000
Create: 647 of 64800 : L+170000--070000
Create: 648 of 64800 : L+170000--080000
Storing : C:/VKHCG/88-DV/datavault.db Table: Process-Location
Storing : C:/VKHCG/88-DV/datavault.db Table: Hub-Location
#####
Vacuum Databases
#####
## Done!! #####
>>> 

```

## Forecasting

Forecasting is the ability to project a possible future, by looking at historical data. The datavault enables these types of investigations, owing to the complete history it collects as it processes the source's systems data. A data scientist supply answers to such questions as the following:

- What should we buy?
- What should we sell?
- Where will our next business come from?

People want to know what you calculate to determine what is about to happen.

Open a new file in your Python editor and save it as Process-Shares-Data.py in directory C:\VKHCG\04-Clark\03-Process. I will guide you through this

process. You will require a library called quandl type pip install quandl in cmd

```

#####
import sys
import os
import sqlite3
as sqimport
quandl import
pandas as pd
#####
# Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')

```

```
#####
#
Company='04-Clark'
sInputFileName='00-RawData/VKHCG_Shares.csv'
sOutputFileName='Shares.csv'
#####
#####
sDataBaseDir=Base + '/' + Company + '/03-
Process/SQLite'if not
os.path.exists(sDataBaseDir):
os.makedirs(sDataBaseDir)
#####
sFileDir1=Base + '/' + Company + '/01-Retrieve/01-EDS/02-Python'if not
os.path.exists(sFileDir1):
os.makedirs(sFileDir1)
#####
sFileDir2=Base + '/' + Company + '/02-Assess/01-EDS/02-Python' if not
os.path.exists(sFileDir2):
os.makedirs(sFileDir2)
#####
sFileDir3=Base + '/' + Company + '/03-Process/01-EDS/02-Python'if not
os.path.exists(sFileDir3):
os.makedirs(sFileDir3)
#####
sDatabaseName=sDataBaseDir + '/clark.db'conn = sq.connect(sDatabaseName)
#####
### Import Share Names Data
#####
sFileName=Base + '/' + Company + '/' + sInputFileName
print('#####')
print('Loading :',sFileName) print('#####')
RawData=pd.read_csv(sFileName,header=0,low_memory=False, encoding="latin-1")
RawData.drop_duplicates(subset=None, keep='first', inplace=True)
print('Rows :',RawData.shape[0]) print('Columns:',RawData.shape[1])
print('#####')
#####
sFileName=sFileDir1 + '/Retrieve_' + sOutputFileName
print('#####')
print('Storing :, sFileName) print('#####')
RawData.to_csv(sFileName, index = False) print('#####')
#####
sFileName=sFileDir2 + '/Assess_' + sOutputFileName
print('#####')
print('Storing :, sFileName) print('#####')
RawData.to_csv(sFileName, index = False) print('#####')
#####
sFileName=sFileDir3 + '/Process_' + sOutputFileName
print('#####')
print('Storing :, sFileName) print('#####')
RawData.to_csv(sFileName, index = False) print('#####')
#####
### Import Shares Data DetailsnShares=RawData.shape[0] #nShares=6
for sShare in range(nShares): sShareName=str(RawData['Shares'][sShare])ShareData =
quandl.get(sShareName)
```

```

UnitsOwn=RawData['Units'][sShare] ShareData['UnitsOwn']=ShareData.apply(lambda
row:(UnitsOwn),axis=1) ShareData['ShareCode']=ShareData.apply(lambda
row:(sShareName),axis=1) print('#####')
print('Share :',sShareName) print('Rows :',ShareData.shape[0])
print('Columns:',ShareData.shape[1])print('#####')
#####
print('#####')
sTable=str(RawData['sTable'][sShare]) print('Storing :',sDatabaseName,' Table:',sTable)
ShareData.to_sql(sTable, conn, if_exists="replace") print('#####')
#####
sOutputFileName = sTable.replace("/", "-") + '.csv' sFileName=sFileDir1 + '/Retrieve_' +
sOutputFileNameprint('#####')
print('Storing :', sFileName) print('#####')
ShareData.to_csv(sFileName, index = False) print('#####')
#####
sOutputFileName = sTable.replace("/", "-") + '.csv' sFileName=sFileDir2 + '/Assess_' +
sOutputFileNameprint('#####')
print('Storing :', sFileName) print('#####')
ShareData.to_csv(sFileName, index = False) print('#####')
#####
sOutputFileName = sTable.replace("/", "-") + '.csv' sFileName=sFileDir3 + '/Process_' +
sOutputFileNameprint('#####')
print('Storing :', sFileName) print('#####')
ShareData.to_csv(sFileName, index = False) print('#####')
print('### Done!! #####')
#####

```

Output:

===== RESTART: C:\VKHCG\04-Clark\03-Process\Process-Shares-Data.py =====

Working Base : C:/VKHCG using win32

Loading : C:/VKHCG/04-Clark/00-RawData/VKHCG\_Shares.csv Rows : 10

Columns: 3

Storing : C:/VKHCG/04-Clark/01-Retrieve/01-EDS/02-Python/Retrieve\_Shares.csv Storing :

C:/VKHCG/04-Clark/02-Assess/01-EDS/02-Python/Assess\_Shares.csv Storing :

C:/VKHCG/04-Clark/03-Process/01-EDS/02-Python/Process\_Shares.csv Share :

WIKI/GOOGL

Rows : 3424

Columns: 14

Storing : C:/VKHCG/04-Clark/03-Process/SQLite/clark.db Table: WIKI\_Google

Storing : C:/VKHCG/04-Clark/01-Retrieve/01-EDS/02-Python/Retrieve\_WIKI\_Google.csv

Storing : C:/VKHCG/04-Clark/02-Assess/01-EDS/02-Python/Assess\_WIKI\_Google.

## Practical 7

### Transforming Data

#### Transform Superstep

```
C:\VKHCG\01-Vermeulen\04-Transform.  
import sys  
import os  
from datetime import datetime  
from pytz import timezone  
import pandas as pd  
import sqlite3 as sq  
import uuid  
pd.options.mode.chained_assignment = None  
#####  
Base='C:/VKHCG'  
print('#####')  
print('Working Base :',Base, ' using ', sys.platform)  
print('#####')  
#####  
Company='01-Vermeulen' InputDir='00-RawData' InputFileName='VehicleData.csv'  
#####  
sDataBaseDir=Base + '/' + Company + '/04-Transform/SQLite' if not  
os.path.exists(sDataBaseDir):  
    os.makedirs(sDataBaseDir)  
#####  
sDatabaseName=sDataBaseDir + '/Vermeulen.db' conn1 = sq.connect(sDatabaseName)  
#####  
sDataVaultDir=Base + '/88-DV'  
if not os.path.exists(sDataVaultDir):  
    os.makedirs(sDataVaultDir)  
#####  
sDatabaseName=sDataVaultDir + '/datavault.db' conn2 = sq.connect(sDatabaseName)  
#####  
sDataWarehouseDir=Base + '/99-DW'  
if not os.path.exists(sDataWarehouseDir): os.makedirs(sDataWarehouseDir)  
#####  
sDatabaseName=sDataWarehouseDir + '/datawarehouse.db' conn3 =  
sq.connect(sDatabaseName)  
#####  
print('\n#####')  
print('Time Category') print('UTC Time')  
BirthDateUTC = datetime(1960,12,20,10,15,0)  
BirthDateZoneUTC=BirthDateUTC.replace(tzinfo=timezone('UTC'))  
BirthDateZoneStr=BirthDateZoneUTC.strftime("%Y-%m-%d %H:%M:%S")  
BirthDateZoneUTCStr=BirthDateZoneUTC.strftime("%Y-%m-%d %H:%M:%S (%Z) (%z)")  
print(BirthDateZoneUTCStr)  
print('#####')  
print('Birth Date in Reykjavik :') BirthZone = 'Atlantic/Reykjavik'  
BirthDate = BirthDateZoneUTC.astimezone(timezone(BirthZone))  
BirthDateStr=BirthDate.strftime("%Y-%m-%d %H:%M:%S (%Z) (%z)")  
BirthDateLocal=BirthDate.strftime("%Y-%m-%d %H:%M:%S") print(BirthDateStr)  
print('#####')  
  
IDZoneNumber=str(uuid.uuid4()) sDateTimeKey=BirthDateZoneStr.replace(' ','-').replace(':','-')
```

```

TimeLine=[('ZoneBaseKey', ['UTC']),
          ('IDNumber', [IDZoneNumber]), ('DateTimeKey', [sDateTimeKey]), ('UTCDDateTimeValue',
          [BirthDateZoneUTC]), ('Zone', [BirthZone]),
          ('DateTimeValue', [BirthDateStr])]

TimeFrame = pd.DataFrame.from_items(TimeLine)
#####
TimeHub=TimeFrame[['IDNumber','ZoneBaseKey','DateTimeKey','DateTimeValue']]
TimeHubIndex=TimeHub.set_index(['IDNumber'],inplace=False)
#####
sTable = 'Hub-Time-Gunnarsson' print('\n#####')
print('Storing :,sDatabaseName,'n Table:',sTable)
print("\n#####")
TimeHubIndex.to_sql(sTable, conn2, if_exists="replace")sTable = 'Dim-Time-Gunnarsson'
TimeHubIndex.to_sql(sTable, conn3, if_exists="replace")
#####
TimeSatellite=TimeFrame[['IDNumber','DateTimeKey','Zone','DateTimeValue']]
TimeSatelliteIndex=TimeSatellite.set_index(['IDNumber'],inplace=False)
#####
BirthZoneFix=BirthZone.replace(' ','-').replace('/','-') sTable = 'Satellite-Time-' + BirthZoneFix
+ '-Gunnarsson'print('\n#####')
print('Storing :,sDatabaseName,'n Table:',sTable)
print("\n#####")
TimeSatelliteIndex.to_sql(sTable, conn2, if_exists="replace")sTable = 'Dim-Time-' +
BirthZoneFix + '-Gunnarsson' TimeSatelliteIndex.to_sql(sTable, conn3, if_exists="replace")
#####
print("\n#####")
print('Person Category') FirstName = 'Guðmundur' LastName = 'Gunnarsson'
print('Name:',FirstName,LastName) print('Birth Date:',BirthDateLocal) print('Birth
Zone:',BirthZone)
print('UTC Birth Date:',BirthDateZoneStr) print('#####')
#####
IDPersonNumber=str(uuid.uuid4()) PersonLine=[('IDNumber', [IDPersonNumber]),
          ('FirstName', [FirstName]),
          ('LastName', [LastName]),
          ('Zone', ['UTC']),
          ('DateTimeValue', [BirthDateZoneStr])]

PersonFrame = pd.DataFrame.from_items(PersonLine)
#####
TimeHub=PersonFrame TimeHubIndex=TimeHub.set_index(['IDNumber'],inplace=False)
#####
sTable = 'Hub-Person-Gunnarsson' print('\n#####')
print('Storing :,sDatabaseName,'n Table:',sTable)
print("\n#####")

TimeHubIndex.to_sql(sTable, conn2, if_exists="replace")sTable = 'Dim-Person-Gunnarsson'
TimeHubIndex.to_sql(sTable, conn3, if_exists="replace")

```

**Output :**

```

RESTART: C:\VKHCG\01-Vermeulen\04-Transform\Transform-Gunnarsson_is_Born.py
Working Base : C:/VKHCG using win32
Time Category
UTC Time
1960-12-20 10:15:00 (UTC) (+0000)
#####
Birth Date in Reykjavik :
1960-12-20 09:15:00 (-01) (-0100)
#####
Storing : C:/VKHCG/99-DW/datawarehouse.db
Table: Hub-Time-Gunnarsson
#####
Storing : C:/VKHCG/99-DW/datawarehouse.db
Table: Satellite-Time-Atlantic-Reykjavik-Gunnarsson
#####
Person Category
Name: Guðmundur Gunnarsson
Birth Date: 1960-12-20 09:15:00
Birth Zone: Atlantic/Reykjavik
UTC Birth Date: 1960-12-20 10:15:00
#####
Storing : C:/VKHCG/99-DW/datawarehouse.db
Table: Hub-Person-Gunnarson
#####

```

You must build three items: **dimension Person**, **dimension Time**, and **factPersonBornAtTime**. Open your Python editor and create a file named Transform-Gunnarsson-Sun-Model.py in directory C:\VKHCG\01-Vermeulen\04-Transform.

```

#####
import sys
import os
from datetime import datetime
from pytz import timezone
import pandas as pd
import sqlite3
import uuid
pd.options.mode.chained_assignment = None
#####
if sys.platform == 'linux': Base=os.path.expanduser('~') + '/VKHCG'
else: Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
Company='01-Vermeulen'
#####
sDataBaseDir=Base + '/' + Company + '/04-Transform/SQLite'
if not os.path.exists(sDataBaseDir): os.makedirs(sDataBaseDir)
#####
sDatabaseName=sDataBaseDir + '/Vermeulen.db'
conn1 = sq.connect(sDatabaseName)
#####
sDataWarehouseDir=Base + '/99-DW'
if not os.path.exists(sDataWarehouseDir): os.makedirs(sDataWarehouseDir)

#####
sDatabaseName=sDataWarehouseDir + '/datawarehouse.db'
conn2 =
sq.connect(sDatabaseName)
#####
print("\n#####")
print('Time Dimension')
BirthZone = 'Atlantic/Reykjavik'
BirthDateUTC = datetime(1960,12,20,10,15,0)
BirthDateZoneUTC=BirthDateUTC.replace(tzinfo=timezone('UTC'))
BirthDateZoneStr=BirthDateZoneUTC.strftime("%Y-%m-%d %H:%M:%S")
BirthDateZoneUTCStr=BirthDateZoneUTC.strftime("%Y-%m-%d %H:%M:%S (%Z) (%z)")
BirthDate = BirthDateZoneUTC.astimezone(timezone(BirthZone))
BirthDateStr=BirthDate.strftime("%Y-%m-%d %H:%M:%S (%Z) (%z)")


```

```


BirthDateLocal=BirthDate.strftime("%Y-%m-%d %H:%M:%S")
#####
IDTimeNumber=str(uuid.uuid4()) TimeLine=[('TimeID', [IDTimeNumber]), ('UTCDates', [BirthDateZoneStr]), ('LocalTime', [BirthDateLocal]), ('TimeZone', [BirthZone])]
TimeFrame = pd.DataFrame.from_items(TimeLine)
#####
DimTime=TimeFrame DimTimeIndex=DimTime.set_index(['TimeID'],inplace=False)
#####
sTable = 'Dim-Time' print('\n#####')
print('Storing :',sDatabaseName,'n Table:',sTable)
print("\n#####")
DimTimeIndex.to_sql(sTable, conn1, if_exists="replace") DimTimeIndex.to_sql(sTable, conn2, if_exists="replace")
#####
print("\n#####")
print('Dimension Person') print('\n#####')
FirstName = 'Guðmundur' LastName = 'Gunnarsson'
#####
IDPersonNumber=str(uuid.uuid4()) PersonLine=[('PersonID', [IDPersonNumber]), ('FirstName', [FirstName]), ('LastName', [LastName]), ('Zone', ['UTC']), ('DateTimeValue', [BirthDateZoneStr])]
PersonFrame = pd.DataFrame.from_items(PersonLine)
#####
DimPerson=PersonFrame DimPersonIndex=DimPerson.set_index(['PersonID'],inplace=False)
#####
sTable = 'Dim-Person' print('\n#####')
print('Storing :',sDatabaseName,'n Table:',sTable)
print("\n#####")
DimPersonIndex.to_sql(sTable, conn1, if_exists="replace") DimPersonIndex.to_sql(sTable, conn2, if_exists="replace")
#####
print("\n#####")
print('Fact - Person - time') print('\n#####')
IDFactNumber=str(uuid.uuid4())

PersonTimeLine=[('IDNumber', [IDFactNumber]), ('IDPersonNumber', [IDPersonNumber]), ('IDTimeNumber', [IDTimeNumber])]
PersonTimeFrame = pd.DataFrame.from_items(PersonTimeLine)
#####
FctPersonTime=PersonTimeFrame
FctPersonTimeIndex=FctPersonTime.set_index(['IDNumber'],inplace=False)
#####
sTable = 'Fact-Person-Time' print('\n#####')
print('Storing :',sDatabaseName,'n Table:',sTable)
print("\n#####")

```

```
FctPersonTimeIndex.to_sql(sTable, conn1, if_exists="replace")
FctPersonTimeIndex.to_sql(sTable, conn2, if_exists="replace")
#####
```

## Output:



The screenshot shows the Python 3.7.4 Shell window. The command line shows the execution of a script named 'Transform-Transform-Gunnarsson-Sun-Model.py'. The output indicates the script is working in a directory 'C:\VKHCG\01-Vermeulen\04-Transform'. It shows the creation of a dimension table 'Dim-Time' from a source file 'C:\VKHCG\99-DW\datawarehouse.db'. The script then moves on to creating a dimension table 'Person'.

## Building a Data Warehouse

```
Open the Transform-Sun-Models.py file from directory C:\VKHCG\01-Vermeulen\04-
Transform. #####
import sys
import os
from datetime import datetime
from pytz import timezone
import pandas as pd
import sqlite3 as sq
import uuid
pd.options.mode.chained_assignment = None
#####
if sys.platform == 'linux': Base=os.path.expanduser('~') + '/VKHCG'
else: Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
Company='01-Vermeulen'
#####
sDataBaseDir=Base + '/' + Company + '/04-Transform/SQLite'
if not os.path.exists(sDataBaseDir): os.makedirs(sDataBaseDir)
#####

sDatabaseName=sDataBaseDir + '/Vermeulen.db'
conn1 = sq.connect(sDatabaseName)
```

```

#####
sDataVaultDir=Base + '/88-DV'
if not os.path.exists(sDataVaultDir):
os.makedirs(sDataVaultDir)
#####
sDatabaseName=sDataVaultDir +
'/datavault.db'conn2 =
sq.connect(sDatabaseName)
#####
sDataWarehouseDir=Base + '/99-DW'
if not os.path.exists(sDataWarehouseDir):
os.makedirs(sDataWarehouseDir)
#####
sDatabaseName=sDataWarehouseDir +
'/datawarehouse.db'conn3 =
sq.connect(sDatabaseName)
#####
sSQL=" SELECT DateTimeValue FROM
[Hub-Time];"
DateDataRaw=pd.read_sql_query(sSQL,
conn2) DateData=DateDataRaw.head(1000)
print(DateData)
#####
#### print('\n#####')
print('Time Dimension')
print("\n#####")
#####
t=0
mt=DateData.shap
e[0]for i in
range(mt):
BirthZone =
('Atlantic/Reykjavik','Europe/London','UCT')for j
in range(len(BirthZone)):
t+=1
print(t,mt*3)
BirthDateUTC = datetime.strptime(DateData['DateTimeValue'][i],"%Y-%m-%d
%H:%M:%S")
BirthDateZoneUTC=BirthDateUTC.replace(tzinfo=timezone('UTC'))
BirthDateZoneStr=BirthDateZoneUTC.strftime("%Y-%m-%d %H:%M:%S")
BirthDateZoneUTCStr=BirthDateZoneUTC.strftime("%Y-%m-%d
%H:%M:%S (%Z) (%z)") BirthDate =
BirthDateZoneUTC.astimezone(timezone(BirthZone[j]))
BirthDateStr=BirthDate.strftime("%Y-%m-%d %H:%M:%S (%Z) (%z)")
BirthDateLocal=BirthDate.strftime("%Y-%m-%d %H:%M:%S")
#####
#
IDTimeNumber=str(uuid.uuid4())
TimeLine=[('TimeID',
[str(IDTimeNumber)]),('UTCDate',
[str(BirthDateZoneStr)]),
('LocalTime', [str(BirthDateLocal)]),
('TimeZone', [str(BirthZone)])]
if t==1:

```

```

TimeFrame =
pd.DataFrame.from_items(TimeLine) else:
TimeRow = pd.DataFrame.from_items(TimeLine)
TimeFrame=TimeFrame.append(TimeRow)
#####
#
DimTime=TimeFrame
DimTimeIndex=DimTime.set_index(['TimeID'],inplace=False)
#####
#####
sTable = 'Dim-Time'
print("\n#####")
print('Storing :',sDatabaseName,'n
Table:',sTable)
print("\n#####")
print('Storing :',sDatabaseName,'n
Table:',sTable)
print("\n#####")
DimTimeIndex.to_sql(sTable, conn1, if_exists="replace")
DimTimeIndex.to_sql(sTable, conn3, if_exists="replace")

#####
#####
sSQL=" SELECT " + \
" FirstName," + \
" SecondName," + \
" LastName," + \
" BirthDateKey " + \
" FROM [Hub-Person];" PersonDataRaw=pd.read_sql_query(sSQL, conn2)
PersonData=PersonDataRaw.head(1000)
#####
print("\n#####")
print('Dimension Person') print("\n#####")
t=0 mt=DateData.shape[0]for i in range(mt):
t+=1
print(t,mt)
FirstName = str(PersonData["FirstName"]) SecondName = str(PersonData["SecondName"]) if
len(SecondName) > 0:
SecondName=""
LastName = str(PersonData["LastName"]) BirthDateKey = str(PersonData["BirthDateKey"])
#####
IDPersonNumber=str(uuid.uuid4()) PersonLine=[('PersonID', [str(IDPersonNumber)], ('FirstName', [FirstName]), ('SecondName', [SecondName]), ('LastName', [LastName]), ('Zone', [str('UTC')]), ('BirthDate', [BirthDateKey])]]if t==1:
PersonFrame = pd.DataFrame.from_items(PersonLine) else:
PersonRow = pd.DataFrame.from_items(PersonLine) PersonFrame =
PersonFrame.append(PersonRow)
#####
DimPerson=PersonFrameprint(DimPerson)
DimPersonIndex=DimPerson.set_index(['PersonID'],inplace=False)
#####
sTable = 'Dim-Person' print("\n#####")
print('Storing :',sDatabaseName,'n Table:',sTable)
print("\n#####")

```

```
DimPersonIndex.to_sql(sTable, conn1, if_exists="replace") DimPersonIndex.to_sql(sTable,  
conn3, if_exists="replace")  
#####
```

**Output:**

You have successfully performed data vault to data warehouse transformation. Simple Linear Regression

Linear regression is used if there is a relationship or significant association between the variables. This can be checked by scatterplots. If no linear association appears between the variables, fitting a linear regression model to the data will not provide a useful model. A linear regression line has equations in the following form:

$Y = a + bX$ ,

Where, X = explanatory variable and

Y = dependent variable b = slope of the line

a = intercept (the value of y when x = 0)

```
#####
```

```
# -*- coding: utf-8 -*-  
#####
```

```
import sys  
import os
```

```
import pandas as pd
```

```

import sqlite3 as sq
import matplotlib.pyplot as pltimport numpy as np
from sklearn import datasets, linear_model
from sklearn.metrics import mean_squared_error, r2_score
#####
Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
#####
Company='01-Vermeulen'
#####
sDataBaseDir=Base + '/' + Company + '/04-Transform/SQLite'if not
os.path.exists(sDataBaseDir): os.makedirs(sDataBaseDir)
#####
sDatabaseName=sDataBaseDir + '/Vermeulen.db'conn1 = sq.connect(sDatabaseName)
#####
sDataVaultDir=Base + '/88-DV'
if not os.path.exists(sDataVaultDir): os.makedirs(sDataVaultDir)
#####
sDatabaseName=sDataVaultDir + '/datavault.db'conn2 = sq.connect(sDatabaseName)
#####
sDataWarehouseDir=Base + '/99-DW'
if not os.path.exists(sDataWarehouseDir): os.makedirs(sDataWarehouseDir)
#####
sDatabaseName=sDataWarehouseDir + '/datawarehouse.db'conn3 =
sq.connect(sDatabaseName)
#####
t=0
tMax=((300-100)/10)*((300-30)/5)
for heightSelect in range(100,300,10):for weightSelect in range(30,300,5): height =
round(heightSelect/100,3) weight = int(weightSelect)
bmi = weight/(height*height)if bmi <= 18.5:
    BMI_Result=1
elif bmi > 18.5 and bmi < 25:
    BMI_Result=2
elif bmi > 25 and bmi < 30:
    BMI_Result=3elif bmi > 30:
    BMI_Result=4else: BMI_Result=0
PersonLine=[('PersonID', [str(t)]),
('Height', [height]),
('Weight', [weight]),
('bmi', [bmi]),
('Indicator', [BMI_Result])]t+=1
print('Row:',t,'of',tMax)if t==1:

```

```

PersonFrame = pd.DataFrame.from_items(PersonLine)
else:
    PersonRow = pd.DataFrame.from_items(PersonLine)
    PersonFrame = PersonFrame.append(PersonRow)
#####
#####
DimPerson=PersonFrame
DimPersonIndex=DimPerson.set_index(['PersonID'],inplace=False)
#####
#
sTable = 'Transform-BMI'
print("\n#####")
#####
print('Storing :',sDatabaseName,'\
Table:',sTable)
print("\n#####")
#####
DimPersonIndex.to_sql(sTable, conn1, if_exists="replace")
#####
#####
sTable = 'Person-Satellite-BMI'
print("\n#####")
#####
print('Storing :',sDatabaseName,'\
Table:',sTable)
print("\n#####")
#####
DimPersonIndex.to_sql(sTable, conn2, if_exists="replace")
#####
#####
sTable = 'Dim-BMI'
print("\n#####")
#####
print('Storing :',sDatabaseName,'\
Table:',sTable)
print("\n#####")
#####
DimPersonIndex.to_sql(sTable, conn3, if_exists="replace")
#####
#####
fig = plt.figure()
PlotPerson=DimPerson[DimPerson['Indica
tor']==1]x=PlotPerson['Height']
y=PlotPerson['Wei
ght']plt.plot(x, y,
".")
PlotPerson=DimPerson[DimPerson['Indica
tor']==2]x=PlotPerson['Height']
y=PlotPerson['Wei
ght']plt.plot(x, y,
"o")
PlotPerson=DimPerson[DimPerson['Indica
tor']==3]x=PlotPerson['Height']
y=PlotPerson['Wei
ght']plt.plot(x, y,
"
```

```


"+")
PlotPerson=DimPerson[DimPerson['Indicator']==4]
x=PlotPerson['Height']
y=PlotPerson['Weight']
plt.plot(x, y, "^")
plt.axis('tight')
plt.title("BMI Curve")
plt.xlabel("Height(meters)")
plt.ylabel("Weight(kg")
")

plt.plot()
# Load the diabetes dataset
diabetes =
datasets.load_diabetes()#
Use only one feature
diabetes_X = diabetes.data[:, np.newaxis, 2]
diabetes_X_train = diabetes_X[:-30]
diabetes_X_test = diabetes_X[-30:]
diabetes_y_train = diabetes.target[:-30]
diabetes_y_test = diabetes.target[-30:]
regr = linear_model.LinearRegression()
regr.fit(diabetes_X_train, diabetes_y_train)
diabetes_y_pred =
regr.predict(diabetes_X_test)

print('Coefficients: \n', regr.coef_)
print("Mean squared error: %.2f"
% mean_squared_error(diabetes_y_test, diabetes_y_pred))
print('Variance score: %.2f' % r2_score(diabetes_y_test, diabetes_y_pred))
plt.scatter(diabetes_X_test, diabetes_y_test, color='black')
plt.plot(diabetes_X_test, diabetes_y_pred, color='blue', linewidth=3)
plt.xticks(())
plt.yticks(())
plt.axis('tight')
plt.title("Diabetes")
plt.xlabel("BMI")
plt.ylabel("Age")
plt.show()

```

## Output:



## Practical 8:

### Organizing Data

C:\VKHCG\01-Vermeulen\05-Organise\ Organize-Horizontal.py

```
#####
import sys
import os
import pandas as pd
import sqlite3 as sq
#####
Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
#####
Company='01-Vermeulen'
#####
sDataWarehouseDir=Base + '/99-DW'
if not os.path.exists(sDataWarehouseDir):
    os.makedirs(sDataWarehouseDir)
#####
sDatabaseName=sDataWarehouseDir + '/datawarehouse.db'
conn1 = sq.connect(sDatabaseName)
#####
sDatabaseName=sDataWarehouseDir + '/datamart.db'
conn2 = sq.connect(sDatabaseName)
#####
print('#####')
sTable = 'Dim-BMI'
print('Loading :',sDatabaseName,' Table:',sTable)
sSQL="SELECT * FROM [Dim-BMI];"
PersonFrame0=pd.read_sql_query(sSQL, conn1)
print('#####')
sTable = 'Dim-BMI'
print('Loading :',sDatabaseName,' Table:',sTable)
sSQL="SELECT PersonID,\nHeight,\nWeight,\nbmi,\nIndicator\\
FROM [Dim-BMI]\\
WHERE \
Height > 1.5 \
and Indicator = 1\\
ORDER BY \
Height,\nWeight;"
```

PersonFrame1=pd.read\_sql\_query(sSQL, conn1)

```
#####
```

```

DimPerson=PersonFrame1
DimPersonIndex=DimPerson.set_index(['PersonID'], inplace=False)
#####
sTable = 'Dim-BMI'
print("\n#####")
print('Storing :', sDatabaseName, '\n Table:', sTable)
print("\n#####")
#DimPersonIndex.to_sql(sTable, conn2, if_exists="replace")
#####
print('#####')

sTable = 'Dim-BMI'
print('Loading :', sDatabaseName, ' Table:', sTable)
sSQL="SELECT * FROM [Dim-BMI];"
PersonFrame2=pd.read_sql_query(sSQL, conn2)
print('Full Data Set (Rows):', PersonFrame0.shape[0])
print('Full Data Set (Columns):', PersonFrame0.shape[1])
print('Horizontal Data Set (Rows):', PersonFrame2.shape[0])
print('Horizontal Data Set (Columns):', PersonFrame2.shape[1])

```

```

Python 3.7.4 Shell
File Edit Shell Debug Options Window Help
>>>
>>>
RESTART: C:/Users/User/AppData/Local/Programs/Python/Python37-32/Organize01.py
#####
Working Base : C:/VKHCG using win32
#####
Loading : C:/VKHCG/99-DW/datamart.db Table: Dim-BMI
#####
Loading : C:/VKHCG/99-DW/datamart.db Table: Dim-BMI

#####
Storing : C:/VKHCG/99-DW/datamart.db
Table: Dim-BMI

#####
Loading : C:/VKHCG/99-DW/datamart.db Table: Dim-BMI
Full Data Set (Rows): 1080
Full Data Set (Columns): 5
Horizontal Data Set (Rows): 194
Horizontal Data Set (Columns): 5
>>> |
Ln: 2301 Col: 4

```

## Vertical Style

### C:\VKHCG\01-Vermeulen\05-Organise\ Organize-Vertical.py

```

import sys
import os
import pandas as pd
import sqlite3 as sq
#####
Base='C:/VKHCG'
print('#####')
print('Working Base :', Base, ' using ', sys.platform)
print('#####')
#####
#####
Company='01-Vermeulen'
#####
sDataWarehouseDir=Base + '/99-DW'
if not os.path.exists(sDataWarehouseDir):
    os.makedirs(sDataWarehouseDir)

```

```

#####
sDatabaseName=sDataWarehouseDir + '/datawarehouse.db'
conn1 = sq.connect(sDatabaseName)
#####
sDatabaseName=sDataWarehouseDir + '/datamart.db'
conn2 = sq.connect(sDatabaseName)
#####
print('#####')
sTable = 'Dim-BMI'
print('Loading :',sDatabaseName,' Table:',sTable)
sSQL="SELECT * FROM [Dim-BMI];"
PersonFrame0=pd.read_sql_query(sSQL, conn1)
#####

print('#####')
sTable = 'Dim-BMI'
print('Loading :',sDatabaseName,' Table:',sTable)
print('#####')
sSQL="SELECT \
Height,\
Weight,\
Indicator\
FROM [Dim-BMI];"
PersonFrame1=pd.read_sql_query(sSQL, conn1)
#####
DimPerson=PersonFrame1
DimPersonIndex=DimPerson.set_index(['Indicator'],inplace=False)
#####
sTable = 'Dim-BMI-Vertical'
print("\n#####")
print('Storing :',sDatabaseName,'\n Table:',sTable)
print("\n#####")
DimPersonIndex.to_sql(sTable, conn2, if_exists="replace")
#####
print('#####')
sTable = 'Dim-BMI-Vertical'
print('Loading :',sDatabaseName,' Table:',sTable)
sSQL="SELECT * FROM [Dim-BMI-Vertical];"
PersonFrame2=pd.read_sql_query(sSQL, conn2)
#####
print('#####')
print('Full Data Set (Rows):', PersonFrame0.shape[0])
print('Full Data Set (Columns):', PersonFrame0.shape[1])
print('#####')
print('Horizontal Data Set (Rows):', PersonFrame2.shape[0])
print('Horizontal Data Set (Columns):', PersonFrame2.shape[1])
print('#####')
#####

```

## Output:

```
=====
RESTART: C:\VKHCG\01-Vermeulen\05-Organise\Organize-Vertical.py =====
#####
Working Base : C:/VKHCG using win32
#####
Loading : C:/VKHCG/99-DW/datamart.db Table: Dim-BMI
#####
Loading : C:/VKHCG/99-DW/datamart.db Table: Dim-BMI
#####

#####
Storing : C:/VKHCG/99-DW/datamart.db
Table: Dim-BMI-Vertical

#####
Loading : C:/VKHCG/99-DW/datamart.db Table: Dim-BMI-Vertical
#####
Full Data Set (Rows): 1080
Full Data Set (Columns): 5
#####
Horizontal Data Set (Rows): 1080
Horizontal Data Set (Columns): 3
#####
```

## Island Style

### C:\VKHCG\01-Vermeulen\05-Organise\ Organize-Island.py

```
import sys
import os
import pandas as pd
import sqlite3 as sq
#####
Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
#####
Company='01-Vermeulen'
#####
sDataWarehouseDir=Base + '/99-DW'
if not os.path.exists(sDataWarehouseDir):
    os.makedirs(sDataWarehouseDir)
#####
sDatabaseName=sDataWarehouseDir + '/datawarehouse.db'
conn1 = sq.connect(sDatabaseName)
#####
sDatabaseName=sDataWarehouseDir + '/datamart.db'
conn2 = sq.connect(sDatabaseName)
#####
print('#####')
sTable = 'Dim-BMI'
print('Loading :',sDatabaseName,' Table:',sTable)
sSQL="SELECT * FROM [Dim-BMI];"
PersonFrame0=pd.read_sql_query(sSQL, conn1)
#####
print('#####')
sTable = 'Dim-BMI'
```

```

print('Loading :',sDatabaseName,' Table:',sTable)
sSQL="SELECT \
Height,\
Weight,\
Indicator\
FROM [Dim-BMI]\
WHERE Indicator > 2\
ORDER BY \
Height,\
Weight;"

PersonFrame1=pd.read_sql_query(sSQL, conn1)
#####
DimPerson=PersonFrame1
DimPersonIndex=DimPerson.set_index(['Indicator'], inplace=False)
#####
sTable = 'Dim-BMI-Vertical'
print("\n#####")
print('Storing :',sDatabaseName, '\n Table:',sTable)
print("\n#####")
DimPersonIndex.to_sql(sTable, conn2, if_exists="replace")
#####
print('#####')
sTable = 'Dim-BMI-Vertical'
print('Loading :',sDatabaseName, ' Table:',sTable)
print('#####')
sSQL="SELECT * FROM [Dim-BMI-Vertical];"
PersonFrame2=pd.read_sql_query(sSQL, conn2)
#####
print('#####')
print('Full Data Set (Rows):', PersonFrame0.shape[0])
print('Full Data Set (Columns):', PersonFrame0.shape[1])
print('#####')
print('Horizontal Data Set (Rows):', PersonFrame2.shape[0])
print('Horizontal Data Set (Columns):', PersonFrame2.shape[1])
print('#####')
#####

```

## Output:

```

Python 3.7.4 Shell
File Edit Shell Debug Options Window Help
>>>
===== RESTART: C:\VKHCG\01-Vermeulen\05-Organise\Organize-Island.py =====
#####
Working Base : C:/VKHCG using win32
#####
#####
Loading : C:/VKHCG/99-DW/datamart.db Table: Dim-BMI
#####
Loading : C:/VKHCG/99-DW/datamart.db Table: Dim-BMI
#####
#####
Storing : C:/VKHCG/99-DW/datamart.db
Table: Dim-BMI-Vertical
#####
#####
Loading : C:/VKHCG/99-DW/datamart.db Table: Dim-BMI-Vertical
#####
#####
Full Data Set (Rows): 1080
Full Data Set (Columns): 5
#####
Horizontal Data Set (Rows): 771
Horizontal Data Set (Columns): 3
#####
>>> |
Ln: 53 Col: 4

```

## Secure Vault Style

### C:\VKHCG\01-Vermeulen\05-Organise\ Organize-Secure-Vault.py

```
import sys
import os
import pandas as pd
import sqlite3 as sq
#####
Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
#####
Company='01-Vermeulen'
#####
sDataWarehouseDir=Base + '/99-DW'
if not os.path.exists(sDataWarehouseDir):
    os.makedirs(sDataWarehouseDir)
#####
sDatabaseName=sDataWarehouseDir + '/datawarehouse.db'
conn1 = sq.connect(sDatabaseName)
#####
sDatabaseName=sDataWarehouseDir + '/datamart.db'
conn2 = sq.connect(sDatabaseName)
#####
print('#####')
sTable = 'Dim-BMI'
print('Loading :',sDatabaseName,' Table:',sTable)
sSQL="SELECT * FROM [Dim-BMI];"
PersonFrame0=pd.read_sql_query(sSQL, conn1)
#####
print('#####')
sTable = 'Dim-BMI'
print('Loading :',sDatabaseName,' Table:',sTable)
sSQL="SELECT \
Height,\
Weight,\
Indicator,\
CASE Indicator\
WHEN 1 THEN 'Pip'\
WHEN 2 THEN 'Norman'\
WHEN 3 THEN 'Grant'\
ELSE 'Sam'\
END AS Name\
FROM [Dim-BMI]\
WHERE Indicator > 2\
ORDER BY \
Height,\
Weight;"
```

PersonFrame1=pd.read\_sql\_query(sSQL, conn1)

```
#####
DimPerson=PersonFrame1
DimPersonIndex=DimPerson.set_index(['Indicator'],inplace=False)
#####
sTable = 'Dim-BMI-Secure'
print('\n#####')
print('Storing :',sDatabaseName,' Table:',sTable)
print('\n#####')
DimPersonIndex.to_sql(sTable, conn2, if_exists="replace")
#####
print('#####')
sTable = 'Dim-BMI-Secure'
print('Loading :',sDatabaseName,' Table:',sTable)
print('#####')
sSQL="SELECT * FROM [Dim-BMI-Secure] WHERE Name = 'Sam';"
PersonFrame2=pd.read_sql_query(sSQL, conn2)
#####
print('#####')
print('Full Data Set (Rows):', PersonFrame0.shape[0])
print('Full Data Set (Columns):', PersonFrame0.shape[1])
print('#####')
print('Horizontal Data Set (Rows):', PersonFrame2.shape[0])
print('Horizontal Data Set (Columns):', PersonFrame2.shape[1])
print('Only Sam Data')
print(PersonFrame2.head())
print('#####')
#####


```

## Output:

```

Python 3.7.4 Shell
File Edit Shell Debug Options Window Help
>>>
===== RESTART: C:\VKHCG\01-Vermeulen\05-Organise\Organize-Secure-Vault.py =====
#####
Working Base : C:/VKHCG using win32
#####
Loading : C:/VKHCG/99-DW/datamart.db  Table: Dim-BMI
#####
Loading : C:/VKHCG/99-DW/datamart.db  Table: Dim-BMI-Secure
#####
Storing : C:/VKHCG/99-DW/datamart.db
Table: Dim-BMI-Secure
#####
Loading : C:/VKHCG/99-DW/datamart.db  Table: Dim-BMI-Secure
#####
Full Data Set (Rows): 1080
Full Data Set (Columns): 5
#####
Horizontal Data Set (Rows): 692
Horizontal Data Set (Columns): 4
Only Sam Data
   Indicator  Height  Weight Name
0          4     1.0      35  Sam
1          4     1.0      40  Sam
2          4     1.0      45  Sam
3          4     1.0      50  Sam
4          4     1.0      55  Sam
#####

```

## Association Rule Mining

### C:\VKHCG\01-Vermeulen\05-Organise\ Organize-Association- Rule.py

```

import sys
import os
import pandas as pd

```

```

from mlxtend.frequent_patterns import apriori
from mlxtend.frequent_patterns import association_rules

#####
Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
#####
Company='01-Vermeulen'
InputFileName='Online-Retail-Billboard.xlsx'
EDSAssessDir='02-Assess/01-EDS'
InputAssessDir=EDSAssessDir + '/02-Python'
#####
sFileAssessDir=Base + '/' + Company + '/' + InputAssessDir
if not os.path.exists(sFileAssessDir):
    os.makedirs(sFileAssessDir)
#####
sFileName=Base+'/'+ Company + '/00-RawData/' + InputFileName
#####
df = pd.read_excel(sFileName)
print(df.shape)
#####
df['Description'] = df['Description'].str.strip()
df.dropna(axis=0, subset=['InvoiceNo'], inplace=True)
df['InvoiceNo'] = df['InvoiceNo'].astype('str')
df = df[~df['InvoiceNo'].str.contains('C')]
basket = (df[df['Country'] == "France"])
.groupby(['InvoiceNo', 'Description'])['Quantity']
.sum().unstack().reset_index().fillna(0)
.set_index('InvoiceNo')
#####
def encode_units(x):
    if x <= 0:
        return 0
    if x >= 1:
        return 1
#####
basket_sets = basket.groupby(['InvoiceNo', 'Description']).sum()
basket_sets.drop('POSTAGE', inplace=True, axis=1)
frequent_itemsets = apriori(basket_sets, min_support=0.07, use_colnames=True)
rules = association_rules(frequent_itemsets, metric="lift", min_threshold=1)
print(rules.head())
rules[ (rules['lift'] >= 6) &
      (rules['confidence'] >= 0.8) ]
#####

sProduct1='ALARM CLOCK BAKELIKE GREEN'
print(sProduct1)
print(basket[sProduct1].sum())
sProduct2='ALARM CLOCK BAKELIKE RED'
print(sProduct2)
print(basket[sProduct2].sum())
#####
basket2 = (df[df['Country'] == "Germany"])

```

```

.groupby(['InvoiceNo', 'Description'])['Quantity']
.sum().unstack().reset_index().fillna(0)
.set_index('InvoiceNo')
basket_sets2 = basket2.applymap(encode_units)
basket_sets2.drop('POSTAGE', inplace=True, axis=1)
frequent_itemsets2 = apriori(basket_sets2, min_support=0.05, use_colnames=True)
rules2 = association_rules(frequent_itemsets2, metric="lift", min_threshold=1)

print(rules2[ (rules2['lift'] >= 4) &
(rules2['confidence'] >= 0.5)])
#####
print('### Done!! #####')
#####

```

## Output:

```

Python 3.7.4 Shell
File Edit Shell Debug Options Window Help
Python 3.7.4 (tags/v3.7.4:e09359112e, Jul  8 2019, 19:29:22) [MSC v.1916 32 bit
(Intel)] on win32
Type "help", "copyright", "credits" or "license()" for more information.
>>>
== RESTART: C:\VKHCG\01-Vermeulen\05-Organise\Organize-Association-Rule.py ==
#####
Working Base : C:/VKHCG using win32
#####
[541909, 8]
      antecedents ... conviction
0   (ALARM CLOCK BAKELIKE PINK) ... 3.283859
1   (ALARM CLOCK BAKELIKE GREEN) ... 3.791383
2   (ALARM CLOCK BAKELIKE GREEN) ... 4.916181
3   (ALARM CLOCK BAKELIKE RED) ... 5.568878
4   (ALARM CLOCK BAKELIKE PINK) ... 3.293135

[5 rows x 9 columns]
ALARM CLOCK BAKELIKE GREEN
340.0
ALARM CLOCK BAKELIKE RED
316.0
      antecedents ... conviction
0   (PLASTERS IN TIN CIRCUS PARADE) ... 2.076984
7   (PLASTERS IN TIN SPACEBOY) ... 2.011670
11  (RED RETROSPOT CHARLOTTE BAG) ... 5.587746

[3 rows x 9 columns]
#####
## Done!! #####
>>> |

```

## Create a Network Routing Diagram

I will guide you through a possible solution for the requirement, by constructing an island-style Organize superstep that uses a graph data model to reduce the records and the columns on the data set.

## C:\VKHCG\01-Vermeulen\05-Organise\ Organise-Network- Routing-Company.py

```

import sys
import os
import pandas as pd
import networkx as nx
import matplotlib.pyplot as plt
#####
pd.options.mode.chained_assignment = None
#####
Base='C:/VKHCG'
#####
print('#####')
print('Working Base :',Base, ' using ',sys.platform)
print('#####')
#####

```


```

sInputFileName='02-Assess/01-EDS/02-Python/Assess-Network-Routing-Company.csv'
#####
sOutputFileName1='05-Organise/01-EDS/02-Python/Organise-Network-Routing-
Company.gml'
sOutputFileName2='05-Organise/01-EDS/02-Python/Organise-Network-Routing-
Company.png'
Company='01-Vermeulen'
#####
#####
### Import Country Data
#####
sFileName=Base + '/' + Company + '/' + sInputFileName
print('#####')
print('Loading :',sFileName)

print('#####')
CompanyData=pd.read_csv(sFileName,header=0,low_memory=False, encoding="latin-1")
print('#####')
print(CompanyData.head())
print(CompanyData.shape)
G=nx.Graph()
for i in range(CompanyData.shape[0]):
    for j in range(CompanyData.shape[0]):
        Node0=CompanyData['Company_Country_Name'][i]
        Node1=CompanyData['Company_Country_Name'][j]
        if Node0 != Node1:
            G.add_edge(Node0,Node1)
for i in range(CompanyData.shape[0]):
    Node0=CompanyData['Company_Country_Name'][i]
    Node1=CompanyData['Company_Place_Name'][i] + '('+
    CompanyData['Company_Country_Name'][i] + ')'
    if Node0 != Node1:
        G.add_edge(Node0,Node1)
print('Nodes:', G.number_of_nodes())
print('Edges:', G.number_of_edges())
sFileName=Base + '/' + Company + '/' + sOutputFileName1
print('#####')
print('Storing :',sFileName)
print('#####')
nx.write_gml(G, sFileName)
sFileName=Base + '/' + Company + '/' + sOutputFileName2
print('#####')
print('Storing Graph Image:',sFileName)
print('#####')
plt.figure(figsize=(15, 15))
pos=nx.spectral_layout(G,dim=2)
nx.draw_networkx_nodes(G,pos, node_color='k', node_size=10, alpha=0.8)
nx.draw_networkx_edges(G, pos, edge_color='r', arrows=False, style='dashed')
nx.draw_networkx_labels(G, pos, font_size=12, font_family='sans-serif', font_color='b')
plt.axis('off')
plt.savefig(sFileName,dpi=600)
plt.show()
print('#####')
print('## Done!! #####')

```

```
print('#####')
```



## Picking Content for Billboards

### C:\VKHCG\02-Krennwallner\05-Organise\ Organise-billboards.py

```
#####
import sys
import os
import pandas as pd
import networkx as nx
import matplotlib.pyplot as plt
import numpy as np
#####
pd.options.mode.chained_assignment = None
#####
Base='C:/VKHCG'
#####
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
#####
sInputFileName='02-Assess/01-EDS/02-Python/Assess-DE-Billboard-Visitor.csv'
#####
sOutputFileName1='05-Organise/01-EDS/02-Python/Organise-Billboards.gml'
sOutputFileName2='05-Organise/01-EDS/02-Python/Organise-Billboards.png'
Company='02-Krennwallner'
#####
#####
### Import Company Data
#####
sFileName=Base + '/' + Company + '/' + sInputFileName
print('#####')
print('Loading :',sFileName)
print('#####')
```


```

BillboardDataRaw=pd.read_csv(sFileName,header=0,low_memory=False, encoding="latin-1")
print('#####')
#####
print(BillboardDataRaw.head())
print(BillboardDataRaw.shape)
BillboardData=BillboardDataRaw
sSample=list(np.random.choice(BillboardData.shape[0],20))
#####
G=nx.Graph()
for i in sSample:
    for j in sSample:
        Node0=BillboardData['BillboardPlaceName'][i] + '('+ BillboardData['BillboardCountry'][i] +
        ')'
        Node1=BillboardData['BillboardPlaceName'][j] + '('+ BillboardData['BillboardCountry'][i] +
        ')'
        if Node0 != Node1:
            G.add_edge(Node0,Node1)
    for i in sSample:
        Node0=BillboardData['BillboardPlaceName'][i] + '('+ BillboardData['VisitorPlaceName'][i] +
        ')'
        Node1=BillboardData['BillboardPlaceName'][i] + '('+ BillboardData['VisitorCountry'][i] + ')'
        if Node0 != Node1:
            G.add_edge(Node0,Node1)
    print('Nodes:', G.number_of_nodes())
    print('Edges:', G.number_of_edges())
#####
sFileName=Base + '/02-Krennwallner/' + sOutputFileName1
print('#####')
print('Storing :,sFileName)

print('#####')
nx.write_gml(G, sFileName)
#####
sFileName=Base + '/02-Krennwallner/' + sOutputFileName2
print('#####')
print('Storing Graph Image:,sFileName)
print('#####')
plt.figure(figsize=(15, 15))
pos=nx.circular_layout(G,dim=2)
nx.draw_networkx_nodes(G,pos, node_color='k', node_size=150, alpha=0.8)
nx.draw_networkx_edges(G, pos, edge_color='r', arrows=False, style='solid')
nx.draw_networkx_labels(G, pos, font_size=12, font_family='sans-serif', font_color='b')
plt.axis('off')
plt.savefig(sFileName,dpi=600)
plt.show()
#####
print('#####')
print('## Done!! #####')
print('#####')
#####

```

## **Output :**



## Create a Delivery Route

C:\VKHCG\03-Hillman\05-Organise\Organise-Routes.py

```

import sys
import os
import pandas as pd
#####
Base='C:/VKHCG'
#####
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
#####
sInputFileName='02-Assess/01-EDS/02-Python/Assess_Shipping_Routes.txt'
#####
sOutputFileName='05-Organise/01-EDS/02-Python/Organise-Routes.csv'
Company='03-Hillman'
#####
#####
### Import Routes Data
#####
sFileName=Base + '/' + Company + '/' + sInputFileName
print('#####')

print('Loading :',sFileName)
print('#####')
RouteDataRaw=pd.read_csv(sFileName,header=0,low_memory=False, sep=',',
encoding="latin-1")
print('#####')
#####
RouteStart=RouteDataRaw[RouteDataRaw['StartAt']=='WH-KA13']
#####
RouteDistance=RouteStart[RouteStart['Cost']=='DistanceMiles']
RouteDistance=RouteDistance.sort_values(by=['Measure'], ascending=False)
#####
RouteMax=RouteStart["Measure"].max()
RouteMaxCost=round(((RouteMax/1000)*1.5*2)),2)
print('#####')
print('Maximum (£) per day:')

```

```

print(RouteMaxCost)
print('#####')
#####
RouteMean=RouteStart["Measure"].mean()
RouteMeanMonth=round(((RouteMean/1000)*2*30)),6)
print('#####')
print('Mean per Month (Miles):')
print(RouteMeanMonth)
print('#####')

```

## Output:

```

Python 3.7.4 Shell
File Edit Shell Debug Options Window Help
Python 3.7.4 (tags/v3.7.4-e09359112e, Jul  8 2019, 19:29:22) [MSC v.1916 32 bit
(Intel)] on win32
Type "help", "copyright", "credits" or "license()" for more information.
>>>
===== RESTART: C:/VKHCG/03-Hillman/05-Organise/Organise-Routes.py ======
#####
Working Base : C:/VKHCG using win32
#####
Loading : C:/VKHCG/03-Hillman/02-Assess/01-EDS/02-Python/Assess_Shipping_Routes.
txt
#####
Maximum (£) per day:
21.82
#####
Mean per Month (Miles):
21.56191
#####
>>>

```

## Clark Ltd

Our financial services company has been tasked to investigate the options to convert 1 million pounds sterling into extra income. Mr. Clark Junior suggests using the simple variance in the daily rate between the British pound sterling and the US dollar, to generate extra income from trading. Your chief financial officer wants to know if this is feasible?

## Simple Forex Trading Planner

Your challenge is to take 1 million US dollars or just over six hundred thousand pounds sterling and, by simply converting it between pounds sterling and US dollars, achieve a profit. Are you up to this challenge?

The Program will help you how to model this problem and achieve a positive outcome. The forex data has been collected on a daily basis by Clark's accounting department, from previous overseas transactions.

## C:/VKHCG/04-Clark/05-Organise/Organise-Forex.py

```

import sys
import os
import pandas as pd
import sqlite3 as sq
import re
#####
Base='C:/VKHCG'
#####

print('#####')
print('Working Base :',Base, ' using ', sys.platform)

```

```

print('#####')
sInputFileName='03-Process/01-EDS/02-Python/Process_ExchangeRates.csv'
#####
sOutputFileName='05-Organise/01-EDS/02-Python/Organise-Forex.csv'
Company='04-Clark'
#####
sDatabaseName=Base + '/' + Company + '/05-Organise/SQLite/clark.db'
conn = sq.connect(sDatabaseName)
#conn = sq.connect(':memory:')
#####
### Import Forex Data
#####
sFileName=Base + '/' + Company + '/' + sInputFileName
print('#####')
print('Loading :',sFileName)
print('#####')
ForexDataRaw=pd.read_csv(sFileName,header=0,low_memory=False, encoding="latin-1")
print('#####')
#####
ForexDataRaw.index.names = ['RowID']
sTable='Forex_All'
print('Storing :',sDatabaseName,' Table:',sTable)
ForexDataRaw.to_sql(sTable, conn, if_exists="replace")
#####
sSQL="SELECT 1 as Bag\
, CAST(min(Date) AS VARCHAR(10)) as Date \
,CAST(1000000.000000 as NUMERIC(12,4)) as Money \
,'USD' as Currency \
FROM Forex_All \
;"
sSQL=re.sub("\s\s+", " ", sSQL)
nMoney=pd.read_sql_query(sSQL, conn)
#####
nMoney.index.names = ['RowID']
sTable='MoneyData'
print('Storing :',sDatabaseName,' Table:',sTable)
nMoney.to_sql(sTable, conn, if_exists="replace")
#####
sTable='TransactionData'
print('Storing :',sDatabaseName,' Table:',sTable)
nMoney.to_sql(sTable, conn, if_exists="replace")
#####
ForexDay=pd.read_sql_query("SELECT Date FROM Forex_All GROUP BY Date;", conn)
#####
t=0
for i in range(ForexDay.shape[0]):
    sDay1=ForexDay['Date'][i]
    sDay=str(sDay1)
    sSQL='\
SELECT M.Bag as Bag, \
F.Date as Date, \
round(M.Money * F.Rate,6) AS Money, \

```

```

F.CodeIn AS PCurrency, \
F.CodeOut AS Currency \
FROM MoneyData AS M \

JOIN \
( \
SELECT CodeIn, CodeOut, Date, Rate FROM Forex_All WHERE
CodeIn = "USD" AND CodeOut = "GBP" \
UNION \
SELECT CodeOut AS CodeIn, CodeIn AS CodeOut, Date, (1/Rate) AS Rate FROM \
Forex_All WHERE CodeIn = "USD" AND CodeOut = "GBP" \
) AS F \
ON \
M.Currency=F.CodeIn \
AND \
F.Date ="" +sDay +";"
sSQL=re.sub("\s\s+", " ", sSQL)
ForexDayRate=pd.read_sql_query(sSQL, conn)
for j in range(ForexDayRate.shape[0]):
sBag=str(ForexDayRate['Bag'][j])
nMoney=str(round(ForexDayRate['Money'][j],2))
sCodeIn=ForexDayRate['PCurrency'][j]
sCodeOut=ForexDayRate['Currency'][j]
sSQL='UPDATE MoneyData SET Date= "' + sDay + '", '
sSQL= sSQL + ' Money = ' + nMoney + ', Currency=' + sCodeOut + "'"
sSQL= sSQL + ' WHERE Bag=' + sBag + ' AND Currency=' + sCodeIn +"';"
sSQL=re.sub("\s\s+", " ", sSQL)
cur = conn.cursor()
cur.execute(sSQL)
conn.commit()
t+=1
print('Trade :', t, sDay, sCodeOut, nMoney)
sSQL=' \
INSERT INTO TransactionData ( \
RowID, \
Bag, \
Date, \
Money, \
Currency \
) \
SELECT '+ str(t) + ' AS RowID, \
Bag, \
Date, \
Money, \
Currency \
FROM MoneyData ;'
sSQL=re.sub("\s\s+", " ", sSQL)
cur = conn.cursor()
cur.execute(sSQL)
conn.commit()
#####
sSQL="SELECT RowID, Bag, Date, Money, Currency FROM TransactionData ORDER BY
RowID;"
```

```
sSQL=re.sub("\s\s+", " ", sSQL)
TransactionData=pd.read_sql_query(sSQL, conn)
OutputFile=Base + '/' + Company + '/' + sOutputFileName
TransactionData.to_csv(OutputFile, index = False)
#####
```

### **Output:**

Save the Assess-Forex.py file, then compile and execute with your Python compiler.  
This will produce a set of demonstrated values onscreen.

## Practical 9

### Generating Data

#### Report Superstep

The Report superstep is the step in the ecosystem that enhances the data science findings with the art of storytelling and data visualization. You can perform the best data science, but if you cannot execute a respectable and trustworthy Report step by turning your data science into actionable business insights, you have achieved no advantage for your business.

Vermeulen PLC

Vermeulen requires a map of all their customers' data links. Can you provide a report to deliver this? I will guide you through an example that delivers this requirement.

#### C:\VKHCG\01-Vermeulen\06-Report\Raport-Network-Routing-Customer.py

```
#####
import sys
import os
import pandas as pd
import networkx as nx
import matplotlib.pyplot as plt
#####
pd.options.mode.chained_assignment = None
#####
if sys.platform == 'linux':
    Base=os.path.expanduser('~') + 'VKHCG'
else:
    Base='C:/VKHCG'
#####
print('#####')
print('Working Base :',Base, ' using ',sys.platform)
print('#####')
#####
sInputFileName='02-Assess/01-EDS/02-Python/Assess-Network-Routing-Customer.csv'
#####
sOutputFileName1='06-Report/01-EDS/02-Python/Report-Network-Routing-Customer.gml'
sOutputFileName2='06-Report/01-EDS/02-Python/Report-Network-Routing-Customer.png'
Company='01-Vermeulen'
#####
#####
### Import Country Data
#####
sFileName=Base + '/' + Company + '/' + sInputFileName
print('#####')
print('Loading :',sFileName)
print('#####')
CustomerDataRaw=pd.read_csv(sFileName,header=0,low_memory=False, encoding="latin-1")
CustomerData=CustomerDataRaw.head(100)
```


```
print('Loaded Country:',CustomerData.columns.values)
```

```

print('#####')
#####
print(CustomerData.head())
print(CustomerData.shape)
#####
G=nx.Graph()
for i in range(CustomerData.shape[0]):
    for j in range(CustomerData.shape[0]):
        Node0=CustomerData['Customer_Country_Name'][i]
        Node1=CustomerData['Customer_Country_Name'][j]
        if Node0 != Node1:

            G.add_edge(Node0,Node1)
            for i in range(CustomerData.shape[0]):
                Node0=CustomerData['Customer_Country_Name'][i]
                Node1=CustomerData['Customer_Place_Name'][i] + '('+
                CustomerData['Customer_Country_Name'][i] + ')'
                Node2='(+ {:.9f}'.format(CustomerData['Customer_Latitude'][i]) + ')\
                ('+ {:.9f}'.format(CustomerData['Customer_Longitude'][i]) + ')'
                if Node0 != Node1:
                    G.add_edge(Node0,Node1)
                if Node1 != Node2:
                    G.add_edge(Node1,Node2)
            print('Nodes:', G.number_of_nodes())
            print('Edges:', G.number_of_edges())
#####
sFileName=Base + '/' + Company + '/' + sOutputFileName1
print('#####')
print('Storing :,sFileName')
print('#####')
nx.write_gml(G, sFileName)
#####
sFileName=Base + '/' + Company + '/' + sOutputFileName2
print('#####')
print('Storing Graph Image:,sFileName')
print('#####')
plt.figure(figsize=(25, 25))
pos=nx.spectral_layout(G,dim=2)
nx.draw_networkx_nodes(G,pos, node_color='k', node_size=10, alpha=0.8)
nx.draw_networkx_edges(G, pos, edge_color='r', arrows=False, style='dashed')
nx.draw_networkx_labels(G, pos, font_size=12, font_family='sans-serif', font_color='b')
plt.axis('off')
plt.savefig(sFileName,dpi=600)
plt.show()
print('#####')
print('## Done!! #####')
print('#####')

```



## Krennwallner AG

The Krennwallner marketing department wants to deploy the locations of the billboards onto the company web server. Can you prepare three versions of the locations“ web pages?

- Locations clustered into bubbles when you zoom out
- Locations as pins
- Locations as heat map

Picking Content for Billboards

## C:\VKHCG\02-Krennwallner\06-Report\Report\_Billboard.py

```
import sys
import os
import pandas as pd




from folium.plugins import FastMarkerCluster, HeatMap
from folium import Marker, Map
import webbrowser
#####
Base='C:/VKHCG'
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
#####
sFileName=Base+'/02-Krennwallner/01-Retrieve/01-EDS/02-
Python/Retrieve_DE_Billboard_Locations.csv'
df = pd.read_csv(sFileName,header=0,low_memory=False, encoding="latin-1")
df.fillna(value=0, inplace=True)
print(df.shape)
#####
t=0
for i in range(df.shape[0]):
    try:
        sLongitude=df["Longitude"][i]
        sLongitude=float(sLongitude)
```

```

except Exception:
    sLongitude=float(0.0)
try:
    sLatitude=df["Latitude"][i]
    sLatitude=float(sLatitude)
except Exception:
    sLatitude=float(0.0)
try:
    sDescription=df["Place_Name"][i] + ' (' + df["Country"][i]+)'
except Exception:
    sDescription='VKHCG'
if sLongitude != 0.0 and sLatitude != 0.0:
    DataClusterList=list([sLatitude, sLongitude])
    DataPointList=list([sLatitude, sLongitude, sDescription])
    t+=1
if t==1:
    DataCluster=[DataClusterList]
    DataPoint=[DataPointList]
else:
    DataCluster.append(DataClusterList)
    DataPoint.append(DataPointList)
    data=DataCluster
pins=pd.DataFrame(DataPoint)
pins.columns = [ 'Latitude','Longitude','Description']
#####
stops_map1 = Map(location=[48.1459806, 11.4985484], zoom_start=5)
marker_cluster = FastMarkerCluster(data).add_to(stops_map1)
sFileNameHtml=Base+'/02-Krennwallner/06-Report/01-EDS/02-Python/Billboard1.html'
stops_map1.save(sFileNameHtml)
webbrowser.open('file://' + os.path.realpath(sFileNameHtml))
#####
stops_map2 = Map(location=[48.1459806, 11.4985484], zoom_start=5)
for name, row in pins.iloc[:100].iterrows():
    Marker([row["Latitude"],row["Longitude"]],
    popup=row["Description"]).add_to(stops_map2)
sFileNameHtml=Base+'/02-Krennwallner/06-Report/01-EDS/02-Python/Billboard2.html'
stops_map2.save(sFileNameHtml)
webbrowser.open('file://' + os.path.realpath(sFileNameHtml))
#####
stops_heatmap = Map(location=[48.1459806, 11.4985484], zoom_start=5)
stops_heatmap.add_child(HeatMap([[row["Latitude"], row["Longitude"]]] for name, row in
pins.iloc[:100].iterrows()))
sFileNameHtml=Base+'/02-Krennwallner/06-Report/01-EDS/02-
Python/Billboard_heatmap.html'
stops_heatmap.save(sFileNameHtml)
webbrowser.open('file://' + os.path.realpath(sFileNameHtml))
#####
print('## Done!! #####')
#####

```

## Output:



## Hillman Ltd

Dr. Hillman Sr. has just installed a camera system that enables the company to capture video and, therefore, indirectly, images of all containers that enter or leave the warehouse. Can you convert the number on the side of the containers into digits?

Reading the Containers

### C:\VKHCG\03-Hillman\06-Report\ Report\_Reading\_Container.py

```
from time import time
import numpy as np
import matplotlib.pyplot as plt
from matplotlib import offsetbox
from sklearn import (manifold, datasets, decomposition, ensemble, discriminant_analysis,
random_projection)
digits = datasets.load_digits(n_class=6)
X = digits.data
y = digits.target
n_samples, n_features = X.shape
n_neighbors = 30
def plot_embedding(X, title=None):
    x_min, x_max = np.min(X, 0), np.max(X, 0)
    X = (X - x_min) / (x_max - x_min)
    plt.figure(figsize=(10, 10))
    ax = plt.subplot(111)
    for i in range(X.shape[0]):
        plt.text(X[i, 0], X[i, 1], str(digits.target[i]),
color=plt.cm.Set1(y[i] / 10.),
fontdict={'weight': 'bold', 'size': 9})
    if hasattr(offsetbox, 'AnnotationBbox'):
        # only print thumbnails with matplotlib > 1.0
        shown_images = np.array([[1., 1.]]) # just something big
        for i in range(digits.data.shape[0]):
            dist = np.sum((X[i] - shown_images) ** 2, 1)
            if np.min(dist) < 4e-3:
                # don't show points that are too close
                continue
            shown_images = np.r_[shown_images, [X[i]]]

    imagebox = offsetbox.AnnotationBbox(offsetbox.OffsetImage(digits.images[i],
cmap=plt.cm.gray_r), X[i])
    ax.add_artist(imagebox)
    plt.xticks([]), plt.yticks([])
    if title is not None:
        plt.title(title)
    n_img_per_row = 20
    img = np.zeros((10 * n_img_per_row, 10 * n_img_per_row))
    for i in range(n_img_per_row):
        ix = 10 * i + 1
        for j in range(n_img_per_row):
            iy = 10 * j + 1
            img[ix:ix + 8, iy:iy + 8] = X[i * n_img_per_row + j].reshape((8, 8))
    plt.figure(figsize=(10, 10))
```

```

plt.imshow(img, cmap=plt.cm.binary)
plt.xticks([])
plt.yticks([])
plt.title('A selection from the 64-dimensional digits dataset')
print("Computing random projection")
rp = random_projection.SparseRandomProjection(n_components=2, random_state=42)
X_projected = rp.fit_transform(X)
plot_embedding(X_projected, "Random Projection of the digits")
print("Computing PCA projection")
t0 = time()
X_pca = decomposition.TruncatedSVD(n_components=2).fit_transform(X)
plot_embedding(X_pca,"Principal Components projection of the digits (time %.2fs)" %(time() - t0))
print("Computing Linear Discriminant Analysis projection")
X2 = X.copy()
X2.flat[::X.shape[1] + 1] += 0.01 # Make X invertible
t0 = time()
X_lda =
discriminant_analysis.LinearDiscriminantAnalysis(n_components=2).fit_transform(X2, y)
plot_embedding(X_lda,"Linear Discriminant projection of the digits (time %.2fs)" %(time() - t0))
print("Computing Isomap embedding")
t0 = time()
X_iso = manifold.Isomap(n_neighbors, n_components=2).fit_transform(X)
print("Done.")
plot_embedding(X_iso,"Isomap projection of the digits (time %.2fs)" %(time() - t0))
print("Computing LLE embedding")
clf = manifold.LocallyLinearEmbedding(n_neighbors, n_components=2,method='standard')
t0 = time()
X_lle = clf.fit_transform(X)
print("Done. Reconstruction error: %g" % clf.reconstruction_error_)
plot_embedding(X_lle,"Locally Linear Embedding of the digits (time %.2fs)" %(time() - t0))
print("Computing modified LLE embedding")
clf = manifold.LocallyLinearEmbedding(n_neighbors, n_components=2,
method='modified')
t0 = time()
X_mlle = clf.fit_transform(X)
print("Done. Reconstruction error: %g" % clf.reconstruction_error_)
plot_embedding(X_mlle,"Modified Locally Linear Embedding of the digits (time %.2fs)" %(time() - t0))
print("Computing Hessian LLE embedding")
clf = manifold.LocallyLinearEmbedding(n_neighbors, n_components=2,method='hessian')
t0 = time()
X_hlle = clf.fit_transform(X)
print("Done. Reconstruction error: %g" % clf.reconstruction_error_)
plot_embedding(X_hlle,"Hessian Locally Linear Embedding of the digits (time %.2fs)" %(time() - t0))
print("Computing LTSA embedding")
clf = manifold.LocallyLinearEmbedding(n_neighbors, n_components=2,method='ltsa')
t0 = time()
X_ltsa = clf.fit_transform(X)

print("Done. Reconstruction error: %g" % clf.reconstruction_error_)

```

```

plot_embedding(X_ltsa,"Local Tangent Space Alignment of the digits (time %.2fs)" %(time()
- t0))
print("Computing MDS embedding")
clf = manifold.MDS(n_components=2, n_init=1, max_iter=100)
t0 = time()
X_mds = clf.fit_transform(X)
print("Done. Stress: %f" % clf.stress_)
plot_embedding(X_mds,"MDS embedding of the digits (time %.2fs)" %(time() - t0))
print("Computing Totally Random Trees embedding")
hasher = ensemble.RandomTreesEmbedding(n_estimators=200, random_state=0,
max_depth=5)
t0 = time()
X_transformed = hasher.fit_transform(X)
pca = decomposition.TruncatedSVD(n_components=2)
X_reduced = pca.fit_transform(X_transformed)
plot_embedding(X_reduced,"Random forest embedding of the digits (time %.2fs)" %(time() -
t0))
print("Computing Spectral embedding")
embedder = manifold.SpectralEmbedding(n_components=2, random_state=0,
eigen_solver="arpack")
t0 = time()
X_se = embedder.fit_transform(X)
plot_embedding(X_se,"Spectral embedding of the digits (time %.2fs)" %(time() - t0))
print("Computing t-SNE embedding")
tsne = manifold.TSNE(n_components=2, init='pca', random_state=0)
t0 = time()
X_tsne = tsne.fit_transform(X)
plot_embedding(X_tsne,"t-SNE embedding of the digits (time %.2fs)" %(time() - t0))
plt.show()

```

The screenshot shows a Python 3.7.4 Shell window. The command line displays the following output:


```

*Python 3.7.4 Shell*
File Edit Shell Debug Options Window Help
Python 3.7.4 (tags/v3.7.4:e09359112e, Jul  8 2019, 19:29:22) [MSC v.1916 32 bit
(Intel)] on win32
Type "help", "copyright", "credits" or "license()" for more information.
>>>
===== RESTART: C:/VKHCG/03-Hillman/06-Report/Report_Reading.Container.py =====
1. Computing random projection
2. Computing PCA projection
3. Computing Linear Discriminant Analysis projection
4. Computing Isomap embedding
Done.
5. Computing LLE embedding
Done. Reconstruction error: 1.63544e-06
6. Computing modified LLE embedding
Done. Reconstruction error: 0.360655
7. Computing Hessian LLE embedding
Done. Reconstruction error: 0.212804
8. Computing LTSA embedding
Done. Reconstruction error: 0.212804
9. Computing MDS embedding
Done. Stress: 136501329.149015
10. Computing Totally Random Trees embedding
11. Computing Spectral embedding
12. Computing t-SNE embedding


```

The window title is "\*Python 3.7.4 Shell\*". The status bar at the bottom right shows "Ln: 3 Col: 4".


A selection from the 64-dimensional digits dataset




Random Projection of the digits








Principal Components projection of the digits (time 0.01s)



Linear Discriminant projection of the digits (time 0.07s)







## Clark Ltd

The financial company in VKHCG is the Clark accounting firm that VKHCG owns with a 60% stake. The accountants are the financial advisers to the group and handle everything to do with the complex work of international accounting.

### Financials

The VKHCG companies did well last year, and the teams at Clark must prepare a balance sheet for each company in the group. The companies require a balance sheet for each company, to be produced using the template (Balance-Sheet-Template.xlsx) that can be found in the example directory (..\VKHCG\04-Clark\00-RawData).

The Program will guide you through a process that will enable you to merge the data science with preformatted Microsoft Excel template, to produce a balance sheet for each of the VKHCG companies.

### C:\VKHCG\04-Clark\06-Report\Report-Balance-Sheet.py

```
import sys
import os
import pandas as pd
import sqlite3 as sq
import re
from openpyxl import load_workbook
#####
Base='C:/VKHCG'
#####
print('#####')
print('Working Base :',Base, ' using ', sys.platform)
print('#####')
#####
sInputTemplateName='00-RawData/Balance-Sheet-Template.xlsx'
#####
sOutputFileName='06-Report/01-EDS/02-Python/Report-Balance-Sheet'

Company='04-Clark'
#####
sDatabaseName=Base + '/' + Company + '/06-Report/SQLite/clark.db'
conn = sq.connect(sDatabaseName)
#conn = sq.connect(':memory:')
#####
## Import Balance Sheet Data
#####
for y in range(1,13):
    sInputFileName='00-RawData/BalanceSheets' + str(y).zfill(2) + '.csv'
    sFileName=Base + '/' + Company + '/' + sInputFileName
    print('#####')
    print('Loading :',sFileName)
```

```

print#####
ForexDataRaw=pd.read_csv(sFileName,header=0,low_memory=False, encoding="latin-1")
print#####
#####
ForexDataRaw.index.names = ['RowID']
sTable='BalanceSheets'
print('Storing :,sDatabaseName, Table:',sTable)
if y == 1:
    print('Load Data')
    ForexDataRaw.to_sql(sTable, conn, if_exists="replace")
else:
    print('Append Data')
    ForexDataRaw.to_sql(sTable, conn, if_exists="append")
#####
sSQL="SELECT \
Year, \
Quarter, \
Country, \
Company, \
CAST(Year AS INT) || 'Q' || CAST(Quarter AS INT) AS sDate, \
Company || '(' || Country || ')' AS sCompanyName , \
CAST(Year AS INT) || 'Q' || CAST(Quarter AS INT) || '-' || \
Company || '-' || Country AS sCompanyFile \
FROM BalanceSheets \
GROUP BY \
Year, \
Quarter, \
Country, \
Company \
HAVING Year is not null \
;"

sSQL=re.sub("\s\s+", " ", sSQL)
sDatesRaw=pd.read_sql_query(sSQL, conn)
print(sDatesRaw.shape)
sDates=sDatesRaw.head(5)
#####
## Loop Dates
#####
for i in range(sDates.shape[0]):
    sFileName=Base + '/' + Company + '/' + sInputTemplateName
    wb = load_workbook(sFileName)
    ws=wb.get_sheet_by_name("Balance-Sheet")
    sYear=sDates['sDate'][i]
    sCompany=sDates['sCompanyName'][i]
    sCompanyFile=sDates['sCompanyFile'][i]
    sCompanyFile=re.sub("\s+", "", sCompanyFile)\

    ws['D3'] = sYear
    ws['D5'] = sCompany
    sFields = pd.DataFrame(
    [
        ['Cash','D16', 1],
        ['Accounts_Receivable','D17', 1],
        ['Doubtful_Accounts','D18', 1],
        ['Inventory','D19', 1],
        ['Temporary_Investment','D20', 1],
    ]
)

```

```

['Prepaid_Expenses','D21', 1],
['Long_Term_Investments','D24', 1],
['Land','D25', 1],
['Buildings','D26', 1],
['Depreciation_Buildings','D27', -1],
['Plant_Equipment','D28', 1],
['Depreciation_Plant_Equipment','D29', -1],
['Furniture_Fixtures','D30', 1],
['Depreciation_Furniture_Fixtures','D31', -1],
['Accounts_Payable','H16', 1],
['Short_Term_Notes','H17', 1],
['Current_Long_Term_Notes','H18', 1],
['Interest_Payable','H19', 1],
['Taxes_Payable','H20', 1],
['Accrued_Payroll','H21', 1],
['Mortgage','H24', 1],
['Other_Long_Term_Liabilities','H25', 1],
['Capital_Stock','H30', 1]
]
)
nYear=str(int(sDates['Year'][i]))
nQuarter=str(int(sDates['Quarter'][i]))
sCountry=str(sDates['Country'][i])
sCompany=str(sDates['Company'][i])
sFileName=Base + '/' + Company + '/' + sOutputFileName + \
'-' + sCompanyFile + '.xlsx'
print(sFileName)
for j in range(sFields.shape[0]):
    sSumField=sFields[0][j]
    sCellField=sFields[1][j]
    nSumSign=sFields[2][j]
    sSQL="SELECT \
Year, \
Quarter, \
Country, \
Company, \
SUM(" + sSumField + ") AS nSumTotal \
FROM BalanceSheets \
GROUP BY \
Year, \
Quarter, \
Country, \
Company \
HAVING \
Year=" + nYear + " \
AND \
Quarter=" + nQuarter + " \
AND \
Country=""" + sCountry + """ \
AND \
Company=""" + sCompany + """ \
;"""
    sSQL=re.sub("\s\s+", " ", sSQL)
    sSumRaw=pd.read_sql_query(sSQL, conn)
    ws[sCellField] = sSumRaw["nSumTotal"][0] * nSumSign
    print('Set cell',sCellField,' to ', sSumField,'Total')
    wb.save(sFileName)

```

## Output:


### Graphics

This section will now guide you through a number of visualizations that particularly useful in presenting data to my customers.

#### Pie Graph


#### Double Pie

C:/VKHCG/01-Vermeulen/06-Report/Report\_Graph\_A.py




## Line Graph

C:/VKHCG/01-Vermeulen/06-Report/Report\_Graph\_A.py




## Bar Graph / Horizontal Bar Graph

C:/VKHCG/01-Vermeulen/06-Report/Report\_Graph\_A.py




## Area Graph

C:/VKHCG/01-Vermeulen/06-Report/Report\_Graph\_A.py




## SCATTER GRAPH

C:/ VKHCG/03-HILLMAN/06-REPORT/REPORT-SCATTERPLOT-WITH-ENCIRCLING.R




## Hexbin:

Program : C:\VKHCG\01-Vermeulen\06-Report\Report\_Graph\_A.py




## Kernel Density Estimation (KDE) Graph

C:\VKHCG\01-Vermeulen\06-Report\Report\_Graph\_B.py




## Scatter Matrix Graph

C:\VKHCG\01-Vermeulen\06-Report\Report\_Graph\_B.py




### Andrews' Curves

C:\VKHCG\01-Vermeulen\06-Report\Report\_Graph\_C.py




### Parallel Coordinates

C:\VKHCG\01-Vermeulen\06-Report\Report\_Graph\_C.py




### RADVIZ Method

C:\VKHCG\01-Vermeulen\06-Report\Report\_Graph\_C.py




### Lag Plot

C:\VKHCG\01-Vermeulen\06-Report\Report\_Graph\_D.py




### Autocorrelation Plot

C:\VKHCG\01-Vermeulen\06-Report\Report\_Graph\_D.py




### Bootstrap Plot

C:\VKHCG\01-Vermeulen\06-Report\Report\_Graph\_D.py




### Contour Graphs

C:\VKHCG\01-Vermeulen\06-Report\Report\_Graph\_G.py



## 3D Graphs

C:\VKHCG\01-Vermeulen\06-Report\Report\_PCA\_IRIS.py




# Practical 10

## Data Visualization with Power BI

### Case Study : Sales Data

#### Step 1: Connect to an Excel workbook

1. Launch Power BI Desktop.
2. From the Home ribbon, select Get Data. Excel is one of the **Most Common** data connections, so you can select it directly from the Get Data menu.



3. If you select the Get Data button directly, you can also select File > Excel and select Connect.
4. In the Open File dialog box, select the Products.xlsx file.

In this step you remove all columns except ProductID, ProductName, UnitsInStock, and QuantityPerUnit.

The screenshot shows the Power BI Navigator on the left, which lists a single connection named 'Products.xlsx'. Underneath, there are two tables: 'Products' and 'Sheet1'. A red arrow points from the text above to the 'Products' table header in the Navigator. To the right is the 'Products' table preview window. The table has columns: ProductID, ProductName, SupplierID, CategoryID, and Discontinued. A red arrow points from the text above to the 'ProductID' column header in the preview window. A purple arrow points from the text above to the 'QuantityPerUnit' column header in the preview window. The preview shows 42 rows of product data.



| ProductID | ProductName                      | SupplierID | CategoryID | Discontinued |
|-----------|----------------------------------|------------|------------|--------------|
| 1         | Chai                             | 2          | 1          | 0            |
| 2         | Cheesecake                       | 2          | 1          | 0            |
| 3         | Aniseed Syrup                    | 2          | 2          | 0            |
| 4         | Chef Anton's Cajun Seasoning     | 2          | 2          | 0            |
| 5         | Chef Anton's Gumbo Mix           | 2          | 2          | 0            |
| 6         | Grandma's Boysenberry Spread     | 3          | 2          | 0            |
| 7         | Lilac Beer's Organic Dried Pears | 3          | 2          | 0            |
| 8         | Mt. Hood's Cinnamon Spice        | 3          | 2          | 0            |
| 9         | Monte Roja Niku                  | 4          | 0          | 0            |
| 10        | Nutty <sup>TM</sup>              | 4          | 0          | 0            |
| 11        | Queso Casado                     | 5          | 4          | 1            |
| 12        | Queso Manchego La Pastora        | 5          | 4          | 0            |
| 13        | Konkola                          | 6          | 8          | 0            |
| 14        | Tofte                            | 6          | 7          | 0            |
| 15        | Gremm Shores                     | 6          | 2          | 0            |
| 16        | Pavlova                          | 7          | 7          | 0            |
| 17        | Aloco Molata                     | 7          | 6          | 0            |
| 18        | Concertina Tigers                | 7          | 6          | 0            |
| 19        | Feastive Chocolate Biscuits      | 8          | 7          | 0            |
| 20        | Sir Kowhai's Marmalade           | 8          | 7          | 0            |
| 21        | Sir Kowhai's Scampi              | 8          | 7          | 0            |
| 22        | Ungu's Indukuku                  | 9          | 6          | 0            |

You can also open the Query Editor by selecting Edit Queries from the Home ribbon in Power BI Desktop. The following steps are performed in Query Editor.

1. In Query Editor, select the ProductID, ProductName, QuantityPerUnit, and UnitsInStock columns

(use *Ctrl+Click* to select more than one column, or *Shift+Click* to select columns that are beside each other)

2. Select Remove Columns [Remove Other Columns from the ribbon, or right-click on a column header and click Remove Other Columns.



### Step 3: Change the data type of the UnitsInStock column

For the Excel workbook, products in stock will always be a whole number, so in this step you confirm the UnitsInStock column's datatype is Whole Number.

1. Select the UnitsInStock column.
2. Select the Data Type drop-down button in the Home ribbon.
3. If not already a Whole Number, select Whole Number for data type from the drop down (*the Data Type: button also displays the data type for the current selection*).

### Task 2: Import order data from an OData feed

You import data into Power BI Desktop from the sample Northwind OData feed at the following URL, which you can copy (and then paste) in the steps below:


<http://services.odata.org/V3/Northwind/Northwind.svc/>

#### Step 1: Connect to an OData feed

1. From the Home ribbon tab in Query Editor, select **Get Data**.
2. Browse to the **OData Feed** data source.
3. In the **OData Feed** dialog box, paste the **URL** for the Northwind OData feed.
4. Select OK.

| OrderID | CustomerID | EmployeeID | OrderDate             | RequiredDate | ProductID | UnitPrice | Quantity | Discount | RowNumber |
|---------|------------|------------|-----------------------|--------------|-----------|-----------|----------|----------|-----------|
| 10248   | VINET      | 5          | 7/4/1994 12:00:00 AM  | 8/1/1994     |           |           |          |          | 1         |
| 10249   | TOMSP      | 6          | 7/5/1994 12:00:00 AM  | 8/5/1994     |           |           |          |          | 2         |
| 10250   | HANAR      | 4          | 7/6/1994 12:00:00 AM  | 8/6/1994     |           |           |          |          | 3         |
| 10251   | VICTE      | 5          | 7/8/1994 12:00:00 AM  | 8/8/1994     |           |           |          |          | 4         |
| 10252   | SUPRD      | 4          | 7/10/1994 12:00:00 AM | 8/10/1994    |           |           |          |          | 5         |
| 10253   | MANAR      | 3          | 7/10/1994 12:00:00 AM | 8/10/1994    |           |           |          |          | 6         |
| 10254   | CHIPS      | 5          | 7/13/1994 12:00:00 AM | 8/13/1994    |           |           |          |          | 7         |
| 10255   | RICSU      | 3          | 7/12/1994 12:00:00 AM | 8/12/1994    |           |           |          |          | 8         |
| 10256   | WELLU      | 3          | 7/13/1994 12:00:00 AM | 8/13/1994    |           |           |          |          | 9         |
| 10257   | HILAR      | 4          | 7/16/1994 12:00:00 AM | 8/13/1994    |           |           |          |          | 10        |
| 10258   | ERNSH      | 3          | 7/17/1994 12:00:00 AM | 8/14/1994    |           |           |          |          | 11        |
| 10259   | CENTC      | 4          | 7/18/1994 12:00:00 AM | 8/15/1994    |           |           |          |          | 12        |
| 10260   | OTTIK      | 4          | 7/19/1994 12:00:00 AM | 8/16/1994    |           |           |          |          | 13        |
| 10261   | QUESDE     | 4          | 7/19/1994 12:00:00 AM | 8/16/1994    |           |           |          |          | 14        |
| 10262   | RATTIC     | 3          | 7/22/1994 12:00:00 AM | 8/19/1994    |           |           |          |          | 15        |
| 10263   | ERNSH      | 3          | 7/23/1994 12:00:00 AM | 8/20/1994    |           |           |          |          | 16        |
| 10264   | POLKO      | 6          | 7/24/1994 12:00:00 AM | 8/21/1994    |           |           |          |          | 17        |
| 10265   | BLONP      | 2          | 7/25/1994 12:00:00 AM | 8/22/1994    |           |           |          |          | 18        |
| 10266   | VWAETH     | 3          | 7/26/1994 12:00:00 AM | 8/23/1994    |           |           |          |          | 19        |
| 10267   | FRANK      | 4          | 7/29/1994 12:00:00 AM | 8/26/1994    |           |           |          |          | 20        |
| 10268   | GROSR      | 8          | 7/30/1994 12:00:00 AM | 8/27/1994    |           |           |          |          | 21        |
| 10269   | WMHTC      | 5          | 7/31/1994 12:00:00 AM | 8/28/1994    |           |           |          |          | 22        |
| 10270   | VWAETH     | 1          | 8/1/1994 12:00:00 AM  | 8/29/1994    |           |           |          |          | 23        |

## Step 2: Expand the Order\_Details table



Expand the **Order\_Details** table that is related to the **Orders** table, to combine the **ProductID**, **UnitPrice**, and **Quantity** columns from **Order\_Details** into the **Orders** table. The **Expand** operation combines columns from a related table into a subject table. When the query runs, rows from the related table (**Order\_Details**) are combined into rows from the subject table (**Orders**).

After you expand the **Order\_Details** table, three new columns and additional rows are added to the **Orders** table, one for each row in the nested or related table.

- In the **Query View**, scroll to the **Order\_Details** column.

- In the **Order\_Details** column, select the expand icon ( ).

- In the **Expand** drop-down: a. Select **(Select All Columns)** to clear all columns.

Select **ProductID**, **UnitPrice**, and **Quantity**.

click OK.

### Step 3: Remove other columns to only display columns of interest

In this step you remove all columns except **OrderDate**, **ShipCity**, **ShipCountry**, **Order\_Details.ProductID**, **Order\_Details.UnitPrice**, and **Order\_Details.Quantity** columns. In the previous task, you used **Remove Other Columns**. For this task, you remove selected columns.

In the **Query View**, select all columns by completing a.

- Click the first column (**OrderID**).
- Shift+Click the last column (**Shipper**).
- Now that all columns are selected, use Ctrl+Click to unselect the following columns: **OrderDate**, **ShipCity**, **ShipCountry**, **Order\_Details.ProductID**, **Order\_Details.UnitPrice**, and **Order\_Details.Quantity**.

Now that only the columns we want to remove are selected, right-click on any selected column header and click **Remove Columns**.

### Step 4: Calculate the line total for each Order\_Details row

Power BI Desktop lets you to create calculations based on the columns you are importing, so you can enrich the data that you connect to. In this step, you create a **Custom Column** to calculate the line total for each **Order\_Details** row.

Calculate the line total for each **Order\_Details** row:


- In the **Add Column** ribbon tab, click **Add Custom Column**.
- In the Add Custom Column dialog box, in the Custom Column Formula textbox, enter **[Order\_Details.UnitPrice] \* [Order\_Details.Quantity]**.
- In the New column name textbox, enter **LineTotal**.

The screenshot shows the Power BI Desktop ribbon with the 'Home' tab selected. Below the ribbon, a preview of the 'Orders' table is displayed. A tooltip for the 'Close & Load' button is visible, stating: 'Close the Query Editor window and load any pending changes to the report.' The table preview shows two rows: one for France with a value of 168 and another for France with a value of 98.



## Step 5: Set the datatype of the LineTotal field

1. Right click the **LineTotal** column.
2. Select **Change Type** and choose **Decimal Number**.



## Step 6: Rename and reorder columns in the query

1. In **Query Editor**, drag the **LineTotal** column to the left, after **ShipCountry**.
2. Remove

The screenshot shows the Power BI Query Editor with the 'Order' query selected. The 'LineTotal' column is now positioned to the left of the 'ShipCountry' column. The 'APPLIED STEPS' pane on the right shows the 'Removed Other Columns' step is applied. The preview pane at the bottom right shows the updated data.


2. Remove the *Order\_Details.* prefix from the **Order\_Details.ProductID**, **Order\_Details.UnitPrice** and **Order\_Details.Quantity** columns, by double-clicking on each column header, and then deleting that text from the column name.

The screenshot shows the Power BI Query Editor with the 'Order' query selected. The 'Order\_Details.' prefix has been removed from the 'ProductID', 'UnitPrice', and 'Quantity' columns. The 'APPLIED STEPS' pane on the right shows the 'Removed Other Columns' step is applied. The preview pane at the bottom right shows the updated data.


## Task 3: Combine the Products and Total Sales queries


### Step 1: Confirm the relationship between Products and Total Sales

1. First, we need to load the model that we created in Query Editor into Power BI Desktop. From the Home ribbon of Query Editor, select **Close & Load**.




2. Power BI Desktop loads the data from the two queries
3. Once the data is loaded, select the Manage Relationships button Home ribbon
4. Select the New... button
5. When we attempt to create the relationship, we see that one already exists! As shown in the Create Relationship dialog (by the shaded columns), the ProductsID fields in each query already have an established relationship.





## 6. Select Cancel, and then select Relationship view in Power BI Desktop.




### Task 4: Build visuals using your data

#### Step 1: Create charts showing Units in Stock by Product and Total Sales by Year



1. Next, drag ShipCountry to a space on the canvas in the top right. Because you selected a geographic field, a map was created automatically. Now drag LineTotal to the Values field; the circles on the map for each country are now relative in size to the LineTotal

for orders shipped to that country.



## Step 2: Interact with your report visuals to analyze further



~~~~~ \* \* \* \* ~~~~