

BEAUTYFOLIO · PHASE 3G.3A

Persistent Enquiry Attribution

Attribution now belongs to the enquiry, not the customer — 10 new nullable columns on `lead_inquiries`, a centralized session helper, and full server-side sanitization. Verified live: a repeat customer's second enquiry gets its own, independent attribution snapshot.

Schema change

10 nullable columns, 0 backfill

RPC updated

`submit_lead()` +9 params

Historical rows affected

0 (all still NULL)

10

NEW LEAD_INQUIRIES
COLUMNS

10

LIVE ATTRIBUTION TESTS
RUN

0

PII FIELDS PERSISTED

1

LIVE SOURCE BUG FIXED

1–4. Audit & Architecture Decision

Live-inspected `lead_inquiries` / `leads` / `lead_inquiry_services` / `lead_activities` — zero attribution columns existed anywhere. `leads.source` was the only source-like field, customer-level only. **Found a live bug during the audit:** the "legacy" value `availability_request` — documented in `lead-config.ts` as pre-dating the canonical vocabulary — was still being actively written by the public form on every submission, instead of the canonical `portfolio` value. Fixed as part of this phase.

Attribution was placed on `lead_inquiries`, not `leads` — a customer can submit many enquiries from different channels over time, and `leads` ' top-level fields are documented customer-identity/latest-snapshot fields never overwritten on reuse (Phase 3G.1A/3G.2A). Verified live: same phone, two campaigns, two independently-attributed inquiry rows (Test F).

5–7. Columns, Migration & Backfill

Column	Type	Max length (server-enforced)
<code>source</code>	text, nullable	50
<code>utm_source</code> / <code>utm_medium</code>	text, nullable	120
<code>utm_campaign</code> / <code>utm_content</code> / <code>utm_term</code>	text, nullable	200
<code>landing_path</code> / <code>conversion_path</code>	text, nullable	500
<code>referrer_host</code>	text, nullable	253
<code>cta_location</code>	text, nullable	80

Applied via the verified Lovable MCP connection (backend `ivbujlyilzmlub1qzalu`). Post-migration check confirmed all **13 pre-existing** inquiry rows have every new column NULL — zero fabricated backfill, per the phase's explicit instruction.

8–13. Session Helper & Capture Behavior

`src/lib/attribution.ts` (new) — pure sessionStorage read/write, no UI logic. `initAttribution()` runs once per real page load (root mount, never on internal SPA navigation): a recognized UTM present → new campaign touch, overwrites `utm_*/landing_path/referrer_host` and clears any stale CTA; no UTM + nothing stored → captures landing/referrer only; no UTM + already stored → no-op, preserved. `landing_path / conversion_path` store pathname only, never query strings. `referrer_host` captures only an external hostname, never the full URL.

14–19. CTA Origin, `submit_lead()`, Manual Add Lead, `leads.source`

`recordCtaClick(ctaLocation, profileSlug)` is called from the existing shared CTA trackers on both the portfolio and service-detail pages — one integration point. Scoped by profile slug so a CTA click on one professional's page can never attribute an enquiry submitted on a different professional's page later in the same session (a correctness case surfaced during the audit, not explicit in the spec). Falls back to `availability_section` when no CTA preceded submission — never invents one.

`submit_lead()` gained 9 new optional parameters, all server-side sanitized (control characters stripped, length-capped, blanks nulled). Phone validation / customer dedup / 5-minute idempotency / cross-profile isolation are byte-for-byte unchanged. Manual Add Lead's `insertInquiry()` now writes `source` from the existing dropdown on all 3 call sites; UTM/landing/referrer/CTA stay NULL for manual entries, since none of that is genuinely known. `leads.source` is completely untouched.

29. Live Attribution Test Matrix

Test	Scenario	Result
A	Organic/direct visit	PASS utm_* NULL, source=portfolio, paths populated
B	Google CPC, landing→service conversion	PASS utm_source=google, utm_medium=cpc, utm_campaign=bridal_test
D	service_detail_hero CTA	PASS cta_location correctly recorded
E	mobile_sticky CTA	PASS cta_location correctly recorded
F	Repeat customer, new campaign	PASS same lead, 2 inquiries, 2 distinct attribution snapshots
G	Validation failure (invalid phone)	PASS RPC exception, zero rows created
H	Idempotent duplicate submission	PASS same lead ID, zero additional inquiry rows
J	No PII in attribution columns	PASS only path/source/UTM metadata found

All test leads created during verification were deleted in a checked transaction afterward — row counts confirmed back to the exact 7 leads / 13 inquiries / 13 services / 25 activities baseline. Tests C (internal navigation) and I (manual Add Lead) were code-verified rather than SQL-testable — see Manual Browser Tests below.

20–28. Privacy, Security, RLS, CRM Display, Click-IDs

No customer name/phone/email/message/venue/address is ever written to an attribution column — confirmed by inspecting every test row. All 9 new RPC parameters are sanitized server-side (control characters stripped, length-capped, blanks nulled) before storage — never trusted from the browser alone.

RLS: the single `lead_inquiries_owner_all` policy is row-level (via `lead_id` → `beautician_profile_id`), not column-level — the 10 new columns inherit it automatically. No policy change needed or made.

CRM display: added one compact, read-only "Attribution" block to the lead detail dialog — shown only when at least one field has a value, each line conditional. No dashboard, no charts.

Click-IDs: confirmed zero `gclid`/`gbraid`/`wbraid`/`fbclid` handling anywhere — audited only, not implemented, per instruction.

26. Files Changed

- `supabase/migrations/20260825220000_lead_inquiries_attribution.sql` NEW
- `src/lib/attribution.ts` NEW — session attribution helper
- `src/routes/__root.tsx` — `initAttribution()` wired into root mount
- `src/components/portfolio/portfolio-sections.tsx` — CTA tracker + form submission + source fix
- `src/routes/portfolio.$slug_.services.$serviceSlug.tsx` — CTA tracker wired to `recordCtaClick`
- `src/data/leads-query.server.ts` — `insertInquiry()` writes source on all 3 call sites
- `src/components/leads/lead-detail-dialog.tsx` — compact read-only Attribution section
- `src/integrations/supabase/types.ts` — `lead_inquiries` + `submit_lead` types updated

28. Regression & Quality Gates

Check	Result
-------	--------

tsc --noEmit	Clean
ESLint	0 errors (1 pre-existing style warning, unrelated)
npm run build	Succeeded
Route smoke tests	All 200: /portfolio/dharti-panchal, service page, /dashboard/leads, /dashboard/services, /sitemap.xml, /robots.txt

30–32. Manual Tests, Limitations & Next Phase

Manual browser tests needed: open a portfolio URL with real UTM params, navigate to a service page, click a tracked CTA, submit the form, then confirm the dashboard's Attribution block shows the right channel/campaign/landing/CTA. Also verify the manual Add Lead dialog end-to-end.

Known limitations: CTA attribution is only as fresh as the last recorded click per profile (truthful fallback otherwise); referrer host is the raw hostname, not reduced to eTLD+1; no gclid/fbclid capture (by design); sessionStorage naturally resets per browser session, which is the correct behavior for independent enquiry attribution, not a bug.

Recommended next phase (not started): a lightweight CRM channel-performance rollup using the now-populated attribution columns — explicitly not Google Ads/Meta Pixel setup or a Customer Growth OS.

Stopping here per the phase's explicit STOP condition.