OS & SP

Name : D. Teja Sadwika **Roll No :** 2520030536

SKILL – 07

1.Skill7.c

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>
#include <sys/types.h>
#include <sys/wait.h>

#define MAX_INPUT 1024
#define MAX_ARGS 100

/* Parse command into arguments */
int parse_command(char *input, char *args[])
{
```

```
    int argc = 0;
    char *token = strtok(input, " \t");

    while (token != NULL && argc < MAX_ARGS - 1) {
        args[argc++] = token;
        token = strtok(NULL, " \t");
    }

    args[argc] = NULL;
    return argc;
}

/* Display PATH */
void display_path(void)
{
    char *path = getenv("PATH");

    if (path == NULL) {
```

```
        printf("PATH is not set.\n");
        return;
    }

    printf("PATH:\n%s\n", path);
}

/* Display PATH directories separately */
void display_pathlist(void)
{
    char *path = getenv("PATH");

    if (path == NULL) {
        printf("PATH is not set.\n");
        return;
    }

    char *copy = strdup(path);
```

```
    if (copy == NULL) {
        perror("strdup");
        return;
    }

    printf("PATH directories:\n");

    int count = 1;
    char *dir = strtok(copy, ":");

    while (dir != NULL) {
        printf("%d. %s\n", count++, dir);
        dir = strtok(NULL, ":");
    }

    free(copy);
}
```

```
/* Find executable in PATH */
char *find_executable(const char *command)
{
    if (strchr(command, '/') != NULL) {
        if (access(command, X_OK) == 0)
            return strdup(command);
        return NULL;
    }

    char *path = getenv("PATH");
    if (path == NULL)
        return NULL;

    char *copy = strdup(path);
    if (copy == NULL)
        return NULL;

    char *dir = strtok(copy, ":");
```

```
    char candidate[MAX_INPUT];

    while (dir != NULL) {
        snprintf(candidate, sizeof(candidate),
                "%s/%s", dir, command);

        if (access(candidate, X_OK) == 0) {
            char *result = strdup(candidate);
            free(copy);
            return result;
        }

        dir = strtok(NULL, ":");
    }

    free(copy);
    return NULL;
}
```

```
int main(void)
{
    char input[MAX_INPUT];
    char *args[MAX_ARGS];

    printf("====================================\n");
    printf("        OSSP PROGRAM 7\n");
    printf("     waitpid() + PATH Searching\n");
    printf("====================================\n");

    printf("\nCommands:\n");
    printf("  path     - display PATH\n");
    printf("  pathlist - display PATH directories\n");
    printf("  exit     - quit\n\n");

    while (1) {
        printf("shell7> ");
```

```
fflush(stdout);

if (fgets(input, sizeof(input), stdin) == NULL)
    break;

input[strcspn(input, "\n")] = '\0';

if (input[0] == '\0')
    continue;

if (strcmp(input, "exit") == 0)
    break;

int argc = parse_command(input, args);

if (argc == 0)
    continue;
```

```
if (strcmp(args[0], "path") == 0) {
    display_path();
    continue;
}

if (strcmp(args[0], "pathlist") == 0) {
    display_pathlist();
    continue;
}

char *executable = find_executable(args[0]);

if (executable == NULL) {
    printf("Command not found or not executable: %s\n",
        args[0]);
    continue;
}
```

```
printf("\nExecutable found:\n%s\n", executable);

pid_t pid = fork();

if (pid < 0) {
    perror("fork");
    free(executable);
    continue;
}

if (pid == 0) {
    printf("Child process started.\n");
    printf("Child PID: %d\n", getpid());

    execv(executable, args);

    perror("execv");
    _exit(EXIT_FAILURE);
```

```
} else {
    int status;


    printf("Parent PID: %d\n", getpid());
    printf("Child PID: %d\n", pid);
    printf("Parent waiting using waitpid()...\n");

    if (waitpid(pid, &status, 0) == -1) {
        perror("waitpid");
    } else if (WIFEXITED(status)) {
        printf("Child %d exited normally.\n", pid);
        printf("Exit status: %d\n",
                WEXITSTATUS(status));
    } else {
        printf("Child terminated abnormally.\n");
    }
}
```

```
        free(executable);
        printf("\n");
    }

    printf("Program 7 terminated.\n");
    return 0;
}
```

OUTPUT :


sadwika@DESKTOP-8CQAO1L
sadwika@DESKTOP-8CQAO1L:~$ nano skill7.c
sadwika@DESKTOP-8CQAO1L:~$ gcc -Wall -Wextra -g skill7.c -o skill7
sadwika@DESKTOP-8CQAO1L:~$ ./skill7
==========
OSSP PROGRAM 7
waitpid() + PATH Searching
==========
Commands:
path - display PATH
pathlist - display PATH directories
exit - quit
shell7> valgrind --leak-check=full --show-leak-kinds=all ./program7
Command not found or not executable: valgrind
shell7> pwd
Executable found:
/usr/bin/pwd
Parent PID: 1569
Child PID: 1623
Parent waiting using waitpid()...
Child process started.
Child PID: 1623
/home/sadwika
Child 1623 exited normally.
Exit status: 0
shell7> exit
Program 7 terminated.
sadwika@DESKTOP-8CQAO1L:~$