Main Power Switch	ing	V104	V102	140
	0) X0	X104	X103	M0
				_
	Drive ena ble	Drive Dis able	EMERGE NCY Swit	power me mory bit
			ch	,
	M0			
	$\vdash$	-		
	power me			
	mory bit			
SERVO-MOTOR F	ORWARD N	JOVEMEN	T CONTROL	
(2	M0 7) —	M1	M2	Y1
(-				
	power me	Forward	Reverse Memory S witch	Forward Move
	ITIOLY DIL	witch	witch	Move
		M30		
		IVI30		
		posi 1 for ward mov		
		е		
		M40		
		<u> </u>		
		posin.2 fo		
		rward		
		M50		
		$\vdash\vdash\vdash$		
		Posi. 3 Fo		
		rwerd		
	Y1	SM411		M3
(7	4)	<del>                                     </del>		$ \circ$
	Forward	200(ms) o lock		forver mo
	Move	lock` ´		V
SERVO-MOTOR F	REVERSE M	OVEMENT	CONTROL	 V/2
(7	M0 7) ─	M2	M1	Y2
	1			
	power me	Reverse Memory S	Forward Memory S witch	Revers M ove
	mory on	witch	witch	0.0
		M20		
		for borns		
		for home mode Ena		
		ble		
		M31		
		<u> </u>		
	1			

10/25, 5.56 PIVI	l				Servo	_IVIOLOI_PL	C_Progrim	ning_nie		
			posin 1 re verse mo							
			Ve136 1110 V.							
			M41							
			$\vdash\vdash\vdash$							
			posin. 2 R							
			everse							
			M51							
			- WIST	J						
			position 3.							
			reverse							
			01444							
	(125)	Y2 ——	SM411							M4
		ove	200(ms) c lock							Reverse memory
										it
COUNTER U	SE FOR	R CALCUL	ATING FO	RWARD & REV	ERSE DIRECTI	ON CTUD_3	(OTUD)			
	(128)					C10D_3	(CTOD)			
		M3								Y3
		$\dashv$ $\vdash$ $\vdash$				CU	QU			<del>  </del> Õ
		forver mo				Count U	Count U			
		v				p Signal Input	p Coinci dence O			
						·	utput			
		N//								
		M4 ——   ——				CD	QD			Y4 O
		Reverse				Count D	Count D			lowest co
		memory b				own Sig nal Input	own Coi ncidenc			nv. positi n Indicat
		it				nai input	e Output			n Indicat r
		X101				R	CV	[ D0 ]—		
						Count U				
		forward R eset				p Reset	Count V	Actual for ward posit		
							alue	ion reach		
		X102				LD				
		$\dashv \vdash$								
						Count D own Res				
						et				
					•					
					_	_,,				
					[ D101 ]					
					max conv	Count M				
					eyor mom ent Outpo	Value				
					t Data Re					
HOMEMODE	SWITC	HING								
I IOIVILIVIODL		M0	X1	X2 X	3 X6					M20
	(213)	-+	<del></del>	<u> </u>						
		power me	Homema	Home mo Jog n	node Position					for home
1		1							:	1

		mory bit	de Enable	de start	Enble	Mode En ble	a						mode Ena ble
		DOE MEM		FOLI									
FURWAR	DAKEVE	M0	IORY SWIT	X1	X6	X4	X5						M1
	(239)		—-ΠΗ	—Ĵ/ <u>†</u>	—ĴŸ_	-	—ĴĬ—						
	` ′					' '							
		power me	Jog mode	Homema	Position	Jog Forw	Jog Revei	r					Forward
		mory bit	Enble	de Enabi	e Mode En ble	ard mov.	se mov.						Memory S witch
					DIC								WILCIT
						X5	X4						M2
						$\vdash$	<u> </u>						-0 $-$
						Jog Reve	er Jog Forw						Reverse
						se mov.	ard mov.						Memory S witch
													WILCIT
POSITION	MODE (F	POSITION	SWITCHIN	JG)						<u>L</u>		<u> </u>	<u> </u>
	· \.	M0	Х6	X1	Х3	X7	X8	Х9	SM411				M5
	(284)	$\vdash \vdash \vdash$	+	<u> </u>	<b>─</b> //	+	<u> </u>	<b>─</b> //					-0 $-$
		power me	Position	Homema	Jog mod	e Position	1 position 2	position (	3 200(ms) c	;			position 1
		mory bit	Mode Ena	ade Enabi	ie Endie				lock				memo. bit
			DIE										
						X8	<b>V</b> 7	VΩ	SM411				M6
							X7	X9 /1—	——————————————————————————————————————				
						''	~ '	* 1					~
						position 2	Position 1	position 3	3 200(ms) c	:			posi.2 me
									lock` ´				mory bit
								>/0	01444				
						X9	X7	X8	SM411				M7
													$\overline{}$
						nosition 3	R Position 1	nosition :	2 200(ms) c				Posi. 3 m
						pooliion	7 1 00111011 1	poomon	lock				emory bit
													,
POSITION	N- 1 VALUE			1								1	1
	(0.40)	M5	M500								MOV	D1	D101
	(342)	$\vdash$	<u> </u>								MOV	D1 Position 1	D101 max conv
		position 1	dissbale t									IP display	evor mom
		memo hit	t he sudde									ii diopidy	eyor mom ent Outpo t Data Re
		momo. bii	n movemt	t									t Data Re
			on 0 posit	i									
													M30
				>	D1	D0							0 $-$
					Position	1 Actual for ward pos	[						
					IP dispia	ion reach	11						posi 1 for
						lonreach	'						ward mov e
													C
										-			M31
				<	D1	D0							—Ö—
					Position	1 Actual for							Ŭ
					IP displa	y ward pos	it						posin 1 re
						ion reach							verse mo
													٧.
DOO!T!C:		<u> </u>											<u> </u>
POSITION	<u> </u>	L NAC	N4000	1						Ţ			
	(375)	M6	M600								MOV	D2	D101
	(3/3)	7	7								IVIOV	position 2	max conv
		posi.2 me	,									ip disp.	eyor mom ent Outpo
		mory bit											ent Outpo
1													t Data Re

				>	D2	D0	<u> </u>				M40
					position 2 ip disp.	Actual for ward posit ion reach					posin.2 fo rward
				<	D2	D0	}				M41
					position 2 ip disp.	Actual for ward posit ion reach					posin. 2 R everse
POSITION		M7	M700								
	(409)	Posi. 3 m emory bit							MOV	D3 position3 p disp.	D101 imax conv eyor mom ent Outpo t Data Re
											M50
				>	D3 position3	D0 iActual for ward posit					<del>-</del> 0-
					p alsp.	ion reach					Posi. 3 Fo rwerd
				<	D3	D0	1				M51
					position3 p disp.	iActual for ward posit ion reach					position 3. reverse
					_						M500
	(443)	=	D1 Position 1 IP display	0							dissbale t he sudde n movemt on 0 positi
	(447)	=	D2	0	7						M600
	()		position 2 ip disp.								M700
	(451)	=	D3 position3 i p disp.	0							M700
DEFAULT	200 LOCA (455)	M500	M600	S GIVEN M700	FOR FOR	WARD MO\	/EMENT		MOV	200	D101
		dissbale t he sudde n movemt on 0 positi							IVIOV	200	max conv eyor mom ent Outpo t Data Re
		s poolu									
	(523)										[END ]

file:///E:/Servo	Motor-control	project/Servo	Motor	PLC	Progrmming	file.html