Code

MySQL Auto

```sql
select customer_number from orders
group by customer_number
order by count(order_number) desc
limit 1;
```

Saved Ln 5, Col 1

Testcase | Test Result

```
| customer_number |
| --------------- |
| 3               |
```

Expected

```
| customer_number |
| --------------- |
| 3               |
```

Contribute a testcase

Code

MySQL Auto

```sql
# Write your MySQL query statement below

with uniq_num as
(select num from mynumbers group by num having count(num) =1 )

select max(num) as num from uniq_num;
```

Saved Ln 6, Col 38

Testcase | Test Result

Output

```
| num  |
| ---- |
| null |
```

Expected

```
| num  |
| ---- |
| null |
```

Contribute a testcase

Code

MySQL Auto

```sql
# Write your MySQL query statement below
select distinct player_id , min(event_date) as first_login from activity
group by player_id;
```

Saved

Ln 3, Col 20

Testcase | Test Result

| player_id | first_login |
| --- | --- |
| 1 | 2016-03-01 |
| 2 | 2017-06-25 |
| 3 | 2016-03-02 |

Expected

| player_id | first_login |
| --- | --- |
| 1 | 2016-03-01 |
| 2 | 2017-06-25 |
| 3 | 2016-03-02 |

Code

MySQL Auto

```sql
# Write your MySQL query statement below
select date_id,make_name,count(distinct lead_id) as unique_leads ,count
(distinct partner_id) as unique_partners from dailysales group by date_id,
make_name;
```

Saved

Ln 2, Col 82

Testcase | Test Result

| date_id | make_name | unique_leads | unique_partners |
| --- | --- | --- | --- |
| 2020-12-07 | honda | 3 | 2 |
| 2020-12-07 | toyota | 1 | 2 |
| 2020-12-08 | honda | 2 | 2 |
| 2020-12-08 | toyota | 2 | 3 |

Expected

| date_id | make_name | unique_leads | unique_partners |
| --- | --- | --- | --- |
| 2020-12-07 | honda | 3 | 2 |
| 2020-12-07 | toyota | 1 | 2 |

Code

MySQL Auto

```sql
# Write your MySQL query statement below
select emp_id,event_day as day ,sum(out_time-in_time) as total_time from employees group by event_day , emp_id;
```

Saved Ln 2, Col 33

Testcase | Test Result

| emp_id | day | total_time |
| --- | --- | --- |
| 1 | 2020-11-28 | 173 |
| 1 | 2020-12-03 | 41 |
| 2 | 2020-11-28 | 30 |
| 2 | 2020-12-09 | 27 |

Expected

| day | emp_id | total_time |
| --- | --- | --- |
| 2020-11-28 | 1 | 173 |
| 2020-12-03 | 1 | 41 |

Code

MySQL Auto

```sql
# Write your MySQL query statement below
select actor_id,director_id from actordirector
group by actor_id,director_id having count(director_id)>=3;
```

Saved Ln 3, Col 59

Testcase | Test Result

| actor_id | director_id |
| --- | --- |
| 1 | 1 |

Expected

| actor_id | director_id |
| --- | --- |
| 1 | 1 |

Contribute a testcase

Code

MySQL Auto

```sql
# Write your MySQL query statement below
select distinct user_id , max(time_stamp) as last_stamp from logins where year
(time_stamp)=2020
group by user_id ;
```

Saved Ln 2, Col 42

Testcase | Test Result

| user_id | last_stamp |
| --- | --- |
| 6 | 2020-06-30 15:06:07 |
| 8 | 2020-12-30 00:46:50 |
| 2 | 2020-01-16 02:49:50 |

Expected

| user_id | last_stamp |
| --- | --- |
| 6 | 2020-06-30 15:06:07 |
| 8 | 2020-12-30 00:46:50 |

Code

MySQL Auto

```sql
# Write your MySQL query statement below
select query_name,round(sum(rating/position)/count(position),2) as quality ,
round(sum(if (rating<3,1,0))*100/count(rating),2) as poor_query_percentage
from queries
where query_name is not null
group by query_name;
```

Saved Ln 6, Col 21

Testcase | Test Result

Accepted Runtime: 84 ms

Case 1

Input

Queries =

| query_name | result | position | rating |
| --- | --- | --- | --- |
| Dog | Golden Retriever | 1 | 5 |
| Dog | German Shepherd | 2 | 5 |
| Dog | Mule | 200 | 1 |
| Cat | Shirazi | 5 | 2 |

Code

MySQL Auto

```sql
# Write your MySQL query statement below
select query_name,round(sum(rating/position)/count(position),2) as quality ,
round(sum(if (rating<3,1,0))*100/count(rating),2) as poor_query_percentage
from queries
where query_name is not null
group by query_name;
```

Saved    Ln 1, Col 1

Testcase | Test Result

```
| ---------- | ------- | --------------------- |
| Dog        | 2.5     | 33.33                 |
| Cat        | 0.66    | 33.33                 |
```

Expected

```
| query_name | quality | poor_query_percentage |
| ---------- | ------- | --------------------- |
| Dog        | 2.5     | 33.33                 |
| Cat        | 0.66    | 33.33                 |
```

Contribute a testcase

Code

MySQL Auto

```sql
# Write your MySQL query statement below
SELECT activity_date AS day, COUNT(DISTINCT user_id) AS active_users
FROM Activity
WHERE (activity_date > "2019-06-27" AND activity_date <= "2019-07-27")
GROUP BY activity_date;
```

Saved    Ln 5, Col 24

Testcase | Test Result

```
| ---------- | ------------ |
| 2019-07-20 | 2            |
| 2019-07-21 | 2            |
```

Expected

```
| day        | active_users |
| ---------- | ------------ |
| 2019-07-20 | 2            |
| 2019-07-21 | 2            |
```

Contribute a testcase

Code

MySQL Auto

```sql
# Write your MySQL query statement below
select product_name ,year,price from product s inner join sales p
on s.product_id  = p.product_id;
```

Saved Ln 3, Col 33

Testcase | Test Result

Product =

```
| product_id | product_name |
| ---------- | ------------ |
| 100        | Nokia        |
| 200        | Apple        |
| 300        | Samsung      |
```

Output

```
| product_name | year | price |
| ------------ | ---- | ----- |
| Nokia        | 2008 | 5000  |
| Nokia        | 2009 | 5000  |
```

Code

MySQL Auto

```sql
SELECT a.name, b.bonus
FROM Employee AS a
LEFT JOIN Bonus AS b
ON a.empId = b.empId
WHERE b.bonus < 1000
   OR b.bonus IS NULL;
```

Saved Ln 9, Col 1

Testcase | Test Result

Output

```
| name | bonus |
| ---- | ----- |
| Brad | null  |
| John | null  |
| Dan  | 500   |
```

Expected

```
| name | bonus |
| ---- | ----- |
| Brad | null  |
| John | null  |
```

Code

MySQL Auto

```sql
# Write your MySQL query statement below
select s.student_id, s.student_name,sub.subject_name,count(e.subject_name) as attended_exams
from students s cross join subjects sub
left join examinations e
on s.student_id = e.student_id
and sub.subject_name = e.subject_name
group by s.student_id , s.student_name, sub.subject_name
```

Saved Ln 2, Col 93

Testcase | Test Result

| student_id | student_name | subject_name | attended_exams |
| --- | --- | --- | --- |
| 1 | Alice | Math | 3 |
| 1 | Alice | Physics | 2 |
| 1 | Alice | Programming | 1 |
| 2 | Bob | Math | 1 |
| 2 | Bob | Physics | 0 |
| 2 | Bob | Programming | 1 |

View more

Expected

| student_id | student_name | subject_name | attended_exams |
| --- | --- | --- | --- |

Code

MySQL Auto

```sql
# Write your MySQL query statement below
select name from employee
where id in
(
    select managerId from employee
    group by managerID
    having count(managerid) > 4
)
```

Saved Ln 6, Col 23

Testcase | Test Result

Accepted Runtime: 83 ms

Case 1

Input

Employee =

| id | name | department | managerId |
| --- | --- | --- | --- |
| 101 | John | A | null |
| 102 | Dan | A | 101 |
| 103 | James | A | 101 |
| 104 | Amy | A | 101 |
| 105 | Anne | A | 101 |

```sql
select sum(city.population) from city
inner join country
on city.countrycode = country.code
where continent = "Asia";
```

Code

MySQL Auto

```sql
# Write your MySQL query statement below
select q1.person_name from queue q1
join queue q2
on q1.turn >= q2.turn
group by q1.turn
having sum(q2.weight)<=1000
order by sum(q2.weight) desc
limit 1;
```

Saved Ln 6, Col 23

Testcase | Test Result

```
| person_name |
| ----------- |
| John Cena   |
```

Expected

```
| person_name |
| ----------- |
| John Cena   |
```

Contribute a testcase

Code

MySQL Auto

```sql
# Write your MySQL query statement below
select product_id ,new_price as price from products
where (product_id,change_date )In(select product_id,max(change_date)
from products
where change_date <= '2019-08-16'
group by product_id
)
union select distinct product_id,10 as price
from products
```

Saved Ln 3, Col 30

Testcase | Test Result

Output

```
| product_id | price |
| ---------- | ----- |
| 2          | 50    |
| 1          | 35    |
| 3          | 10    |
```

Expected

```
| product_id | price |
| ---------- | ----- |
| 1          | 35    |
```

Code

MySQL Auto

```sql
# Write your MySQL query statement below
select e1.name as employee from employee e1 join employee e2
where e1.managerId = e2.id and e1.salary > e2.salary;


```

Saved Ln 2, Col 44

Testcase | Test Result

```
| employee |
| -------- |
| Joe      |
```

Expected

```
| Employee |
| -------- |
| Joe      |
```

Contribute a testcase

Code

MySQL Auto

```sql
# Write your MySQL query statement below

SELECT name AS Customers
FROM Customers
LEFT JOIN Orders ON Customers.id = Orders.customerId
WHERE Orders.customerId IS NULL;

```

Saved Ln 7, Col 1

Testcase | Test Result

```
| 4  | Max   |
```

Orders =

```
| id | customerId |
| -- | ---------- |
| 1  | 3          |
| 2  | 1          |
```

Output

```
| Customers |
| --------- |
| Henry     |
```

Code

MySQL Auto

```sql
# Write your MySQL query statement below
SELECT w1.id
FROM Weather w1, Weather w2
WHERE DATEDIFF(w1.recordDate, w2.recordDate) = 1 AND w1.temperature > w2.temperature;
```

Saved Ln 4, Col 86

Testcase | Test Result

| id |
| -- |
| 2 |
| 4 |

Expected

| Id |
| -- |
| 2 |
| 4 |

Code

MySQL Auto

```sql
FROM SalesPerson S
WHERE NOT EXISTS (
    SELECT 1
    FROM Orders O
    JOIN Company C
        ON O.com_id = C.com_id
    WHERE O.sales_id = S.sales_id
      AND C.name = 'RED'
);
```

Saved Ln 14, Col 1

Testcase | Test Result

| com_id | name | city |
| --- | --- | --- |
| 1 | RED | Boston |
| 2 | ORANGE | New York |
| 3 | YELLOW | Boston |
| 4 | GREEN | Austin |

Orders =

| order_id | order_date | com_id | sales_id | amount |
| --- | --- | --- | --- | --- |
| 1 | 1/1/2014 | 3 | 4 | 10000 |
| 2 | 2/1/2014 | 4 | 5 | 5000 |
| 3 | 3/1/2014 | 1 | 1 | 50000 |

```sql
with cte as (
    select num,
    lead(num,1) over() num1,
    lead(num,2) over() num2
    from logs

)

select distinct num ConsecutiveNums from cte where (num=num1) and (num=num2)
```

ved Ln 2, Col 1

Testcase | Test Result

| ConsecutiveNums |
| --- |
| 1 |

xpected

| ConsecutiveNums |
| --- |
| 1 |

Code

MySQL Auto

```sql
# Write your MySQL query statement below
# Write your MySQL query statement below
SELECT Person.firstName, Person.lastName, Address.city, Address.state
FROM Person
LEFT JOIN Address ON Person.personId=Address.personId;
```

Saved Ln 5, Col 55

Testcase | Test Result

| addressId | personId | city | state |
| --- | --- | --- | --- |
| 1 | 2 | New York City | New York |
| 2 | 3 | Leetcode | California |

Output

| firstName | lastName | city | state |
| --- | --- | --- | --- |
| Allen | Wang | null | null |
| Bob | Alice | New York City | New York |

Expected

Code

MySQL Auto

```sql
# Write your MySQL query statement below
SELECT S.score ,COUNT(S2.SCORE) as `rank` FROM SCORES S,
(SELECT DISTINCT SCORE FROM SCORES)  S2
WHERE S.SCORE<=S2.SCORE
GROUP BY S.ID
ORDER BY S.SCORE DESC;
```

Saved Ln 6, Col 23

Testcase | Test Result

Expected

```
| score | rank |
| ----- | ---- |
| 4     | 1    |
| 4     | 1    |
| 3.85  | 2    |
| 3.65  | 3    |
| 3.65  | 3    |
| 3.5   | 4    |
```

Contribute a testcase

Code

MySQL Auto

```sql
# Write your MySQL query statement below
DELETE p FROM Person p
JOIN Person p2
ON p.Email = p2.Email AND p.Id > p2.Id;

```

Saved Ln 5, Col 1

Testcase | Test Result

```
| -- | ---------------- |
| 1  | john@example.com |
| 2  | bob@example.com  |
```

Expected

```
| id | email            |
| -- | ---------------- |
| 1  | john@example.com |
| 2  | bob@example.com  |
```

Contribute a testcase

Code

MySQL Auto

```sql
# Write your MySQL query statement below
select q1.person_name from queue q1
join queue q2
on q1.turn >= q2.turn
group by q1.turn
having sum(q2.weight)<=1000
order by sum(q2.weight) desc
limit 1;
```

Saved Ln 1, Col 1

Testcase | Test Result

Output

```
| person_name |
| ----------- |
| John Cena   |
```

Expected

```
| person_name |
| ----------- |
| John Cena   |
```

Code

MySQL Auto

```sql
select
(select distinct Salary
from Employee order by salary desc
limit 1 offset 1)
as SecondHighestSalary;
```

Saved Ln 5, Col 24

Testcase | Test Result

Output

```
| SecondHighestSalary |
| ------------------- |
| 200                 |
```

Expected

```
| SecondHighestSalary |
| ------------------- |
| 200                 |
```