

ASSIGNMENT 1:

DATABASE spj

```
mysql> CREATE TABLE P
-> ('P#' CHAR(6) NOT NULL,
-> Pname CHAR(20),
-> color
-> CHAR(6),
-> weight SMALLINT,
-> city CHAR(15));
Query OK, 0 rows affected (0.04 sec)
```

```
mysql> CREATE TABLE J
-> ('J#' CHAR(4) NOT NULL,
-> Jname CHAR(10),
-> City CHAR(15));
Query OK, 0 rows affected (0.04 sec)
```

```
mysql> CREATE TABLE sp
-> ('S#' CHAR(4) NOT NULL,
-> 'P#' CHAR(4) NOT NULL,
-> 'J#' CHAR(4) NOT NULL,
-> QTY INT);
Query OK, 0 rows affected (0.04 sec)
```

```
mysql> CREATE TABLE S
-> ('S#' CHAR(5) NOT NULL,
-> Sname CHAR(20),
-> status SMALLINT,
-> city CHAR(15));
Query OK, 0 rows affected (0.03 sec)
```

```
mysql> show tables;
+-----+
| Tables_in_spj |
+-----+
| j              |
| p              |
| s              |
| sp             |
+-----+
4 rows in set (0.00 sec)
```

*Table j

```
mysql> INSERT INTO J (J#, Jname, City) VALUES ('J1', 'Sorter', 'Paris');
Query OK, 1 row affected (0.02 sec)

mysql> INSERT INTO J (J#, Jname, City) VALUES ('J2', 'Punch', 'Rome');
Query OK, 1 row affected (0.00 sec)

mysql> INSERT INTO J (J#, Jname, City) VALUES ('J3', 'Reader', 'Athens');
Query OK, 1 row affected (0.00 sec)

mysql> INSERT INTO J (J#, Jname, City) VALUES ('J4', 'Console', 'Athens');
Query OK, 1 row affected (0.00 sec)

mysql> INSERT INTO J (J#, Jname, City) VALUES ('J5', 'Collator', 'London');
Query OK, 1 row affected (0.00 sec)

mysql> INSERT INTO J (J#, Jname, City) VALUES ('J6', 'Terminal', 'Oslo');
Query OK, 1 row affected (0.00 sec)

mysql> INSERT INTO J (J#, Jname, City) VALUES ('J7', 'Tape', 'London');
Query OK, 1 row affected (0.01 sec)
```

```
mysql> select * from J;
+----+-----+-----+
| J# | Jname   | City   |
+----+-----+-----+
| J1 | Sorter  | Paris  |
| J2 | Punch   | Rome   |
| J3 | Reader  | Athens |
| J4 | Console | Athens |
| J5 | Collator | London |
| J6 | Terminal | Oslo   |
| J7 | Tape    | London |
+----+-----+-----+
7 rows in set (0.00 sec)
```

*TABLE p

```
mysql> INSERT INTO P (`P#`, Pname, Color, Weight, City) VALUES ('P1', 'Nut', 'Red', 12, 'London');
Query OK, 1 row affected (0.01 sec)

mysql> INSERT INTO P (`P#`, Pname, Color, Weight, City) VALUES ('P2', 'Bolt', 'Green', 17, 'Paris');
Query OK, 1 row affected (0.01 sec)

mysql> INSERT INTO P (`P#`, Pname, Color, Weight, City) VALUES ('P3', 'Screw', 'Blue', 17, 'Rome');
Query OK, 1 row affected (0.00 sec)

mysql> INSERT INTO P (`P#`, Pname, Color, Weight, City) VALUES ('P4', 'Screw', 'Red', 14, 'London');
Query OK, 1 row affected (0.00 sec)

mysql> INSERT INTO P (`P#`, Pname, Color, Weight, City) VALUES ('P5', 'Cam', 'Blue', 12, 'Paris');
Query OK, 1 row affected (0.00 sec)

mysql> INSERT INTO P (`P#`, Pname, Color, Weight, City) VALUES ('P6', 'Cog', 'Red', 19, 'London');
Query OK, 1 row affected (0.02 sec)
```

```
mysql> select * from p;
+----+-----+-----+-----+-----+
| P# | Pname | color | weight | city |
+----+-----+-----+-----+-----+
| P1 | Nut   | Red   | 12     | London |
| P2 | Bolt  | Green | 17     | Paris  |
| P3 | Screw | Blue  | 17     | Rome   |
| P4 | Screw | Red   | 14     | London |
| P5 | Cam   | Blue  | 12     | Paris  |
| P6 | Cog   | Red   | 19     | London |
+----+-----+-----+-----+-----+
6 rows in set (0.00 sec)
```

*TABLE s

```
mysql> INSERT INTO S (`S#`, Sname, status, city) VALUES ('S1', 'Smith', 20, 'London');
Query OK, 1 row affected (0.02 sec)

mysql> INSERT INTO S (`S#`, Sname, status, city) VALUES ('S2', 'Jones', 10, 'Paris');
Query OK, 1 row affected (0.01 sec)

mysql> INSERT INTO S (`S#`, Sname, status, city) VALUES ('S3', 'Blake', 30, 'Paris');
Query OK, 1 row affected (0.02 sec)

mysql> INSERT INTO S (`S#`, Sname, status, city) VALUES ('S4', 'Clark', 20, 'London');
Query OK, 1 row affected (0.00 sec)

mysql> INSERT INTO S (`S#`, Sname, status, city) VALUES ('S5', 'Adams', 30, 'Athens');
Query OK, 1 row affected (0.02 sec)
```

```
mysql> select * from s;
+----+-----+-----+-----+
| S# | Sname | status | city |
+----+-----+-----+-----+
| S1 | Smith | 20     | London |
| S2 | Jones | 10     | Paris  |
| S3 | Blake | 30     | Paris  |
| S4 | Clark | 20     | London |
| S5 | Adams | 30     | Athens |
+----+-----+-----+-----+
5 rows in set (0.00 sec)
```

*TABLE sp

```
mysql> INSERT INTO SP (`S#`, `P#`, `J#`,
-> VALUES
-> ('S1', 'P1', 'J1', 200),
-> ('S1', 'P1', 'J4', 700),
-> ('S2', 'P3', 'J1', 400),
-> ('S2', 'P3', 'J2', 200),
-> ('S2', 'P3', 'J3', 200),
-> ('S2', 'P3', 'J4', 500),
-> ('S2', 'P3', 'J5', 600),
-> ('S2', 'P3', 'J6', 400),
-> ('S2', 'P3', 'J7', 800),
-> ('S2', 'P5', 'J2', 100),
-> ('S3', 'P3', 'J1', 200),
-> ('S3', 'P4', 'J2', 500),
-> ('S4', 'P6', 'J3', 300),
-> ('S4', 'P6', 'J7', 300),
-> ('S5', 'P2', 'J2', 200),
-> ('S5', 'P2', 'J4', 100),
-> ('S5', 'P5', 'J5', 500),
-> ('S5', 'P5', 'J7', 100),
-> ('S5', 'P6', 'J2', 200),
-> ('S5', 'P1', 'J4', 100),
-> ('S5', 'P3', 'J4', 200),
-> ('S5', 'P4', 'J4', 800),
-> ('S5', 'P5', 'J4', 400),
-> ('S5', 'P6', 'J4', 500);
Query OK, 24 rows affected (0.02 sec)
Records: 24  Duplicates: 0  Warnings: 0
```

```
mysql> select * from sp;
+----+-----+-----+-----+
| S# | P# | J# | QTY |
+----+-----+-----+-----+
| S1 | P1 | J1 | 200 |
| S1 | P1 | J4 | 700 |
| S2 | P3 | J1 | 400 |
| S2 | P3 | J2 | 200 |
| S2 | P3 | J3 | 200 |
| S2 | P3 | J4 | 500 |
| S2 | P3 | J5 | 600 |
| S2 | P3 | J6 | 400 |
| S2 | P3 | J7 | 800 |
| S2 | P5 | J2 | 100 |
| S3 | P3 | J1 | 200 |
| S3 | P4 | J2 | 500 |
| S4 | P6 | J3 | 300 |
| S4 | P6 | J7 | 300 |
| S5 | P2 | J2 | 200 |
| S5 | P2 | J4 | 100 |
| S5 | P5 | J5 | 500 |
| S5 | P5 | J7 | 100 |
| S5 | P6 | J2 | 200 |
| S5 | P1 | J4 | 100 |
| S5 | P3 | J4 | 200 |
| S5 | P4 | J4 | 800 |
| S5 | P5 | J4 | 400 |
| S5 | P6 | J4 | 500 |
+----+-----+-----+-----+
24 rows in set (0.00 sec)
```