

1. Write a query that lists each order number followed by the name of the customer who made the order.

```
D6_99024_tejas>select c.cname , o.onum from customers c inner join orders o
-> ON c.cnum = o.cnum;
```

cname	onum
Cisneros	3001
Hoffman	3003
Pereira	3002
Liu	3005
Cisneros	3006
Giovanni	3009
Grass	3007
Clemens	3008
Grass	3010
Clemens	3011

2. Write a query that gives the names of both the salesperson and the customer for each order along with the order number.

```
D6_99024_tejas>select o.onum ,s.sname ,c.cname
-> from salespeople s inner join customers c
-> ON s.snum = c.snum
-> inner join orders o
-> ON s.snum = c.snum;
```

onum	sname	cname
3001	Motika	Pereira
3001	Rifkin	Cisneros
3001	Peel	Clemens
3001	Serres	Grass
3001	Serres	Liu

2. Write a query that produces all customers serviced by salespeople with a commission above 12%. Display the customer's name, the salesperson's name, and the salesperson's rate of commission.

```
D6_99024_tejas>select c.cname,s.sname ,s.comm
-> from salespeople s inner join customers c
-> ON s.snum = c.snum
-> where s.comm > 0.12;
```

cname	sname	comm
Liu	Serres	0.13
Grass	Serres	0.13
Cisneros	Rifkin	0.15

3. Write a query that calculates the commission earned by each salesperson for orders placed by customers with a rating above 100.

```
D6_99024_tejas>select s.sname ,s.snum , round(s.comm * o.amt,2) as commision
-> from salespeople s inner join customers c
-> ON s.snum = c.snum
-> inner join orders o
-> ON s.snum=o.snum;
```

sname	snum	commision
Rifkin	1007	2.80
Peel	1001	92.06
Peel	1001	92.06
Motika	1004	209.01
Serres	1002	670.86
Serres	1002	670.86
Rifkin	1007	164.72
Axelrod	1003	171.32
Serres	1002	9.85
Serres	1002	9.85
Peel	1001	566.76
Peel	1001	566.76

4. Write a query that calculates the commission earned by each salesperson for orders placed by customers with a rating above 100.

```
D6_99024_tejas>select distinct o.onum ,s.comm , round(s.comm * o.amt) as commision
-> from salespeople s inner join customers c
-> ON s.snum = c.snum
-> inner join orders o
-> ON s.snum = o.snum
-> where c.rating >100;
```

onum	comm	commision
3001	0.15	3
3005	0.13	671
3006	0.15	165
3009	0.10	171
3007	0.13	10
3010	0.13	40

5. Write a query that produces all pairs of salespeople who are living in the same city. Exclude combinations of salespeople with themselves as well as duplicate rows with the order reversed.

```
D6_99024_tejas>SELECT s1.sname, s2.sname, s1.city
-> FROM salespeople s1
-> JOIN salespeople s2
-> ON s1.city = s2.city
-> AND s1.snum < s2.snum;
+-----+-----+-----+
| sname | sname | city  |
+-----+-----+-----+
| Peel  | Motika | London |
+-----+-----+-----+
```

1. Display the Supplier name and the Quantity sold.

```
D6_99024_tejas>select s.sname ,SUM(sp.QTY) as qty_sold
-> from sp inner join s
-> ON s.`S#`=sp.`S#`
-> group by s.sname,sp.`s#`;
+-----+-----+
| sname | qty_sold |
+-----+-----+
| Smith | 900      |
| Jones | 3200     |
| Blake | 700      |
| Clark | 600      |
| Adams | 3100     |
+-----+-----+
```

2. Display the Part name and Quantity sold.

```
D6_99024_tejas>select p.pname,sum(sp.QTY)
-> from p inner join sp
-> ON p.`p#` = sp.`p#`
-> group by p.pname;
+-----+-----+-----+
| pname | sum(sp.QTY) |
+-----+-----+-----+
| Nut   | 1000         |
| Screw | 4800         |
| Cam   | 1100         |
| Cog   | 1300         |
| Bolt  | 300          |
+-----+-----+-----+
```

3. Display the Job name and Quantity sold.

```
D6_99024_tejas>select j.jname,sum(sp.QTY)
-> from j inner join sp
-> ON j.`j#` = sp.`j#`
-> group by j.jname;
+-----+-----+-----+
| jname | sum(sp.QTY) |
+-----+-----+-----+
| Sorter | 800          |
| Console | 3300         |
| Punch  | 1200         |
| Reader | 500          |
| Collator | 1100         |
| Terminal | 400          |
| Tape   | 1200         |
+-----+-----+-----+
```

4. Display the Supplier name, Part name, Job name and Quantity sold.

```
D6_99024_tejas>select s.sname,p.pname,j.jname,sum(sp.QTY)
-> from sp inner join j
-> ON sp.`j#` = j.`j#`
-> inner join p
-> ON sp.`p#` = p.`p#`
-> inner join s
-> ON sp.`s#` = s.`s#`
-> group by s.sname,p.pname,j.jname;
```

sname	pname	jname	sum(sp.QTY)
Jones	Screw	Sorter	400
Blake	Screw	Sorter	200
Smith	Nut	Sorter	200
Adams	Cog	Punch	200
Jones	Cam	Punch	100
Blake	Screw	Punch	500
Jones	Screw	Punch	200
Adams	Bolt	Punch	200
Clark	Cog	Reader	300

5. Display the Supplier name, Supplying Parts to a Job in the same City.

```
D6_99024_tejas>select s.sname
-> from sp inner join s
-> on sp.`s#` = s.`s#`
-> inner join p
-> on sp.`p#` = p.`p#`
-> group by s.sname;
```

sname
Adams
Smith
Blake
Jones
Clark

6. Display the Part name that is 'Red' in color, and the Total Quantity sold for that part.

```
D6_99024_tejas>select Pname, sum(sp.QTY)
-> from sp inner join p
-> ON sp.`p#` = p.`p#`
-> where color = 'Red'
-> group by pname;
```

Pname	sum(sp.QTY)
Nut	1000
Screw	1300
Cog	1300

7. Display all the Quantity sold by Suppliers with the Status = 20.

```
D6_99024_tejas>select sname , sum(sp.QTY)
-> from s inner join sp
-> on s.`s#` = sp.`s#`
-> where status= 20
-> group by sname;
+-----+-----+
| sname | sum(sp.QTY) |
+-----+-----+
| Smith |          900 |
| Clark |          600 |
+-----+-----+
```

8. Display all the Parts and their Total Quantity for the parts with the Weight > 14.

```
D6_99024_tejas>select pname ,sum(sp.QTY)
-> from sp inner join p
-> on sp.`p#` = p.`p#`
-> where weight >14
-> group by pname;
+-----+-----+
| pname | sum(sp.QTY) |
+-----+-----+
| Screw |          3500 |
| Cog   |          1300 |
| Bolt  |           300 |
+-----+-----+
```

9. Display all the Job names and City, which has bought more than 500 Parts.

```
D6_99024_tejas>select jname ,city ,sum(sp.QTY)
-> from sp inner join j
-> on sp.`j#`=j.`j#`
-> group by jname,city
-> having sum(sp.QTY)>500;
+-----+-----+-----+
| jname | city | sum(sp.QTY) |
+-----+-----+-----+
| Sorter | Paris |          800 |
| Console | Athens |         3300 |
| Punch | Rome |         1200 |
| Collator | London |         1100 |
| Tape | London |         1200 |
+-----+-----+-----+
```

10. Display all the Part names and Quantity sold that have a Weight less than 15.

```
D6_99024_tejas>select pname , sum(sp.QTY)
-> from sp inner join p
-> on sp.`p#`=p.`p#`
-> where p.weight<15
-> group by pname;
+-----+-----+
| pname | sum(sp.QTY) |
+-----+-----+
| Nut |          1000 |
| Cam |          1100 |
| Screw |          1300 |
+-----+-----+
```

11. Display all the Suppliers with the same Status as the supplier, 'CLARK'.

```
D6_99024_tejas>select s1.sname , s2.status
-> from s s1 join s s2
-> on s1.status = s2.status
-> where s2.sname = 'clark'
-> AND s1.sname <> 'clark'
-> ;
```

sname	status
Smith	20

12. Display all the Parts which have more Weight than any "Red" parts.

```
D6_99024_tejas>select distinct p1.pname , p1.weight,p1.color
-> from p p1 join p p2
-> on p1.weight > p2.weight
-> where p2.color = 'red' ;
```

pname	weight	color
Bolt	17	Green
Screw	17	Blue
Screw	14	Red
Cog	19	Red

13. Display all the Jobs going on in the same city as the job 'TAPE'.

```
D6_99024_tejas>select j1.jname , j1.city
-> from j j1 join j j2
-> on j1.city = j2.city
-> where j2.jname='Tape'
-> and j1.jname != 'Tape';
```

jname	city
Collator	London

14. Display all the Parts with Weight less than any of the "Green" parts.

```
D6_99024_tejas>select p1.pname,p1.weight
-> from p p1 join p p2
-> on p1.weight < p2.weight
-> where p2.color='green';
```

pname	weight
Nut	12
Screw	14
Cam	12

15. Display the name of the Supplier who has sold the maximum Quantity (in one sale).

```
D6_99024_tejas>select sname,max(sp.QTY)
-> from sp inner join s
-> on sp.`s#`=s.`s#`
-> group by sname
-> order by max(sp.qty)desc
-> limit 1 ;
```

sname	max(sp.QTY)
Adams	800

16. Display the name of the Supplier who has sold the maximum overall Quantity (sum of Sales).

```
D6_99024_tejas>select sname,sum(sp.QTY)
-> from sp inner join s
-> on sp.`s#`=s.`s#`
-> group by sname
-> order by sum(sp.qty)desc
-> limit 1 ;
```

sname	sum(sp.QTY)
Jones	3200