

MC-AWS-HYBRID TABLES ASSIGNMENT PDF

--Q1

--Create a new Database with any name of your choice .Create a new schema in the database you just created

```
CREATE OR REPLACE DATABASE NEW_UNISTORE ;
```

```
CREATE OR REPLACE SCHEMA NEW_HR;
```

--Q2

--Get the table structure of the CUSTOMER and ORDERS table from Snowflake
SNOWFLAKE_SAMPLE_DATA.TPCH_SF1 schema
--by using DESCRIBE TABLE <TableName>

```
DESCRIBE TABLE SNOWFLAKE_SAMPLE_DATA.TPCH_SF1.CUSTOMER;
```

```
DESCRIBE TABLE SNOWFLAKE_SAMPLE_DATA.TPCH_SF1.ORDERS;
```

--Q3

--Create the CUSTOMER table as a HYBRID table and set the column C_CUSTKEY as the PK,C_PHONE as the Unique Key

```
CREATE OR REPLACE HYBRID TABLE CUSTOMER (  
    C_CUSTKEY    NUMBER(38,0)  PRIMARY KEY,  
    C_NAME       VARCHAR(25),  
    C_ADDRESS    VARCHAR(40),  
    C_NATIONKEY   NUMBER(38,0),  
    C_PHONE      VARCHAR(15)   UNIQUE,  
    C_ACCTBAL     NUMBER(12,2),  
    C_MKTSEGMENT  VARCHAR(10),  
    C_COMMENT     VARCHAR(117)  
);
```

--Q4

--Create the ORDERS table as a HYBRID table and set the column O_ORDERKEY as the PK and the O_CUST_KEY as FK to the CUSTOMERS table C_CUSTKEY.

--When creating ORDERS Create an Index on O_ORDERDATE

```
CREATE OR REPLACE HYBRID TABLE ORDERS (  
    O_ORDERKEY      NUMBER(38,0) PRIMARY KEY,  
    O_CUSTKEY       NUMBER(38,0) FOREIGN KEY REFERENCES  
CUSTOMER(C_CUSTKEY),  
    O_ORDERSTATUS   VARCHAR(1),  
    O_TOTALPRICE    NUMBER(12,2),  
    O_ORDERDATE     DATE,  
    O_ORDERPRIORITY VARCHAR(15),  
    O_CLERK         VARCHAR(15),  
    O_SHIPPRIORITY  NUMBER(38,0),  
    O_COMMENT       VARCHAR(79),  
    INDEX INDEX_ORDER_DATE(O_ORDERDATE)  
);
```

--Q5

--Insert 5 rows in the CUSTOMERS table and ensure that the PK and Unique Key is not violated

INSERT INTO CUSTOMER VALUES

(135936,'Customer#000135936','qcfTTfM2uTlaf',11,'21-482-295-1589',4777.54,'HOUSEHOLD',
fully above the slyly even decoys. fluffily bold packages impress. final accounts sleep. furiously
un');

INSERT INTO CUSTOMER VALUES

(135937,'Customer#000135937','g6gmDfzotGlaaqMceZzcN7ZDVvgIhtnN04IDqAF',21,'31-176-8
82-3362',5069.65,'BUILDING','lyly regular deposits. regular, even frets requests along t');

INSERT INTO CUSTOMER VALUES(

135938,'Customer#000135938','VnWcN3
2XwOc55SNi',19,'29-653-849-5482',8675.25,'HOUSEHOLD','en accounts sleep furiously. ironic
requests haggle');

INSERT INTO CUSTOMER VALUES

(135939,'Customer#000135939','6S0TgG
0FAaytXVKAP',4,'14-524-594-3734',9024.47,'MACHINERY','beans are above the final
instructions. ideas about the slyly ironic deposits affix furious');

INSERT INTO CUSTOMER VALUES

(135940,'Customer#000135940','AU5DoNiiA8ujZBS5qFOrw9z5sxAghQ',17,'27-874-905-1997',4315.85,'BUILDING','deposits. quickly around');

INSERT INTO CUSTOMER VALUES

(135941,'Customer#000135941','53jrg9M9CLWi7RU2PSQM',14,'24-716-197-8674',555.78,'HOUSEHOLD','kages boost slyly busy packages boost');

--Q6

--Insert 5 rows in the ORDERS table and ensure that the PK and FK are not violated

INSERT INTO ORDERS

VALUES(2400001,135936,'P',80291.26,'1995-04-03','3-MEDIUM','Clerk#000000085',1,'en accounts sleep furiously. ironic requests haggle');

INSERT INTO ORDERS

VALUES(2400002,135937,'F',119166.38,'1994-08-25','2-HIGH','Clerk#000000698',2,'en instructions sleep furiously. ironic requests haggle');

INSERT INTO ORDERS

VALUES(2400003,135938,'O',271227.3,'1996-07-09','1-URGENT','Clerk#000000557',3,'en accounts beans furiously. ironic requests haggle');

INSERT INTO ORDERS

VALUES(2400004,135940,'O',150853.32,'1996-09-30','1-URGENT','Clerk#000000938',4,'en quickly sleep furiously. ironic requests haggle');

INSERT INTO ORDERS

VALUES(2400005,135941,'F',96488.6,'1994-05-03','2-HIGH','Clerk#000000844',5,'en around ironic furiously. ironic requests haggle');

--Q7

--Attempt to re-insert a duplicate C_CUSTKEY in the CUSTOMER TABLE and check if the the Hybrid table allows insert.

INSERT INTO CUSTOMER VALUES

(135936,'Customer#000135936','qcfTTfM2uTlaf',11,'21-482-295-1589',4777.54,'HOUSEHOLD','fully above the slyly even decoys. fluffily bold packages impress. final accounts sleep. furiously un');

--Q8

--Attempt to insert a row in ORDERS table with a CUSTKEY that is not in CUSTOMER and see if the FK error is encountered.

INSERT INTO ORDERS

VALUES(3400006,135949,'F',96488.6,'1994-05-03','2-HIGH','Clerk#000000844',5,'en around ironic furiously. ironic requests haggle');

--Q9

--Select data from the Information_schema view that provides constraint information about referential integrity and once the constraint is located please drop the constraint

```
SELECT * FROM INFORMATION_SCHEMA.REFERENTIAL_CONSTRAINTS;
```

```
ALTER TABLE ORDERS DROP CONSTRAINT  
"SYS_CONSTRAINT_5d5f33fa-d988-400a-9ccf-b977126139e5"
```

--Q10

--Once the referential integrity constraint is dropped, select data from INFORMATION_SCHEMA.REFERENTIAL_CONSTRAINTS and verify that the constraint has been dropped, Re-insert row into orders table

--with a CUST_KEY which is not in the CUSTOMER table

```
INSERT INTO ORDERS  
VALUES(3400006,135949,'F',96488.6,'1994-05-03','2-HIGH','Clerk#000000844',5,'en around  
ironic furiously. ironic requests haggle');
```