

CS163: Deep Learning for Computer Vision


Lecture 7: Convolutional Networks

Announcement: Assignment

- Assignment 1 was due two days ago
 - Remember you have three late days to use
 - Once late days are exhausted, 25% penalty per day
- Assignment 2 is out (two weeks to go):
<https://github.com/UCLAdEEPvision/CS163-Assignments-2024Fall/tree/main/Assignment2>
- Build and train a CNN from scratch
 - Build ResNet-18 and finetuning
 - Visualize the attention of ResNet using Class Activation Mapping
 - Leaderboard for miniPlaces
 - **Suggestion: develop and test your code using Colab CPU instance or local machine, after everything works then switch to GPU instance**

Last Time: Backpropagation


Represent complex expressions as **computational graphs**



Forward pass computes outputs


Backward pass computes gradients

During the backward pass, each node in the graph receives **upstream gradients** and multiplies them by **local gradients** to compute **downstream gradients**




Problem: So far our classifiers don't consider the spatial structure of images!

$$f = W_2 \max(0, W_1 x)$$




$$f(x, W) = Wx + b$$




Problem: So far our classifiers don't consider the spatial structure of images!

Solution: Define new spatial operations tailored to an image

$$f = W_2 \max(0, W_1 x)$$




$$f(x, W) = Wx + b$$




Components of a Fully-Connected Network

Fully-Connected Layers




Activation Function




Components of a Convolutional Network


Fully-Connected Layers




Activation Function



Convolution Layers



Pooling Layers




Normalization


$$\hat{x}_{i,j} = \frac{x_{i,j} - \mu_j}{\sqrt{\sigma_j^2 + \varepsilon}}$$

Components of a Convolutional Network


Fully-Connected Layers




Activation Function



Convolution Layers



Pooling Layers




Normalization

$$\hat{x}_{i,j} = \frac{x_{i,j} - \mu_j}{\sqrt{\sigma_j^2 + \varepsilon}}$$


Fully-Connected Layer

32x32x3 image is vectorized to 3072 x 1




Fully-Connected Layer

32x32x3 image is vectorized to 3072 x 1




Convolution Layer

3x32x32 image contains spatial structure



Convolution Layer

3x32x32 image




3x5x5 filter



Convolve the filter with the image
i.e. “slide over the image spatially,
computing dot products”

Convolution Layer

3x32x32 image



Filters always extend the full depth of the input volume


3x5x5 filter



Convolve the filter with the image
i.e. “slide over the image spatially,
computing dot products”

Convolution Layer

3x32x32 image




1 number:

the result of taking a dot product between the filter and a small 3x5x5 chunk of the image
(i.e. $3 \times 5 \times 5 = 75$ -dimensional dot product + bias)

$$w^T x + b$$

Convolution Layer

3x32x32 image



3x5x5 filter


32

32

3

convolve (slide) over
all spatial locations

1x28x28
activation map



28

28

1

Convoluting over all the spatial location



an image of the Where's Waldo game

a template (filter)




Convoluting over all the spatial location



an image of the Where's Waldo game

a template (filter)



activation map

Convolution as Cross-Correlation Operation

0	1	2
3	4	5
6	7	8

 *

0	1
2	3

 =

19	25
37	43

$$0 \times 0 + 1 \times 1 + 3 \times 2 + 4 \times 3 = 19,$$

$$1 \times 0 + 2 \times 1 + 4 \times 2 + 5 \times 3 = 25,$$

$$3 \times 0 + 4 \times 1 + 6 \times 2 + 7 \times 3 = 37,$$


$$4 \times 0 + 5 \times 1 + 7 \times 2 + 8 \times 3 = 43.$$

```
def corr2d(X, K):  #@save
    """Compute 2D cross-correlation."""
    h, w = K.shape
    Y = torch.zeros((X.shape[0] - h + 1, X.shape[1] - w + 1))
    for i in range(Y.shape[0]):
        for j in range(Y.shape[1]):
            Y[i, j] = (X[i:i + h, j:j + w] * K).sum()
    return Y
```


basic implementation

Convolution Layer

3x32x32 image



3x5x5 filter




Consider repeating with
a second (green) filter:




convolve (slide) over
all spatial locations

two 1x28x28
activation map




Convolution Layer

3x32x32 image




Consider 6 filters,
each 3x5x5

6x3x5x5
filters



Convolution
Layer


6 activation maps,
each 1x28x28




Stack activations to get a
6x28x28 output image!

Convolution Layer


3x32x32 image




Also 6-dim bias vector:



6x3x5x5
filters




6 activation maps,
each 1x28x28




Stack activations to get a
6x28x28 output image!

Convolution Layer


3x32x32 image




Also 6-dim bias vector:



6x3x5x5
filters



28x28 grid, at each
point a 6-dim vector




Stack activations to get a
6x28x28 output image!

Convolution Layer

2x3x32x32

Batch of images




Also 6-dim bias vector:




Convolution
Layer

6x3x5x5
filters




2x6x28x28
Batch of outputs



Convolution Layer

$N \times C_{in} \times H \times W$
Batch of images




Also C_{out} -dim bias vector:




Convolution
Layer


$C_{out} \times C_{in} \times K_w \times K_h$
filters



$N \times C_{out} \times H' \times W'$
Batch of outputs




Stacking Convolutions



Stacking Convolutions


Q: What happens if we stack two convolution layers?




Stacking Convolutions

Q: What happens if we stack two convolution layers? (Recall $y=W_2W_1x$ is a linear classifier)


A: We get another convolution!



What do convolutional filters learn?



What do convolutional filters learn?




Input:

$N \times 3 \times 32 \times 32$


First hidden layer:

$N \times 6 \times 28 \times 28$

Linear classifier: One template per class



What do convolutional filters learn?



Input:

$N \times 3 \times 32 \times 32$

First hidden layer:

$N \times 6 \times 28 \times 28$

First-layer conv filters: local image templates
(Often learns oriented edges, opposing colors)




6 filters, each $3 \times 5 \times 5$



AlexNet: 64 filters,
each $3 \times 11 \times 11$

A closer look at spatial dimensions




Input:

$N \times 3 \times 32 \times 32$

First hidden layer:

$N \times 6 \times 28 \times 28$

A closer look at spatial dimensions




7

7

Input: 7x7

Filter: 3x3

A closer look at spatial dimensions




7

7

Input: 7x7

Filter: 3x3

A closer look at spatial dimensions




7

7

Input: 7x7

Filter: 3x3

A closer look at spatial dimensions




7

7

Input: 7x7

Filter: 3x3

A closer look at spatial dimensions



7


7

Input: 7x7

Filter: 3x3

Output: 5x5

A closer look at spatial dimensions



Input: 7x7

Filter: 3x3

Output: 5x5

In general:

Input: W

Filter: K

Output: $W - K + 1$

Problem: Feature maps “shrink” with each layer!

A closer look at spatial dimensions

0	0	0	0	0	0	0	0	0
0								0
0								0
0								0
0								0
0								0
0								0
0								0
0	0	0	0	0	0	0	0	0

Input: 7x7

Filter: 3x3

Output: 5x5

In general: Problem: Feature
Input: W maps “shrink”
Filter: K with each layer!

Output: $W - K + 1$

Solution: **padding**
Add zeros around the input

A closer look at spatial dimensions

0	0	0	0	0	0	0	0	0
0								0
0								0
0								0
0								0
0								0
0								0
0								0
0	0	0	0	0	0	0	0	0

Input: 7x7

Filter: 3x3

Output: 5x5

In general:

Input: W

Filter: K

Padding: P


Output: $W - K + 1 + 2P$

Very common:

Set $P = (K - 1) / 2$ to
make output have
same size as input!


Receptive Fields

For convolution with kernel size K , each element in the output depends on a $K \times K$ **receptive field** in the input



Receptive Fields


Each successive convolution adds $K - 1$ to the receptive field size
With L layers the receptive field size is $1 + L * (K - 1)$



Be careful – “receptive field in the input” vs “receptive field in the previous layer”
Hopefully clear from context!

Receptive Fields

Each successive convolution adds $K - 1$ to the receptive field size
With L layers the receptive field size is $1 + L * (K - 1)$




Input

Problem: For large images we need many layers for each output to “see” the whole image

Output

Receptive Fields

Each successive convolution adds $K - 1$ to the receptive field size
With L layers the receptive field size is $1 + L * (K - 1)$




Input

Problem: For large images we need many layers for each output to “see” the whole image

Solution: Downsample inside the network

Output

Strided Convolution




Input: 7x7

Filter: 3x3

Stride: 2

Strided Convolution



Input: 7x7

Filter: 3x3

Stride: 2

Strided Convolution


Input: 7x7

Filter: 3x3

Stride: 2

Output: 3x3

Strided Convolution



Input: 7x7

Filter: 3x3

Stride: 2

Output: 3x3

In general:

Input: W

Filter: K

Padding: P


Stride: S

Output: $(W - K + 2P) / S + 1$

Convolution Example

Input volume: 3 x 32 x 32
10 5x5 filters with stride 1, pad 2

Output volume size: ?



Convolution Example


Input volume: 3 x 32 x 32

10 5x5 filters with stride 1, pad 2

Output volume size:

$(32 + 2 * 2 - 5) / 1 + 1 = 32$ spatially, so

10 x 32 x 32




Convolution Example

Input volume: $3 \times 32 \times 32$

10 5×5 filters with stride 1, pad 2

Output volume size: $10 \times 32 \times 32$

Number of learnable parameters: ?



Convolution Example

Input volume: **3** x 32 x 32


10 **5x5** filters with stride 1, pad 2

Output volume size: 10 x 32 x 32

Number of learnable parameters: **760**

Parameters per filter: **3*****5*****5** + 1 (for bias) = **76**


10 filters, so total is **10** * **76** = **760**



Convolution Example


Input volume: $3 \times 32 \times 32$
10 5×5 filters with stride 1, pad 2

Output volume size: $10 \times 32 \times 32$
Number of learnable parameters: 760
Number of multiply-add operations: ?



Convolution Example

Input volume: **3** x 32 x 32
10 **5x5** filters with stride 1, pad 2




Output volume size: **10 x 32 x 32**

Number of learnable parameters: 760


Number of multiply-add operations: **768,000**

10*32*32 = 10,240 outputs; each output is the inner product of two **3x5x5** tensors (75 elems); total = $75 * 10240 = 768K$

Example: 1x1 Convolution




Example: 1x1 Convolution



Lin et al, "Network in Network", ICLR 2014

Example: 1x1 Convolution

Works like a dimensionality reduction



Lin et al, "Network in Network", ICLR 2014

Convolution Summary

Input: $C_{in} \times H \times W$

Hyperparameters:

- **Kernel size:** $K_H \times K_W$
- **Number filters:** C_{out}
- **Padding:** P
- **Stride:** S

Weight matrix: $C_{out} \times C_{in} \times K_H \times K_W$

giving C_{out} filters of size $C_{in} \times K_H \times K_W$

Bias vector: C_{out}

Output size: $C_{out} \times H' \times W'$ where:

- $H' = (H - K + 2P) / S + 1$
- $W' = (W - K + 2P) / S + 1$

Convolution Summary

Input: $C_{in} \times H \times W$

Hyperparameters:

- **Kernel size:** $K_H \times K_W$
- **Number filters:** C_{out}
- **Padding:** P
- **Stride:** S

Weight matrix: $C_{out} \times C_{in} \times K_H \times K_W$
giving C_{out} filters of size $C_{in} \times K_H \times K_W$

Bias vector: C_{out}

Output size: $C_{out} \times H' \times W'$ where:

- $H' = (H - K + 2P) / S + 1$
- $W' = (W - K + 2P) / S + 1$

Common settings:

$K_H = K_W$ (Small square filters)

$P = (K - 1) / 2$ ("Same" padding)

$C_{in}, C_{out} = 32, 64, 128, 256$ (powers of 2)

$K = 3, P = 1, S = 1$ (3x3 conv)


$K = 5, P = 2, S = 1$ (5x5 conv)

$K = 1, P = 0, S = 1$ (1x1 conv)

$K = 3, P = 1, S = 2$ (Downsample by 2)


Other types of convolution

So far: 2D Convolution




Other types of convolution

So far: 2D Convolution




1D Convolution




Other types of convolution

So far: 2D Convolution



3D Convolution

Input: $C_{in} \times H \times W \times D$
Weights: $C_{out} \times C_{in} \times K \times K \times K$



PyTorch Convolution Layer

Conv2d

CLASS `torch.nn.Conv2d(in_channels, out_channels, kernel_size, stride=1, padding=0, dilation=1, groups=1, bias=True, padding_mode='zeros')`

[\[SOURCE\]](#)

Applies a 2D convolution over an input signal composed of several input planes.

In the simplest case, the output value of the layer with input size (N, C_{in}, H, W) and output $(N, C_{\text{out}}, H_{\text{out}}, W_{\text{out}})$ can be precisely described as:

$$\text{out}(N_i, C_{\text{out}_j}) = \text{bias}(C_{\text{out}_j}) + \sum_{k=0}^{C_{\text{in}}-1} \text{weight}(C_{\text{out}_j}, k) \star \text{input}(N_i, k)$$

PyTorch Convolution Layers

Conv2d

CLASS `torch.nn.Conv2d(in_channels, out_channels, kernel_size, stride=1, padding=0, dilation=1, groups=1, bias=True, padding_mode='zeros')`

[\[SOURCE\]](#)

Conv1d

CLASS `torch.nn.Conv1d(in_channels, out_channels, kernel_size, stride=1, padding=0, dilation=1, groups=1, bias=True, padding_mode='zeros')`

[\[SOURCE\]](#) 

Conv3d

CLASS `torch.nn.Conv3d(in_channels, out_channels, kernel_size, stride=1, padding=0, dilation=1, groups=1, bias=True, padding_mode='zeros')`

[\[SOURCE\]](#)

PyTorch Convolution Layer


```
import torch
from torch import nn

# We define a convenience function to calculate the convolutional layer. This
# function initializes the convolutional layer weights and performs
# corresponding dimensionality elevations and reductions on the input and
# output
def comp_conv2d(conv2d, X):
    # Here (1, 1) indicates that the batch size and the number of channels
    # are both 1
    X = X.reshape((1, 1) + X.shape)
    Y = conv2d(X)
    # Exclude the first two dimensions that do not interest us: examples and
    # channels
    return Y.reshape(Y.shape[2:])


# Note that here 1 row or column is padded on either side, so a total of 2
# rows or columns are added
conv2d = nn.Conv2d(1, 1, kernel_size=3, padding=1)
X = torch.rand(size=(8, 8))
comp_conv2d(conv2d, X).shape
```


Components of a Convolutional Network


Fully-Connected Layers




Activation Function



Convolution Layers




Pooling Layers



Normalization

$$\hat{x}_{i,j} = \frac{x_{i,j} - \mu_j}{\sqrt{\sigma_j^2 + \varepsilon}}$$

Pooling Layers: Another way to downsample feature map




Hyperparameters:
Kernel Size
Stride
Pooling function

Max Pooling

Single depth slice

x ↑	1	1	2	4
	5	6	7	8
	3	2	1	0
	1	2	3	4
	y →			

64 x 224 x 224



Max pooling with 2x2
kernel size and stride 2



6	8
3	4

Introduces **invariance** to
small spatial shifts
No learnable parameters!

Pooling Summary

Input: $C \times H \times W$

Hyperparameters:

- Kernel size: K
- Stride: S
- Pooling function (max, avg)

Output: $C \times H' \times W'$ where

- $H' = (H - K) / S + 1$
- $W' = (W - K) / S + 1$

Learnable parameters: None!


Common settings:

max, $K = 2$, $S = 2$


max, $K = 3$, $S = 2$ (AlexNet)

Components of a Convolutional Network


Fully-Connected Layers




Activation Function



Convolution Layers



Pooling Layers




Normalization

$$\hat{x}_{i,j} = \frac{x_{i,j} - \mu_j}{\sqrt{\sigma_j^2 + \varepsilon}}$$

Convolutional Networks

Classic architecture: [Conv, ReLU, Pool] x N, flatten, [FC, ReLU] x N, FC


Example: LeNet-5



Lecun et al, "Gradient-based learning applied to document recognition", 1998

Example: LeNet-5


Layer	Output Size	Weight Size
Input	1 x 28 x 28	



Lecun et al, "Gradient-based learning applied to document recognition", 1998

Example: LeNet-5


Layer	Output Size	Weight Size
Input	1 x 28 x 28	
Conv ($C_{out}=20$, $K=5$, $P=2$, $S=1$)	20 x 28 x 28	20 x 1 x 5 x 5
ReLU	20 x 28 x 28	



Lecun et al, "Gradient-based learning applied to document recognition", 1998

Example: LeNet-5


Layer	Output Size	Weight Size
Input	1 x 28 x 28	
Conv ($C_{out}=20$, $K=5$, $P=2$, $S=1$)	20 x 28 x 28	20 x 1 x 5 x 5
ReLU	20 x 28 x 28	
MaxPool($K=2$, $S=2$)	20 x 14 x 14	



Lecun et al, "Gradient-based learning applied to document recognition", 1998

Example: LeNet-5


Layer	Output Size	Weight Size
Input	1 x 28 x 28	
Conv ($C_{out}=20$, $K=5$, $P=2$, $S=1$)	20 x 28 x 28	20 x 1 x 5 x 5
ReLU	20 x 28 x 28	
MaxPool($K=2$, $S=2$)	20 x 14 x 14	
Conv ($C_{out}=50$, $K=5$, $P=2$, $S=1$)	50 x 14 x 14	50 x 20 x 5 x 5
ReLU	50 x 14 x 14	



Lecun et al, "Gradient-based learning applied to document recognition", 1998

Example: LeNet-5


Layer	Output Size	Weight Size
Input	1 x 28 x 28	
Conv ($C_{\text{out}}=20$, $K=5$, $P=2$, $S=1$)	20 x 28 x 28	20 x 1 x 5 x 5
ReLU	20 x 28 x 28	
MaxPool($K=2$, $S=2$)	20 x 14 x 14	
Conv ($C_{\text{out}}=50$, $K=5$, $P=2$, $S=1$)	50 x 14 x 14	50 x 20 x 5 x 5
ReLU	50 x 14 x 14	
MaxPool($K=2$, $S=2$)	50 x 7 x 7	



Lecun et al, "Gradient-based learning applied to document recognition", 1998

Example: LeNet-5


Layer	Output Size	Weight Size
Input	1 x 28 x 28	
Conv ($C_{\text{out}}=20$, $K=5$, $P=2$, $S=1$)	20 x 28 x 28	20 x 1 x 5 x 5
ReLU	20 x 28 x 28	
MaxPool($K=2$, $S=2$)	20 x 14 x 14	
Conv ($C_{\text{out}}=50$, $K=5$, $P=2$, $S=1$)	50 x 14 x 14	50 x 20 x 5 x 5
ReLU	50 x 14 x 14	
MaxPool($K=2$, $S=2$)	50 x 7 x 7	
Flatten	2450	



Lecun et al, "Gradient-based learning applied to document recognition", 1998

Example: LeNet-5


Layer	Output Size	Weight Size
Input	1 x 28 x 28	
Conv ($C_{out}=20$, $K=5$, $P=2$, $S=1$)	20 x 28 x 28	20 x 1 x 5 x 5
ReLU	20 x 28 x 28	
MaxPool($K=2$, $S=2$)	20 x 14 x 14	
Conv ($C_{out}=50$, $K=5$, $P=2$, $S=1$)	50 x 14 x 14	50 x 20 x 5 x 5
ReLU	50 x 14 x 14	
MaxPool($K=2$, $S=2$)	50 x 7 x 7	
Flatten	2450	
Linear (2450 -> 500)	500	2450 x 500
ReLU	500	



Lecun et al, "Gradient-based learning applied to document recognition", 1998

Example: LeNet-5


Layer	Output Size	Weight Size
Input	1 x 28 x 28	
Conv ($C_{\text{out}}=20$, $K=5$, $P=2$, $S=1$)	20 x 28 x 28	20 x 1 x 5 x 5
ReLU	20 x 28 x 28	
MaxPool($K=2$, $S=2$)	20 x 14 x 14	
Conv ($C_{\text{out}}=50$, $K=5$, $P=2$, $S=1$)	50 x 14 x 14	50 x 20 x 5 x 5
ReLU	50 x 14 x 14	
MaxPool($K=2$, $S=2$)	50 x 7 x 7	
Flatten	2450	
Linear (2450 -> 500)	500	2450 x 500
ReLU	500	
Linear (500 -> 10)	10	500 x 10



Lecun et al, "Gradient-based learning applied to document recognition", 1998

Example: LeNet-5

Layer	Output Size	Weight Size
Input	1 x 28 x 28	
Conv ($C_{\text{out}}=20$, $K=5$, $P=2$, $S=1$)	20 x 28 x 28	20 x 1 x 5 x 5
ReLU	20 x 28 x 28	
MaxPool($K=2$, $S=2$)	20 x 14 x 14	
Conv ($C_{\text{out}}=50$, $K=5$, $P=2$, $S=1$)	50 x 14 x 14	50 x 20 x 5 x 5
ReLU	50 x 14 x 14	
MaxPool($K=2$, $S=2$)	50 x 7 x 7	
Flatten	2450	
Linear (2450 -> 500)	500	2450 x 500
ReLU	500	
Linear (500 -> 10)	10	500 x 10



As we go through the network:


Spatial size **decreases**
(using pooling or strided conv)

Number of channels **increases**
(total “volume” is preserved!)


Problem: Deep Networks very hard to train!

Components of a Convolutional Network


Fully-Connected Layers




Activation Function



Convolution Layers



Pooling Layers



Normalization

$$\hat{x}_{i,j} = \frac{x_{i,j} - \mu_j}{\sqrt{\sigma_j^2 + \varepsilon}}$$

Batch Normalization

Idea: “Normalize” the outputs of a layer so they have zero mean and unit variance



Why? Helps reduce “internal covariate shift”, improves optimization

We can normalize a batch of activations like this:

$$\hat{x} = \frac{x - E[x]}{\sqrt{Var[x]}}$$


This is a **differentiable function**, so we can use it as an operator in our networks and backprop through it!

Similar to whitening as data preprocessing



Batch Normalization

Input: $x \in \mathbb{R}^{N \times D}$



$$\mu_j = \frac{1}{N} \sum_{i=1}^N x_{i,j}$$

Per-channel
mean, shape is D

$$\sigma_j^2 = \frac{1}{N} \sum_{i=1}^N (x_{i,j} - \mu_j)^2$$

Per-channel
std, shape is D


$$\hat{x}_{i,j} = \frac{x_{i,j} - \mu_j}{\sqrt{\sigma_j^2 + \varepsilon}}$$

Normalized x,
Shape is N x D

Batch Normalization

each dimension of its input is then normalized (i.e. re-centered and re-scaled) separately

Input: $x \in \mathbb{R}^{N \times D}$



$$\mu_j = \frac{1}{N} \sum_{i=1}^N x_{i,j}$$

Per-channel
mean, shape is D

$$\sigma_j^2 = \frac{1}{N} \sum_{i=1}^N (x_{i,j} - \mu_j)^2$$

Per-channel
std, shape is D

$$\hat{x}_{i,j} = \frac{x_{i,j} - \mu_j}{\sqrt{\sigma_j^2 + \epsilon}}$$

Normalized x,
Shape is N x D

**Problem: What if zero-mean, unit
variance contains too less information?**

Batch Normalization

Input: $x \in \mathbb{R}^{N \times D}$

Learnable scale and shift parameters:

$$\gamma, \beta \in \mathbb{R}^D$$

Learning $\gamma = \sigma$, $\beta = \mu$
will recover the identity
function (in expectation)

$$\mu_j = \frac{1}{N} \sum_{i=1}^N x_{i,j}$$

Per-channel
mean, shape is D

$$\sigma_j^2 = \frac{1}{N} \sum_{i=1}^N (x_{i,j} - \mu_j)^2$$

Per-channel
std, shape is D

$$\hat{x}_{i,j} = \frac{x_{i,j} - \mu_j}{\sqrt{\sigma_j^2 + \varepsilon}}$$

Normalized x,
Shape is N x D

$$y_{i,j} = \gamma_j \hat{x}_{i,j} + \beta_j$$

Output,
Shape is N x D

Batch Normalization

Problem: Estimates depend on minibatch; can't do this at test-time!

Input: $x \in \mathbb{R}^{N \times D}$

Learnable scale and shift parameters:

$$\gamma, \beta \in \mathbb{R}^D$$

Learning $\gamma = \sigma$, $\beta = \mu$
will recover the identity
function (in expectation)

$$\mu_j = \frac{1}{N} \sum_{i=1}^N x_{i,j}$$

Per-channel
mean, shape is D

$$\sigma_j^2 = \frac{1}{N} \sum_{i=1}^N (x_{i,j} - \mu_j)^2$$

Per-channel
std, shape is D

$$\hat{x}_{i,j} = \frac{x_{i,j} - \mu_j}{\sqrt{\sigma_j^2 + \epsilon}}$$

Normalized x,
Shape is N x D

$$y_{i,j} = \gamma_j \hat{x}_{i,j} + \beta_j$$

Output,
Shape is N x D

Batch Normalization: Test-Time

Input: $x \in \mathbb{R}^{N \times D}$

$\mu_j =$ (Running) average of values seen during training

Per-channel mean, shape is D

Learnable scale and shift parameters:

$\gamma, \beta \in \mathbb{R}^D$

$\sigma_j^2 =$ (Running) average of values seen during training

Per-channel std, shape is D

Learning $\gamma = \sigma, \beta = \mu$ will recover the identity function (in expectation)

$$\hat{x}_{i,j} = \frac{x_{i,j} - \mu_j}{\sqrt{\sigma_j^2 + \varepsilon}}$$

Normalized x,
Shape is N x D

$$y_{i,j} = \gamma_j \hat{x}_{i,j} + \beta_j$$

Output,
Shape is N x D

Batch Normalization: Test-Time

Input: $x \in \mathbb{R}^{N \times D}$

$\mu_j =$ (Running) average of values seen during training

Per-channel mean, shape is D

Learnable scale and shift parameters:

$\sigma_j^2 =$ (Running) average of values seen during training

Per-channel std, shape is D

$\gamma, \beta \in \mathbb{R}^D$

$$\hat{x}_{i,j} = \frac{x_{i,j} - \mu_j}{\sqrt{\sigma_j^2 + \varepsilon}}$$

Normalized x,
Shape is N x D

During testing batchnorm becomes a linear operator!
Can be fused with the previous fully-connected or conv layer

$$y_{i,j} = \gamma_j \hat{x}_{i,j} + \beta_j$$

Output,
Shape is N x D

Batch Normalization for ConvNets

Batch Normalization for
fully-connected networks

$$x : N \times D$$

Normalize



$$\mu, \sigma : 1 \times D$$

$$\gamma, \beta : 1 \times D$$

$$y = \frac{(x - \mu)}{\sigma} \gamma + \beta$$

Batch Normalization for
convolutional networks
(Spatial Batchnorm, BatchNorm2D)

$$x : N \times C \times H \times W$$

Normalize




$$\mu, \sigma : 1 \times C \times 1 \times 1$$

$$\gamma, \beta : 1 \times C \times 1 \times 1$$

$$y = \frac{(x - \mu)}{\sigma} \gamma + \beta$$


Batch Normalization




Usually inserted after Fully Connected or Convolutional layers, and before nonlinearity.

$$\hat{x} = \frac{x - E[x]}{\sqrt{Var[x]}}$$


Batch Normalization



- Makes deep networks **much** easier to train!
- Allows higher learning rates, faster convergence
- Networks become more robust to initialization
- Acts as regularization during training
- Zero overhead at test-time: can be fused with conv!



Batch Normalization



- Makes deep networks **much** easier to train!
- Allows higher learning rates, faster convergence
- Networks become more robust to initialization
- Acts as regularization during training
- Zero overhead at test-time: can be fused with conv!
- Not well-understood theoretically (yet)
- Behaves differently during training and testing: this is a very common source of bugs!
 - One hacky solution is to freeze batchnorm parameters in testing time

Example of Batchnorm in NN

```
class Net(nn.Module):
    def __init__(self):
        super(Net, self).__init__()
        self.conv1=nn.Conv2d(1,32,3,1)
        self.conv1_bn=nn.BatchNorm2d(32)
        self.conv2=nn.Conv2d(32,64,3,1)
        self.conv2_bn=nn.BatchNorm2d(64)
        self.dropout1=nn.Dropout(0.25)
        self.fc1=nn.Linear(9216,128)
        self.fc1_bn=nn.BatchNorm1d(128)
        self.fc2=nn.Linear(128,10)
    def forward(self,x):
        x=self.conv1(x)
        x=F.relu(self.conv1_bn(x))
        x=self.conv2(x)
        x=F.relu(self.conv2_bn(x))
        x=F.max_pool2d(x,2)
        x=self.dropout1(x)
        x=torch.flatten(x,1)
        x=self.fc1(x)
        x=F.relu(self.fc1_bn(x))
        x=self.fc2(x)
        output=F.log_softmax(x,dim=1)
        return output
```

Layer Normalization

Batch Normalization for
fully-connected networks

$$x : N \times D$$

Normalize

$$\mu, \sigma : 1 \times D$$

$$\gamma, \beta : 1 \times D$$

$$y = \frac{(x - \mu)}{\sigma} \gamma + \beta$$

Layer Normalization for fully-
connected networks
Same behavior at train and test!
Used in RNNs, Transformers

$$x : N \times D$$

Normalize

$$\mu, \sigma : N \times 1$$

$$\gamma, \beta : 1 \times D$$

$$y = \frac{(x - \mu)}{\sigma} \gamma + \beta$$

Instance Normalization

Batch Normalization for
convolutional networks

$$x : N \times C \times H \times W$$

Normalize

$$\mu, \sigma : 1 \times C \times 1 \times 1$$

$$\gamma, \beta : 1 \times C \times 1 \times 1$$

$$y = \frac{(x - \mu)}{\sigma} \gamma + \beta$$

Instance Normalization for
convolutional networks

$$x : N \times C \times H \times W$$


Normalize

$$\mu, \sigma : N \times C \times 1 \times 1$$

$$\gamma, \beta : 1 \times C \times 1 \times 1$$


$$y = \frac{(x - \mu)}{\sigma} \gamma + \beta$$

Comparison of Normalization Layers



The pixels in blue are normalized by the same mean and variance, computed by aggregating the values of these pixels


Group Normalization




The pixels in blue are normalized by the same mean and variance, computed by aggregating the values of these pixels

Components of a Convolutional Network


Convolution Layers




Pooling Layers



Fully-Connected Layers



Activation Function




Normalization


$$\hat{x}_{i,j} = \frac{x_{i,j} - \mu_j}{\sqrt{\sigma_j^2 + \varepsilon}}$$

Components of a Convolutional Network


Convolution Layers




Pooling Layers



Fully-Connected Layers



Activation Function




Normalization


$$\hat{x}_{i,j} = \frac{x_{i,j} - \mu_j}{\sqrt{\sigma_j^2 + \varepsilon}}$$

Summary: Components of a Convolutional Network


Convolution Layers




Pooling Layers



Fully-Connected Layers



Activation Function




Normalization

$$\hat{x}_{i,j} = \frac{x_{i,j} - \mu_j}{\sqrt{\sigma_j^2 + \varepsilon}}$$

Summary: Components of a Convolutional Network

Problem: What is the right way to combine all these components?




Reading and Practice

D2L Chapter 7. Convolutional Neural Networks

Notebook practice:

https://github.com/d2l-ai/d2l-en/tree/master/chapter_convolutional-neural-networks



Next time:
Modern CNN Architectures