
CS 181 PRACTICE MIDTERM 1B

You may state without proof any fact taught in lecture.

1 Give a simple verbal description of the language recognized by the following NFA:



- 2 Draw a finite automaton (deterministic or nondeterministic) for each of the following languages:
 - **a.** binary strings that have odd length or contain at most one 1;
 - **b.** binary strings in which every 0 is immediately preceded and immediately followed by a 1.

- **3** Give a regular expression for each of the following languages:
 - **a.** binary strings other than 01;
 - **b.** binary strings that do not contain 100 as a substring;
 - **c.** strings over the alphabet $\{a, b, c\}$ that contain all three alphabet symbols.

© 2013–2024 A. A. Sherstov. All rights reserved. No part of this document can be distributed, forwarded, or otherwise shared with any person(s) or entity(ies), in any form or medium, without the copyright owner's written permission.		
obtained by the language		
concatenating		

© 2013–2024 A. A. Sherstov. All rights reserved. No part of this document can be distributed, forwarded, or otherwise shared with any person(s) or entity(ies), in any form or medium, without the copyright owner's written permission.		
6	Prove or disprove: for any nonregular language L , the palindromes in L also form a nonregular language.	
7	For a language L , let permute(L) denote the set of all strings that can be obtained by taking a string in L and keeping it as is or reordering its symbols. For example, permute($\{\epsilon, ab, abb\}$) = $\{\epsilon, ab, ba, abb, bab, bba\}$. Prove that regular languages are not closed under the permute operation.	
	(c, az, za, azz, zaz). Trove that regular languages are not closed under the permate operation.	


- **8** For each of the following languages *L* over the binary alphabet, determine whether it is regular and prove your answer:
 - **a.** strings of the form wwu, where $w \in \{0, 1\}^+$ and $u \in \{0, 1\}^*$;
 - **b.** strings that are palindromes or contain 00 as a substring;
 - c. strings that contain a nonempty substring with equally many 0s and 1s.

SOLUTIONS

CS 181 PRACTICE MIDTERM 1B

You may state without proof any fact taught in lecture.

1 Give a simple verbal description of the language recognized by the following NFA:




Solution: binary strings that do not start with 11111.


- 2 Draw a finite automaton (deterministic or nondeterministic) for each of the following languages:
 - **a.** binary strings that have odd length or contain at most one 1;
 - **b.** binary strings in which every 0 is immediately preceded and immediately followed by a 1.

Solution.

a.



b.



- **3** Give a regular expression for each of the following languages:
 - **a.** binary strings other than 01;
 - **b.** binary strings that do not contain 100 as a substring;
 - **c.** strings over the alphabet $\{a, b, c\}$ that contain all three alphabet symbols.

Solution.

- **a.** $\varepsilon \cup \Sigma \cup 1\Sigma \cup \Sigma 0 \cup \Sigma^3 \Sigma^*$
- **b.** $0*(1 \cup 10)*$
- **c.** $a\Sigma^*b\Sigma^*c\Sigma^* \cup a\Sigma^*c\Sigma^*b\Sigma^* \cup b\Sigma^*a\Sigma^*c\Sigma^* \cup b\Sigma^*c\Sigma^*a\Sigma^* \cup c\Sigma^*a\Sigma^*b\Sigma^* \cup c\Sigma^*b\Sigma^*a\Sigma^*$

	13–2024 A. A. Sherstov. All rights reserved. No part of this document can be distributed, forwarded, or otherwise d with any person(s) or entity(ies), in any form or medium, without the copyright owner's written permission.
4	For a binary string w , its <i>bitwise complement</i> is denoted \overline{w} and defined as the string obtained by flipping every bit of w . Prove that for every regular language L over the binary alphabet, the language $L' = \{\overline{w} : w \in L\}$ is also regular.
	Solution. Starting with a DFA for L , swap the edge labels 0 and 1 out of every state. The resulting DFA recognizes L' . Formally, let $D=(Q,\Sigma,\delta,q_0,F)$ be a DFA for L . Then L' is recognized by (Q,Σ,δ',q_0,F) , where $\delta'(q,\sigma)=\delta(q,\neg\sigma)$.
5	Let L be a regular language. Define L^{\dagger} to be the set of all strings that can be obtained by concatenating one or more nonempty strings in L . Prove that L^{\dagger} is regular.
	Solution. Note that $L^{\dagger} = L^* \setminus \{\varepsilon\}$, where L and $\{\varepsilon\}$ are regular. Since regular languages are closed under Kleene star and set difference, L^{\dagger} is also regular.
	An incorrect solution. Starting with a DFA for L , make the initial state rejecting and add ε -transitions from every accepting state back to the initial state. It is tempting to claim that the resulting automaton recognizes L^{\dagger} . This is incorrect in general. The new automaton may not accept all strings in L^{\dagger} .

© 2013–2024 A. A. Sherstov. All rights reserved. No part of this document can be distributed, forwarded, or otherwise shared with any person(s) or entity(ies), in any form or medium, without the copyright owner's written permission.		
6	Prove or disprove: for any nonregular language L , the palindromes in L also form a nonregular language.	
	Solution. False. Let $L=\{0^n1^n:n\geqslant 0\}$. We proved in class that L is nonregular. Yet, the palindromes in L form the regular language $\{\varepsilon\}$.	
7	For a language L , let permute(L) denote the set of all strings that can be obtained by taking a string in L and keeping it as is or reordering its symbols. For example, permute($\{\epsilon, ab, abb\}$) = $\{\epsilon, ab, ba, abb, bab, bba\}$. Prove that regular languages are not closed under the permute operation.	
	Solution. Consider the regular language $L=(01)^*$. Then permute(L) is the language of binary strings with as many 0s as 1s, which we proved in class is nonregular.	

- **8** For each of the following languages *L* over the binary alphabet, determine whether it is regular and prove your answer:
 - **a.** strings of the form wwu, where $w \in \{0, 1\}^+$ and $u \in \{0, 1\}^*$;
 - **b.** strings that are palindromes or contain 00 as a substring;
 - **c.** strings that contain a nonempty substring with equally many 0s and 1s.

Solution.

- a. Nonregular. We will first prove that the language $L' = L \cap 01^+01^+$ is nonregular. Let $p \geqslant 1$ be arbitrary. Consider the string $w = 01^p01^p \in L'$. Let w = xyz be any decomposition such that y is nonempty and is contained within the first p symbols. If y contains the leading 0, then xz contains only one 0 and therefore $xz \notin L'$. If y is composed entirely of 1s, then the pumped-up string xy^2z is not even in L and therefore also not in L'. By the pumping lemma, L' is nonregular. Now, if L were regular, the closure properties would force the intersection $L \cap 01^+01^+$ to be a regular language as well, we which just showed is not the case. Therefore, L is nonregular.
- **b.** Nonregular. Let $p \ge 1$ be arbitrary. Consider the string $w = 1^p 01^p \in L$. Let w = xyz be any decomposition such that y is nonempty and is contained within the first p ones. Then pumping up results in the string $1^{p+|y|}01^p$, which is neither a palindrome nor does it contain 00. Thus, $xy^2z \notin L$. By the pumping lemma, L is nonregular.
- **c.** Regular, with regular expression $\Sigma^*(01 \cup 10)\Sigma^*$. Indeed, L by definition contains every string that has 01 or 10 as a substring. Conversely, any string $w \in L$ must contain both 0s and 1s, which means that w must contain 01 or 10.