


1. >npx create-react-app routing
2. Create components folder in src folder
 - a. Create 4 folders in src – navbar, home, product, contact
 - b. Create js file for each in respective folder



3. Code for navbar

```
JS Navbar.js X
src > components > navabr > JS Navbar.js > ...
1  import React from 'react'
2  import './navbar.css'
3
4  export default function Navbar() {
5    return (
6      <div className='navbar'>
7        <nav>
8          <h1>Reat Routing</h1>
9
10         <a href="">Home</a>
11         <a href="">Product</a>
12         <a href="">Contact</a>
13       </nav>
14     </div>
15   )
16 }
17

# navbar.css X
src > components > navabr > # navbar.css > .navbar nav h1
1  .navbar{
2    background-color: aqua;
3  }
4  .navbar nav
5  {
6    display: flex;
7    gap: 10px;
8    align-items: center;
9    margin: 0 20px;
10 }
11
12 .navbar nav h1
13 {
14   margin-right: auto;
15 }
```

4. Display navbar component in App component

```
JS App.js X
src > JS App.js > ...
1  import logo from './logo.svg';
2  import './App.css';
3  import Navbar from './components/navbar/Navbar';
4
5  function App() {
6    return (
7      <>
8        <Navbar/>
9      </>
10   );
11 }
12
13 export default App;
14
```

5. Npm start and check output



6. Implementing routing


- >npm i react-router-dom
- Create router array and attach it to the RouterProvider as property in index.js

```
JS index.js X
src > JS index.js > ...
4  import App from './App';
5  import reportWebVitals from './reportWebVitals';
6  import { RouterProvider, createBrowserRouter } from 'react-router-dom';
7
8  const routes=createBrowserRouter([
9    {
10     path: "/",
11     element:<App/>
12   }
13 ])
14
15 const root = ReactDOM.createRoot(document.getElementById('root'));
16 root.render(
17   // <React.StrictMode>
18   // <App />
19   // </React.StrictMode>
20   <RouterProvider router={routes}/>
21 );
22
```

c. Output



- d. If we try to provide any other path than "/" we will get error



Unexpected Application Error!


404 Not Found

Hey developer 🙌

You can provide a way better UX than this when your app throws errors by providing your own `ErrorBoundary` or `errorElement` prop on your route.

7. Handling Error page

- a. Create error page folder inside components folder. In error page folder create NotFound.js



- b. Code for NotFound.js

```
import React from 'react'

export default function NotFound() {
  return (
    <center>
      
    </center>
  )
}
```

- c. Check output



404 error
page not found



8. Handling routing from navbar

- a. In index.js provide children array

```
JS index.js X
src > JS index.js > ...
11
12 const routes=createBrowserRouter([
13   {
14     path:"/",
15     element:<App/>,
16     errorElement:<NotFound/>,
17     children:[
18       {
19         path:'/home',
20         element:<Home/>
21       },
22       {
23         path:'/contact',
24         element:<Contact/>
25       },
26       {
27         path:'/product',
28         element:<Product/>
29       }
30     ]
31   }
32 ])
```

- b. In Navbar.js provide links




```
export default function Navbar() {
  return (
    <div className='navbar'>
      <nav>
        <h1>Reat Routing</h1>
        <a href="/home">Home</a>
        <a href="/product">Product</a>
        <a href="/contact">Contact</a>
      </nav>
    </div>
  )
}
```

- c. In App.js provide <Outlet/> for component switching

```
function App() {
  return (
    <>
      <Navbar/>
      <Outlet/>
    </>
  );
}

export default App;
```

- d. Output




9. Handling index page (displaying home component as home/index page)

a. In index.js provide index:true

```
11
12 const routes=createBrowserRouter([
13   {
14     path:"/",
15     element:<App/>,
16     errorElement:<NotFound/>,
17     children:[
18       {
19         index:true, ✓
20         element:<Home/> ✓
21       },
22       {
23         path:'/home',
24         element:<Home/>
25       },
26     ],
27   },
28 ],
```

b. Output



c.


10. Preventing page from getting refersh

- a. If we click on home/contact/product from navbar then ypu will see, our page is getting refersh. As REACT is used to create SPA, we have to prevent our page from getting refresh. We can achieve this bye converting anchor tag to Link tag provided by react-router-dom

```
export default function Navbar() {
  return (
    <div className='navbar'>
      <nav>
        <h1>Reat Routing</h1>
        <a href="/home">Home</a>
        <a href="/product">Product</a>
        <a href="/contact">Contact</a>
      </nav>
    </div>
  )
}
```


```
export default function Navbar() {
  return (
    <div className='navbar'>
      <nav>
        <h1>Reat Routing</h1>
        <Link to="/home">Home</Link>
        <Link to="/product">Product</Link>
        <Link to="/contact">Contact</Link>
      </nav>
    </div>
  )
}
```

But if you inspect, you will see anchor tag only



11. Providing CSS on navbar

- a. Convert Link to NavLink – this will automatically add active class on anchor tag (inspect and check)




The screenshot shows two files in a code editor. On the left is `Navbar.js` with the following code:

```
4
5 export default function Navbar() {
6   return (
7     <div className='navbar'>
8       <nav>
9         <h1>Reat Routing</h1>
10
11         <NavLink to="/home">Home</NavLink>
12         <NavLink to="/product">Product</NavLink>
13         <NavLink to="/contact">Contact</NavLink>
14       </nav>
15     </div>
16   )
17 }
18
```

On the right is `navbar.css` with the following code:

```
10
11
12 .navbar nav h1
13 {
14   margin-right: auto;
15 }
16
17 .navbar nav a.active
18 {
19   text-decoration: none;
20   background-color: red;
21   color: white;
22 }
```

- b. Output



12. Implementing dynamic routing

- a. Create products.json inside src folder
b. Code for products.json



```
[
  {
    "id": 1,
    "title": "Backpack",
    "price": 109.95,
    "image": "https://fakestoreapi.com/img/81fPKd-2AYL._AC_SL1500_.jpg"
  },
  {
    "id": 2,
    "title": "Slim T-Shirts ",
    "price": 22.3,
    "image": "https://fakestoreapi.com/img/71-3HjGNDUL._AC_SY879._SX._UX._SY._UY_.jpg"
  },
  {
    "id": 3,
    "title": "Cotton Jacket",
    "price": 55.99,
    "image": "https://fakestoreapi.com/img/71li-ujt1UL._AC_UX679_.jpg"
  }
]
```

- c. Fetch data from products.json into Product.js and display into a card

```
import React from 'react'
import products from '../products.json'
import './card.css'
import { Link } from 'react-router-dom'


export default function Product() {
  return (
    <div className='card'>
      {
        products.map(product =>
          {
            return (
              <div className='card-items'>
                <img src={product.image} width="200px"
height="200px"/>
                <h2>{product.title}</h2>
                <h4>Price : {product.price}</h4>
                <button><Link
to={` /product/${product.id}`}>View More</Link></button>
              </div>
            )
          }
        )
      }
    </div>
  )
}
```

Create card.css in product folder. Code –


```
.card
{
  display: flex;
  justify-content: space-evenly;
  margin-top: 10px;
}

.card-items
{
  text-align: center;
  border: 1px solid black;
  padding: 15px;
  border-radius: 25px;
  box-shadow: 3px 5px 5px grey;
}

.card-items h2
{
  color: red;
}
```




- d. Create ProductDetails.js component in product folder



- e. Provide path for ProductDetails from Index.js

```
JS index.js x
src > JS index.js > routes > children
30     },
31     {
32       path: '/product',
33       element: <Product/>
34     },
35     {
36       path: '/product/:id',
37       element: <ProductDetails/>
38     }
39   ]
40 }
41 )
```

Output :




ProductDetails

13. Displaying product in ProductDetails.js

```
import React from 'react'
import { useParams } from 'react-router-dom';
import products from '../products.json'

export default function ProductDetails() {
  const param=useParams() //to get id from url
  console.log(param.id);
  return (
    <div className='card'>
      {
        products.map((product) =>
          {
            if(product.id==param.id)
            {
              return(
                <div className='card-items' style={{width:200}} key={product.id}>
                  <img src={product.image} width="200px" height="200px"/>
                  <h2>{product.title}</h2>
                  <h4>Price : {product.price}</h4>
                </div>
              )
            }
          }
        )
      }
    </div>
  )
}
```



14. Back button functionality

```
JS ProductDetails.js X
src > components > product > JS ProductDetails.js > ProductDetails
1 import React from 'react'
2 import { useParams,useNavigate } from 'react-router-dom';
3 import products from '../../products.json'
4
5 export default function ProductDetails() {
6   const param=useParams() //to get id from url
7   const navigate=useNavigate() 2
8   console.log(param.id);
9   return (
10     <div className='card'>
11       {
12         products.map((product) =>
13           {
14             if(product.id==param.id)
15             {
16               return(
17                 <div className='card-items' style={{width:200}} key={product.id}>
18                   <img src={product.image} width="200px" height="200px"/>
19                   <h2>{product.title}</h2>
20                   <h4>Price : {product.price}</h4>
21                   <button onClick={()=>navigate('/product')}>Back</button> 3
22                 </div>

```

React Routing




15. Search parameter/query parameter

`product/1` => here 1 is called as dynamic parameter => `useParams()`

`product?name=backpack` => here name is called as Search parameter/query parameter => `useSearchParams()`

```
JS ProductDetails.js X
src > components > product > JS ProductDetails.js > ...
1 import React from 'react'
2 import { useParams,useNavigate, useSearchParams } from 'react-router-dom';
3 import products from '../products.json'
4
5 export default function ProductDetails() {
6   const param=useParams() //to get id from url
7   const [serach_param] = useSearchParams() 2
8   console.log(serach_param.get('name'));
9 }
```



TEJAS KASARE 8459849415

16. Working with forms – in Contact.js

```
import React, { useState } from 'react'

export default function Contact() {
  const [contactForm, setContactForm] = useState({
    username: '',
    useremail: '',
    useraddress: '',
    usercountry: ''
  })
  const handleSubmit = (event) => {
    event.preventDefault()
    console.log(contactForm)
  }

  const handleChange = (event) => {
    // console.log(event.target.value);
    // console.log(event.target.name);
    setContactForm(
      {
        ...contactForm,
        [event.target.name]: event.target.value
      }
    )
  }


  return (
    <div>
      <h1 style={{color: "red", textAlign: "center"}}>Contact US</h1>
      <form onSubmit={handleSubmit} style={{textAlign: 'center'}}>
        <label htmlFor="username">UserName: </label>
        <input type="text" id="username"
          name='username'
          value={contactForm.username}
          onChange={handleChange}
        />

        <br/><br/>
        <label htmlFor="useremail">UserEmail: </label>
        <input type="email" id="useremail"
          name='useremail'
          value={contactForm.useremail}
          onChange={handleChange}/>

        <br/><br/>
        <label htmlFor="useraddress">Address: </label>
        <textarea id="useraddress" cols="20" rows="5"
          name='useraddress'
          value={contactForm.useraddress}
          onChange={handleChange}></textarea>

        <br/><br/>
        <label htmlFor="usercountry">Usercountry:</label>
        <select name="usercountry" id="usercountry"
          value={contactForm.usercountry}
          onChange={handleChange}>
          <option value="india">INDIA</option>
          <option value="us">AMERICA</option>
          <option value="china">CHINA</option>
        </select>
        <br/><br/>
        <input type="submit" style={{width: "100vh"}}/>
      </form>
    </div>
  )
}
```

Output :




17. Handling checkbox and radio buttons

a. Create variables in useState()

```
export default function Contact() {  
  const [contactForm, setContactForm] = useState({  
    username: '',  
    useremail: '',  
    useraddress: '',  
    usercountry: '',  
    usergender: '',  
    useragreement: false,  
  })  
}
```


b. Create UI for radio button and check box



c. Checking type and collecting check box input

```
setContactForm(  
  {  
    ...contactForm,  
    // [event.target.name]:event.target.value  
    [event.target.name]: event.target.type === 'checkbox' ? event.target.checked : event.target.value  
  }  
)
```

d. Output



18. Handling Form Errors

a. Handling form errors by traditional way

- Add noValidate on form tag and formNoValidate on input tag to enable react from validation

```
<h1 style={{color:"red",textAlign:"center"}}>Contact US</h1>
<form onSubmit={handleSubmit} style={{textAlign:'center'}} noValidate>
  <label htmlFor="username">UserName: </label>
  <input type="text" id='username'
    name='username'
    value={contactForm.username}
    onChange={handleChange} formNoValidate
  />
  <br/><br/>
  <label htmlFor="useremail">UserEmail: </label>
  <input type="email" id='useremail'
    name='useremail'
    value={contactForm.useremail}
    onChange={handleChange} formNoValidate/>
  </form>
```

- Manage error state

```
    useragreement:false,
  })
  const [errors,setErrors]=useState({})
  const handleSubmit = (event)=>{
    event.preventDefault()
    if(contactForm.username==='' || contactForm.username===null)
    {
      setErrors({name:'Please enter your name'})
      return
    }
    setErrors({})
    console.log(contactForm);
  }
```

- iii. Display error message on respective input

```
<form onSubmit={handleSubmit} style={{textAlign:'center'}} noValidate>
  <label htmlFor="username">UserName: </label>
  <input type="text" id='username'
    name='username'
    value={contactForm.username}
    onChange={handleChange} formNoValidate
  />
  {errors && errors.name && errors.name}
  <br/><br/>
</form>
```

- iv. Output : click on submit button without providing username

React App

localhost:3000/contact

React Routing

Home Product Contact

Contact US

UserName:

Please enter your name

UserEmail:

Address:

Usercountry: INDIA

User Gender: ☐ Male ☐ Female


☐ Accespt terms and conditions

Submit

- v. DONE !!

b. Handling form errors by using external libraries : React Hook Form

- i. Install npm install react-hook-form
- ii. Create ReactHookFormm.js in components folder > contact folder
- iii. In index.js change reference of contact path to above ReactHookFormm.js



```
JS index.js  X
src > JS index.js > routes > children
28      {
29        path: '/contact',
30        element: <ReactHookFormm />
31      },
```

iv. Code ReactHookFormm.js

```
import React from 'react'
import { useForm } from 'react-hook-form'


export default function ReactHookFormm() {
  const {register,handleSubmit,formState}=useForm()
  //to register out input tag use register
  //handleSubmit check the validation before submitting data
  //formState manage the errors
  const submitData =(data) =>{
    console.log(data);
  }

  return (
    <div>
      <form onSubmit={handleSubmit(submitData)}>
        <label>First Name</label>
        <input type='text' {...register("firstname",{required:true,minLength:3})} />
        <br />
        {formState.errors && formState.errors.firstname && formState.errors.firstname.type=="required" &&
"First name is required"}

        {formState.errors && formState.errors.firstname && formState.errors.firstname.type=="minLength" && "min
3 characters required"}

        <br /><br />
        <label>Last Name</label>
        <input type='text' {...register("lastname")} />
        <br /><br />
        <input type="submit" />
      </form>
    </div>
  )
}
```


- v. DONE !!
- vi. Output :



React App


localhost:3000/contact

Reat Routing

First Name

First name is required

Last Name



React App

localhost:3000/contact

Reat Routing

First Name

min 3 characters required

Last Name

19. COMPLETED !!!!! see you in context, reducer and redux

TEJAS KASARE 8459849415