“ZFNet: A Visual Journey into Convolutional Neural Networks — Architecture, Innovation, and Evolution”



PROJECT SUBMITTED TO

DEPARTMENT OF STATISTICS

SVKM’S NMIMS (DEEMED-TO-BE-UNIVERSITY)

DLT ICA 3 ASSIGNMENT

MASTER OF SCIENCE

STATISTICS AND DATA SCIENCE

BY

Kamma Tanushree (A060)

UNDER THE SUPERVISION OF

Prof. Pratik Desai

Nilkamal School of Mathematics, Applied Statistics and Analytics (NSOMASA)

SVKM’S Narsee Monjee Institute of Management Studies

(Deemed-To-Be-University)

Vile Parle West, Mumbai, Maharashtra 400056

Introduction

For this case study I picked ZFNet, the network proposed by Matthew Zeiler and Rob Fergus in their paper “Visualizing and Understanding Convolutional Networks” (2014). I found ZFNet more interesting for a different reason. It is not remembered mainly for a clever new layer. It is remembered because it asked a question that the field was avoiding: why do these networks work at all? The paper gave researchers a way to look inside a CNN, find what was going wrong, and fix it using that evidence instead of guesswork.

Abstract

Convolutional neural networks (CNNs) became highly successful in image recognition, but their internal representations were difficult to interpret. ZFNet, introduced by Matthew Zeiler and Rob Fergus, addressed this problem by using visualisation as a practical diagnostic tool for CNN design. Rather than proposing a completely new learning principle, the authors inspected what intermediate layers had learned and used the evidence to refine an AlexNet-style network. A key change was reducing the first convolutional filter from 11 × 11 with stride 4 to 7 × 7 with stride 2. This preserved more spatial detail and reduced undesirable aliasing effects in early feature maps. The paper reported improved ImageNet classification results and demonstrated that learned features could transfer to other datasets. This case study explains the historical motivation, architecture, design choices, strengths and limitations of ZFNet, and its influence on later CNN development. The central lesson is that model improvement can come not only from making a network deeper or larger, but also from carefully examining what it learns.

Motivation and historical context

Before the rapid rise of deep CNNs, image recognition often relied on hand-designed features such as SIFT or HOG followed by a classifier. These pipelines could work well, but their performance depended on the features chosen by people. AlexNet, presented by Krizhevsky, Sutskever and Hinton in 2012, showed that a deep CNN trained on a large labelled dataset could achieve a major improvement on the ImageNet Large Scale Visual Recognition Challenge (ILSVRC). The result helped establish learned visual features as a powerful alternative to manual feature engineering.

However, a CNN’s success did not mean that researchers understood its internal behaviour. A network might classify an image correctly for the wrong reason—for example, using background texture rather than the object itself. It was also difficult to know which architectural changes would improve performance. Zeiler and Fergus therefore asked a practical question: if we could visualise the patterns that activate each layer, could we diagnose weaknesses and design a better network?

Their 2013 preprint and 2014 ECCV paper, “Visualizing and Understanding Convolutional Networks,” introduced a deconvolutional-network approach for mapping activations back toward image space. The resulting visualisations exposed issues in the early layers of AlexNet, including aliasing artefacts associated with the large first-layer stride. ZFNet—named from the authors’ initials—was the improved architecture that emerged from this analysis . Its historical contribution is both an architecture refinement and a method: visual evidence can guide design choices rather than treating a CNN as an entirely opaque box.




Figure : ILSVRC winning top-5 error by year

Architecture and design choices

ZFNet keeps the overall AlexNet skeleton: five convolutional layers, three max-pooling layers, two fully connected layers of 4096 units and a 1000-way softmax. The input is a 224×224 colour image. The differences look small on paper but each one was motivated by the visualisations.

Key design changes

- **Smaller first-layer filters:** 11×11 became 7×7. A smaller window keeps more detail from the original pixels, so layer 1 retains more information.
- **Smaller stride:** stride 4 became stride 2 in layer 1. This removed the aliasing seen in layer 2 and gave cleaner, more varied filters.
- **Dense connections, single GPU:** AlexNet split its layers across two GPUs with restricted connectivity. ZFNet was trained on one GPU (about 12 days on a GTX 580), so layers 3 to 5 are fully connected to the previous maps.
- **Standard training recipe:** ReLU activations, cross-entropy loss, SGD with momentum 0.9, mini-batches of 128, and dropout (0.5) in the fully connected layers to reduce overfitting.

	AlexNet (2012)	ZFNet (2013)
Layer 1 filter	11×11, stride 4	7×7, stride 2
Layer 2 filter	5×5	5×5, stride 2
Layers 3 to 5	Split across 2 GPUs	Dense, 1 GPU
Main contribution	Showed deep CNNs win	Showed how to see and debug them




Figure : Layer-wise Architecture of ZFNet

This side (Layer-wise Architecture of ZFNet) diagram illustrates the flow of ZFNet , from a 224 x 224 x 3 input image through convolutional and max-pooling layers to fully connected layers. Each layer extracts increasingly complex visual features, which are combined to classify the image into one of 1000 classes.




Figure 7. Three test examples where we systematically cover up different portions of the scene with a gray square (1st column) and see how the top (layer 5) feature maps ((b) & (c)) and classifier output ((d) & (e)) changes. (b): for each position of the gray scale, we record the total activation in one layer 5 feature map (the one with the strongest response in the unoccluded image). (c): a visualization of this feature map projected down into the input image (black square), along with visualizations of this map from other images. The first row example shows the strongest feature to be the dog's face. When this is covered-up the activity in the feature map decreases (blue area in (b)). (d): a map of correct class probability, as a function of the position of the gray square. E.g. when the dog's face is obscured, the probability for "pomeranian" drops significantly. (e): the most probable label as a function of occluder position. E.g. in the 1st row, for most locations it is "pomeranian", but if the dog's face is obscured but not the ball, then it predicts "tennis ball". In the 2nd example, text on the car is the strongest feature in layer 5, but the classifier is most sensitive to the wheel. The 3rd example contains multiple objects. The strongest feature in layer 5 picks out the faces, but the classifier is sensitive to the dog (blue region in (d)), since it uses multiple feature maps.

Above figure shows the occlusion-sensitivity experiment by Zeiler and Fergus (2014). By covering different parts of an image with a grey square, the researchers observed changes in feature activations and classification probabilities. Hiding the dog's face reduced the probability of predicting "Pomeranian," while the car example showed the importance of the wheel. This experiment demonstrates how visualisation helps identify the image regions influencing a CNN's predictions and understand its behavior.

How visualisation informed the redesign

The authors used a deconvolutional network (deconvnet) to project the activations of selected CNN units back into an approximate input-space pattern. In simple terms, it helped answer: "What kind of image pattern made this neuron respond strongly?" The method used operations corresponding to unpooling, rectification and filtering to trace strong activations back through the network. It was not a perfect explanation of every neuron, but it made layer behaviour easier to inspect.

The visualisations suggested that AlexNet's early filters and feature maps did not preserve image structure as cleanly as they could. With the smaller first-layer filter and stride, ZFNet produced more distinctive first-layer features and cleaner second-layer visualisations, with fewer visible aliasing artefacts [1]. This is a useful example of interpretability leading to an engineering decision.

A second technique in the paper was occlusion sensitivity. The researchers covered different parts of an image and observed how the class score changed. If covering the dog's face substantially lowered the "dog" score, that region was likely important to the prediction. If covering the background caused the largest change, the network might be relying on an unintended cue. This resembles a simple real-world test: hide parts of a photograph and see which missing part confuses the classifier.

Figure 2 illustrates the iterative process. The visualisation does not automatically improve a model; researchers still need to interpret it, change the architecture, retrain the network and evaluate it on held-out data. It is best viewed as a diagnostic instrument, not as proof that a model is unbiased or fully explainable.




Figure : Diagnostic loop: visualisation guides a redesign, followed by retraining and evaluation.


Strengths and limitations

Strengths

- **Better accuracy at almost no extra cost.** The single-model top-5 error on the ImageNet validation set improved from about 18.2% (AlexNet) to about 16.5%, and an ensemble reached about 14.8% on the test set. The compute cost stayed almost the same.
- **Transfer learning.** When the ImageNet-trained features were frozen and only a new softmax was trained, ZFNet reached about 86.5% on Caltech-101 and about 74.2% on Caltech-256, which beat earlier methods trained on those small datasets. This is the same idea we use today when fine-tuning a pretrained model for medical or satellite images.
- **Interpretability.** It gave a systematic way to debug a network, instead of tuning hyperparameters blindly.

Limitations

- **Heavy fully connected layers.** Using the same layer sizes as AlexNet, around 62 million parameters (my own count) with FC6 alone holding about 38 million. This makes it memory heavy and prone to overfitting (Figure 5).
- **Shallow by modern standards.** Only 8 learned layers. The paper's own ablation hinted that depth matters, but ZFNet did not explore it.
- **Weak on some tasks.** On PASCAL VOC 2012 the transferred features did slightly worse (about 79% mean accuracy) than the best competing methods (about 82%), probably because VOC images often contain several objects while ImageNet has one.
- **Visualisation is qualitative.** The deconvnet pictures need human interpretation, and they are not guaranteed to show exactly what the network uses.



There is a trade-off between predictive performance, complexity and generalisation here. ZFNet gets its gain without adding layers, so complexity barely rises, but the large FC layers still give it a big model for the accuracy it delivers. Any comparison with other results should also be careful, because ILSVRC numbers differ in single-model versus ensemble settings, validation versus test sets, and the amount of data augmentation used.

Real-life illustration and application areas

Imagine a phone gallery that automatically labels photographs as "dog," "bicycle" or "flower." A CNN first detects basic visual patterns, then combines them into more complex structures. For a bicycle, early layers may respond to edges and circles, while later layers may respond to wheels, a frame and the arrangement of these parts. ZFNet's design change aims to preserve more of the small details in the early stages, which can be important when objects have thin edges or closely spaced parts.


The same principle is relevant to industrial inspection. A camera may need to identify a hairline crack in a manufactured component. If early processing discards fine detail, the defect may be harder to detect. A smaller stride can preserve more local information, although it may increase computation and still requires suitable training examples. In medical imaging, a CNN might help flag suspicious regions in X-rays, but it should be treated as decision support rather than a replacement for a clinician.
Performance must be validated on the intended patient population and equipment.

ZFNet itself is mainly important as a historical and methodological milestone rather than the default model for every current application. Its broader contribution is the idea that visualising intermediate representations and testing model sensitivity can make deep learning development more systematic.

Subsequent developments and lasting influence

ZFNet came at the start of a very fast period, and many of its lessons showed up in later models.

Year	Model	What it changed (and the link to ZFNet)
2014	VGGNet	Used only 3×3 filters stacked deep (16 to 19 layers). It follows the ZFNet lesson that smaller filters keep detail, and pushed it much further.
2014	GoogLeNet	Inception modules and about 6.8M parameters. It dropped the big FC layers and used global average pooling instead.
2015	ResNet	Skip connections allowed 50 to 152 layers. Batch normalisation replaced local response normalisation.
2017	Grad-CAM	Heatmap explanations for any CNN. This is the direct descendant of the visualisation work.
2020	Vision Transformer	Attention-based, not convolutional, but still uses the pretrain and fine-tune workflow that ZFNet's transfer results hinted at.



Looking at what survived: small early filters and stride, ReLU, dropout and ImageNet pretraining all stood the test of time. Parts that were modified include the big FC head (replaced by global average pooling), and the normalisation, where batch norm replaced local response normalisation. What became less widely adopted was the idea of fixed, shallow 8-layer designs and hand-tuned ensembles of several models. The visualisation idea did not disappear either; it moved on into saliency maps and Grad-CAM, which doctors and engineers use today to check why a model made a prediction.

Critical assessment and conclusion

In my view ZFNet's lasting contribution is more about method than architecture. As a model it was overtaken within a year, and nobody would choose it for a new project now. But it changed how people did research: look at what the network has learned, find the fault, then redesign. The step from 11×11 stride 4 to 7×7 stride 2 is a good example of a small change that was justified by evidence.

It is still relevant today. A hospital that uses a CNN to detect pneumonia in chest X-rays needs to check that the model looks at the lungs and not at a hospital tag in the corner of the image, which is exactly the occlusion and visualisation logic of this paper. Its weaknesses, mainly the oversized FC layers and shallow depth, were fixed by later work. So ZFNet is best seen as a bridge between AlexNet, which proved the idea, and VGG, GoogLeNet and ResNet, which scaled it up.

Overall, ZFNet marks a useful step in the evolution of CNNs: it demonstrated that researchers can learn about a model by inspecting its internal representations, then use that evidence to make better design choices. For students of data science, the key lesson is to treat a neural network not as a mysterious box, but as a system whose assumptions, errors and limitations should be investigated systematically.

References

[1] Zeiler, M. D., & Fergus, R. (2014). Visualizing and understanding convolutional networks. ECCV 2014, 818-833.

[2] Krizhevsky, A., Sutskever, I., & Hinton, G. E. (2012). ImageNet classification with deep convolutional neural networks. NIPS 25.

[3] Russakovsky, O., et al. (2015). ImageNet large scale visual recognition challenge. IJCV, 115, 211-252.

[4] Simonyan, K., & Zisserman, A. (2015). Very deep convolutional networks for large-scale image recognition. ICLR.

[5] Szegedy, C., et al. (2015). Going deeper with convolutions. CVPR.

[6] He, K., Zhang, X., Ren, S., & Sun, J. (2016). Deep residual learning for image recognition. CVPR.

[7] Srivastava, N., et al. (2014). Dropout: a simple way to prevent neural networks from overfitting. JMLR, 15, 1929-1958.

[8] Ioffe, S., & Szegedy, C. (2015). Batch normalization: accelerating deep network training. ICML.

[9] Selvaraju, R. R., et al. (2017). Grad-CAM: visual explanations from deep networks via gradient-based localization. ICCV.

[10] Dosovitskiy, A., et al. (2021). An image is worth 16x16 words: transformers for image recognition at scale. ICLR.