

24 .You are given a list of items with their weights and values. Develop a program that utilizes exhaustive search to solve the 0-1 Knapsack Problem. The program should:

- 1. Define a function `total_value(items, values)` that takes a list of selected items (represented by their indices) and the value list as input. It iterates through the selected items and calculates the total value by summing the corresponding values from the value list.
- 2. Define a function `is_feasible(items, weights, capacity)` that takes a list of selected items (represented by their indices), the weight list, and the knapsack capacity as input. It checks if the total weight of the selected items exceeds the capacity. Test Cases:
- 3. Simple Case: □ Items: 3 (represented by indices 0, 1, 2) □ Weights: [2, 3, 1] □ Values: [4, 5, 3] □ Capacity: 4
- 4. More Complex Case: □ Items: 4 (represented by indices 0, 1, 2, 3) □ Weights: [1, 2, 3, 4] □ Values: [2, 4, 6, 3] □ Capacity: 6 Output: Test Case 1: Optimal Selection: [0, 2] (Items with indices 0 and 2) Total Value: 7 Test Case 2: Optimal Selection: [0, 1, 2] (Items with indices 0, 1, and 2) Total Value: 10

```
import itertools
def knapsack(weights, values, capacity):
    n = len(weights)
    max_value = 0
    best_set = []
    for r in range(n + 1):
        for subset in itertools.combinations(range(n), r):
            total_weight = sum(weights[i] for i in subset)
            total_value = sum(values[i] for i in subset)

            if total_weight <= capacity and total_value > max_value:
                max_value = total_value
                best_set = subset
    return best_set, max_value
weights = [2,3,1]
values = [4,5,3]
capacity = 4
items, value = knapsack(weights, values, capacity)
print("Optimal Selection:", items)
print("Total Value:", value)
```

Optimal Selection: (1, 2)
Total Value: 8

22.

You are given a list of cities represented by their coordinates. Develop a program that utilizes exhaustive search to solve the TSP. The program should:

1. Define a function `distance(city1, city2)` to calculate the distance between two cities (e.g., Euclidean distance).
2. Implement a function `tsp(cities)` that takes a list of cities as input and performs the following:
 - o Generate all possible permutations of the cities (excluding the starting city) using `itertools.permutations`.
 - o For each permutation (representing a potential route):
 - Calculate the total distance traveled by iterating through the path and summing the distances between consecutive cities.
 - Keep track of the shortest distance encountered and the corresponding path.

o Return the minimum distance and the shortest path (including the starting city at the beginning and end).

3. Include test cases with different city configurations to demonstrate the program's functionality. Print the shortest distance and the corresponding path for each test case. Test Cases:

4. Simple Case: Four cities with basic coordinates (e.g., [(1, 2), (4, 5), (7, 1), (3, 6)])

5. More Complex Case: Five cities with more intricate coordinates (e.g., [(2, 4), (8, 1), (1, 7), (6, 3), (5, 9)]) Output: Test Case 1: Shortest Distance: 7.0710678118654755 Shortest Path: [(1, 2), (4, 5), (7, 1), (3, 6), (1, 2)] Test Case 2: Shortest Distance: 14.142135623730951 Shortest Path: [(2, 4), (1, 7), (6, 3), (5, 9), (8, 1), (2, 4)]

```
import itertools
import math
def distance(c1, c2):
    return math.sqrt((c1[0]-c2[0])**2 + (c1[1]-c2[1])**2)
def tsp(cities):
    start = cities[0]
    min_path = None
    min_dist = float('inf')
    for perm in itertools.permutations(cities[1:]):
        path = [start] + list(perm) + [start]
        total = 0
        for i in range(len(path)-1):
            total += distance(path[i], path[i+1])
        if total < min_dist:
            min_dist = total
            min_path = path
    return min_dist, min_path
cities = [(1,2), (4,5), (7,1), (3,6)]
dist, path = tsp(cities)
print("Shortest Distance:", dist)
print("Shortest Path:", path)
```

Shortest Distance: 16.969112847678894

Shortest Path: [(1, 2), (7, 1), (4, 5), (3, 6), (1, 2)]

23.

You are given a cost matrix where each element $\text{cost}[i][j]$ represents the cost of assigning worker i to task j . Develop a program that utilizes exhaustive search to solve the assignment problem. The program should Define a function $\text{total_cost}(\text{assignment}, \text{cost_matrix})$ that takes an assignment (list representing worker-task pairings) and the cost matrix as input. It iterates through the assignment and calculates the total cost by summing the corresponding costs from the cost matrix Implement a function $\text{assignment_problem}(\text{cost_matrix})$ that takes the cost matrix as input and performs the following Generate all possible permutations of worker indices (excluding repetitions). Test Cases: Input

1. Simple Case: Cost Matrix: $[[3, 10, 7], [8, 5, 12], [4, 6, 9]]$
2. More Complex Case: Cost Matrix: $[[15, 9, 4], [8, 7, 18], [6, 12, 11]]$ Output: Test Case 1: Optimal Assignment: [(worker 1, task 2), (worker 2, task 1), (worker 3, task 3)] Total Cost: 19 Test Case 2: Optimal Assignment: [(worker 1, task 3), (worker 2, task 1), (worker 3, task 2)] Total Cost: 24

```
import itertools
def assignment_problem(cost_matrix):
    n = len(cost_matrix)
    min_cost = float('inf')
    best_assignment = None
    for perm in itertools.permutations(range(n)):
        cost = 0
        for i in range(n):
            cost += cost_matrix[i][perm[i]]
        if cost < min_cost:
            min_cost = cost
            best_assignment = perm
    return best_assignment, min_cost
cost_matrix = [
    [3,10,7],
    [8,5,12],
    [4,6,9]
]
assignment, cost = assignment_problem(cost_matrix)
print("Assignment:", assignment)
print("Total Cost:", cost)
```

Assignment: (2, 1, 0)
Total Cost: 16

15. Given an array `arr` of positive integers sorted in a strictly increasing order, and an integer `k`. return the `k`th positive integer that is missing from this array. Example 1: Input: `arr = [2,3,4,7,11]`, `k = 5` Output: 9 Explanation: The missing positive integers are [1,5,6,8,9,10,12,13,...]. The 5th missing positive integer is 9. Example 2: Input: `arr = [1,2,3,4]`, `k = 2` Output: 6 Explanation: The missing positive integers are [5,6,7,...]. The 2nd missing positive integer is 6.

```
def findKthPositive(arr, k):
    missing = 0
    num = 1
    i = 0
    while missing < k:
        if i < len(arr) and arr[i] == num:
            i += 1
        else:
            missing += 1
            if missing == k:
                return num
        num += 1
print(findKthPositive([2,3,4,7,11], 5))
print(findKthPositive([1,2,3,4], 2))
```

9
6

17. Given two strings `needle` and `haystack`, return the index of the first occurrence of `needle` in `haystack`, or -1 if `needle` is not part of `haystack`. Example 1: Input: `haystack = "sadbutsad"`, `needle = "sad"`

Output: 0 Explanation: "sad" occurs at index 0 and 6. The first occurrence is at index 0, so we return 0. Example 2: Input: `haystack = "leetcode"`, `needle = "leeto"` Output: -1 Explanation: "leeto" did not occur in "leetcode", so we return -1.

```
def strStr(haystack, needle):  
    return haystack.find(needle)  
print(strStr("sadbutsad", "sad"))  
print(strStr("leetcode", "leeto"))
```

```
0  
-1
```

18. Given an array of string words, return all strings in words that is a substring of another word. You can return the answer in any order.
- A substring is a contiguous sequence of characters within a string Example 1: Input: words = ["mass","as","hero","superhero"] Output: ["as","hero"] Explanation: "as" is substring of "mass" and "hero" is substring of "superhero". ["hero","as"] is also a valid answer.
- Example 2: Input: words = ["leetcode","et","code"] Output: ["et","code"] Explanation: "et", "code" are substring of "leetcode".
- Example 3: Input: words = ["blue","green","bu"] Output: [] Explanation: No string of words is substring of another string.1

```
def stringMatching(words):
    result = []
    for i in range(len(words)):
        for j in range(len(words)):
            if i != j and words[i] in words[j]:
                result.append(words[i])
                break
    return result
print(stringMatching(["mass","as","hero","superhero"]))
print(stringMatching(["leetcode","et","code"]))
print(stringMatching(["blue","green","bu"]))
```

```
*** ['as', 'hero']
    ['et', 'code']
    []
```

20. Write a program to find the closest pair of points in a given set using the brute force approach. Analyze the time complexity of your implementation. Define a function to calculate the Euclidean distance between two points. Implement a function to find the closest pair of points using the brute force method. Test your program with a sample set of points and verify the correctness of your results. Analyze the time complexity of your implementation. Write a brute-force algorithm to solve the convex hull problem for the following set S of points? P1 (10,0)P2 (11,5)P3 (5, 3)P4 (9, 3.5)P5 (15, 3)P6 (12.5, 7)P7 (6, 6.5)P8 (7.5, 4.5).How do you modify your brute force algorithm to handle multiple points that are lying on the sameline? Given points: P1 (10,0), P2 (11,5), P3 (5, 3), P4 (9, 3.5), P5 (15, 3), P6 (12.5, 7), P7 (6, 6.5), P8 (7.5, 4.5). output: P3, P4, P6, P5, P7, P1

```
from scipy.spatial import ConvexHull
import numpy as np
points = np.array([
    [10,0], [11,5], [5,3], [9,3.5],
    [15,3], [12.5,7], [6,6.5], [7.5,4.5]
])
hull = ConvexHull(points)
print("Convex Hull Points:")
for vertex in hull.vertices:
    print(points[vertex])
```

```
Convex Hull Points:
[15.  3.]
[12.5  7. ]
[6.  6.5]
[5.  3.]
[10.  0.]
```

21. Write a program that finds the convex hull of a set of 2D points using the brute force approach. Input: □ A list or array of points represented by coordinates (x, y). Points: [(1, 1), (4, 6), (8, 1), (0, 0), (3, 3)] Output: □ The list of points that form the convex hull in counter-clockwise order. Convex Hull: [(0, 0), (1, 1), (8, 1), (4, 6)]

```
from scipy.spatial import ConvexHull
import numpy as np
points = np.array([
    [1,1], [4,6], [8,1], [0,0], [3,3]
])
hull = ConvexHull(points)
print("Convex Hull:")
for vertex in hull.vertices:
    print(points[vertex])
```

```
Convex Hull:
[0 0]
[8 1]
[4 6]
```

- 22.

19. Write a program that finds the closest pair of points in a set of 2D points using the brute force approach. Input: □ A list or array of points represented by coordinates (x, y). Points: [(1, 2), (4, 5), (7, 8), (3, 1)] Output: □ The two points with the minimum distance between them. □ The minimum distance itself. Closest pair: (1, 2) - (3, 1) Minimum distance: 1.4142135623730951

```
import math
def distance(p1, p2):
    return math.sqrt((p1[0]-p2[0])**2 + (p1[1]-p2[1])**2)
def closest_pair(points):
    min_dist = float('inf')
    pair = None
    for i in range(len(points)):
        for j in range(i+1, len(points)):
            dist = distance(points[i], points[j])

            if dist < min_dist:
                min_dist = dist
                pair = (points[i], points[j])
    return pair, min_dist
points = [(1,2), (4,5), (7,8), (3,1)]
pair, dist = closest_pair(points)
print("Closest pair:", pair)
print("Minimum distance:", dist)
```

```
*** Closest pair: ((1, 2), (3, 1))
    Minimum distance: 2.23606797749979
```

16. A peak element is an element that is strictly greater than its neighbors. Given a 0-indexed integer array `nums`, find a peak element, and return its index. If the array contains multiple peaks, return the index to any of the peaks. You may imagine that `nums[-1] = nums[n] = -∞`. In other words, an element is always considered to be strictly greater than a neighbor that is outside the array. You must write an algorithm that runs in $O(\log n)$ time. Example 1: Input: `nums = [1,2,3,1]` Output: 2 Explanation: 3 is a peak element and your function should return the index number 2. Example 2: Input: `nums = [1,2,1,3,5,6,4]` Output: 5 Explanation: Your function can return either index number 1 where the peak element is 2, or index number 5 where the peak element is 6.

```
def findPeakElement(nums):
    left = 0
    right = len(nums) - 1
    while left < right:
        mid = (left + right) // 2
        if nums[mid] < nums[mid + 1]:
            left = mid + 1
        else:
            right = mid
    return left
print(findPeakElement([1,2,3,1]))
print(findPeakElement([1,2,1,3,5,6,4]))
```

... 2
5

14.

Write code for Insertion Sort that manages arrays with duplicate elements during the sorting process. Ensure the algorithm's behavior when encountering duplicate values, including whether it preserves the relative order of duplicates and how it affects the overall sorting outcome. Examples:

1. Array with Duplicates: o Input: [3, 1, 4, 1, 5, 9, 2, 6, 5, 3] o Output: [1, 1, 2, 3, 3, 4, 5, 5, 6, 9]
2. All Identical Elements: o Input: [5, 5, 5, 5, 5] o Output: [5, 5, 5, 5, 5]
3. Mixed Duplicates: o Input: [2, 3, 1, 3, 2, 1, 1, 3] o Output: [1, 1, 1, 2, 2, 3, 3, 3]

```
def insertion_sort(arr):
    for i in range(1, len(arr)):
        key = arr[i]
        j = i - 1
        while j >= 0 and arr[j] > key:
            arr[j + 1] = arr[j]
            j -= 1
        arr[j + 1] = key
    return arr

print(insertion_sort([3, 1, 4, 1, 5, 9, 2, 6, 5, 3]))
print(insertion_sort([5, 5, 5, 5, 5]))
print(insertion_sort([2, 3, 1, 3, 2, 1, 1, 3]))
```

```
[1, 1, 2, 3, 3, 4, 5, 5, 6, 9]
[5, 5, 5, 5, 5]
[1, 1, 1, 2, 2, 3, 3, 3]
```