

Mobile Apps 2010 iPhone and Android

March 9, 2010

Norman McEntire, Founder
Servin Corporation - <http://servin.com>
Technology Training for Technology Professionals™
norman.mcentire@servin.com

Legal Info

- Android is a trademark of Google Inc.
- iPhone is a trademark of Apple Inc.
- Servin is a trademark of Servin Corporation.

About Servin Corporation

- Servin On-Site Training
 - “Get Your Development Team Up To Speed Fast!”
- Servin Web-Based Training
 - “Watch Code Written Before Your Eyes!”
- Servin Books
 - Books available on Amazon Kindle and Amazon Kindle Reader (iPhone, PC, Blackberry)
- Servin Apps
 - 25+ iPhone Apps in various categories

Servin On-Site Training

- “Get Your Development Team Up To Speed Fast!”
- iPhone Programming Courses
 - Intro and Advanced
- Android Programming Courses
 - Intro and Advanced
- Linux Programming Courses
 - Embedded Linux
 - Device Drivers
 - Services/Daemons

Servin Web-Based Training

- “Watch Code Written Before Your Eyes!”
 - Uses Cisco WebEx Player
 - Cisco WebEx Player supported on
 - Linux
 - Mac
 - Windows
- This demo/presentation is also available as Web-Based Training
 - <http://servin.com>

Servin Books

- Books available on [Amazon Kindle](#) and [Amazon Kindle Reader](#) (iPhone, PC, Blackberry)
 - iPhone [Objective-C 2.0](#) Programming Exercises
 - iPhone [Database](#) Programming Exercises: SQLite
 - iPhone [Camera](#) Programming Exercises
 - iPhone [External Accessory](#) Programming Exercises
 - iPhone Flashlight Programming Tutorial
 - iPhone 3 Programming Templates Explained
 - Red Hat Enterprise Linux 5 Admin Skills
 - SUSE Linux Enterprise Server 11 Admin Skills

Servin Apps

25+ iPhone Apps

- Technology Professionals
 - [Device Info Plus](#)
 - Device ID Info, Font Info, CPU Info, Network Info, and more!
 - [Accelerometer Fun](#)
 - Display, record, and export accelerometer info
 - [Process Log](#)
 - Display list of processes
- Health/Fitness
 - [Weight Log Simple](#) – keep log of your weight
 - [Sleep Log Simple](#) – keep log of your sleep
- Games and Entertainment
 - [Touch Fast](#) – how fast can you touch the screen?
 - [Simon Says Face Up](#) – can you do as simon says?

UCSD Extension Courses

- These courses are taught by Norman McEntire and fill up quickly so register early
 - iPhone Programming: Touch, Sound, and More!
 - Spring 2010 Session: April 7 – June 2
 - Wednesdays, 6PM - 9PM
 - Introduction to Objective-C
 - Spring 2010 Session: April 8 – June 3
 - Thursdays, 7pm – 9:50pm
 - iPhone Programming: Advanced
 - Summer 2010 Session: Watch Catalog for Dates/Times

Opening Remarks

- Welcome!
- Thank you!
- My Promise To You
 - Show you Mobile App Development 2010!
 - iPhone OS SDK 3.2 Beta 3 (includes iPad)
 - Android SDK 2.1
- My style
 - Show a few slides
 - Do lots of live demos
 - Questions at anytime are great!

PDF Slides and WebEx Recording Will Be Posted on <http://servin.com>

- My goal is to show you, ***faster than any method on planet earth***, how to use both the iPhone SDK and the Android SDK
 - The tools. The Methods. The Source Code.
- This demo is fast paced but PDF slides and WebEx recording will be posted on <http://servin.com>
 - The PDF Slides include the source code
 - The WebEx Recording can be paused/replayed

Demo is very focused.

Here are the Guideposts

- Guidepost #1
 - Use only the **latest native SDKs** downloaded March 2010
 - iPhone OS SDK 3.2 Beta 3 (iPhone, iPod Touch, iPad)
 - Android SDK 2.1
- Guidepost #2.
 - Make **zero changes or modifications** to the native SDKs
 - use the defaults as they come
- Guidepost #3.
 - Use **no 3rd party tools or add-ons** – just the SDKs

Briefly...because the question always comes up...

- Question: Are there alternatives to using the native SDKs?
- Answer: Yes. Many alternatives, but that is not the focus of this demo/presentation.
- Some alternatives to native SDKs – great topics for other SDSIC speakers
 - Rhomobile.com - “HTML + Ruby” Native Apps
 - PhoneGap.com - “HTML + JavaScript” Native Apps
 - MonoTouch.net - “C#” Native Apps

Introducing the SDKs

iPhone SDK 3.2 Beta 3

- Hardware Requirements
 - Mac (running Mac OS 10.6 Snow Leopard)
- Membership Requirements
 - To download SDK
 - Register as **Apple Developer**. Free registration.
 - To run on device and submit to store
 - Join iPhone Developer Program. Yearly fee.
- Software Requirements
 - iPhone SDK. Includes everything.

Android SDK 2.1

- Hardware Requirements
 - Any Hardware running Linux, Mac, or Windows
- Membership Requirements
 - To download SDK: None
 - To run on device: None
 - To submit to store: Small One-Time Fee
- Software Requirements
 - Java SDK + Java IDE for Eclipse + Android SDK + Android Plugin for Eclipse


Time for the Demos!

Demo 1


Building the Default App

Demo 1: iPhone SDK

Xcode: File > New Project





Demo 1: iPhone SDK Xcode IDE



Demo 1: iPhone SDK

iPhone Simulator – iPad Mode



Demo 1: iPhone SDK

iPhone Simulator – iPhone Mode



User Interface Observations

1. Status bar at top

2. Single Home Button at bottom

Demo 1: Android SDK

Eclipse: New Android Project

The screenshot shows the 'New Android Project' dialog box in the Eclipse IDE. The dialog is titled 'New Android Project' and has a subtitle 'Creates a new Android Project resource.' with an Android logo icon.

Project name: SDSIC

Contents

- ☒ Create new project in workspace
- ☐ Create project from existing source
- ☒ Use default location

Location: / [text box] **Browse...**

☐ Create project from existing sample

Samples: MapsDemo

Build Target

Target Name	Vendor	Platform	API
<input type="checkbox"/> Android 2.1	Android Open Source Project	2.1	7
<input checked="" type="checkbox"/> Google APIs	Google Inc.	2.1	7

Android + Google APIs

Properties

Application name: SDSIC


Package name: com.servin.android.sdsic

☒ **Create Activity:** Demo

Min SDK Version: 7

Buttons at the bottom: ? < Back Next > Cancel Finish

Demo 1: Android SDK Eclipse IDE



Demo 1: Android SDK Android Emulator



User Interface Observations

1. Status bar at top
2. Title Bar
3. Multiple Buttons
 - Home
 - Menu
 - Return
 - Search
 - D-Pad (Directional Pad)
 - Others
4. Keyboard

Demo 2

Application Startup and Logging

Demo 2: iPhone SDK

Logging: NSLog() - C Function

```
// SDSICAppDelegate.m
```

...code not shown...

```
- (BOOL)application:(UIApplication *)application  
    didFinishLaunchingWithOptions:(NSDictionary *)launchOptions {
```

```
    // Log a startup message  
    NSLog(@"Application Startup!");  
    NSLog(@"application: %@", [application description]);  
    NSLog(@"launchOptions: %@", [launchOptions description]);
```


```
    [window addSubview:viewController.view];  
    [window makeKeyAndVisible];
```

```
    return YES;
```

```
}
```

Demo 2: iPhone SDK

Xcode: Run > Console



Demo 2: Android SDK

Logging: Log.v() - Java Class

```
// Demo.java
```

```
...code not shown...
```

```
public class Demo extends Activity {  
    private static final String TAG = "SDSIC";  
  
    @Override  
    public void onCreate(Bundle savedInstanceState) {  
        super.onCreate(savedInstanceState);
```

```
        // Log a startup message  
        Log.v(TAG, "Application Startup!");  
        Log.v(TAG, "savedInstanceState: " +  
            savedInstanceState.toString());  
        setContentView(R.layout.main);
```


```
    }
```

```
}
```

This code crashes if
savedInstanceState is
NULL. That is part of
the demo...


Demo 2: Android SDK

Eclipse: Window > Show View > Other



The LogCat view shows messages output from the Log class

Demo 2: Android SDK Eclipse: LogCat After Running




Demo 3

Debugging


Demo 3: iPhone SDK

Xcode: Debugger



Demo 3: Android SDK

Eclipse: Debug Perspective



Demo 4

Create UITextView/TextView at Runtime

iPhone: UITextView
Android: TextView

Demo 4: iPhone SDK UITextView at Runtime

- (BOOL)application:(UIApplication *)application
didFinishLaunchingWithOptions:(NSDictionary *)launchOptions {

...code not shown...

```
CGRect frame = viewController.view.bounds;
UITextView *myTextView =
    [[UITextView alloc] initWithFrame:frame];
myTextView.text = @"SDSIC Demo\n"
    @"This is a test\nBe at your best";
myTextView.editable = NO;
[viewController.view addSubview:myTextView];
```

```
[window addSubview:viewController.view];
[window makeKeyAndVisible];
```

```
return YES;
```

```
}
```

Demo 4: iPhone SDK UITextView at Runtime



Demo 4: Android SDK TextView at Runtime

// Demo.java

...code not shown...


```
public void onCreate(Bundle savedInstanceState) {  
    super.onCreate(savedInstanceState);
```

...code not shown

```
    TextView myTextView = new TextView(this);  
    myTextView.setText("SDIC Demo\n" +  
        "This is a test\nBe at your best.");  
    this.setContentview(myTextView);
```

```
}
```



Demo 4: Android SDK TextView at Runtime




Demo 5

Create UIButton/Button using Layout Tools


Demo 5: iPhone SDK Interface Builder and UIButton




Demo 5: iPhone SDK Running the App



Demo 5: Android SDK Eclipse: XML Layout



Demo 5: Android SDK Running the App



Demo 6

Change Value of UIButton/Button At Runtime

Demo 6: iPhone SDK

IBOutlet - SDSICViewController.h

```
// SDSICViewController.h

#import <UIKit/UIKit.h>

@interface SDSICViewController : UIViewController {

    IBOutlet UIButton *myButton;

}
```

Demo 6: iPhone SDK SDSICViewController.m

```
// SDSICViewController.m

#import "SDSICViewController.h"

@implementation SDSICViewController

- (void)viewDidLoad {
    [super viewDidLoad];

    [myButton setTitle:@"0" forState:UIControlStateNormal];
}

@end
```

Demo 6: iPhone SDK Interface Builder - Control-Click-Drag



To connect the IBOutlet:
Control-Click-Drag
FROM File's Owner
TO the UIButton.

Demo 6: iPhone SDK Running



Demo 6: Android SDK Button As Runtime

```
package com.servin.android.mon2;
```

```
...code not shown...
```

```
public class Demo extends Activity {
```

```
    private Button myButton;
```

```
    @Override
```

```
    public void onCreate(Bundle savedInstanceState) {  
        super.onCreate(savedInstanceState);  
        setContentView(R.layout.main);
```

```
        myButton = (Button) this.findViewById(R.id.Button01);  
        myButton.setText("0");
```

```
    }
```

```
}
```

Demo 6: Android SDK Button As Runtime



Demo 7

Handle UIButton/Button Events

Demo 7: iPhone SDK

IBOutlet - SDSICViewController.h

```
// SDSICViewController.h

#import <UIKit/UIKit.h>

@interface SDSICViewController : UIViewController {

    IBOutlet UIButton *myButton;

    int counter;

}

-(IBAction) doButton;

@end
```

Demo 7: iPhone SDK


SDSICViewController.m

```
// SDSICViewController.m
```

...code not shown...

```
-(IBAction) doButton {  
    counter++;  
    NSString *s = [NSString stringWithFormat:@"%d", counter];  
    [myButton setTitle:s forState:UIControlStateNormal];  
}
```

Demo 7: iPhone SDK Interface Builder - Control-Click-Drag



To connect the IBAction:
Control-Click-Drag
FROM UIButton
TO File's Owner.

Demo 7: iPhone SDK Running



Demo 7: Android SDK

Demo.java - 1

```
public class Demo extends Activity
    implements OnClickListener {
    private Button button;
    private int counter;
```

@Override

```
public void onCreate(Bundle savedInstanceState) {
    super.onCreate(savedInstanceState);

    setContentView(R.layout.main);
    button = (Button) this.findViewById(R.id.Button01);
    button.setText("0");
```

```
button.setOnClickListener(this);
```

```
}
```


Demo 7: Android SDK

Demo.java - 2

```
@Override
public void onClick(View v) {
    Counter++;
    // Either method will work
    //myButton.setText(String.format("%d", counter));
    myButton.setText("" + counter);
}
```

Demo 7: Android SDK Button As Runtime



We Are Done!

Thank You!