

Skill-6

Program:

```
tejaswini@teju: ~/OS_Lab/skil  ×  +  ∨
GNU nano 8.7.1 skill_6.c *
#include <stdio.h>
#include <unistd.h>
#include <sys/wait.h>
#include <string.h>
#include <stdlib.h>
int main() {
    char command[100];
    printf("Enter command: ");
    fgets(command, sizeof(command), stdin);

    command[strcspn(command, "\n")] = '\0';

    pid_t pid = fork();

    if (pid < 0) {
        perror("fork");
        return 1;
    }

    if (pid == 0) {
        char *args[20];
        int i = 0;

        char *token = strtok(command, " ");

        while (token != NULL && i < 19) {
            args[i++] = token;
            token = strtok(NULL, " ");
        }

        args[i] = NULL;

        execvp(args[0], args);

        perror("execvp failed");
        exit(1);
    } else {
        wait(NULL);
        printf("Command execution completed.\n");
    }

    return 0;
}
```

Output:

```
tejaswini@teju:~/OS_Lab/skill$ gcc skill_6.c -o skill_6
tejaswini@teju:~/OS_Lab/skill$ ./skill_6
Enter command: ls
child_process child_process.c escape_sequence escape_sequence.c prog1 prog1.c prog1.c.save prog2 prog2.c skill_5 skill_5.c skill_6 skill_6.c
Command execution completed.
tejaswini@teju:~/OS_Lab/skill$ |
```