

Lec 04: FOR-Loops

Approximating π

Suppose the circle $x^2 + y^2 = n^2$, $n \in \mathbb{N}$, is drawn on graph paper.

- The area of the circle can be approximated by counting the number uncut grids, N_{in} .

$$\pi n^2 \approx N_{\text{in}},$$


and so

$$\pi \approx \frac{N_{\text{in}}}{n^2}.$$

- Using symmetry, may only count the grids in the first quadrant and modify the formula accordingly:

$$\pi \approx \frac{4N_{\text{in},1}}{n^2},$$

where $N_{\text{in},1}$ is the number of inscribed grids in the first quadrant.



Approximating π

Problem Statement

Write a script that inputs an integer n and displays the approximation of π by

$$\rho_n = \frac{4N_{\text{in},1}}{n^2},$$

along with the (absolute) error $|\rho_n - \pi|$.

Note. The approximation gets enhanced and approaches the true value of π as $n \rightarrow \infty$.

Strategy: Iterate

The key to this problem is to count the number of uncut grids in the first quadrant programmatically.

Set $N_{in,1} = 0$.


Count the number of uncut grids
in row 1. Add that to $N_{in,1}$.

Count the number of uncut grids
in row 2. Add that to $N_{in,1}$.

\vdots

Count the number of uncut grids
in row 10. Add that to $N_{in,1}$.

Set $\rho_{10} = 4N_{in,1}/10^2$.



MATLAB Way

The repeated counting can be delegated to MATLAB using `for`-loop. The procedure outlined above turns into

Assume `n` is initialized and set $N_{\text{in},1}$ to zero.

for `k = 1:n`

Count the number of uncut grids
in row `k`. Add that to $N_{\text{in},1}$.

end

Set $\rho_{10} = 4N_{\text{in},1}/10^2$.

Counting Uncut Tiles

The problem is reduced to counting the number of uncut grids in each row.


- The x -coordinate of the intersection of the top edge of the k th row and the circle $x^2 + y^2 = n^2$ is

$$x = \sqrt{n^2 - k^2}.$$

- The number of uncut grids in the k th row is the largest integer less than or equal to this value, i.e.,

$$\lfloor \sqrt{n^2 - k^2} \rfloor. \quad (\text{floor function})$$

- MATLAB provides `floor`.



For $n = 10$ and $k = 5$:

$$\begin{aligned} x &= \sqrt{n^2 - k^2} \\ &= \sqrt{10^2 - 5^2} = 8.6602 \dots \end{aligned}$$

Main Fragment Using FOR-Loop

```
N1 = 0;  
for k = 1:n  
    m = floor(sqrt(n^2 - k^2));  
    N1 = N1 + m;  
end  
rho_n = 4*N1/n^2;
```

Exercise. Complete the program.

Exercise 1: Overestimation

Question

Note that ρ_n is always less than π . If N_1 denotes the total number of grids, both cut and uncut, within the quarter disk, then $\mu_n = 4N_1/n^2$ is always larger than π . Modify the previous (complete) script so that it prints ρ_n , μ_n , and $\mu_n - \rho_n$.

- `ceil`, an analogue of `floor`, is useful.

Notes on FOR-Loop

- The construct is used when a code fragment needs to be repeatedly run. The number of repetition is known in advance.

```
for <loop variable> = 1:<arithmetic expression>  
    <code fragment>  
end
```

- Examples:

```
for k = 1:3  
    fprintf('k = %d\n', k)  
end
```

```
nIter = 100;  
for k = 1:nIter  
    fprintf('k = %d\n', k)  
end
```

Caveats

Run the following script and observe the displayed result.

```
for k = 1:3
    disp(k)
    k = 17;
    disp(k)
end
```

- The loop header `k = 1:3` guarantees that `k` takes on the values 1, 2, and 3, one at a time even if `k` is modified within the loop body.
- However, it is a recommended practice that the value of the loop variable is *never* modified in the loop body.

Simulation Using `rand`

`rand` is a built-in function which generate a (uniform) “random” number between 0 and 1. Try:

```
for k = 1:10
    x = rand();
    fprintf('%10.6f\n', x);
end
```

Let's use this function to solve:

Question

A stick with length 1 is split into two parts at a random breakpoint. *On average*, how long is the shorter piece?

Program Development – Single Instance

Consider breaking *one* stick.

- Random breakage can be simulated with `rand`; denote by $x \in (0, 1)$.
- The length of the shorter piece can be determined using `if`-construct; denote by $s \in (0, 1/2)$.

```
x = rand();           % x: the location of breakage
if x <= 0.5            % if  $x \leq 0.5$ 
    s = x;             % shorter part has length  $x$ 
else                  % otherwise
    s = 1-x           % shorter part has length  $1-x$ 
end
```

Program Development – Multiple Instances

- Repeat the previous multiple times using a `for`-loop. Pseudocode: if 1000 breaks are to be simulated:

```
nBreaks = 1000;  
for k = 1:nBreaks  
    <code from previous page>  
end
```

- But how are calculating the *average* length of the shorter pieces?

Calculating Average Using Loop

Recall how the total number of uncut grids were calculated using iterations.

Assume n is initialized and set $N_{in,1}$ to zero.

for $k = 1:n$

Count the number of
uncut grids in row k .
Add that to $N_{in,1}$.

end

The value of $N_{in,1}$ is the total numbers
of uncut grids.

Similarly, we can compute an average
by:

Assume n is initialized and set s to
zero.

for $k = 1:n$

Simulate a break and
find the length of the
shorter piece. Add that
to s .

end

Set $s_{avg} = s/n$.

Complete Solution

```
nBreaks = 1000;  
s = 0;  
for k = 1:nBreaks  
    x = rand();  
    if x <= 0.5  
        s = s + x;  
    else  
        s = s + (1-x);  
    end  
end  
s_avg = s/nBreaks;
```

Exercise 2: Game of 3-Stick

Game: 3-Stick

Pick three sticks each having a random length between 0 and 1. You win if you can form a triangle using the sticks; otherwise, you lose.

Question

Estimate the probability of winning a game of 3-Stick by simulating one million games and counting the number of wins^a.

^aOf course, divide it by 1,000,000 to calculate the probability

