# **Conditioning of Square Linear Systems**

#### **Contents**

O Vector and Matrix Norms

2 Conditioning

## **Vector and Matrix Norms**

#### **Vector Norms**

The "length" of a vector v can be measured by its norm.

#### Definition 1 (*p*-Norm of a Vector)

Let  $p \in [1, \infty)$ . The p-norm of  $\mathbf{v} \in \mathbb{R}^m$  is denoted by  $\|\mathbf{v}\|_p$  and is defined by

$$\|\mathbf{v}\|_p = \left(\sum_{i=1}^m |v_i|^p\right)^{1/p}.$$

When  $p = \infty$ ,

$$\|\mathbf{v}\|_{\infty} = \max_{1 \leqslant i \leqslant m} |v_i| .$$

The most commonly used p values are 1, 2, and  $\infty$ :


$$\|\mathbf{v}\|_1 = \sum_{i=1}^m |v_i|\,, \quad \|\mathbf{v}\|_2 = \sqrt{\sum_{i=1}^m |v_i|^2}.$$
 Figure an .

#### **Vector Norms**

In general, any function  $\|\cdot\|:\mathbb{R}^m\to\mathbb{R}^+\cup\{0\}$  is called a **vector norm** if it satisfies the following three properties:

- $2 \|\alpha \mathbf{x}\| = |\alpha| \|\mathbf{x}\|$  for any constant  $\alpha$  and any  $\mathbf{x} \in \mathbb{R}^m$ .
- 3  $\|\mathbf{x} + \mathbf{y}\| \le \|\mathbf{x}\| + \|\mathbf{y}\|$  for any  $\mathbf{x}, \mathbf{y} \in \mathbb{R}^m$ . This is called the *triangle inequality*.





Examples Let 
$$\vec{V} = \begin{bmatrix} 6 \\ -3 \\ 93 \\ 5 \end{bmatrix}$$
.  $(90+3)^{2} = 8100 + 540 + 9$ 

= 6 + 3 + 93 + 5 = 107

#### **Unit Vectors**

- A vector  $\mathbf{u}$  is called a **unit vector** if  $\|\mathbf{u}\| = 1$ .
- Depending on the norm used, unit vectors will be different.
- For instance:  $\mathbb{R}^2$




Figure 1: 1-norm




Figure 2: 2-norm




Figure 3: ∞-norm

$$P = 2 \quad \vec{u} = \begin{bmatrix} u_1 \\ u_2 \end{bmatrix} \quad \text{is a unit vector in 2-norm, that is,}$$

$$1 = ||\vec{u}||_2 = \sqrt{u_1^2 + u_2^2} \implies u_1^2 + u_2^2 = 1 \quad \text{(unit circle)}$$

$$1 = \|\vec{u}\|_{2} = \sqrt{u_{1}^{2} + u_{2}^{2}} \implies u_{1}^{2} + u_{2}^{2} = 1 \quad (\text{unit circle})$$

$$P = 1$$

$$1 = \|\vec{u}\|_{1} = |u_{1}| + |u_{2}| \implies \pm u_{1} \pm u_{2} = 1$$

$$||u_{2}|| = ||u_{1}||_{2} =$$

#### **Matrix Norms**

The "size" of a matrix  $A \in \mathbb{R}^{m \times n}$  can be measured by its **norm** as well. As above, we say that a function  $\|\cdot\|: \mathbb{R}^{m \times n} \to \mathbb{R}^+ \cup \{0\}$  is a **matrix norm** if it satisfies the following three properties:

- **1** ||A|| = 0 if and only if A = 0.
- 2  $\|\alpha A\| = |\alpha| \|A\|$  for any constant  $\alpha$  and any  $A \in \mathbb{R}^{m \times n}$ .
- 3  $\|A+B\| \le \|A\| + \|B\|$  for any  $A,B \in \mathbb{R}^{m \times n}$ . This is called the *triangle inequality*.

#### Matrix Norms (cont')

If, in addition to satisfying the three conditions, it satisfies

$$\|AB\|\leqslant \|A\|\,\|B\|\quad \text{ for all }A\in\mathbb{R}^{m\times n}\text{ and all }B\in\mathbb{R}^{n\times p}\text{,}$$

it is said to be consistent.

• If, in addition to satisfying the three conditions, it satisfies

then we say that it is **compatible** with a vector norm.

#### **Induced Matrix Norms**

#### Definition 2 (p-Norm of a Matrix)


Let  $p \in [1, \infty]$ . The *p*-norm of  $A \in \mathbb{R}^{m \times n}$  is given by

$$\|A\|_p = \max_{\mathbf{x} \neq 0} \frac{\|A\mathbf{x}\|_p}{\|\mathbf{x}\|_p} = \max_{\|\mathbf{x}\|_p = 1} \|A\mathbf{x}\|_p.$$

$$\max_{\mathbf{x} \in \text{over all }} \max_{\mathbf{x} \in \text{over all }}$$

- The definition of this particular matrix norm is induced from the vector p-norm.
- By construction, matrix p-norm is a compatible norm. It is also consistent.
- Induced norms describe how the matrix stretches unit vectors with respect to the vector norm.

Example p=2, M=2 (i.e., 2-0)



#### **Induced Matrix Norms**

The commonly used p-norms (for  $p = 1, 2, \infty$ ) can also be calculated by

$$\|A\|_{1} = \max_{1 \leq j \leq n} \sum_{i=1}^{m} |a_{ij}|, \qquad \qquad > \qquad \max \left( \operatorname{sum} \left( \operatorname{abs} \left( A \right), \right) \right)$$

$$\|A\|_{2} = \sqrt{2} \operatorname{max} \left( A^{\mathrm{T}} A \right) = \operatorname{com}(A), \qquad > > \qquad \operatorname{sqrt} \left( \operatorname{max} \left( \operatorname{eig} \left( A' + A \right) \right) \right)$$

$$\|A\|_{\infty} = \max_{1 \leq i \leq m} \sum_{j=1}^{n} |a_{ij}|. \qquad > > \qquad \operatorname{max} \left( \operatorname{sum} \left( \operatorname{abs}(A), 2 \right) \right)$$

In words,

- The 1-norm of A is the maximum of the 1-norms of all column vectors.
- The 2-norm of A is the square root of the largest eigenvalue of  $A^{T}A$ .
- The  $\infty$ -norm of A is the maximum of the 1-norms of all row vectors.

#### Non-Induced Matrix Norm - Frobenius Norm

#### Definition 3 (Frobenius Norm of a Matrix)

The Frobenius norm of  $A \in \mathbb{R}^{m \times n}$  is given by

$$A \in \mathbb{R}^{m \times n}$$
 is given by  $A = \left(\sum_{i=1}^{m} \sum_{j=1}^{n} |a_{ij}|^2\right)^{1/2}$ .  $A = \left(\sum_{i=1}^{m} \sum_{j=1}^{n} |a_{ij}|^2\right)^{1/2}$ .

- This is not induced from a vector p-norm.
- However, both p-norm and the Frobenius norm are consistent and compatible.
- For compatibility of the Frobenius norm, the vector norm must be the vector-norm, that is,  $\|A\mathbf{x}\|_2 \leqslant \|A\|_F \|\mathbf{x}\|_2$ .

#### Norms in MATLAB

norm (A): 2-norm by default.

 $\frac{\vec{V}^T \vec{V}}{\sqrt{N}} = [v_1 \cdots v_N] \begin{bmatrix} v_1 \\ \vdots \\ \vdots \end{bmatrix} = \frac{v_1^2 + \cdots + v_N^2}{N}$ 

• Vector *p*-norms can be easily computed:

• The same function norm is used to calculate matrix *p*-norms:

To calculate the Frobenius norm:

```
norm(A, 'fro') % = sqrt(A(:)'*A(:))
% = norm(A(:), 2)
```

# Conditioning

## Conditioning of Solving Linear Systems: Overview

- Analyze how robust (or sensitive) the solutions of  $\underline{A}\mathbf{x} = \mathbf{b}$  are to perturbations of A and  $\mathbf{b}$ .
- Inputs: A, B
  Outputs: X

- For simplicity, consider separately the cases where
  - **1** b changes to  $\mathbf{b} + \delta \mathbf{b}$ , while A remains unchanged, that is

$$A\mathbf{x} = \mathbf{b} \longrightarrow A(\mathbf{x} + \delta \mathbf{x}) = \mathbf{b} + \delta \mathbf{b}.$$

2 A changes to  $A + \delta A$ , while b remains unchanged, that is

$$A\mathbf{x} = \mathbf{b} \longrightarrow (A + \delta A)(\mathbf{x} + \delta \mathbf{x}) = \mathbf{b}.$$

· Assume the matrix norm used is consistent and compatible.

## Sensitivity to Perturbation of RHS

Case 1. 
$$A\mathbf{x} = \mathbf{b} \rightarrow A(\mathbf{x} + \delta \mathbf{x}) = \mathbf{b} + \delta \mathbf{b}$$

• Bound  $\|\delta \mathbf{x}\|$  in terms of  $\|\delta \mathbf{b}\|$ :

$$A\mathbf{x} + A\delta\mathbf{x} = \mathbf{b} + \delta\mathbf{b}$$

$$A\delta\mathbf{x} = \delta\mathbf{b} \qquad \Longrightarrow \qquad \|\delta\mathbf{x}\| \le \|A^{-1}\| \|\delta\mathbf{b}\|.$$

$$\delta\mathbf{x} = A^{-1}\delta\mathbf{b}$$

Sensitivity in terms of relative errors:

$$\frac{\frac{\|\delta \mathbf{x}\|}{\|\mathbf{x}\|}}{\frac{\|\delta \mathbf{b}\|}{\|\mathbf{b}\|}} = \frac{\|\delta \mathbf{x}\| \|\mathbf{b}\|}{\|\delta \mathbf{b}\| \|\mathbf{x}\|} \le \frac{\|A^{-1}\| \|\delta \mathbf{b}\| \cdot \|A\| \|\mathbf{x}\|}{\|\delta \mathbf{b}\| \|\mathbf{x}\|} = \|A^{-1}\| \|A\|.$$

## Sensitivity to Perturbation of Matrix

Case 2. 
$$A\mathbf{x} = \mathbf{b} \rightarrow (A + \delta A)(\mathbf{x} + \delta \mathbf{x}) = \mathbf{b}$$

• Bound  $\|\delta \mathbf{x}\|$  now in terms of  $\|\delta A\|$ :

$$A\mathbf{x} + A\delta\mathbf{x} + (\delta A)\mathbf{x} + (\delta A)\delta\mathbf{x} = \mathbf{b}$$

$$A\delta\mathbf{x} = -(\delta A)\mathbf{x} - (\delta A)\delta\mathbf{x}$$

$$\delta\mathbf{x} = -A^{-1}(\delta A)\mathbf{x} - A^{-1}(\delta A)\delta\mathbf{x}$$

$$||\delta\mathbf{x}|| \lesssim ||A^{-1}|| ||\delta A|| ||\mathbf{x}||.$$
(first-order truncation)

Sensitivity in terms of relative errors:

$$\frac{\frac{\|\delta \mathbf{x}\|}{\|\mathbf{x}\|}}{\frac{\|\delta A\|}{\|A\|}} = \frac{\|\delta \mathbf{x}\| \|A\|}{\|\delta A\| \|\mathbf{x}\|} \lesssim \frac{\|A^{-1}\| \|\delta A\| \|\mathbf{x}\| \cdot \|A\|}{\|\delta A\| \|\mathbf{x}\|} = \|A^{-1}\| \|A\|.$$

#### **Matrix Condition Number**

 Motivated by the previous estimations, we define the matrix condition number by

$$\kappa(A) = ||A^{-1}|| ||A||,$$

where the norms can be any p-norm or the Frobenius norm.

• A subscript on  $\kappa$  such as 1, 2,  $\infty$ , or F(robenius) is used if clarification is needed.

#### Matrix Condition Number (cont')

We can write

$$\frac{\|\delta \mathbf{x}\|}{\|\mathbf{x}\|} \leqslant \kappa(A) \frac{\|\delta \mathbf{b}\|}{\|\mathbf{b}\|}, \quad \frac{\|\delta \mathbf{x}\|}{\|\mathbf{x}\|} \leqslant \kappa(A) \frac{\|\delta A\|}{\|A\|},$$

where the second inequality is true only in the limit of infinitesimal perturbations  $\delta A$ .

- The matrix condition number  $\kappa(A)$  is equal to the condition number of solving a linear system of equation  $A\mathbf{x} = \mathbf{b}$ .
- The exponent of  $\kappa(A)$  in scientific notation determines the approximate number of digits of accuracy that will be lost in calculation of  $\mathbf{x}$ .
- Since  $1 = ||I|| = ||A^{-1}A|| \le ||A^{-1}|| ||A|| = \kappa(A)$ , a condition number of 1 is the best we can hope for.
- If  $\kappa(A) > \text{[eps]}^{-1}$ , then for computational purposes the matrix is singular.

#### **Condition Numbers in MATLAB**

• Use cond to calculate various condition numbers:

```
cond(A) % the 2-norm; or cond(A, 2)
cond(A, 1) % the 1-norm
cond(A, Inf) % the infinity-norm
cond(A, 'fro') % the Frobenius norm
```

A condition number estimator (in 1-norm)

```
condest(A) % faster than cond
```

 The fastest method to estimate the condition number is to use linsolve function as below:

```
[x, inv_condest] = linsolve(A, b);
fast_condest = 1/inv_condest;
```