

360AP CISCO MPP Audio Call

Test Plan Name: CiscoMPP_AudioCall_TestSuite

Introduction

> This test plan pertains to Cisco regression testing of call features, with test calls conducted between Cisco MPP phones utilizing the Tekvizion Automation Platform. To use this test plan effectively, the following steps must be followed:

Prerequisites:

- > The Test Plan Required minimum of 4 MPP phones.
- The minimum software version on the MPP phones for use with the 360 Automation Platform is **11.3.1** and higher.
- "Dial Plan" should be configured in MPP phone as below.

 - ⇒ Login to MPP phone-> Admin-> Advanced-> Voice-> Ext1 -> Dial Plan.
- "Auto Answer" should be disabled for all the respective MPP phones.
- ➤ WebSocket connection should be established between tap and MPP phone. (This applies for all available phones. Refer "360 Automation Platform Prerequisites Document -> Section No. 2.Prerequisites on MPP -> Pg No.2")
 - i. Access the phone Web UI: /admin/advanced.
 - ii. Navigate to Voice-> Phone-> WebSocket API fields a. Configure the Control Server URL to: ws://:80/onPOINTLink/sockserver b. Allowed APIs: .*
 - iii. Upon completing the aforementioned configuration, the respective MPP phones should be displayed in "Phone Manager" under "Unmanaged."
- Speed Dial number should be configured in MPP phone. It can be configured in TAP as well as below. (Reference "360 Automation Platform User Guide -> Section 7.11 Visual Device Management-> Pg No. 33")

Copyright © 2023 by TekVizion PVS, Inc. All Rights Reserved.

TekVizion reserves the right to modify Cisco MPP Audio Call Regression Testing as a Service and the descriptions herein may vary from actual service delivery. Consult Service Terms and Conditions for up-to-date information.

- Navigate to Phone Manager on TAP->Click the ellipsis of the MPP phone -> Visual Device Management -> Speed Dial dropdown-> Enter the Extension/DID of 'a' variable-> Apply Changes.
- > Feature Access Codes should work for all the MPP phones to test the features below.
 - i. Call Park (*68) and Retrieve (*88).
 - ii. Call Forward Always (Activate -*72, Deactivate-*73)
 - iii. Call Forward Busy (Activate -*90, Deactivate-*91)
 - iv. Call Forward NoAnswer (Activate -*92, Deactivate-*93)
 - v. Redial (*66).
 - vi. Return (*69).
 - vii. Cancel Call Waiting (*70).
 - viii. Do not disturb (Activate -*78, Deactivate-*79).
 - ix. Call Pickup (*98).
- > Call Pickup should be configured as below.
 - i. In BWKS Navigate to Enterprise/Service provider user group
 - ii. Services >> call pickup >> Add >> Group Name>> Search User >> Add >> ok.
 - iii. Assign the Call pickup service to variable phone A and B as per the test Plan.

Broadworks_Services:

> In accordance with the **Test Plan**, the following BroadWorks services must be enabled for the corresponding Cisco MPP phone variables in order to conduct comprehensive testing.

Phone Variables	BWK Services
	Calling Name Delivery
	2. Calling Number Delivery
	3. Three-Way Call
	4. Call Waiting
	5. Call Transfer
	6. Call Forwarding Busy
	7. Call Forwarding Always
	8. Call Forwarding No Answer
	9. Do Not Disturb
	10. Last Number Redial
DUT	11. Anonymous Call Rejection.
	Calling Name Delivery
	2. Calling Number Delivery
	3. Three-Way Call
	4. Call Waiting
	5. Call Transfer
	6. Call Forwarding Busy
	7. Call Forwarding Always
	8. Call Forwarding No Answer
	9. Do Not Disturb
	10. Call Return
Α	11. Call Pickup.
	Calling Name Delivery
	2. Calling Number Delivery
	3. Three-Way Call
	4. Call Waiting
В	5. Call Pickup
	Calling Name Delivery
	2. Calling Number Delivery
С	3. Call Waiting.