

DocuPrint P225 d / P265 dw / M225 dw / M225 z / M265 z A4 Monochrome Printers

Delivering performance and productivity with clever connectivity



Powerful, efficient performers

The Fuji Xerox DocuPrint P225 d / P265 dw / M225 dw / M225 z / M265 z are the perfect solution for personal use or small workgroups requiring high quality, efficient monochrome printing together with flexible connectivity capabilities.

Performance and reliability

- **Speed and quality.** With a print resolution of up to 2400 x 600 dpi and printing speeds of 26 ppm across the 225 Series, and 30 ppm for the 265 Series, they deliver quality print results fast.
- All-in-one functionality. Multifunction models allow you to print, copy, scan and fax* in an efficient, low cost device giving you maximum productivity.
- Clever features for reliable operation.
 Fuji Xerox is renowned for reliable printing.
 The DocuPrint P225 d / P265 dw / M225 dw /
 M225 z / M265 z are no exception with
 simple engineering and clever new ideas
 designed for trouble-free printing.

*Only available on DocuPrint M225 z / M265 z

Affordable, efficient printing

- Low cost hardware is only half of the story. Thanks to the separate toner and drum cartridge, you will only ever have to replace one component at a time. This results in maximum use of each component, longer operating times and cost savings.
- Save toner save cost. Toner save mode extends the life of the toner cartridge by varying the density of toner that is printed on a page.
- Use less paper and toner. The built in N-UP print feature gives users the ability to save on paper and toner by printing multiple pages on a single sheet of paper. This also reduces the overall cost of printing.



Easily connect and print via your iOS or Android devices

AirPrint and Google Cloud Print Ready



AirPrint^{\mathbb{M}} and Google Cloud Print^{\mathbb{M}} enables you to print directly from your mobile device without the need to download mobile apps or to install print drivers.





Wi-Fi Direct

The DocuPrint P265 dw / M225 dw / M225 z / M265 z are Wi-Fi Direct™ certified, allowing devices to connect and print easily without requiring a wireless access point.



Print Utility



Whether it's an iOS or Android device, the Fuji Xerox Print Utility puts mobile printing at your fingertips. Print stored photo albums, web pages or shoot and print on the go from your iOS or Android device.

Fuji Xerox Print Utility can be easily downloaded from the App Store for iOS and Play Store for Android devices.









Print from anywhere Google Cloud Print allows you to connect your printers to the web, so you can make your home and work printers available to you from the applications you use every day, from wherever you are.

DocuPrint M225 z 4-in-1 Wireless Multifunction Laser Printer



Smart features increase productivity

2.7" Colour Touch Screen



The 2.7" colour touch screen available on the DocuPrint M265 z provides a clear, simple user interface that makes walk up functions easy to access.

Duplex printing as standard

Enjoy increased productivity and cost savings with Duplex printing as standard across the entire printer lineup.

The DocuPrint M265 z also features a single pass Duplex Automatic Document Feeder (DADF) supporting duplex scanning and copying, delivering efficiency and productivity gains to any workspace.

Clever ID Card Copying*

The easy-to-use ID card copy feature allows you to copy both sides of the card onto the same side of the paper. Simply place an ID card both face up & down on the copier surface, pressing the start button each time. There is no need to change the position of the cards when copying the other side, as the feature automatically adjusts this for you.









*Available on multifunction models



DocuPrint P225 d Network Laser Printer



DocuPrint P265 dw Wireless Laser Printer



DocuPrint M225 dw 3-in-1 Wireless Multifunction Laser Printer



DocuPrint M225 z 4-in-1 Wireless Multifunction Laser Printer



DocuPrint M265 z 4-in-1 Wireless Multifunction Laser Printer with single pass Duplex Automatic Document Feeder and 2.7" colour touch screen

DocuPrint P225 d / P265 dw / M225 dw / M225 z / M265 z Specifications

Product Name	DocuPrint P225 d	DocuPrint P265 dw	DocuPrint M225 dw	DocuPrint M225 z	DocuPrint M265 z
unction rint Function	A4 monochr	ome printer	1	A4 monochrome MFP	
rint Speed (A4)	Up to 26 ppm ¹	Up to 30 ppm ¹	Up to 26 ppm ¹	Up to 26 ppm ¹	Up to 30 ppm ¹
int Resolution	Ор со 20 ррпп		Q1200 technology (2400 x 600 dp		р то зо ррпп
rst-page-out Time (A4 SEF) (from ready mode)			8.5 second or less		
arm-up Time			9 seconds or less (from sleep mode		
lemory	32MB	32 MB	64 MB	64MB	64 MB
rocessor			266 MHZ		I DOLG D
DL	PCL6, Host-Based	PCL6, Host-Based	PCL6, Host-Based	PCL6, Host-Based	PCL6, Postscript®3™ Emulati Host-Based
olour Touchscreen	_		_	_	2.7" Colour Touchscreen
onnectivity	10 Base-T/100Base-TX Ethernet		1	TV 5:1	2.7 Colodi lodelisereen
*	USB2.0 Hi-Speed			-TX Ethernet, USB2.0 Hi-Speed	
etwork protocol for models with	IPv4: ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS name resolution, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port 9100, IPP, FT				
etwork function	IPv6 : NDP, RA, DNS Resolver, mD	NS, LLMNR responder, LPR/LPD, C	erver, TFTP Client and Server, SMTP ustom Raw Port/ Port 9100, IPP, FT Client, ICMPv6, Web Services (Print	P Server, SNMPv1/v2c/v3, HTTP Se :)	erver, TFTP Client and Server, SM
obile Print			gle Cloud Print, FX Print Utility for iC		
pported Operating System	Windows Vista®, Windows® /,	Windows® 8, Windows® 8.1, Wind	ows Server 2003, Windows Server 2 Vindows Server 2012 R2 ⁸ . Mac OS	2003 x64 Edition, Windows Server	2008, Windows Server 2008 R2,
iplex Printing		Windows Server 2012, v	Automatic (A4 SEF only)	X V, 10.7.5, 10.8.X, 10.9.X	
out Paper Size (Paper Tray)		A4 SEE Letter SEE A5 SEE/LEE	A6 SEF, Executive SEF, 16K(China	only) 210x270mm (Taiwan only)	
edia Input Capacity (Paper Tray)		A4 SEI, LELLEI SEI, AS SEITEEI,	250 sheets 80qsm	only), 2 rox27 orrini (raiwari orliy)	
edia Input Capacity (manual feed slot)			1 sheet		
out Paper Size (Manual Feed slot)		Wid	th 76.2~216 mm, Length 127~355.	6mm	
edia Output Capacity			n (Face down), 1 sheet (Face up wi		
edia Types (Main Tray, or Duplex)		DI .	Plain paper, Recycled paper		
dia Types (Manual Feed slot)		Plain paper, Thin Pape	r, Thick Paper, Recycled paper, labe	I, envelope, bond paper	
out Paper Weight (Paper Tray)	 		60 to 105 gsm		
out Paper Weight (Manual Feed slot)			60 to 163 gsm	Up to 35 sheets (64-90 gsm)	
tomatic Document Feeder agle pass Duplex Automatic Document Feeder	_		_	op to 33 sileets (64-90 gsm)	Yes
onthly Maximum Duty Cycle			10K pages		1 163
achine Life		5	OK page (Duplex 25k page) or 5 ye	ars	
nt Features	Toner Save Mode, N-up(2,4,9,16		r/Footer5(time & date and/or user I		orinting ⁵ , manual booklet printir
mensions (WxDxH)	356 x 360		409 x 398.5 x 316.5 mm		5 x 316.5 mm
eight (without supplies)	5.9	kg	10.7 kg	11.1 kg	11.5 kg
erating Environment Temperature			e: 0° C to 40° C, Operating: 10° C to		
midity oustics: Sound Pressure level	Deintin or FO HP(A)	Operating Env	ironment: 20% to 80%RH (withou	t condensation)	Deintin or E1 dD/A)
ectrical Power	Printing: 50 dB(A)	Printing: 51 dB(A)	220–240 VAC, 50/60 Hz	50 dB(A)	Printing: 51 dB(A)
wer consumption ¹⁰	Ready/Standby: 58W	Poady/Standby: 59W	Ready/Standby: 60W	Poady/St	andby: 60W
wer consumption	ENERGY STAR® qualified	Ready/Standby: 58W ENERGY STAR® qualified	ENERGY STAR® qualified	FNFRGY S	andby: 60W TAR® qualified
C value	1.0 k Wh/w	1.2 k Wh/w	1.2 k Wh/w	1.2 k Wh/w	1.4 k Wh/w
ireless Specification				,	
reless LAN	_	IFFE	802.11b/g/n (Infrastructure/Ad-hc	oc Mode) IEEE 802.11a/n (Wi-Ei D	irect™)
ireless Network Security	-		WEP 64/128 bit, WPA-PSK	(TKIP/AÉS), WPA2-PSK(AES)	, , , , , , , , , , , , , , , , , , , ,
etwork security (Wireless)	-		SMTP-AUT	H, SNMP v3	
ireless Certification	_	Wi-Fi Certification Mark I	icense (WPA/WPA2-Personal), Wi-F	i Protected Setup (WPS) Identifier	Mark Licensee, AOSS Logo,
_			Wi-Fi CERTIFI	ED Wi-Fi Direct	
ppy Function					
ppy Speed (A4)	-		Up to 2	26 cpm ¹	Up to 30 cpm ¹
py Resolution	-	_	Flat Dad	Up to 600 x 600 dpi	
st-copy-out Time duction / Enlargement	-		Flat Bed	:10 seconds or less; ADF : 11 seco 25 - 400% in 1% increments	nas or iess
ulti-Copy	_			Up to 99	
py Feature	_		ID Card Co.	py, N in 1 copying (N=2,4), sort(up	to 99 nages)
tomatic 2-sided copy	_	_	-		Standard
an Function			'	·	
De	_			Colour CIS	
tomatic 2-sided scan	_	_	-	-	Standard
anning Resolution			Optical :(Scanner Glo	uss) up to 600 x 1200 dpi (mono),	600x2400 dpi (colour)
	_	-	Enhanced: up to 19,200 x 19,200 dpi		
	<u> </u>			: (ADF) up to 600 x 600 dpi (mor	
an Depth	-	-		Colour 24 bit, Mono 8bit Gray Sco	
cument Size	_	_		Platen: max 215.9mm x 300mm	
D 10 10		_		dth 147.3 – 215.9mm x Length 14	
an Destinations	_	_	Scan to PC and ap	oplication (Email, Image, File) by M265 z only: Scan to FTP	ControlCenter utility
pported Driver			Windows®-TWATN W/TA	for Windows Vista®/Mindows® 7/	Mindows® 8 /Windows® 9 1
pported Driver	-	-	Windows®: TWAIN, WIA for Windows Vista®/Windows® 7/Windows® 8 /Windows® 8 .1 Mac:TWAIN, ICA for OS 10.7.5/10.8.x/10.9.x		
x Function			, Water	,	
mpatibility	_	_	_	JTU-T	Super G3
mmunication System	-	_	-		STN
odem Speed	-	_	-	33.	6 Kbps
mory Transmission	-	_	-	Up to 5	000 pages ⁷
ıt-of-paper reception	-	_	-	Up to 5	00 pages ⁷
Resolution	-	_	-		mm x 15.4line/mm
eed Dials	-	_	-	Up to 20	00 locations
oadcasting	_		_	Up to 258 locations	Up to 250 locations d and Receive ⁵
x Features Indset	_	<u>_</u>	-	PC Fax Sen	u und keceive-
AI IMPEL		Dlages check with	your Fuji Xerox Printers reseller for	more information	
		Fieuse crieck Witi	1 your ruji herox i filiters reseiter for	more information	
arranty					
arranty onsumables		1 2008 pages +oper / 225 5 -	rios \ / 2.6008 pagas tapas /265 5	os) and 12,0009 pages deur-	
onsumables ipped consumables (approx.)		1,200 ⁸ pages toner (225 Se	ries) / 2,6008 pages toner (265 Seri	es) and 12,000 ⁹ pages drum	
onsumables ipped consumables (approx.) andard Capacity Toner cartridge (approx.) ⁸ ph Capacity Toner cartridge (approx.) ⁸		1,200 ⁸ pages toner (225 Se	ries) / 2,600 ⁸ pages toner (265 Seri CT202329 (1,200 pages) CT202330 (2,600 pages)	es) and 12,000 ⁹ pages drum	

¹ Print/copy speed may decrease due to factors such as paper type, paper size, and printing conditions. ² Measured diagonally. ³ Mac drivers are available by web download. ⁴ N-up for Mac (2,4,6,9, or 16). ³ Windows Only. ⁶ Max 1200 x 1200 dpi scanning with WIIS (Windows Image Acquisition) driver in Windows Vista, Windows 7 and Windows 8. ⁷ ITU-T Test Chart, Standard resolution. ⁸ Declared yield in accordance with ISO/IEC 19752. Yield will vary based on image area coverage and print mode. ⁹ Drum yield may vary by the type of use. ¹⁹ Measured when the machine is connected to the USB interface. This product has been tested and found to comply with the Class 1 Laser Equipment requirements defined by the intermational standard IEC60825-1:2007 and has no light exposure hazard. The product has no hazardous light emission as it features light protection components and covers to shut in all light beam during operation and maintenance. Internal Laser radiation. Wave length: 770 - 800 nm. Output: 25 mW max. Laser Class: Class 3B

Reproduction Prohibitions Please note that reproduction of the following is prohibited by law:

Domestic and foreign currencies, government-issued securities, and national bonds and local bond certificates. Unused postage stamps, post cards, etc. Certificate stamps stipulated by law. Reproducing works forming the subject matter of copyright (literary works, musical works, paintings, engravings, maps, cinematographic works, drawings, photographic works, etc.) is not permitted unless the reproduction is for the purpose of personal use, family use or other similar uses within a limited circle.

















For Your Sarety

Before using the product, read the Instruction Manual carefully

With the power source and voltage for proper use. Use the product with the power source and voltage specified. Be sure to establish ground connection. Otherwise, electronic shock may result in the case of a failure or short circuit.

For more information or detailed product specification, please call or visit us at

Fuji Xerox Asia Pacific Pte Ltd

C/O Jl Kramat Raya No. 43, Jakarta 10450 Tel: 1-500-909 Email: fxpc.idn@fujixerox.com



