

수정 전

```

20211689@20211689-os:~
파일(F) 편집(E) 보기(V) 검색(S) 터미널(T) 도움말(H)
#include <stdio.h>
#include <fcntl.h>

int main(void) {
    int fd1, n_write, i;

    mkfifo("/tmp/my_pipe1", 0644);

    fd1 = open("/tmp/my_pipe1", O_WRONLY, 0644);
    if(fd1 == -1) {
        printf("Open Error\n"); return -1; }

    for(i=0; i<10; i++) {
        n_write = write(fd1, &i, sizeof(i));
        if (n_write == -1) {
            printf("Write Error\n"); return -1; }

        printf("Producer Sent: %d\n", i);
        sleep(1);
    }
    close(fd1);
    return 0;
}
"producer.c" 23L, 421C 1,1

20211689@20211689-os:~
파일(F) 편집(E) 보기(V) 검색(S) 터미널(T) 도움말(H)
#include <stdio.h>
#include <fcntl.h>

int main(void) {
    int fd1, n_read, i;
    int msg;

    fd1 = open("/tmp/my_pipe1", O_RDONLY, 0644);
    if(fd1 == -1) {
        printf("Open Error\n"); return -1; }

    for(i=0; i<10; i++) {
        n_read = read(fd1, &msg, sizeof(msg));
        if (n_read == -1) {
            printf("Read Error\n"); return -1; }

        printf("Consumer Received: %d\n", msg);
        sleep(2);
    }
    close(fd1);
    return 0;
}
"consumer.c" 22L, 402C 5, 2-9 모두

[20211689@20211689-os ~]$ gcc consumer.c -o consumer
[20211689@20211689-os ~]$ ./producer
Producer Sent: 0
Producer Sent: 1
Producer Sent: 2
Producer Sent: 3
Producer Sent: 4
Producer Sent: 5
Producer Sent: 6
Producer Sent: 7
Producer Sent: 8
Producer Sent: 9
[20211689@20211689-os ~]$

[20211689@20211689-os ~]$ gcc consumer.c -o consumer
[20211689@20211689-os ~]$ ./consumer
Consumer Received: 0
Consumer Received: 1
Consumer Received: 2
Consumer Received: 3
Consumer Received: 4
Consumer Received: 5
Consumer Received: 6
Consumer Received: 7
Consumer Received: 8
Consumer Received: 9
[20211689@20211689-os ~]$
  
```

수정 후

```

20211689@20211689-os:~
파일(F) 편집(E) 보기(V) 검색(S) 터미널(T) 도움말(H)
#include <stdio.h>
#include <fcntl.h>

int main(void) {
    int fd1, n_write, i;
    int fd2, n_read, new;

    mkfifo("/tmp/my_pipe1", 0644);

    fd1 = open("/tmp/my_pipe1", O_WRONLY, 0644);
    fd2 = open("/tmp/my_pipe2", O_RDONLY, 0644);

    if(fd1 == -1) {
        printf("Open Error\n"); return -1; }
    if(fd2 == -1) {
        printf("Open Error\n"); return -1; }

    for(i=0; i<10; i++) {
        n_write = write(fd1, &i, sizeof(i));
        if(n_write == -1) {
            printf("Write Error\n"); return -1; }

        printf("Producer Sent: %d\n", i);
        sleep(1);

        n_read = read(fd2, &new, sizeof(new));
        if(n_read == -1) {
            printf("Read Error\n"); return -1; }
        printf("Producer Received: %d\n", new);
    }
    close(fd1);
    close(fd2);
    return 0;
}
"newproducer.c" 34L, 704C 1,9

20211689@20211689-os:~
파일(F) 편집(E) 보기(V) 검색(S) 터미널(T) 도움말(H)
#include <stdio.h>
#include <fcntl.h>

int main(void) {
    int fd1, n_read, i;
    int msg;
    int fd2, n_write, new;

    mkfifo("/tmp/my_pipe2", 0644);

    fd1 = open("/tmp/my_pipe1", O_RDONLY, 0644);
    fd2 = open("/tmp/my_pipe2", O_WRONLY, 0644);

    if(fd1 == -1) {
        printf("Open Error\n"); return -1; }
    if(fd2 == -1) {
        printf("Open Error\n"); return -1; }

    for(i=0; i<10; i++) {
        n_read = read(fd1, &msg, sizeof(msg));
        if (n_read == -1) {
            printf("Read Error\n"); return -1; }

        printf("Consumer Received: %d\n", msg);
        sleep(2);

        new = msg + 10;
        n_write = write(fd2, &new, sizeof(new));
        if(fd2 == -1) {
            printf("Write Error\n"); return -1; }
        printf("Consumer Sent: %d\n", new);
    }
    close(fd1);
    close(fd2);
    return 0;
}
"newconsumer.c" 36L, 736C 저장 했습니다 1,18 모두

[20211689@20211689-os ~]$ gcc newproducer.c -o producer
[20211689@20211689-os ~]$ ./producer
Producer Sent: 0
Producer Received: 10
Producer Sent: 1
Producer Received: 11
Producer Sent: 2
Producer Received: 12
Producer Sent: 3
Producer Received: 13
Producer Sent: 4
Producer Received: 14
Producer Sent: 5
Producer Received: 15
Producer Sent: 6
Producer Received: 16
Producer Sent: 7
Producer Received: 17
Producer Sent: 8
Producer Received: 18
Producer Sent: 9
Producer Received: 19
[20211689@20211689-os ~]$

[20211689@20211689-os ~]$ gcc newconsumer.c -o consumer
[20211689@20211689-os ~]$ ./consumer
Consumer Received: 0
Consumer Sent: 10
Consumer Received: 1
Consumer Sent: 11
Consumer Received: 2
Consumer Sent: 12
Consumer Received: 3
Consumer Sent: 13
Consumer Received: 4
Consumer Sent: 14
Consumer Received: 5
Consumer Sent: 15
Consumer Received: 6
Consumer Sent: 16
Consumer Received: 7
Consumer Sent: 17
Consumer Received: 8
Consumer Sent: 18
Consumer Received: 9
Consumer Sent: 19
[20211689@20211689-os ~]$
  
```