

수정 전

20211689@20211689-os:~

파일(F) 편집(E) 보기(V) 검색(S) 터미널(T) 도움말(H)

```
#include <stdio.h>
#include <sys/socket.h>
#include <sys/types.h>
#include <sys/un.h>
#include <time.h>

int main() {
    int sock1, sock2, length, i;
    struct sockaddr_un server, client;

    if((sock1 = socket(AF_UNIX, SOCK_STREAM, 0)) == -1)
    {
        printf("Server: Socket Open Error\n"); return -1;
    }

    server.sun_family = AF_UNIX;
    strcpy(server.sun_path, "/tmp/sock_box");

    if(bind(sock1, (struct sockaddr *)&server, sizeof(server)) == -1)
    {
        printf("Server: Bind Error\n"); return -1;
    }

    if(listen(sock1, 5) == -1)
    {
        printf("Server: Listen Error\n"); return -1;
    }

    if((sock2 = accept(sock1, (struct sockaddr *)&client, &length)) == -1)
    {
        printf("Server: Accept Error\n"); return -1;
    }

    for(i=0; i<10; i++) {
        send(sock2, &i, sizeof(i), 0);
        printf("Server Send: %d\n", i);
        sleep(1);
    }

    close(sock2);
    close(sock1);
    return 0;
}
```

1,9

20211689@20211689-os:~

파일(F) 편집(E) 보기(V) 검색(S) 터미널(T) 도움말(H)

```
#include <stdio.h>
#include <sys/socket.h>
#include <sys/types.h>
#include <sys/un.h>
#include <time.h>

int main() {
    int sock, i, read;
    struct sockaddr_un client;

    if((sock = socket(AF_UNIX, SOCK_STREAM, 0)) == -1)
    {
        printf("Client: Socket Open Error\n"); return -1;
    }

    client.sun_family = AF_UNIX;
    strcpy(client.sun_path, "/tmp/sock_box");

    if(connect(sock, (struct sockaddr *)&client, sizeof(client)) == -1)
    {
        printf("Client: Connect Error\n"); return -1;
    }

    printf("Client: Connection Established. \n");
    for(i=0; i<10; i++) {
        if(recv(sock, &read, sizeof(read), 0) == -1)
        {
            printf("Client: Receive Error\n"); return -1;
        }
        printf("Client Received: %d\n", read);
        sleep(1);
    }

    close(sock);
    return 0;
}
```

1,1

20211689@20211689-os:~

파일(F) 편집(E) 보기(V) 검색(S) 터미널(T) 도움말(H)

```
[20211689@20211689-os ~]$ ./server
Server Send: 0
Server Send: 1
Server Send: 2
Server Send: 3
Server Send: 4
Server Send: 5
Server Send: 6
Server Send: 7
Server Send: 8
Server Send: 9
[20211689@20211689-os ~]$
```

1,9

20211689@20211689-os:~

파일(F) 편집(E) 보기(V) 검색(S) 터미널(T) 도움말(H)

```
[20211689@20211689-os ~]$ ./client
Client: Connect Error
[20211689@20211689-os ~]$ vi client.c
[20211689@20211689-os ~]$ gcc client.c -o client
[20211689@20211689-os ~]$ ./client
Client: Connection Established.
Client Received: 0
Client Received: 1
Client Received: 2
Client Received: 3
Client Received: 4
Client Received: 5
Client Received: 6
Client Received: 7
Client Received: 8
Client Received: 9
[20211689@20211689-os ~]$
```

1,1

수정 후

20211689@20211689-os:~

파일(F) 편집(E) 보기(V) 검색(S) 터미널(T) 도움말(H)

```
#include <stdio.h>
#include <sys/socket.h>
#include <sys/types.h>
#include <sys/un.h>
#include <time.h>

int main() {
    int sock1, sock2, length, i, read, sock;
    struct sockaddr_un server, client;

    if((sock1 = socket(AF_UNIX, SOCK_STREAM, 0)) == -1)
    {
        printf("Server: Socket Open Error\n"); return -1;
    }

    server.sun_family = AF_UNIX;
    strcpy(server.sun_path, "/tmp/sock_box");

    if(bind(sock1, (struct sockaddr *)&server, sizeof(server)) == -1)
    {
        printf("Server: Bind Error\n"); return -1;
    }

    if(listen(sock1, 5) == -1)
    {
        printf("Server: Listen Error\n"); return -1;
    }

    if((sock2 = accept(sock1, (struct sockaddr *)&client, &length)) == -1)
    {
        printf("Server: Accept Error\n"); return -1;
    }

    for(i=0; i<10; i++) {
        send(sock2, &i, sizeof(i), 0);
        printf("Server Send: %d\n", i);
        sleep(1);
        if(recv(sock2, &read, sizeof(read), 0) == -1)
        {
            printf("Server: Received Error\n"); return -1;
        }
        printf("Server Received: %d\n", read);
    }

    close(sock2);
    close(sock1);
    return 0;
}
```

36L, 988C

20211689@20211689-os:~

파일(F) 편집(E) 보기(V) 검색(S) 터미널(T) 도움말(H)

```
#include <stdio.h>
#include <sys/socket.h>
#include <sys/types.h>
#include <sys/un.h>
#include <time.h>

int main() {
    int sock, i, read, msg;
    struct sockaddr_un client;

    if((sock = socket(AF_UNIX, SOCK_STREAM, 0)) == -1)
    {
        printf("Client: Socket Open Error\n"); return -1;
    }

    client.sun_family = AF_UNIX;
    strcpy(client.sun_path, "/tmp/sock_box");

    if(connect(sock, (struct sockaddr *)&client, sizeof(client)) == -1)
    {
        printf("Client: Connect Error\n"); return -1;
    }

    printf("Client: Connection Established. \n");
    for(i=0; i<10; i++) {
        if(recv(sock, &read, sizeof(read), 0) == -1)
        {
            printf("Client: Receive Error\n"); return -1;
        }
        printf("Client Received: %d\n", read);
        sleep(1);
        msg = i + 10;
        send(sock, &msg, sizeof(msg), 0);
        printf("Client Send: %d\n", msg);
    }

    close(sock);
    return 0;
}
```

9, 1-8

```
[20211689@20211689-os ~]$ rm /tmp/sock_box
[20211689@20211689-os ~]$ ./server
Server Send: 0
Server Received: 10
Server Send: 1
Server Received: 11
Server Send: 2
Server Received: 12
Server Send: 3
Server Received: 13
Server Send: 4
Server Received: 14
Server Send: 5
Server Received: 15
Server Send: 6
Server Received: 16
Server Send: 7
Server Received: 17
Server Send: 8
Server Received: 18
Server Send: 9
Server Received: 19
[20211689@20211689-os ~]$
```

```
[20211689@20211689-os ~]$ ./client
Client: Connection Established.
Client Received: 0
Client Send: 10
Client Received: 1
Client Send: 11
Client Received: 2
Client Send: 12
Client Received: 3
Client Send: 13
Client Received: 4
Client Send: 14
Client Received: 5
Client Send: 15
Client Received: 6
Client Send: 16
Client Received: 7
Client Send: 17
Client Received: 8
Client Send: 18
Client Received: 9
[20211689@20211689-os ~]$
```