

MARU 320 DME				
Main Status	Site	SLO	Active TXP	TXP1
	Date	Wed Jan 14 2026 22:55:21		

ç¹ TXP Configuration	TXP1	TXP2
Status	NORMAL Active	NORMAL Standby
Channel	110 X	110 X
IDENT Code	SLO	SLO
Output Power	1000W	1000W
System Delay	50.00usec	50.00usec
Dead Time	60.00usec	60.00usec
SDES	Enabled	Enabled
LDES	Disabled	Disabled
Squitter Pulse	700pp/s	700pp/s
Equalizer Pulse	Disabled	Disabled

ç¹ MON Major Measurement	MON1	MON2
Status	NORMAL	NORMAL
IDENT Code	SLO	SLO
Frequency	1197.0067MHz	1196.9996MHz
Output Power	1068.7W	1040.5W
System Delay	50.15usec	50.14usec
Reply Pulse Spacing	12.00usec	12.00usec
Reply Pulse Rise Time	2.07usec	1.96usec
Reply Pulse Decay Time	1.97usec	1.94usec
Reply Pulse Duration	3.39usec	3.34usec
Reply Efficiency	95%	93%
Reply Pulse Rate	950pp/s	1006pp/s

MARU 320 DME				
Transponder	Site	SLO	Active TXP	TXP1
	Date	Wed Jan 14 2026 22:55:21		

ç <sup>1</sup> General Status	TXP1		TXP2	
Status	NORMAL		NORMAL	
ç <sup>1</sup> Channel	TXP1		TXP2	
Channel	110 X		110 X	
Frequency	1197MHz		1197MHz	
ç <sup>1</sup> IDENT	TXP1		TXP2	
IDENT Code	SLO		SLO	
IDENT Mode	Associated, Slave		Associated, Slave	
IDENT Keying	ON		ON	
ç <sup>1</sup> Output Power	TXP1		TXP2	
Gaussian Pulse	1000W		1000W	
ç <sup>1</sup> System Configuration	TXP1		TXP2	
System Delay	50.00usec		50.00usec	
ç <sup>1</sup> Echo Suppression	TXP1		TXP2	
SDES	3.20usec		3.20usec	
LDES	Disabled		Disabled	
Dead Time	60.00usec		60.00usec	
ç <sup>1</sup> Pulse Rate	TXP1		TXP2	
Squitter Pulse	700pp/s		700pp/s	
Equalizer Pulse	Disabled		Disabled	
ç <sup>1</sup> DC/DC	TXP1		TXP2	
DC/DC	ON		ON	

MARU 320 DME				
Monitor	Site	SLO	Active TXP	TXP1
	Date	Wed Jan 14 2026 22:55:21		

ç¹ General Status	MON1	MON2
-------------------	------	------

Status	NORMAL	NORMAL
--------	--------	--------

ç¹ TXP1 Measurement [ Active ]	MON1	MON2
--------------------------------	------	------

IDENT Code	SLO	SLO
Frequency	1197.0067MHz	1196.9996MHz
Output Power	1068.7W	1040.5W
System Delay	50.15usec	50.14usec
Reply Pulse Spacing	12.00usec	12.00usec
Reply Pulse Rise Time	2.07usec	1.96usec
Reply Pulse Decay Time	1.97usec	1.94usec
Reply Pulse Duration	3.39usec	3.34usec
Reply Efficiency	95%	93%
Reply Pulse Rate	950pp/s	1006pp/s

ç¹ TXP2 Measurement [ Standby ]	MON1	MON2
---------------------------------	------	------

IDENT Code	-	-
Frequency	1197.0038MHz	1196.9971MHz
Output Power	-	-
System Delay	50.06usec	50.03usec
Reply Pulse Spacing	12.02usec	12.02usec
Reply Pulse Rise Time	1.93usec	1.91usec
Reply Pulse Decay Time	1.92usec	1.89usec
Reply Pulse Duration	3.60usec	3.60usec
Reply Efficiency	96%	95%
Reply Pulse Rate	731pp/s	799pp/s

MARU 320 DME				
Alarm Limit	Site	SLO	Active TXP	TXP1
	Date	Wed Jan 14 2026 22:55:21		

ç <sup>1</sup> MON1	LOWER	UPPER
TXP1 System Delay	49.50usec	50.50usec
TXP2 System Delay	49.50usec	50.50usec
TXP1 Pulse Spacing	11.75usec	12.25usec
TXP2 Pulse Spacing	11.75usec	12.25usec
TXP1 Pulse Duration	3.00usec	4.00usec
TXP2 Pulse Duration	3.00usec	4.00usec
TXP1 Pulse Rise Time	1.00usec	3.00usec
TXP2 Pulse Rise Time	1.00usec	3.00usec
TXP1 Pulse Decay Time	1.00usec	3.00usec
TXP2 Pulse Decay Time	1.00usec	3.00usec
TXP1 Output Power	500.0W	1500.0W
TXP2 Output Power	500.0W	1500.0W
TXP1 Efficiency	70%	100%
TXP2 Efficiency	70%	100%
TXP1 Pulse Rate	700pp/s	5400pp/s
TXP2 Pulse Rate	700pp/s	5400pp/s
TXP1 Frequency	1196.9000MHz	1197.1000MHz
TXP2 Frequency	1196.9000MHz	1197.1000MHz

ç <sup>1</sup> MON2	LOWER	UPPER
TXP1 System Delay	49.50usec	50.50usec
TXP2 System Delay	49.50usec	50.50usec
TXP1 Pulse Spacing	11.75usec	12.25usec
TXP2 Pulse Spacing	11.75usec	12.25usec
TXP1 Pulse Duration	3.00usec	4.00usec
TXP2 Pulse Duration	3.00usec	4.00usec
TXP1 Pulse Rise Time	1.00usec	3.00usec
TXP2 Pulse Rise Time	1.00usec	3.00usec
TXP1 Pulse Decay Time	1.00usec	3.00usec
TXP2 Pulse Decay Time	1.00usec	3.00usec
TXP1 Output Power	500.0W	1500.0W
TXP2 Output Power	500.0W	1500.0W
TXP1 Efficiency	70%	100%
TXP2 Efficiency	70%	100%
TXP1 Pulse Rate	700pp/s	5400pp/s
TXP2 Pulse Rate	700pp/s	5400pp/s
TXP1 Frequency	1196.9000MHz	1197.1000MHz
TXP2 Frequency	1196.9000MHz	1197.1000MHz

MARU 320 DME				
MISC	Site	SLO	Active TXP	TXP1
	Date	Wed Jan 14 2026 22:55:21		

ç¹ Changeover Configuration	Alarm Duration	Mode
	30sec	AND
ç¹ PSS Status	SYS1	SYS2
AC/DC Status	NORMAL	NORMAL
AC/DC Voltage	27.79V	27.79V
AC/DC Current	45.92A	37.92A
DC/DC Status	NORMAL	NORMAL
DC/DC Voltage	49.31V	50.06V
DC/DC Current	18.40A	18.40A
Battery Status	NORMAL	NORMAL
Battery Voltage	24.89V	0.39V
Battery Current	0.96A	0.96A
ç¹ System Temperature	SYS1	SYS2
HPA Temperature	34.0	3.3
LPA Temperature	31.0	3.1
Ambient Temperature		-