



API Documentation

DOMESTIC A2P SMS SERVICE

telSpiel Communications Private Limited



Preamble	2
Support	2
Assumptions	2
Successful Transmission of SMS	3
HTTPS URL Format	3
Base URL	3
HTTP API Parameters Specification.....	3
Sample Success Response.....	4
Sample Error Response	4
Error Code Description	4
Send Plain Message.....	5
Send Unicode/Multilingual Message	5
Send Bulk Message	5
XML URL format.....	5
XML API Parameter Definition.....	7
Types of XML request	7
Request Status Check API	11
Balance Check API	11
Push/Call Back Delivery API.....	11
JSON URL format	12
JSON API Parameter Definition.....	12





Preamble

This document underlines the specifications of the HTTP/HTTPS based API provided by telSpiel for the automated sending of SMS via Internet within telSpiel infrastructure. The document is intended for developers planning on integrating their systems with telSpiel's SMS service. It also provides information about sending the Unicode and Flash messages.

Support

As an organization we do follow strict timelines and adhere to the highest level of SLAs to fulfil our commitment. Our customer support team professionals are highly qualified industry veterans and are handholding with you 24X7X365 from proof of concept till post-sales support. Our team is reachable at the following touchpoints.

Support	Technical	Billing	Sales
Email	care@telspiel.com	finance@telspiel.com	marketing@telspiel.com
Phone	+919999998898 (Ext 1)	+919999998898 (Ext 2)	+919999998898 (Ext 3)
Timing	24 / 7	09:00 - 18:00 Hrs	09:00 - 18:00 Hrs
Days	All days	Mon-Sat	Mon-Fri
Exceptions	NA	Holidays	Holidays

Assumptions

The guide assumes that you are familiar with and have sufficient experience in applying the following technologies and concepts of HTTP and XML.

- HTTP/HTTPS communications using the GET and POST methods for parameter passing through API.
- A programming language such as Java, C/C++, Visual Basic or PHP to integrate the HTTP URL with the Application.
- Application designed in any of the above Language should be capable of capturing the Message ID (MID).



Successful Transmission of SMS

For each successful submission, the API would return a unique message ID (MID) for that transaction. The Client's Application should capture the MID and Delivery Report (DLR) can be fetched against that MID. This message ID then can be used to track the status of the message and receive the DLR against this MID through DLR URL.

HTTPS URL Format

The below HTTPS API can be used by Client to send the messages to telSpiel's Server. A sample of the URL could be in the format below.

Base URL

All URLs referenced in the API documentation have the following base:

```
https://api.telsp.in
```

Sample format single request

```
https://api.telsp.in/pushapi/sendmsg?username=xxxxxx&dest=xxxxxx&apikey=xxxxx&signature=SENDERID&msgtype=TypeofMessage&msgtxt=template&entityid=entityIdvalue&templateid=templateIDvalue&custref=uniquereferenceid
```

Sample format multiple request

```
https://api.telsp.in/pushapi/sendbulkmsg?username=xxxxxx&dest=xxxxxx,xxxxxx&apikey=xxxxx&signature=SENDERID&msgtype=TypeofMessage&msgtxt=template&entityid=entityIdvalue&templateid=templateIDvalue&custref=uniquereferenceid
```

HTTP API Parameters Specification

Whenever the Client Application hits the HTTP URL, it should include the following parameters as per the requirement. The following parameters should be used in the same order as given below to call HTTP API.

Parameter Name	Value	Description
Username	string	Account id; will be provided by SMS Platform
Dest	string	The target mobile number on which the SMS is being sent



APIkey	string	User specific key for every request
Signature	string	Sender ID, While sending sms via Gateway & id should be 6 alpha characters / numbers.
msgType	string	Type of message (PM for plain text or UC for Unicode message/multilingual message)
msgText	string	Text to be send
entityid	Numeri c	Entity ID Value
templateid	Numeri c	Template ID Value
Custref	Numeri c	Reference unique ID (optional)

Sample Success Response

While sending normal text SMS Client needs to ensure that any optional parameters are not used (except for DLR-URL to receive delivery acknowledgment on to predefined URL).

Success API Response Sample Format

```
[{"code": "6001", "desc": "Messagereceivedbyplatform.", "reqId": "4813450031619 945525810870", "time": "2021-050214:22:05.81", "partMessageIds": ["4813450031619945525810870"], "totalMessageParts": 1}]
```

Sample Error Response

API Response Sample Format

```
[{"code": "110", "desc": "INVALID_DESTINATION_NUMBER", "totalMessageParts": 0}]
```

Error Code Description

The below error can be displayed while hitting the HTTP API if there is any wrong parameter entered or issue with the account.

Error Code	Description
114	Invalid API key
105	Invalid Sender ID





110	Invalid destination
6001	Success

Send Plain Message

HTTP API has end to end support for plain message.

Sample Format

```
https://api.telsp.in/pushapi/sendmsg?username=xxxxxx&dest=xxxxxx&apikey=xxxxxx&signature=SENDERID&msgtype=PM&msgtxt=template&entityid=entityIdvalue&templateid=templateIDvalue&custref=uniquereferenceid
```

Send Unicode/Multilingual Message

HTTP API has end to end support for Unicode characters.

Sample Format

```
https://api.telsp.in/pushapi/sendmsg?username=xxxxxx&dest=xxxxxx&apikey=xxxxxx&signature=SENDERID&msgtype=UC&msgtxt=template&entityid=entityIdvalue&templateid=templateIDvalue&custref=uniquereferenceid
```

Send Bulk Message

HTTP API has end to end support for bulk SMS/messages.

Sample Format

```
https://api.telsp.in/pushapi/sendbulkmsg?username=xxxxxx&dest=xxxxxx,xxxxxx&apikey=xxxxxx&signature=SENDERID&msgtype=TypeofMessage&msgtxt=template&entityid=entityIdvalue&templateid=templateIDvalue&custref=uniquereferenceid
```

XML URL format

Sample URL Format

```
http://api.telsp.in/pushapi/sendxmlmsg?
```

Sample Request Format

```
<xmlPushRequest username="XXXXXX" pin="XXXXXXXXXXXXXXXXXX">
  <campaignName>test-campaign</campaignName>
  <entityId>XXXXXXXXXXXXXXXXXX</entityId>
  <data>
    <from>SENDERID</from>
    <recipientList>
      <recipient>
```





```
<destAddress>97110XXXXX</destAddress>
</recipient>
</recipientList>
<message>
<messageType>PM</messageType>
<messageTxt>DLT APPROVED TEMPLATE</messageTxt>
<templateId>XXXXXXXXXXXXXXXXXXXX</templateId>
</message>
</data>
</xmlPushRequest>
```

Sample Response Format

```
<?xml version="1.0" encoding="UTF-8" standalone="yes" ?>
<xmlPushResponse>
<recipientList>
<recipient>
<code>6001</code>
<desc>Message received by platform.</desc>
<timestamp>2021-05-01 22:49:04.503</timestamp>
<destAddress>9711XXXXX</destAddress>
<requestId>4813450031619889544502224</requestId>
<totalMessageParts>1</totalMessageParts>
<partMessageIdList>
<partMessageId>4813450031619889544502224</partMessageId>
</partMessageIdList>
</recipient>
</recipientList>
</xmlPushResponse>
```



XML API Parameter Definition

Parameter Name	Type	Need	Use	Description
username	String	Required	All	Account id; will be provided by SMS Platform
destAddress	Numeric	Required	All	The target mobile number on which the SMS is being sent
pin	String	Required	All	User specific api key for every request
signature	String	Required	All	Sender ID
messageType	String	Required	All	Type of message (PM for plain text or UC for Unicode message/multilingual message)
messageTxt	String	Required	All	Text to be sent
custref	String	Optional	All	Customer reference key specific to campaign
entityId	Numeric	Required	All	DLT register Entity ID for the Header
templateId	Numeric	Required	All	DLT register Template ID for the Message Template
Campaignname	String	Optional	ShortURL	Campaign name for the campaign, if not provided. Then it will be auto generated by system for the day and can be used for tracking.

Types of XML request

1. One to One
2. One to Many

One to One

The following API format to be used when one SMS to be sent to one mobile number.

Example of API format for English language





```
https://api.telsp.in/pushapi/sendxmlmsg?
<xmlPushRequest username="XXXXXX" pin="XXXXXXXXXXXXXXXXXX">
<campaignName>test-campaign</campaignName>
<entityId>XXXXXXXXXXXXXXXXXX</entityId>
<data>
<from>SENDERID</from>
<recipientList>
<recipient>
<destAddress>97110XXXXX</destAddress>
</recipient>
</recipientList>
<message>
<messageType>PM</messageType>
<messageTxt>DLT APPROVED TEMPLATE</messageTxt>
<templateId>XXXXXXXXXXXXXXXXXX</templateId>
</message>
</data>
</xmlPushRequest>
```

Example of API format for Unicode

```
https://api.telsp.in/pushapi/sendxmlmsg?
<xmlPushRequest username="XXXXXX" pin="XXXXXXXXXXXXXXXXXX">
<campaignName>test-campaign</campaignName>
<entityId>XXXXXXXXXXXXXXXXXX</entityId>
<data>
<from>SENDERID</from>
<recipientList>
<recipient>
<destAddress>97110XXXXX</destAddress>
```



```
</recipient>
</recipientList>
<message>
<messageType>UC</messageType>
<messageTxt>DLT APPROVED TEMPLATE</messageTxt>
<templateId>XXXXXXXXXXXXXXXXXXXX</templateId>
</message>
</data>
</xmlPushRequest>
```

One to Many

The following API format to be used when one SMS to be sent to multiple mobile numbers.

Example of API format for English language

```
https://api.telsp.in/pushapi/sendxmlmsg?
<xmlPushRequest username="XXXXXX" pin="XXXXXXXXXXXXXXXXXXXX">
<campaignName>test-campaign</campaignName>
<entityId>XXXXXXXXXXXXXXXXXXXX</entityId>
<data>
<from>SENDERID</from>
<recipientList>
<recipient>
<destAddress>97110XXXXX</destAddress>
<custref>a</custref>
</recipient>
<recipient>
<destAddress>98101XXXXX</destAddress>
<custref>a</custref>
</recipient>
</recipientList>
<message>
```



```
<messageType>PM</messageType>
<messageTxt>DLT APPROVED TEMPLATE</messageTxt>
<templateId>XXXXXXXXXXXXXXXXXXXX</templateId>
</message>
</data>
</xmlPushRequest>
```

Example of API format for Unicode

```
https://api.telsp.in/pushapi/sendxmlmsg?
<xmlPushRequest username="XXXXXX" pin="XXXXXXXXXXXXXXXXXXXX">
<campaignName>test-campaign</campaignName>
<entityId>XXXXXXXXXXXXXXXXXXXX</entityId>
<data>
<from>SENDERID</from>
<recipientList>
<recipient>
<destAddress>97110XXXXX</destAddress>
<custref>a</custref>
</recipient>
<recipient>
<destAddress>98101XXXXX</destAddress>
<custref>a</custref>
</recipient>
</recipientList>
<message>
<messageType>UC</messageType>
<messageTxt>DLT APPROVED TEMPLATE</messageTxt>
<templateId>XXXXXXXXXXXXXXXXXXXX</templateId>
</message>
```



```
</data>  
</xmlPushRequest>
```

Request Status Check API

Sample Format

```
https://api.telsp.in/pulldlr/pullsmppdlr?username=xxxxxxx&apikey=xxx  
xx&msgid=xxxxxxx&for mat=json&signature=xxxxxxx
```

Parameters	Description
username	Account id provided by service provider
apikey	API Key
msgid	Unique message ID for every SMS
signature	Sender ID used to send SMSs

Balance Check API

Sample Format

```
https://api.telsp.in/pushapi/getUserCredit?username=xxxxx&apikey=xxx  
xxxxxxx
```

Parameters	Description
username	Account id provided by service provider
apikey	API Key
msgid	Unique message ID for every SMS
signature	Sender ID used to send SMSs

Push/Call Back Delivery API

Sample Format

```
https://sample.com/c70831d5-a8b1-49d8-bded-  
34edf593dcbf?sid=##messageid##&status=##status##&stime=##submittime#  
##&dest=##mobile##&dtime=##deliverytime##&reason=##deliverycode##
```

Parameters	Description
reason	'000'/'101'/'180'/'97'/'98'/ (wherein "000" stands for delivered and rest code are mapped for failure.)



status	“DELIVRD” or “FAILED” or “UNDELIV” or “REJECTD” or “EXPIRED”
--------	--

JSON URL format

Sample URL Format

http://api.telsp.in/pushapi/json/sendmsg

Sample Request Format

```
{
  "var": "", "username": "userid",
  "apikey": "xxxxxxxxxxxxxxxxxxxxxx", "msgtype": "PM",
  "msgtext": "dlt template", "signature": "xxxxxx", "entity": "entity id value",
  "templateid": "template id value", "tag": "123456",
  "dest": ["98918xxx", "8588xxx"]
}
```

JSON API Parameter Definition

Parameter Name	Type	Need	Use	Description
username	String	Required	All	Account id; will be provided by SMS Platform
dest	Numeric	Required	All	The target mobile number on which the SMS is being sent
APIkey	String	Required	All	User specific api key for every request
signature	String	Required	All	Sender ID
messageType	String	Required	All	Type of message (PM for plain text or UC for Unicode message/multilingual message)
messageTxt	String	Required	All	Text to be sent



tag	String	Optional	All	Customer reference key specific to campaign
entity	Numeric	Required	All	DLT register Entity ID for the Header
templateId	Numeric	Required	All	DLT register Template ID for the Message Template
var	String	Optional	All	Customer reference key specific to campaign

DELHI • NOIDA • BENGALURU • GURUGRAM • MUMBAI • DUBAI

www.telspiel.com | marketing@telspiel.com | +91 0120 4108800

