



API Documentation

WHATSAPP BUSINESS API SERVICE

telSpiel Communications Private Limited



Preamble	2
Support	2
Generate Token API	2
Sample Curl Request:	3
Success Response:.....	3
Failure Response:	3
API Parameters.....	4
Send Message API: Text	5
Sample Curl Request	5
Send Message API: Text, Variable, Dynamic header, Buttons	6
Sample Curl Request	6
Parameters.....	7
Send Message API: Media	8
Sample curl request.....	8
Send Message API: Media, Variable, Buttons	9
Sample Curl Request:	9
Send Carousel Message API	11
Sample Curl Request	11
Authentication APIs.....	13
Send Auth Message API	13
Send LTO Message API	14
Upload Media API.....	15
Response Codes	15
Success Response.....	15
Failure Responses: Wrong Journey ID	15
Delivery Events.....	16
Sample Payload.....	16
Delivery Reports	17
Filtering Messages Using Tags	17
Live Agent Satisfaction Rating API.....	18
Sample Curl Request:	18



Preamble

This document underlines the specifications of the WhatsApp APIs. It offers robust, secure, and flexible integrations with your system, allowing seamless incorporation of WhatsApp capabilities into your applications. With WhatsApp API, you can efficiently send messages, ensuring reliable communication with your users globally.

Support

As an organization we do follow strict timelines and adhere to the highest level of SLAs to fulfil our commitment. Our customer support team professionals are highly qualified industry veterans and are handholding with you 24X7X365 from proof of concept till post-sales support. Our team is reachable at the following touchpoints.

Support	Technical	Billing	Sales
Email	care@telspiel.com	finance@telspiel.com	marketing@telspiel.com
Phone	+919999998898 (Ext 1)	+919999998898 (Ext 2)	+919999998898 (Ext 3)
Timing	24 / 7	09:00 – 18:00 Hrs	09:00 – 18:00 Hrs
Days	All days	Mon-Sat	Mon-Fri
Exceptions	NA	Holidays	Holidays

Generate Token API

To start using the API, you will need to generate a token using the Generate token API and pass the same token as authentication for all the send message APIs.

Request URL: <https://telligx.io/account/enterprise/login>

HTTP Method: POST

Parameters	Description
Email	Indicates the email id used for logging in to the tellix.io platform.





Password	Indicates the password used for logging in to the tellix.io platform.
Long Term Token	Indicates if the authentication token remains valid indefinitely

Sample Curl Request:

```
curl --location 'https://tellix.io/account/enterprise/login' \\  
--header 'Content-Type: application/x-www-form-urlencoded' \\  
--data-urlencode 'email=xx' \\  
--data-urlencode 'password=xx'
```

Success Response:

```
{  
  "response": {  
    "uId": 100,  
    "token": "VF16Zz6ZMezrz+12+8CqIHRZdtxxxxxxxxxxxxxxxxxx"  
  },  
  "message": {  
    "code": 0,  
    "message": "Login success"  
  },  
  "status": true  
}
```

Failure Response:

```
{  
  "message": {  
    "code": 1403,  
  },  
}
```





```
"message": "Login failed! wrong email id and password combination"
},
"status": false
}
```

API Parameters

The following are mandatory and optional parameters for all APIs.

Parameters	Description	Mandatory
authentication-token	Token generated from Generate Token API	Yes
from	Specifies the sender's phone number.	Yes
to	Specifies the recipient's phone number.	Yes
journeyId	Represents the unique identifier for the journey associated with the message.	Yes
templateId	Identifies the specific template for the message.	Yes
deptId	Represents the department of the given account.	No
callbackUrl	Indicates the URL used for receiving delivery callbacks (Sent, Delivered, Failed, Read)	No



metaData	It contains custom tags (tag1, tag2, tag3) that provide additional context or categorization for each message.	No
-----------------	--	----

Note – To get **journeyId**, follow these steps:

1. Log in to the tellix.io platform.
2. Go to Flow Builder -> Streams and click on the stream.
3. Under Configurations, copy journey id from the webhook URL.

e.g.: If webhook URL is

<https://tellix.io/chatbird/message/66c3054f9xxxxxx61f5501e/send>,
journey id is [66c3054f9xxxxxx61f5501e](#).

tag1, tag2, tag3: These are customizable fields where you can specify extra information for the particular message.

Info! By including these tags while sending a message, you can easily filter messages in the delivery report section of the tellix.io platform based on these tags. This allows for efficient categorization and retrieval of messages according to your specific criteria.

Send Message API: Text

Sample Curl Request

```
curl --location 'https://tellix.io/chatbird/api/message/send' \\  
--header 'authentication-token: xx' \\  
--header 'Content-Type: application/json' \\  
--data '{ "from": "xx",  
"to": "xx",  
"journeyId": "xx", "message": { "template": {
```





```
"templateId": "xx"
}
},
"deptId": "xx",
"callbackUrl": "xx", "metaData": { "tag1": "xx",
"tag2": "xx",
"tag3": "xx"
}
}
```

Send Message API: Text, Variable, Dynamic header, Buttons

Sample Curl Request

```
curl --location 'https://tellix.io/chatbird/api/message/send' \\  
--header 'authentication-token: xx' \\  
--header 'Content-Type: application/json' \\  
--data '{ "from": "xx",  
"to": "xx",  
"journeyId": "xx", "message": { "template": {  
"templateId": "xx", "headerParameterValues": { "0": "xx"  
},  
"parameterValues": { "0": "xx"  
},  
"buttons": \[  
{  
"type": "xx",  
"text": "xx",  
"payload": "xx"  
},  
}
```



```
{
  "payload": "xx",
  "text": "xx",
  "type": "xx"
},
{
  "type": "xx",
  "text": "xx",
  "payload": "xx"
}
\]
}
},
"deptId": "xx",
"callbackUrl": "xx", "metaData": { "tag1": "xx",
"tag2": "xx",
"tag3": "xx"
}
}
```

Parameters

Parameters	Description	Mandatory
headerParameterValues	Identifies variable values in Header content	Yes if header is dynamic
parameterValues	Identifies variable values in Body content	Yes if template have variables
Buttons		





type	Specifies that the button is a "URL" or "Quick_Reply" or "Phone_Number" button.	Yes if template have buttons
text	Specifies the button text as passed in the template	No
payload	Payload associated with the URL or Quick Reply or Phone Number button.	Yes if its Dynamic URL

Send Message API: Media

Sample curl request

```
{
  "from": "xxxxxxxx",
  "to": "xxxxxxxx", "journeyId": "xxxxxxxx", "message": { "template": {
    "templateId": "xxxxxxxx", "media": { "type": "xx",
    "url": "xxxxxxxx", "fileName": "xxxxxxxx"
    }
  }
},
  "deptId": "xx",
  "callbackUrl": "xx", "metaData": { "tag1": "xx",
  "tag2": "xx",
  "tag3": "xx"
}
}
```

Parameters	Description	Mandatory
Media		





type	Indicates the type of media. It could be 1. IMAGE for image templates 2. DOC for pdf templates 3. VIDEO for video templates	Yes if template have media
url	Represents the URL of the media file (image, document, or video) to be sent	Yes if template have media
fileName	Specifies the name of the media file attached.	No

Send Message API: Media, Variable, Buttons

Sample Curl Request:

```
curl --location 'https://tellix.io/chatbird/api/message/send' \\  
--header 'authentication-token: xx' \\  
--header 'Content-Type: application/json' \\  
--data '{ "from": "xx",  
"to": "xx",  
"journeyId": "xx", "message": { "template": {  
"templateId": "xx" "parameterValues": { "0": "xx"  
},  
"media": { "type": "xx",  
"url": "xx",  
"fileName": "xx"  
},  
"buttons": \[  
{  
"type": "xx",  
"text": "xx",  
"payload": "xx"  
},  
}
```





```
{
  "type": "xx",
  "text": "xx",
  "payload": "xx"
}
\]
}
},
"deptId": "xx",
"callbackUrl": "xx", "metaData": { "tag1": "xx",
"tag2": "xx",
"tag3": "xx"
}
}
```

Parameters	Description	Mandatory
parameterValues	Identifies variable values in Body content	Yes if template have variables
Media		
type	Indicates the type of media. Enter: could be 1. IMAGE for image templates 2. DOC for pdf templates 3. VIDEO for video templates	Yes if template have media
url	Represents the URL of the media file (image, document, or video) to be sent	Yes if template have media
fileName	Specifies the name of the media file attached.	
Buttons		



type	Specifies that the button is a URL or Quick Reply button.	Yes if template have buttons
text	Specifies the button text as passed in the template	No
payload	Payload associated with the URL or Quick Reply button.	Yes if its Dynamic URL

Send Carousel Message API

Sample Curl Request

```
curl --location 'https://tellix.io/chatbird/api/message/send' \\  
--header 'authentication-token: xx' \\  
--header 'Content-Type: application/json' \\  
--data '{ "from": "xx",  
"to": "xx",  
"journeyId": "xx", "message": { "template": {  
"templateId": "xx", "cards": \\  
{  
"media": { "type": "xx",  
"url": "xx"  
},  
"buttons": \\  
{  
"type": "xx",  
"payload": "xx"  
}  
},  
{  
"media": { "type": "xx",
```



```
"url": "xx"
},
"buttons": \[
{
  "type": "xx",
  "payload": "xx"
}
\]
},
{
  "media": { "type": "xx",
  "url": "xx"
},
  "buttons": \[
  {
    "type": "xx",
    "payload": "xx"
  }
  \]
}
\]
}
}
}'
```

Parameters	Description
parameterValues	Identifies variable values in Body content For eg: 0 maps value for variable 1 and 1 maps value for variable 2
callbackUrl	Indicates the URL used for receiving callbacks





Media	
url	Indicates the URL of the media.
type	Specifies the type of the media (e.g., IMAGE or VIDEO).
Buttons	
type	Specifies that the button is a URL or Quick Reply button.
payload	Payload associated with the URL or Quick Reply button.

Authentication APIs

Send Auth Message API

```
curl --location 'https://tellix.io/chatbird/api/message/send' \\  
--header 'authentication-token: XXXXXXXX' \\  
--header 'Content-Type: application/json' \\  
--header 'Cookie: authentication-token=XXXXXXX; time-  
stamp=1739437982712' \\  
--data '{  
  "from": "+91XXXXXXXX", "to": "+91XXXXXXXX",  
  "journeyId": "XXXXXX", "message": {  
    "eId": 100,  
    "template": { "templateId": "XXXXXXX", "parameterValues": {  
      "0": "123"  
    },  
    "buttons": \[  
      {  
        "type": "URL",  
        "payload": "123"  
      }  
    ]  
  }  
}
```



```
}  
}  
'
```

Send LTO Message API

```
curl --location 'https://tellig.io/chatbird/api/message/send' \  
\--header 'authentication-token: XXXXXXXXXX' \  
\--header 'Content-Type: application/json' \  
\--header 'Cookie: authentication-token=XXXXXXXXXXXX; time-  
stamp=1739437982712' \  
\--data '{  
  "journeyId": "XXXXXXXX", "from": "+91XXXXXXXX", "to": "+91XXXXXXXX"  
  "message": {  
    "eId": 103,  
    "template": { "templateId": "XXXXXXXX", "category": "MARKETING",  
    "buttons": [  
      {  
        "payload": "123456",  
        "index": 0,  
        "type": "COPY_CODE"  
      }  
    ],  
    "buttonType": "CALL_TO_ACTION", "limitedTimeOffer": {  
      "expirationTime": 78678678678686  
    }  
  }  
}'
```



Upload Media API

```
curl --location 'https://tellix.io/e/drive/upload' \\  
\--header 'authentication-token: XXXXXXXXXXXXX' \\  
\--header 'Cookie: authentication-token=XXXXXXXXXX; time-  
stamp=1739437982712' \\  
\--form 'message="XXXXXX"' \\  
\--form 'file=@"/Users/XXXXXX/Downloads/XXXXX"'
```

Response Codes

Success Response

```
{  
  "message": null,  
  "code": 100,  
  "status": true,  
  "data": { "id": "669e5778a8f5d50aad723e7c"  
}  
}
```

Failure Responses: Wrong Journey ID

```
{  
  "message": "Journey not found", "code": 101,  
  "status": false, "data": null  
}
```




Delivery Events

Sample Payload

```
{
  "context": {
    "id": "xxxxxxxx"
  },
  "from": "xxxxxxxx",
  "to": "xxxxxxxx",
  "type": "event", "event": { "status": "DELIVERED"
},
  "error": { "code": "0",
  "message": "Failed Retry"
},
  "conversation": { "id": "xxxxxxxx", "type": "marketing", "billable": true
},
  "timestamp": xxxxxxxx
}
```

Parameters	Description
context.id	The message ID used to identify which message the event corresponds to.
from	The sender's phone number
to	The recipient's phone number.





event.status	The delivery status of the message. Possible values are READ,DELIVERED, SENT, FAILED.
error	Provides error details if the message delivery fails.
conversation	Contains details about the conversation, such as the ID, type (e.g., marketing), and indicating whether the message is billable.

Delivery Reports

The Delivery Report in the tellix.io platform provides a comprehensive overview of all messages sent through various channels. This feature also allows users to track the status of each message, including whether it was sent, delivered, read, or failed. The Delivery Report is essential for analyzing communication effectiveness and identifying any issues in message delivery.

Filtering Messages Using Tags

To enhance message tracking and categorization, the tellix.io platform allows users to filter messages in the Delivery Report using metadata tags. By including metadata tags in the "Send Message" API Request payload, you can filter messages in the Delivery Report to view specific messages sent based on these tags.

To Filter Messages in Delivery Report,

1. Choose the resource type as API, for messages sent through the API.
2. Specify the channel type (e.g., WhatsApp) and channel name used for the messages.
3. Set the desired time range for your message search.
4. Use the tag fields (Message Tag 1, Message Tag 2 and Message Tag 3) to filter messages. Enter the specific tags (tag1, tag2, tag3) you used in the API request to narrow down your results.



Live Agent Satisfaction Rating API

Use this API for enabling the live agent Average Rating feature in Converse Reports on tellix.io platform. Create a live agent flow with API widget for capturing ratings assigned to the agent from end users.

Request URL: `https://tellix.io/whatsapp/chat/feedback`

HTTP Method: POST

Headers: Add a new key referring to the table below.

Key	Value
chatId	Identifies and works as a unique identifier for chats
customerPhoneNumber	Indicates the end user's phone number
rating	Indicates the variable which stores the rating provided by the end user

Sample Curl Request:

```
{
  "chatId": "${chatId}",
  "customerPhoneNumber": "${_sys.phoneNumber}", "rating": ${rating}
}
```

DELHI • NOIDA • BENGALURU • GURUGRAM • MUMBAI • DUBAI

www.telspiel.com | marketing@telspiel.com | +91 0120 4108800

