T3000 API & Protocol

Message 8: OPEN_ENTRY_EDIT_WINDOW · built Nov 13, 2026

Message 8: OPEN_ENTRY_EDIT_WINDOW

The OPEN_ENTRY_EDIT_WINDOW message opens edit dialogs for schedules, holidays, and programs in the T3000 desktop application. This bridges the web interface with native T3000 editing windows.

When to Use:

- User clicks "Edit" button on a schedule
- Double-clicking a holiday entry
- Opening program editor from web interface

Overview

Action: `OPEN_ENTRY_EDIT_WINDOW` (8) **Direction:** Frontend → Backend **Location:** BacnetWebView.cpp line 2807 **Purpose:** Trigger native T3000 edit dialogs from web interface

Request Format

JSON Structure:

JSON

```
{
  "action": "OPEN_ENTRY_EDIT_WINDOW",
  "panelId": 0,
  "entryIndex": 5,
  "entryType": 12
}
```

Request Parameters

Parameter	Type	Required	Description
`panelId`	number	Yes	Panel ID (must match local panel)
`entryIndex`	number	Yes	Entry index to edit
`entryType`	number	Yes	Entry type constant

Entry Types

Type	Constant	Value	Editor Opened
Schedule	BAC_SCH	12	Weekly Schedule Editor
Holiday	BAC_HOL	13	Annual Holiday Editor
Program	BAC_PRG	6	Program Code Editor

Response Format

No response - This is a one-way command that triggers UI action

Implementation

Location: BacnetWebView.cpp line 2807

C++

```
case OPEN_ENTRY_EDIT_WINDOW:
{
    tempjson["action"] = "OPEN_ENTRY_EDIT_WINDOW";
    int npanel_id = json.get("panelId", Json::nullValue).asInt();
    int entry_index = json.get("entryIndex", Json::nullValue).asInt();
    int entry_type = json.get("entryType", Json::nullValue).asInt();

    if (npanel_id == bac_gloab_panel) // Only for local panel
    {
        switch (entry_type)
        {
        case BAC_SCH:  // Schedule
        {
            if (entry_index < BAC_SCHEDULE_COUNT)
            {
                weekly_list_line = entry_index;
                WeeklyRoutine_Window->OnBnClickedButtonWeeklyScheduleEdit();
            }
        }
        break;
        case BAC_HOL:  // Holiday
        {
            if (entry_index < BAC_HOLIDAY_COUNT)
            {
                annual_list_line = entry_index;
                AnnualRoutine_Window->OnBnClickedButtonAnnualEdit();
            }
        }
        break;
        case BAC_PRG:  // Program
        {
            if (entry_index < BAC_PROGRAM_ITEM_COUNT)
            {
                program_list_line = entry_index;
                Program_Window->OnBnClickedButtonProgramEdit();
            }
        }
        break;
        default:
            break;
```

```
        }
    }
}
```

Behavior

Local Panel Only

The message **only works for the local panel** (npanel_id == bac_gloab_panel). Remote panel editing is not supported.

Editor Windows

Weekly Schedule Editor:

- Maximum 32 schedules (BAC_SCHEDULE_COUNT)
- Sets `weekly_list_line` to entry_index
- Calls `WeeklyRoutine_Window->OnBnClickedButtonWeeklyScheduleEdit()`

Annual Holiday Editor:

- Maximum 32 holidays (BAC_HOLIDAY_COUNT)
- Sets `annual_list_line` to entry_index
- Calls `AnnualRoutine_Window->OnBnClickedButtonAnnualEdit()`

Program Editor:

- Maximum 16 programs (BAC_PROGRAM_ITEM_COUNT)
- Sets `program_list_line` to entry_index
- Calls `Program_Window->OnBnClickedButtonProgramEdit()`

Frontend Usage

Open Schedule Editor

TYPESCRIPT

```typescript
const openScheduleEditor = (panelId: number, scheduleIndex: number) => {
  const message = {
    action: 'OPEN_ENTRY_EDIT_WINDOW',
    panelId: panelId,
    entryIndex: scheduleIndex,
    entryType: 12  // BAC_SCH
  };

  sendMessage(JSON.stringify(message));
};

// Usage
openScheduleEditor(0, 5);  // Edit schedule #5
```

Open Holiday Editor

TYPESCRIPT

```typescript
const openHolidayEditor = (panelId: number, holidayIndex: number) => {
  const message = {
    action: 'OPEN_ENTRY_EDIT_WINDOW',
    panelId: panelId,
    entryIndex: holidayIndex,
    entryType: 13  // BAC_HOL
  };

  sendMessage(JSON.stringify(message));
};
```

Open Program Editor

TYPESCRIPT

```typescript
const openProgramEditor = (panelId: number, programIndex: number) => {
  const message = {
    action: 'OPEN_ENTRY_EDIT_WINDOW',
    panelId: panelId,
    entryIndex: programIndex,
    entryType: 6  // BAC_PRG
  };

  sendMessage(JSON.stringify(message));
};
```

Add Edit Buttons to Tables

TYPESCRIPT

```typescript
const renderEditButton = (entryType: number, entryIndex: number) => {
  return (
    <button
      onClick={() => {
        openEditor(currentPanelId, entryIndex, entryType);
      }}
    >
      Edit
    </button>
  );
};

const openEditor = (panelId: number, index: number, type: number) => {
  const message = {
    action: 'OPEN_ENTRY_EDIT_WINDOW',
    panelId: panelId,
    entryIndex: index,
    entryType: type
  };

  sendMessage(JSON.stringify(message));
};
```

Limitations

Local Panel Only

Not supported:

```JSON
{
  "action": "OPEN_ENTRY_EDIT_WINDOW",
  "panelId": 5,  // Remote panel - will be ignored
  "entryIndex": 0,
  "entryType": 12
}
```

The command is silently ignored for remote panels.

No Response

This message does not send a response. The web interface cannot detect:

- Whether the dialog opened successfully
- Whether the user saved or canceled
- What changes were made

Limited Entry Types

Only 3 entry types supported:

- Schedules (BAC_SCH = 12)
- Holidays (BAC_HOL = 13)
- Programs (BAC_PRG = 6)

Other types (inputs, outputs, variables, etc.) are ignored.

Validation

Index Range Checks

TYPESCRIPT

```typescript
const validateEditRequest = (entryType: number, entryIndex: number): boolean => {
  switch (entryType) {
    case 12:  // BAC_SCH
      return entryIndex >= 0 && entryIndex < 32;
    case 13:  // BAC_HOL
      return entryIndex >= 0 && entryIndex < 32;
    case 6:   // BAC_PRG
      return entryIndex >= 0 && entryIndex < 16;
    default:
      return false;
  }
};

// Usage
if (validateEditRequest(entryType, entryIndex)) {
  openEditor(panelId, entryIndex, entryType);
} else {
  showError('Invalid entry type or index');
}
```

Use Cases

Schedule Management

TYPESCRIPT

```typescript
// Schedule table with edit buttons
schedules.forEach((schedule, index) => {
  renderScheduleRow({
    name: schedule.label,
    status: schedule.status,
    onEdit: () => openScheduleEditor(panelId, index)
  });
});
```

Holiday Calendar

TYPESCRIPT

```typescript
// Holiday list with edit capability
holidays.forEach((holiday, index) => {
  renderHolidayItem({
    date: holiday.date,
    name: holiday.name,
    onEdit: () => openHolidayEditor(panelId, index)
  });
});
```

Program Editor Access

TYPESCRIPT

```typescript
// Program table with code editor link
programs.forEach((program, index) => {
  renderProgramRow({
    label: program.label,
    status: program.on_off ? 'Running' : 'Stopped',
    onEditCode: () => openProgramEditor(panelId, index)
  });
});
```

See Also

- Platform Overview - Architecture
- Data Structures - Entry type constants