## EE402 Mini Project 6

## M. Mert Ankarali\* Department of Electrical and Electronics Engineering Middle East Technical University

Due: 14-Jan-2018, @10:30 AM


- 1. (30 Points)
  - (a) Find a minimal state-space realization for the following discrete time transfer function

$$G_1(z) = \frac{z^2 + 0.5z}{z^3 - 2.2z^2 + 1.52z - 0.32}$$

(b) Find a minimal state-space realization for the following discrete time transfer function

$$G_2(z) = \frac{z^2 + 0.4z - 0.12}{z^2 + 0.6z - 0.4}$$

(c) Using the answers of parts 1(a) and 1(b), find a minimal state-space realization for the following discrete-time closed-loop system.



- 2. (30 Points) In this problem, we will investigate the matrix exponential. Consider  $A, P \in \mathbb{R}^{nn}$ 
  - (a) Show that when  $det(P) \neq 0$

$$e^{\left(P^{-1}AP\right)t} = P^{-1}e^{At}P$$

(b) Show that when  $det(A) \neq 0$ 

$$\left(\int_{0}^{T} e^{A\lambda} d\lambda\right) = A^{-1} \left(e^{AT} - I\right) = \left(e^{AT} - I\right) A^{-1}$$

(c) Given that  $(\lambda, \nu)$  is an eigenvalue and eigenvector pair of A. Based on this information, derive the associated eigenvalue and eigenvector pair of  $e^{At}$ .

You are supposed to derive the result, thus don't just type the answer.

<sup>\*</sup>This document © M. Mert Ankarali

(d) Compute  $e^{At}$  for the following matrix

$$A = \left[ \begin{array}{cc} \sigma & \omega \\ -\omega & \sigma \end{array} \right]$$

Hint: Your solution should be in terms of sinusoidal and exponential functions of  $\omega t$  and  $\sigma t$ .

(e) Compute  $e^{At}$  for the following matrix

$$A = \left[ \begin{array}{cc} 0 & 1 \\ 1 & 0 \end{array} \right]$$

without using the Laplace transform domain solution method.

3. (30 Points) Consider the following CT state-space representation

$$\dot{x}(t) = \begin{bmatrix} 0 & 1 \\ 0 & -1 \end{bmatrix} x(t) + \begin{bmatrix} 0 \\ 1 \end{bmatrix} u(t)$$

(a) Based on the procedures detailed in the lecture notes, discretize this state-space formulation under ZOH operation at the input and uniform ideal sampling at the states and compute the DT state-space representation and associated matrixes.

$$x[k+1] = Gx[k] + Hu[k]$$

T should exist symbolically in your matrices.

(b) Now approximate  $e^{AT}$  using the first order approximation given below

$$e^{AT} \approx I + AT$$

and using this approximation compute the approximated discretie time state-space equation

$$x[k+1] \approx \tilde{G}x[k] + \tilde{H}u[k]$$

- (c) Compute (G, H) and  $(\tilde{G}, \tilde{H})$  for different values of T, compre the results, and comment on them.
- 4. (30 Points) Stability of CT and DT dynamical systems
  - (a) Consider the DT system

$$x[k+1] = \begin{bmatrix} 0 & 1 \\ \alpha & 2\alpha - 1/2 \end{bmatrix} x[k] + \begin{bmatrix} 0 \\ 1 \end{bmatrix} u[k]$$
$$y[k] = \begin{bmatrix} -2 & 1 \end{bmatrix} u[k]$$

- i. For what values of parameter  $\alpha$  is the system asymptotically stable?
- ii. For what values of parameter  $\alpha$  is the system BIBO stable?
- (b) Consider the CT system

$$\dot{x}(t) = \begin{bmatrix} 0 & 1 \\ \alpha & 2\alpha - 1/2 \end{bmatrix} x(t) + \begin{bmatrix} 0 \\ 1 \end{bmatrix} u(t)$$
$$y(t) = \begin{bmatrix} -2 & 1 \end{bmatrix} u(t)$$

- i. For what values of parameter  $\alpha$  is the system asymptotically stable?
- ii. For what values of parameter  $\alpha$  is the system BIBO stable?