



AVIATION DISCONTINUED



GMA™ 340

PART NUMBER: 010-00152-11

Version

With Installation Kit and Pilot's Guide \$

FIND A DEALER

Like 0 Share G+

OVERVIEW

SPECS

General

Physical dimensions	6.29"W x 1.3"H x 7.72"D (16 x 3.3 x 19.6 cm)
Weight	1.7 lb (.8 kg)

Audio Panel Features

Telephone interface	tel ringer input, COM3 may be used as keyed (PTT) telephone interface
ICS (intercom system)	6 position intercom (individual VOX circuits for each of the 6 mic positions)

SWAGRAC, 540 Garmin	
ICS isolation modes	3 - All, Pilot, Crew
Transceivers	3 - COM1, COM2, COM3
Additional receiver inputs	4 - NAV1, NAV2, ADF, DME
Music source input	2 stereo music source inputs - isolation modes differ from 347
Music input impedance	460 Ohms
Music frequency response	100Hz - 15kHz
Speaker output	speaker output for radios or PA function (10W into 4 Ohms or 8 Ohms)
PA function	pilot selectable - dedicated button
Marker beacon	dual sensitivity
Manual squelch	⊘
SmartMute (includes SmartMute marker audio muting)	⊘
Intercom volume controls	②
Manual VOX level controls	2 (pilot, co-pilot/passenger)
Avionics squelch (squelch processing for noise reduction)	⊘
Failsafe (connects Pilot PTT, mic and headset to COM1 if unit is turned off)	
Split com (CoPilot transmits and receives on Com2 while Pilot transmits and receives on Com1)	
Alert/Unswitched inputs	2
TSO Authorization	②

IN THE BOX

ACCESSORIES

Related

Manuals Software

Support Center