

Storage of Data on DNA

Teneman Ibrahim Traore

May 25, 2026

Author Note:

This paper was prepared as a personal project.

Development of a C++ Emulator for Synthetic DNA Data Storage

Abstract: The rapid acceleration of global data production has outpaced the capacity of conventional storage infrastructures. As silicon and magnetic-based mediums face density and degradation limits, synthetic deoxyribonucleic acid (DNA) has emerged as a high-density, ultra-stable alternative. This small article details the architecture of a custom C++ emulator designed to translate digital binary data into quaternary nucleotide sequences, applying algorithmic constraints to satisfy the physical Biochemical requirements of laboratory synthesis and sequencing.

1. Introduction: The Archival Storage Paradigm

With global data storage demand having already surpassed the 1.75×10^{14} GB (175 Zettabytes) benchmark projected for 2025 (Doricchi et al., 2022), traditional storage methods are struggling to keep pace. The majority of this volume comprises “cold data” (archival information requiring long-term preservation but infrequent access). Maintaining this data in traditional facilities requires immense energy and water resources, and the underlying silicon hardware degrades within decades.

DNA presents a highly viable biological alternative. A single cubic inch of DNA possesses a theoretical capacity of one Exabyte and, under proper conditions, maintains structural integrity for millennia. To operationalize DNA as a storage medium, an algorithmic bridge must be established to translate silicon-based digital logic into carbon-based molecular architecture.

[DIAGRAM 1: The Molecular Archival Pipeline]

[Digital File] -> [Binary Output] -> [C++ Translation Engine] -> [Oligonucleotide Sequence] -> [Physical Synthesis]

Diag 1: Conceptual overview of the encoding pipeline, translating standard digital files into quaternary nucleotide representations for chemical synthesis.

2. Digital Translation: Binary to Quaternary Mapping

Computational systems operate on a binary architecture, representing data through distinct voltage states. Conversely, DNA functions as a quaternary system composed of four specific nucleotide monomers: Adenine (A), Cytosine (C), Guanine (G), and Thymine (T).

The initial function of the C++ emulator is to execute a direct mapping of binary pairs to these corresponding nucleotides. Because a two-bit sequence yields four possible states, the mapping is structurally perfectly aligned:

- 00 → A
- 01 → C
- 10 → G
- 11 → T

// Translates 8-bit binary strings to Base-4 DNA sequences

```
string binaryToDNA(string binaryStr) {  
    string dna = "";  
    for (size_t i = 0; i < binaryStr.length(); i += 2) {
```

```

    string pair = binaryStr.substr(i, 2);
    if (pair == "00") dna += "A";
    else if (pair == "01") dna += "C";
    else if (pair == "10") dna += "G";
    else if (pair == "11") dna += "T";
}
return dna;
}

```

Through this logic, an 8-bit byte such as 01000010 (the ASCII character ‘B’) is systematically converted into the four-base sequence CAAG.

3. Biophysical Constraints and Algorithm Optimization

Direct translation of a comprehensive digital file into a single, continuous DNA sequence is biochemically impractical. The software must enforce specific biological parameters to ensure the sequences can be successfully synthesized, amplified, and sequenced.

3.1. Synthesis Coupling Limits (Fragmentation)

Artificial DNA synthesis, executed via phosphoramidite chemistry or light-directed maskless synthesis, constructs molecules iteratively. Due to imperfect chemical coupling efficiencies, the probability of introducing insertion or deletion errors increases exponentially with strand length (Agbavwe et al., 2011). To maximize synthesis yield, the emulator actively fragments large data payloads into defined oligonucleotides of 150 to 200 bases.

3.2. Base-Stacking Thermodynamics (GC Content Regulation)

Nucleotide pairings exhibit distinct thermodynamic properties. Guanine-Cytosine (G-C) bonds utilize three hydrogen bonds and possess stronger $\pi - \pi$ orbital base-stacking energies compared to the two hydrogen bonds of Adenine-Thymine (A-T) pairs. This discrepancy dictates the overall stability and melting temperature (T_m) of the DNA double helix (Banerjee et al., 2023).

Sequences with excessive A-T content risk low-temperature denaturation, while excessive G-C content prompts the formation of complex secondary structures. The emulator algorithmically targets a ~50% GC content, normalizing the thermodynamic profile across the entire data pool to ensure uniform behavior during Polymerase Chain Reaction (PCR) amplification.

3.3. Polymerase Slippage Mitigation

High-throughput sequencing platforms and high-fidelity polymerase enzymes frequently exhibit “polymerase slippage” when processing homopolymers extended repetitive sequences such as AAAAAA (Brelsford et al., 2011; Furutani et al., 2022). This slippage introduces critical reading errors. The encoding algorithm incorporates parameters to disrupt extended homopolymer runs prior to synthesis, maintaining reading fidelity.

4. Positional Indexing and Sequence Reassembly

Because the emulator fragments the overarching file into 200-base segments, the resulting synthesized oligonucleotides lack physical ordering within a liquid medium. Reassembly requires the integration of a structural address.

The program calculates a sequential decimal index for each fragment and converts this integer into a distinct Base-4 DNA barcode. This index, alongside required PCR primer binding sites, is appended to the data payload.

[DIAGRAM 2: Single Oligonucleotide Strand Architecture]

[Left PCR primer] -> [Base-4 Index Barcode (page number) (6 bases)] -> [Encrypted Data Payload (150-200 bases)] -> [Right PCR Primer (GCAT)]

Diag 2: Structural layout of the engineered data strand. Primer sequences flank the boundaries to facilitate target amplification, while the mathematical index ensures accurate programmatic reassembly following nucleotide sequencing.

4.1. Structural Considerations: Single-Stranded vs. Double-Stranded DNA

A notable design element of the encoding software is its exclusive generation of a single-stranded sequence (5' to 3'). Computationally mapping the complementary sequence would constitute redundant data storage. Due to Watson-Crick base-pairing principles, the synthesized single-stranded DNA (ssDNA) naturally forms the stable double-stranded DNA (dsDNA) helix once exposed to polymerase enzymes and complementary nucleotides during standard laboratory amplification.

5. Conclusion

This C++ emulator demonstrates the necessary convergence of software engineering and biophysics in developing next-generation archival systems. By translating digital logic while strictly adhering to thermodynamic and synthetic constraints, data can be durably encoded into biological molecules. As synthesis costs decline and sequencing velocities increase, such algorithmic frameworks will be foundational to implementing DNA as a macro-scale storage solution.

Appendix: Technical Implementation Guide

For researchers aiming to replicate or build upon this encoding environment in a Windows operating system, the following pipeline details the necessary compiler configuration and execution steps. You can also go to my [Github](#) page for more information about source code of the project

1. Compiler Installation Windows requires external configuration for C++ compilation.

- Download and execute the [MSYS2](#) installer.
- Launch the MSYS2 terminal and install the GCC toolchain using the following command:

```
pacman -S --needed base-devel mingw-w64-ucrt-x86_64-toolchain
```

2. Environment Variable Configuration To allow IDEs to locate the compiler, the directory path must be registered in the system environment.

- Navigate to Windows **Environment Variables**.
- Under **System Variables**, locate and edit the **Path** entry.
- Append the following new directory path: C:\msys64\ucrt64\bin.

3. Program Compilation and Execution

- Open the project directory within Visual Studio Code.
- Initialize a new integrated terminal.
- Compile the source file into an executable:

```
g++ dna_encoder.cpp -o dna_encoder
```
- Execute the compiled program against the target text file:

```
.\dna_encoder.exe bio.txt
```

The execution will generate a formatted .fasta file containing the structurally constrained, index-barcode oligonucleotide sequences.

References

- **Agbavwe, C., et al. (2011).** Efficiency, Error and Yield in Light-Directed Maskless Synthesis of DNA Microarrays. *Journal of Nanobiotechnology*, 9:57.
- **Banerjee, A., et al. (2023).** Single-molecule analysis of DNA base-stacking energetics using patterned DNA nanostructures. *Nature Nanotechnology*, 18.
- **Brelsford, A., et al. (2011).** Nonspecific PCR amplification by high-fidelity polymerases: implications for next-generation sequencing of AFLP markers. *Molecular Ecology Resources*.
- **Doricchi, A., et al. (2022).** Emerging Approaches to DNA Data Storage: Challenges and Prospects. *ACS Nano*, 16, 17552–17571.
- **Furutani, S., et al. (2022).** Rapid DNA Sequencing Technology Based on the Sanger Method for Bacterial Identification. *Sensors*, 22(2130).
- **Nguyen, B. H., et al. (2020).** Architecting Datacenters for Sustainability: Greener Data Storage using Synthetic DNA. *Microsoft Research*.