

DRA: Distributionally Robust Adversarial Training

Nian Si Fan Zhang Teng Zhang

Department of Management Science and Engineering, Stanford University

Abstract

In this paper, we generalize Wasserstein based distributional robust optimization framework to improve the model's robustness against adversarial examples at scale. We develop the defense framework of multi-cost ensemble and adaptive cost learning. We test our method by training a 13 layers neural net on the CIFAR-10 dataset against various white-box attacks. The result shows that the proposed defense achieves the state-of-art performance in ℓ_∞ based attacks and outperforms other methods in ℓ_2 based attacks.

Introduction

Neural network is a powerful model that has excellent explanatory power in the domain of vision classifications and speech recognitions, etc. However, it is well known that neural network is vulnerable to adversarial examples. In the context such as automatic driving where mistakes are expensive, the robustness of neural network to adversarial examples received increasing attention from machine learning community.

To remedy the vulnerability to adversarial examples, many methodologies are proposed to generate and defend against the adversarial attacks. In this project, we generalized the Wasserstein based adversarial training procedure proposed by Sinha et al., and test its performance on CIFAR-10 datasets.

Contribution

- We show our distributionally robust adversarial training framework encompasses many other popular heuristic methods used in adversarial training.
- We generalize Wasserstein based adversarial training procedure and test our method in larger data sets (CIFAR10).
- We apply attack ensemble techniques to improve the out-of-sample performance of our defend method.

Model Formulation

The adversarial training procedure can be formulated as a distributionally robust optimization problem

$$\min_{\theta \in \Theta} \sup_{P \in \mathcal{P}} E_P[l(\theta; Z)], \quad (1)$$

where \mathcal{P} is the plausible data distribution set. In this paper, we consider the set as an Wasserstein ball, i.e. $\mathcal{P} = \{P : W_c(P, P_0) \leq \delta\}$, where W_c is the Wasserstein metric under cost function c and P_0 is the empirical distribution.

Using strong duality theorem proposed by *Blanchet and Murthy*, (1) is equivalent to

$$\min_{\theta \in \Theta} \inf_{\gamma \geq 0} \gamma \delta + E_{P_0}[\phi_\gamma(\theta; Z)],$$

where

$$\phi_\gamma(\theta; z) = \sup_{\hat{z}} (l(\theta; \hat{z}) - \gamma c(z, \hat{z})).$$

To make the training process tractable, we will fix γ and optimize the Lagrangian relaxation

$$\min_{\theta \in \Theta} E_{P_0}[\phi_\gamma(\theta; Z)]. \quad (\text{DRA})$$

Connection with other model: Since the cost function c is free to select, we can recover many common methods in literature using various cost functions. For example, we can recover Basic Iteration Method, Elastic Net Method, *etc.*

Adaptive Cost Function $c(\cdot)$: For this method, we consider Mahalanobis distance,

$$c_A(x_1, x_2) = (x_1 - x_2)^T A (x_1 - x_2)$$

where A is chosen by the adversary to produce strongest attack, *i.e.*

$$\min_{\theta \in \Theta} \max_{A \in \mathcal{A}} \mathbb{E}_{\hat{P}_n} \phi_\gamma(\theta; z),$$

Cost Function Ensemble: Suppose we know cost function is ℓ_2 norm with probability p and cost function is ℓ_∞ norm with probability $1 - p$. Then, in our training, we randomly pick the cost function with probability p in each steps to train.

Algorithm

Input: The empirical distribution P_0 , learning rate α , minibatch size M , iteration times T .

For $t = 0, \dots, T - 1$

 Sample a minibatch from P_0 and for each image, find an maximizer \hat{z}_i^t of $l(\theta^t; z_i) - \gamma c(z_i, \hat{z}_i^t)$.
 $\theta_{t+1} \leftarrow \theta_t - \alpha \nabla_{\frac{1}{M} \sum_{i=1}^M l(\theta^t; \hat{z}_i^t)}$.

Experiments and Result

Dataset We test on the CIFAR-10 data set.

Network structure We test the defenses and attacks based on a 13-layer convolutional neural nets. It consists 10 convolutional layers and 3 fully connected layers intercepted with max pooling layers. This baseline model achieves 79.9% accuracy on the clean test dataset.

Defense models For our distributionally Robust Adversarial Training method, we compare 4 methods respectively: Basic Distributionally Robust Adversarial Training with ℓ_2 -norm cost function (DRA₂), Basic Distributionally Robust Adversarial Training with ℓ_∞ -norm cost function(DRA _{∞}), Distributionally Robust Adversarial Training with Multi-cost-function Ensemble (DRA_{2- ∞}) and Adaptive Distributionally Robust Adversarial Training (DRA_A). We compare our models with Fast Gradient Sign Method (FGM), Basic Iterative Method (IGM), Momentum Iterative Method (MGM) under the attack mentioned above.

Result of baseline model under attacks:

FGM ₂	FGM _{∞}	IGM ₂	IGM _{∞}	MGM ₂	MGM _{∞}	DRA ₂
0.196	0.107	0.096	0.088	0.097	0.087	0.005

Test accuracy on clean data for various defense model:

Baseline	FGM ₂	FGM _{∞}	IGM ₂	IGM _{∞}	MGM ₂	MGM _{∞}
0.799	0.741	0.739	0.717	0.673	0.713	0.742
DRA ₂	DRA _{∞}	DRA _A	DRA _{2-∞}			
0.652	0.587	0.672	0.577			

Result of ℓ_2 type defense model: Each row corresponds to attacks while each column corresponds to defense models.

	FGM ₂	IGM ₂	MGM ₂	DRA ₂	DRA _A
FGM ₂	0.439	0.446	0.452	0.490	0.515
FGM _{∞}	0.155	0.154	0.162	0.206	0.192
IGM ₂	0.372	0.397	0.399	0.457	0.492
IGM _{∞}	0.119	0.121	0.115	0.146	0.141
MGM ₂	0.384	0.406	0.407	0.462	0.497
MGM _{∞}	0.119	0.122	0.116	0.166	0.155
DRA ₂	0.071	0.104	0.087	0.270	0.254

Result of ℓ_∞ type defense model: Each row corresponds to attacks while each column corresponds to defense models.

	FGM _{∞}	IGM _{∞}	MGM _{∞}	DRA _{∞}	DRA _A	DRA _{2-∞}
FGM ₂	0.288	0.517	0.516	0.427	0.515	0.463
FGM _{∞}	0.645	0.275	0.279	0.226	0.192	0.256
IGM ₂	0.139	0.496	0.497	0.407	0.492	0.439
IGM _{∞}	0.079	0.196	0.201	0.170	0.141	0.201
MGM ₂	0.145	0.500	0.500	0.405	0.497	0.440
MGM _{∞}	0.062	0.196	0.204	0.184	0.155	0.212
DRA ₂	0.002	0.247	0.339	0.209	0.254	0.240

Visualization of Adversarial Examples




Figure 1: DRA₂




Figure 2: Original Image