JUNIOR DEOGRACIAS MAMBO MOTSOU

EMBEDDED SOFTWARE ENGINEER

C firmware · **RTOS & OS** · **Build & toolchains** · **Debug & test**

CONTACT

+33 6 01 16 86 06
motsoujunior17@gmail.com
teo1747.github.io/Portfolio
github.com/teo1747
linkedin.com/in/teo1747
France
Available now

LANGUAGES

English ●●●●●
native (anglophone), TOEIC C1 (2024)

French ●●●●○
fluent, professional use (B2)

TECHNICAL SKILLS

Languages

C (C99/C11) · **Python** · **C++** (Qt) · **Kotlin** · **assembly: x86-64** (NASM) · **Arm Thumb** · **RISC-V**

RTOS & OS

FreeRTOS (tasks, queues, mutexes, event groups, stream buffers) · **Zephyr** (devicetree, Kconfig) · **bare-metal** · **kernel internals: scheduling** · **context switch** · **paging** · **interrupts** · **syscalls** · **filesystems**

Linux

Ubuntu as daily host · **user-space drivers (spidev, i2c-dev, sysfs GPIO) on Raspberry Pi**

Build & toolchains

GCC (arm-none-eabi, x86_64-elf cross) · **Clang** · **linker scripts** · **CMake** · **Ninja** · **GNU Make** · **West** · **Kconfig** · **IAR EWARM** · **MPLAB X** (XC16/XC32)

Debug & test

GDB (remote, QEMU) · **J-Link** · **QEMU** · **unit tests with ASan/UBSan** · **conformance and differential testing against reference models**

Automation

Git (pull-request workflow) · **GitHub Actions CI** · **Python tooling**

Interfaces

UART · **SPI** · **I²C** · **LIN** · **MeLiBu** · **Bluetooth serial with a JSON protocol** · **REST/HTTP clients**

Applications

Python multithreading (PyQt5, OpenCV)

Embedded software engineer (Polytech Dijon, 2026) focused on C firmware, real-time operating systems and their tooling. At FORVIA I wrote and debugged firmware for automotive microcontrollers and a multithreaded Python/Kotlin control stack for a lighting demonstrator. In personal projects I build an RTOS, an x86-64 OS and a C toolchain, with attention to build systems, CI and testing.

Professional experience

Sep. 2025 – Sep. 2026

FORVIA – Faurecia Interior Systems | Embedded Systems Engineer — apprentice (contrat de professionnalisation)

Surface Activation department, France

Interior ambient-lighting demonstrator (software owner)

- Extended the control software of an automotive interior demonstration buck from a few LED displays to nine STM32 UART gateways driving WS2812 LED strips across several lighting zones.
- Wrote a multithreaded Python/PyQt5 application: OpenCV decodes MP4 animations, maps logical LED IDs to frame pixels and distributes each frame to one worker thread per gateway at 921 600 baud, with a barrier to keep all nine gateways in step; custom serial frames (ASCII with delta compression).
- Built an Android tablet app (Kotlin, Jetpack Compose) that controls zones, colours and brightness presets over Bluetooth serial using a JSON command protocol with explicit error codes; added a keyboard fallback mode.
- Adapted the STM32 gateway firmware with minimal changes (ID-offset filtering when two gateways share a UART line).

Python 3 · **PyQt5** · **OpenCV** · **Kotlin/Jetpack Compose** · **STM32** (C) · **WS2812** · **UART** · **Bluetooth SPP** · **Git**

Firmware bring-up: LIN-controlled heating-element controller (TCU)

- Developed C firmware on the Infineon TLD4020-3ET (Arm Cortex-M23 with integrated LIN): LIN ON/OFF command handling, heater PWM through the LDRV peripheral, NTC-based temperature regulation, fault protection and a state-machine architecture.
- Diagnosed early bring-up blockers: traced a HardFault in device initialisation to a silicon-revision mismatch on the evaluation board (register absent on older silicon), and a lost debug connection to boot-mode jumper and USB power conditions.
- The NTC divider is supplied from the switched heater output, so the ADC node is a 100 Hz square wave during PWM. Synchronised sampling to the PWM on-time (ISR at mid-pulse, 16-sample averaging), which brought measurement scatter within the regulation requirement.

TLD4020-3STD_EVAL board · **IAR Embedded Workbench** · **Infineon MCU Configuration Wizard** · **on-board J-Link** · **printf over LIN** (MobaXterm, 19 200 baud 8N1)

MeLiBu LED driver port: Melexis MLX81116 to MLX81143

- Ported an existing MeLiBu 1.x driver on RP2040 to the MLX81143: extended-mode sub-address encoding (14 LEDs per node), linear 15-bit PWM encoding confirmed against the datasheet and on the hardware, for a 22×7 panel (154 RGB LEDs).
- Fixed bus-timing faults: break generation with busy-wait while interrupts are masked, critical section narrowed to the break to stop UART RX byte loss, TX-FIFO drain to prevent back-to-back frame collisions; corrected the bus return pin.

RP2040 · **Raspberry Pi Pico SDK** · **PIO state machines** · **C** · **MeLiBu 1.x**

Apr. – Aug. 2025

KMUTT — MDT Lab | Embedded Systems Intern

Bangkok, Thailand

- Image-processing work for a precision-agriculture project: fruit classification by transfer learning on VGG16 (Keras/TensorFlow), 98.4 % accuracy on a 4 599-image test set (Fruits-360, 131 classes), plus an OpenCV contour/colour detection pipeline.

Python · **TensorFlow/Keras** · **OpenCV**

Personal & academic projects

PERSONAL

Ongoing. Validation so far is in emulation (QEMU, EmbSIM), not on physical boards.

Oct. 2026 –

EmbLinkRTOS — preemptive RTOS for microcontrollers

personal · github.com/EmbLinkOs/EmbLinkRTOS

- Fixed-priority preemptive scheduler (bitmap ready lists, FIFO within a priority); Cortex-M port with PendSV/PSP context switch, lazy FPU save and BASEPRI critical sections; RISC-V (mret, CLINT) and AVR ports.
- Semaphores, mutexes with priority inheritance and priority ceiling, timeouts;

Qt/C++
Android (Kotlin, Jetpack Compose)

CERTIFICATION

- Cisco CCNA 1 (July 2024)

conformance tests and differential testing against a Python reference model of the scheduler.
- CMake/Kconfig build with board definitions (NUCLEO-F446RE, Arduino Uno, ESP32-C3); GitHub Actions CI with ASan/UBSan/TSan, QEMU and EmbSIM runs.

May 2026 –

EmbLinkOS — x86-64 operating system from scratch

personal · github.com/EmbLinkOs/EmbLinkOs

- Two-stage BIOS bootloader in NASM (real, protected, then long mode) and a UEFI PE32+ loader, higher-half kernel in C: 4-level paging, APIC/IO-APIC, SMP, ring-3 processes, syscalls, ELF loader.
- Copy-on-write B-tree filesystem (CRC32C, snapshots, AES-XTS) checked against a Python oracle; FAT32, VFS; PCI, AHCI, NVMe and USB drivers; newlib and TCC ports.
- In-kernel selftests, host unit tests under ASan/UBSan, QEMU-driven integration tests; GDB remote debugging.

Jul. 2026 –

EmbCC — C cross-compiler toolchain

personal · github.com/EmbLinkOs/EmbCC

- C99 compiler, assembler and linker with Cortex-M, RISC-V, AVR and x86-64 back-ends; firmware utilities (SVD-to-header/startup generation, HEX/UF2 packing).
- Verification: encodings cross-checked against llvm-mc/GNU as, generated code run under QEMU and compared with GCC/Clang; GitHub Actions CI on Linux and macOS with GCC and Clang.

Oct. 2026

RFID/PIN access-control terminal on FreeRTOS

personal · github.com/teo1747/stm32-freertos-access-control

- Register-level drivers (no vendor HAL) on STM32F446RE: MFRC522 RFID on SPI, SSD1306, DS3231 RTC and 24LC256 EEPROM on I²C, keypad, servo PWM, watchdog; six FreeRTOS tasks with queues, mutexes, event groups and stream buffers; salted, stretched SHA-256 PINs; CRC-checked log.
- Host unit tests with sanitizers and system scenarios in EmbSIM; not yet tested on a physical board.

NUCLEO-F446RE **FreeRTOS 11** **CMSIS** **arm-none-eabi-gcc** **CMake** **Ninja**

POLYTECH DIJON

2025 – 2026

Real-time thermometer: bare-metal PIC24, then FreeRTOS on PIC32MZ

Polytech, solo then pair · github.com/teo1747/pic24-32-rt-thermometer

- V1 (solo): bare-metal PIC24FJ1024GB610 with RTCC timestamps and SPI EEPROM logging. V2 (pair): FreeRTOS pipeline of acquisition, analysis and display tasks on PIC32MZ2048EFH100, linked by queues and binary semaphores; timestamped messages; °C/°F toggle on a button.

Explorer 16/32 **MPLAB X** **XC16/XC32** **Harmony v3/MCC** **FreeRTOS 10.5** **TC1047A sensor** **on-board debugger**

2025 – 2026

Zephyr RTOS feasibility study on STM32

Polytech lab · github.com/teo1747/zephyr-stm32-sensor-hub

- Three threads share one I²C bus: BMP280 (temperature/pressure), MPU6050 (6-axis IMU) and an SSD1306 OLED through the display API and CFB; shared data protected by a mutex; board configured through a devicetree overlay. (Repository rebuilt from the lab report.)

NUCLEO-G474RE **Zephyr** **West** **CMake** **Ninja** **STM32CubeProgrammer** **serial console**

Mar. 2025

Embedded Linux peripherals on Raspberry Pi

Polytech, team

- User-space C drivers for Pmod modules: SPI ambient-light sensor through spidev (mode 3, 2 MHz), I²C humidity sensor through i2c-dev, GPIO through sysfs; built with Make.

🎓 Education

2023 – Sep. 2026

Engineering degree (Diplôme d'ingénieur, Master's level) — Embedded Systems | Polytech Dijon

Dijon, France

Graduated. Final-year apprenticeship at FORVIA. Coursework: electronics, PCB design, real-time systems, SoC/FPGA.

2021 – 2023

Two-year preparatory programme — mathematics, physics, electronics | IUC

Cameroon