

Print at 100% on 200–300 gsm cardstock. Score all fold lines before folding.

A — HOW TO FOLD A RAMP

1) CUT the ramp on black solid lines. 2) SCORE all BLUE dashed and RED dotted lines. 3) CUT & REMOVE all ORANGE notch triangles before folding. 4) FOLD in sequence: valley and mountain lines, then glue side tabs to walls.

B — WHY NOTCHES ARE REQUIRED

At each step fold, side-wall strips must bend cleanly to 90°. Without removing the notch triangles, paper bunches at the inner corner and the ramp cannot lie flat.

C — OVERALL ASSEMBLY ORDER

1) Print all sheets at 100% (no fit-to-page). 2) Score all fold lines before cutting. 3) Cut black lines and remove all orange notches on ramps. 4) Assemble base tray (Sheet 05): F1-F4 valley, F5 mountain, glue corners. 5) Assemble body A + body B (Sheets 01-02). 6) Pre-fold and glue ramps C, then B, then A on matching anchors. 7) Attach base tray and run a d6 drop test.

D — MATERIALS & TOOLS

• Cardstock: 200-250 gsm recommended. • Glue: PVA or glue stick (thin bead). • Tools: bone folder, craft knife + metal ruler, scissors for small trims. • Avoid hot glue for alignment-sensitive joints.

LEGEND



CUT



VALLEY FOLD



MOUNTAIN FOLD



GLUE TAB



NOTCH – CUT & REMOVE

