
OS-level virtualization

- Let's consider **operating system (OS) level virtualization** (or ***container-based virtualization***)
- It allows running multiple isolated (*sandboxed*) user-space instances on top of a single OS attraverso la condivisione del kernel, che pone però delle limitazioni
  - Such instances are called:
    - **containers**
    - jails
    - zones nasce su Free-BSD

OS-level virtualization

- OS kernel allows the existence of multiple isolated user-space instances, called containers sinteticamente
- Each container has:
  - Its own set of processes, file systems, users, network interfaces with IP addresses, routing tables, firewall rules, …
- Containers share the same OS kernel (e.g., Linux)



OS-level virtualization: mechanisms


- Which OS kernel mechanisms are used to manage containers? più altri meccanismi di sicurezza che non saranno tratti nel corso
  - Containers need to isolate processes from each other in terms of sw and hw (CPU, memory, …) resources
- Main mechanisms offered by Unix-like OS kernels
  - chroot (change root directory) presente su qualsiasi Unix-based OS
    - Allows changing the apparent root folder for the current running process and its children
  - cgroups (Linux-specific)
    - Manage resources for groups of processes, such as CPU and memory allocation
  - namespaces (Linux-specific)
    - Per-process resource isolation, ensuring that each container has its own isolated environment

da considerare con cautela data la possibile problematica di sicurezza che può generare

Mechanisms: namespaces

- Feature of Linux kernel that allows to isolate what a set of processes can see in the operating environment
  - Includes resources such as processes, ports, files, …
- Kernel partitions resources so that one set of processes can see a specific set of resources, while another set of processes sees a different set of resources
- 6 different types of namespaces

i sei tipi sono anche a cosa fa riferimento un namespace



Mechanisms: namespaces

- mnt: isolates mount points seen by a container
  - Virtually partitions the file system, so processes running in separate mount namespaces cannot access files outside of their mount point
- pid: isolates PID space, ensuring that each process only sees itself and its children (PID 1, 2, 3, …)
- network: allows each container to have its dedicated network stack
  - Its own private routing table, set of IP addresses, socket listings, firewall rules, and other network-related resources
- user: isolates user and group IDs
  - E.g., allows a non-root user on host to be mapped to root user within the container, without granting actual root access to host

Mechanisms: namespaces

- uts (Unix timesharing): provides dedicated host and domain names
  - Allows processes to think they are running on servers with different names, even though they share the same host
- ipc: provides dedicated shared memory for IPC
  - E.g., separate Posix message queues for different containers

interprocesscomunication


Mechanisms: cgroups

- cgroups = control groups
- Limit, measure and isolate the use of hw resources (CPU, memory, I/O, network) for a group of processes
- Exposed via a filesystem interface (similar to `sysfs` and `procfs`)
  - Default mount point: `/sys/fs/cgroup/`

- In a nutshell:
  - namespaces implement *information isolation*: what a container can see
  - cgroups implement *resource isolation*: how many resources a container can use

OS-level virtualization: pros

- VMM-based vs container-based virtualization



In a nutshell: lightweight vs. heavyweight

OS-level virtualization: pros

vs. VMM-based virtualization (type-1)

Non è presente Guest OS, dato che il kernel è condiviso

- ✓ Near-native performance nessun intermediario per syscall
  - No VMM indirection for system calls
- ✓ Fast startup and shutdown
  - Seconds (even msec) per container vs. minutes per VM
- ✓ High density
  - Hundreds of containers per physical machine (PM)
- ✓ Small footprint
  - Container images are smaller since they exclude the OS kernel a differenza di poche VM grosse svariati GB.
- ✓ Memory efficiency
  - Containers can share memory pages on the same PM
- ✓ Portability and interoperability
  - Apps run across environments

OS-level virtualization: cons

vs. VMM-based virtualization (type-1)

✗ Less flexible

- Only supports native apps for the OS kernel (e.g., no Windows container on Linux host)
- Cannot run different OS kernels on same PM; however, can run multiple Linux distributions (e.g., Ubuntu, CentOS)

✗ Weaker isolation

- Process-level isolation leads to higher performance interference on shared resources

✗ Higher security risks

un container compromesso permette di attaccare l'host sottostante

- A kernel vulnerability affects the entire system
- Since containers share the kernel, one compromised container can impact other containers and the host


✗ Reduced hardware/device isolation

il container può avere accesso diretto al hardware. nvidia fornisce il passthrough tramite VGPU

- Device passthrough is more difficult and less secure

OS-level virtualization: products

- Docker
  - Most popular container engine
  - Provides *application containers*
    - Package and run *a single application* with its dependencies
  - Supports Open Container Initiative (OCI) standards https://opencontainers.org
- LXC (LinuX Containers) https://linuxcontainers.org/lxc/
  - Supported by mainline Linux kernel
  - Provides *system containers*
    - Run a *whole OS user space with multiple processes*, but share the host kernel




OS-level virtualization: products

- Podman https://podman.io
  - Supports OCI; Docker compatible CLI
  - Daemonless, rootless operation for improved security
- FreeBSD Jail
  - Strong process and filesystem isolation
- OpenVZ / Virtuozzo https://openvz.org
  - For Linux; primarily for system containers
- Non-Linux platforms
  - Windows and macOS support containers (e.g., Docker Desktop)
- Alternative approach
  - Install a Linux VM as a guest OS
  - Run container engines (e.g., Docker) inside the VM si ha nested virtualization insomma
  - Performance Impact: nested virtualization leads to reduced performance

Containers, DevOps and CI/CD


- DevOps: development methodology that bridges the gap between Development and Operations, focusing on collaboration, continuous integration, and automated delivery
- CI/CD:
  - Continuous Integration (CI): merges developers' work into a shared codebase
  - Continuous Delivery (CD): ensures frequent and reliable releases

mentre prima DEV e OPS erano separati e svolti da due team. oggigiorno c'è una stretta collaborazione tra i membri che sviluppano e gestiscono lo sviluppo e la manutenzione del software.



Containers, DevOps and CI/CD

- Containers: simplify building, packaging, sharing, and deploying apps with all dependencies
- Enable collaboration by sharing images, and streamline deployment across environments without extra configuration




Containers, microservices, and serverless

- Using containers
  - Package apps and all dependencies into a single unit that runs almost anywhere
  - Use fewer resources than traditional VMs

    I container sono anche più facili da manutenere
- Containers enable
  - Microservices: break down apps into small, independent services
  - Serverless: package functions into containers for efficient execution assieme alle micro VM

Case study: Docker

- Lightweight and secure container-based virtualization
  - Application containers: contain the application and its dependencies, but share OS kernel with other containers
  - Isolation: containers run as isolated processes in user space on host OS
  - Portability: containers are infrastructure-agnostic and can run anywhere qualche dipendenza però, dall'architettura della CPU c'è in realtà



layer NECESSARIO

Docker: features

- Portable deployment
  - Easily deploy across different machines and environments
- Versioning
  - Git-like version control for container images
- Component reuse
  - Reuse components (e.g., libraries, services) via Docker images aumenta la portabilità e interoperabilità
- Shared libraries
  - Access to pre-built images on Docker Hub https://hub.docker.com
- OCI support
- Scalability
  - Works seamlessly with Kubernetes for scaling applications


Kubernetes permette di eseguire la stessa applicazione su più server. mentre docker compose no anche con docker compose che però non scala dinamicamente le repliche a differenza di Kubernetes

Docker: internals

- Written in Go
- Exploits Linux kernel mechanisms for resource management and isolation (cgroups and namespaces)
  - Early versions were based on Linux Containers
  - Then transitioned to libcontainer, a Go-based container runtime: provides tools for managing containers with namespaces, cgroups, capabilities, and filesystem access controls
    https://pkg.go.dev/github.com/opencontainers/runc/libcontainer
  - runc: libcontainer is now part of runc, the CLI tool for spawning and running containers based on OCI specification
    https://github.com/opencontainers/runc

Docker Engine: architecture

- Docker Engine: core component of Docker that enables containerization
- Client-server application composed by
  - **Docker daemon (dockerd)**: server component that listens for API requests and manages Docker objects like images, containers, networks, and volumes




  - **REST API**: specifies the interfaces that programs can use to interact with Docker daemon for operations like creating, managing, and querying Docker objects
  - **CLI client**: allows users to send commands to Docker daemon via REST API

https://docs.docker.com/get-started/docker-overview/#docker-architecture

Docker: client-server architecture

- Docker client
  - Interface through which users interact with Docker
  - Sends commands to Docker Daemon to build, run, and distribute Docker containers
  - Client and daemon communicate through sockets or the REST API

sul server si può creare una rete interna che viene usata dai container per collaborare



Docker: images

- Read-only template
  - Used to create Docker containers, containing everything needed to run app (code, dependencies, configurations)
- Build component
  - Docker images enable distribution of apps with their runtime environments, removing the need to manually install packages
  - Target machine must be Docker-enabled
- **Dockerfile** cosa sono? Template in particolare:
  - Text file with simple instructions that Docker uses to build images automatically
- **Image registry** in remoto
  - Images can be pulled and pushed to/from public or private registries
- Image naming
  - Format: `[registry/][user/]name[:tag]` opzionali sono gli elementi nelle parentesi
  - Default tag is latest

Docker image: Dockerfile

- Docker images are created from a Dockerfile and a context
  - Dockerfile: text file containing instructions to assemble the image potrebbe essere minimo
  - Context: set of files (e.g., app code, libraries) used during the image build process
  - Images often build on parent images (e.g., Alpine, Ubuntu)
- Dockerfile syntax

  `# Comment` (for comments)

  `INSTRUCTION arguments` (commands like RUN, COPY, etc.)
- Instructions in the Dockerfile run sequentially

Docker image: Dockerfile

- Common Dockerfile instructions
  - **`FROM <image>`**: specifies the parent image (mandatory unless you want to start from **`scratch`**) FROM scratch (per partire da zero)
  - **`WORKDIR <path>`**: sets the working directory inside the container
  - **`COPY <host-path> <image-path>`**: copies files from host to container image
  - **`RUN <command>`**: executes the specified command during image build
  - **`ENV <name> <value>`**: sets an environment variable
  - **`EXPOSE <port>`**: exposes a network port for the container
  - **`CMD ["<command>", "<arg1>"]`**: defines the default command to run when the container starts

https://docs.docker.com/get-started/docker-concepts/building-images/writing-a-dockerfile/

Docker image: Dockerfile

- Example: Dockerfile to build the image of a container that will run as application a simple todo list manager written in Node.js

```
# syntax=docker/dockerfile:1


FROM node:lts-alpine
WORKDIR /app
COPY . .
RUN yarn install --production
CMD ["node", "src/index.js"]
EXPOSE 3000
```

Directory with app code

```
├── getting-started-app/
│   ├── package.json
│   ├── README.md
│   ├── spec/
│   ├── src/
│   └── yarn.lock
```

https://docs.docker.com/get-started/workshop/02_our_app/

Docker image: build

- Building Docker image from Dockerfile and context
  - Context: set of files located in the specified PATH or URL
- Build command

```
$ docker build [OPTIONS] PATH | URL | -
```

- Example: to build an image for Node.js app (slide 24)

```
$ docker build -t getting-started .
```

  - The `-t` flag is used to tag the image with a name (and optionally a version)
  - If Dockerfile is named something different from Dockerfile, use the `-f` flag:

```
$ docker build -t getting-started -f myDockerfile .
```

https://docs.docker.com/reference/cli/docker/build-legacy/


Docker image: layers

- Each Docker image consists of a series of layers
- Docker uses *union file systems* to combine these layers into a single unified view

dando l'illusione che i layer siano un singolo file

  - These layers are stacked to form a base the base of a container's root file system
  - Docker leverages copy-on-write (CoW) strategy to optimize performance

i layer sono codificati con un hash perché due container possono condividere layer, il che permette di risparmiare spazio.




Docker image: layers

- Layering pros
  - ✓ Efficient layer sharing and reuse: common layers are installed only once, saving bandwidth and storage space
  - ✓ Separation of concerns: allows better management of dependencies grazie anche al versioning
  - ✓ Facilitates software specialization

https://docs.docker.com/storage/storagedriver

ciò che è stato scritto, viene cancellato. ad esempio se creo un file nel container sarà cancellato



l'ultimo layer è quindi dinamico rispetto ai restanti che si sono "statici" e immutabili. per dati persistenti si utilizzeranno i volumi

Docker image: layers

- Dockerfile instructions that modify the filesystem create new layers
  - Examples: `FROM`, `RUN`, `COPY`, `ADD`
- Instructions that only modify the image's metadata do not create new layers
  - Examples: `CMD`, `LABEL`
- All image layers (except the top one) are read-only
  - To enable efficient layer sharing across images
- When a container is started, a writable layer (aka *container layer*) is added on top
  - Changes made by a running container (e.g., creating or modifying a file) are written to the writable layer
  - Unique to each container
  - Ephemeral: deleted when the container is removed
  - Use it only for temporary/runtime data, not persistent data

attenzione quindi ad utilizzare RUN per singole istruzioni!
si va a sprecare spazio se si usa in maniera sconsiderata

Docker container storage

- Containers are usually stateless
- Why? Easier to:
  - Scale: start quickly new replicas
  - Restart: from failure
  - Migrate: move between hosts
- Very little data is written to container's writable layer
- Data is typically stored in **Docker volumes**
- However, some workloads require writing data to container's writable layer

Docker: storage backends

- How Docker daemon stores image layers and container writable layers on disk
  - Storage drivers
  - containerd image store
- Storage drivers (legacy): common options
  - Overlay2: file-level, preferred for all Linux distros
  - Btrfs: supports snapshotting
  - Zfs: block-level
- Storage driver considerations
  - Driver choice affects container performance
  - Drivers are optimized for space efficiency
  - Write performance speeds may be lower than native file system performance due to CoW


https://docs.docker.com/storage/storagedriver/select-storage-driver

Docker: storage backends

- New default backend: containerd image store (Docker Engine 29.0+)
- Uses content-addressable blob store
- Pros and cons:
  - ✓ Cleaner architecture
  - ✓ Unifies Docker and containerd ecosystem
  - ✗ Uses more disk space than storage drivers (no deduplication at driver level)

Docker: containers and registry


- Docker **container**: runnable instance of a Docker image
  - Containers are the ***run*** component of Docker
  - Run, start, stop, move, or delete a container using Docker API or CLI commands
  - Stateless nature of containers: when a container is deleted, any data written outside of data volumes is lost



- Docker **registry**: stateless server-side application that stores and distributes Docker images
  - Registry is the ***distribute*** component of Docker
  - Public and private registries
    - Docker-hosted registries: Docker Hub (official one), Docker Store (for open-source and enterprise-verified images)
  - Open library of images


Docker: run container

- When you run a container from an image that is not yet installed locally but is available on Docker Hub, Docker will pull the image from the registry before starting the container



Docker container: states and transitions

- Different states a container can go through during its lifecycle and actions that trigger transitions



Ciclo di vita del container

Docker commands: info

- Get system-wide info on Docker installation

  ```
  $ docker info
  ```

  including:

  - Number of images and containers, along with their status
  - Storage driver
  - Operating system, architecture, total memory
  - Docker registry information

Docker commands: image handling

- List all images on host

  `$ docker images` or `$ docker image ls`

- List all images, including intermediate image layers

  `$ docker images -a` or `$ docker image ls -a`

- You can filter and format the output to list images by name, tag, image digests (sha256) or image that meet specific conditions
  - E.g., list unused images (<none>) that are no longer associated with any tagged images but consume disk space

  `$ docker images --filter "dangling=true"`

- Remove an image

  `$ docker rmi imageid`

  alternatively, `$ docker image rm imageid`

or use *imagename* instead of *imageid*

Docker commands: image handling

- Remove dangling images

```
$ docker image prune
```

- Inspect an image, including layers and image metadata

```
$ docker inspect imageid
```

Docker commands: run

```
$ docker run [OPTIONS] IMAGE [COMMAND] [ARGS]
```

- Common options
  - `--name` set container name
  - `-d` detached mode (background)
  - `-i` interactive (keeps STDIN open)
  - `-t` allocate a pseudo-tty, usually with `-i`
  - `--expose` declare port(s) inside container
  - `-p` or `–publish` map container port(s) to host
  - `-v` mount volume
  - `-e` set environment variables inside container
  - `--rm` automatically remove container when it exits
  - `--restart` set restart policy (e.g., `always`, `on-failure`)

https://docs.docker.com/reference/cli/docker/container/run/

Docker commands: containers management

- List containers
  - Only running containers: `$ docker ps`
    alternatively, `$ docker container ls`
  - All containers (including stopped or killed containers):
    `$ docker ps -a`
- Manage container lifecycle
  - **Stop** a running container
    `$ docker stop containerid`
  - **Start** a stopped container
    `$ docker start containerid`
  - **Kill** a running container
    `$ docker kill containerid`
  - **Remove** a container (after stopping it)
    `$ docker rm containerid`

- Stop and remove a container

```
$ docker ps
$ docker stop containerid
$ docker ps -a
$ docker rm containerid
```

or use *containername* instead of *containerid*

Docker commands: containers management

- Stop all containers

```
$ for i in $(docker ps -q); do docker stop $i; done
```

- Run a command inside a running container

```
$ docker exec [OPTIONS] CONTAINER [COMMAND] [ARGS]
```

Example: `$ docker exec -it mycontainer /bin/bash`

-it è per specificare una shell interattiva

- Inspect a container
  - To get the most detailed view of a container environment

```
$ docker inspect containerid
```

- Copy files between host and container

```
$ docker cp containerid:path localpath
$ docker cp localpath containerid:path
```

la copia sul container mette i dati nel layer effimero, ricordalo

Docker: networking

- Containers communicate with each other or with external systems
- Published ports nel comando docker run
  - Use `-p hostPort:containerPort` (e.g., `-p 8080:80`) in `docker run` to expose a container port externally usato per mappare le porte SUL host
  - Security issue: exposing container ports can be insecure
    - Restrict access to host only by binding to localhost (e.g., `-p 127.0.0.1:8080:80`)
  - Work only on host network: containers can communicate with each other via internal Docker network!
- IP address and hostname
  - Containers get an IP address from Docker's dynamic subnet
  - Docker daemon manages subnetting and IP allocation
  - Default container hostname = container ID (can override with `--hostname`)

Docker: network drivers

- Docker networking is pluggable


docker utilizza diversi driver per usare la rete interna che collega i container.

  - Docker supports multiple network drivers that provide different networking behaviors, including:
- **`bridge`** (default) utilizzato da docker compose
  - Default network driver when no network is specified
  - Use when containers need to communicate on the same host
  - Implements a software bridge
    - Containers on the same bridge network can communicate with each other
    - Containers on different bridge networks are isolated
- **`host`**
  - Removes network isolation between container and host
  - Container uses host's network stack directly (no private IP assigned)

Docker: volumes

- Preferred mechanism for persisting data generated or used by containers
  - Volume content persists outside the container lifecycle: use volumes over container writable layer for persistent data
  - Does not increase container image size
- How volumes work
  - Docker creates a directory inside its storage directory to manage volume content
  - Default location on Linux: `/var/lib/docker/volumes/`
  - Volumes are created automatically if they do not already exist

esistono anche le soluzioni di bind mount e tmpfs mount per avere memoria persistente il mount bind, non mette a dispoizione un intero file system persistente per il container, ma fa il binding per uno specifico file del container con un file su volume in questo modo ogni modifica sul file persistente si riflette per il container



Docker: volumes

- Mounting a volume: use `-v` or `--volume` in `docker run`

  `$ docker run -v source:destination:[options] imageid`

  - If the volume does not exist, Docker automatically creates it
  - `[options]`: optional flags, e.g., **`ro`** for read-only volume
- Managing volumes
  - Create a volume: **`$ docker volume create volumename`**
  - List all volumes: **`$ docker volume ls`**
  - Inspect a volume: **`$ docker volume inspect volumename`**
  - Remove a volume: **`$ docker volume rm volumename`**
- Can also be declared in a Dockerfile using

  ```
  VOLUME ["/localpath"]
  ```
- Working with volume data: pre-populate or load data using `docker cp`

  ```
  docker cp /localpath containerid:/path
  ```


https://docs.docker.com/engine/reference/commandline/

Docker volume: pros

rendere i container statefull

- ✓ Fully managed by Docker
- ✓ Easy to back up or migrate
- ✓ Accessible through Docker CLI or API
- ✓ Work on both Linux and Windows containers
- ✓ Shareable across multiple containers
- ✓ Can store encrypted content
- ✓ Suitable for pre-populated or write-heavy workloads (e.g., database, logging service)

Docker hands-on

- Download and install Docker
  - Available on multiple platforms

  https://docs.docker.com/get-started
- Test Docker installation

  ```
  $ docker --version
  ```
- Run the default hello-world container

  ```
  $ docker run hello-world
  ```
- Run a “Hello World” message using Alpine Linux

  ```
  $ docker run alpine /bin/echo 'Hello world'
  ```
  - alpine: lightweight Linux distro with very small image size
- Use commands to:
  - List containers and container images
  - Stop and remove containers, remove container images

Docker hands-on: networking

- Run nginx Web server inside a container
  - Bind container port 80 to host port 80

```
$ docker run -dp 80:80 --name web nginx
```

Flag `-p`: publish container port (80) to host port (80)

Flag `-d`: run in detached mode

1. Send HTTP request through Web browser
   - First retrieve hostname of host machine (e.g., localhost)
2. Send HTTP requests to nginx from another interactive container using a custom bridge network

```
$ docker network create -d bridge my_net
$ docker run -dp 80:80 --name web --network=my_net nginx
$ docker run -it --network=my_net --name web_test busybox
/ # wget -O - http://web:80/ contattiamo il container nginx per riceve il file html
/ # exit
```

Docker hands-on: from Dockerfile

- Running Apache web server with minimal index page
  1. Define the container image using Dockerfile
     - Start from Ubuntu, install and configure Apache
     - Declare incoming port 80 using EXPOSE

```
FROM ubuntu:22.04

# Install dependencies
RUN apt-get update -y && \
    apt-get install -y apache2 && \
    apt-get clean

# Add simple web page
RUN echo "Hello World!" > /var/www/html/index.html

# Expose port and run Apache in the foreground
EXPOSE 80
CMD ["apache2ctl", "-D", "FOREGROUND"]
```

da notare che sono 3 comandi in una sola RUN. questo perché ogni RUN crea un layer, quindi facendo così risparmiamo spazio di memoria!

anche se manca sudo, i comandi non sono eseguiti come root!

Docker hands-on: from Dockerfile

2. Build the image

```
$ docker build -t hello-apache .
```

3. Run the container and bind ports

```
$ docker run -dp 127.0.0.1:8080:80 hello-apache
```

4. Execute an interactive shell in the running container

```
$ docker exec -it hello-apache /bin/bash
```

- To reduce container image size, avoid unnecessary layers
  - E.g., in Dockerfile combine `apt-get update` and package installation into a single RUN instruction (see slide 48)

Docker hands-on: volumes

- Run nginx container with a volume

```
$ docker volume create my-vol
$ docker volume ls
$ docker volume inspect my-vol
$ docker run -d \
    --name devtest \
    -v my-vol:/app \
    nginx:latest
```

  - `my-vol` is the source volume, `/app` is the target path inside container

```
$ docker inspect devtest
```

  - Check that Docker has created and mounted the volume correctly

Docker: optimize Docker images

- Fewer layers → smaller images → faster builds and deployments
- Why optimize Docker images?
  - Essential for DevOps engineers at every stage of CI/CD process
  - Reduces image size and disk usage
  - Speeds up image transfer, deployment, and startup times
  - Improves security by reducing the attack surface
  - Best practice used by Google and other major tech companies slim tool di Google per ridurre la dimensione. ad esempio per nginx crea una image di 12.4 MB!
  - Best practice employed by Google and other tech giants

https://devopscube.com/reduce-docker-image-size

Docker: optimize Docker images

- Techniques
  1. Use minimal base images (e.g., alpine, minideb) or distroless base images
     - Distroless images:
       - contain only application and its runtime dependencies
       - include package managers, shells, or other common utilities
       - More secure, smaller, harder to tamper with

       https://github.com/GoogleContainerTools/distroless
  2. Minimize the number of image layers
     - Combine related commands in a single RUN instruction
     - Avoid unnecessary COPY, ADD, or repeated RUN steps

Docker: optimize Docker images

- Techniques
  3. Multistage builds
     - Use intermediate images (build stages) to
       - compile code per utilizzare gli eseguibili direttamente
       - install dependencies, and package files
     - Final image contains only the files and libraries needed to run app

i layer non referenziati da alcuna immagine vengono eliminati una volta rimossa l'iimmagine di build

```
# Build stage
FROM golang:1.21 AS builder
WORKDIR /app
COPY . .
RUN go mod init myapp
RUN go mod tidy
RUN go build -o myapp

# Final stage
FROM alpine:3.20
COPY --from=builder /app/myapp /usr/local/bin/myapp
CMD ["myapp"]
```

supposto di avere il sorgente GO nella stessa directory del dockerfile. nel container andiamo a fare il build dell'applicazione copiando il sorgente in /app

l'immagine del build stage pesa 850MB mentre l'immagine final pesa solo 10.7MB!

qui creo l'immagine che sarà utilizzata, banalmente copiando l'eseguibile creato nell'immagine precedente nel container che utilizzerò

Docker: optimize Docker images

- Techniques
  4. Exploit layer caching condivisione dei layer. questo però necessità costruire layer riutilizzabili
     - Place instructions that change infrequently (like installing dependencies) before COPY commands
     - Docker reuses cached layers for faster builds when source code changes.
  5. Use a `.dockerignore` file
     - Specify files and directories to exclude from the build context
     - Common exclusions: `node_modules`, `.git`, `*.log`, `__pycache__/`
  6. Keep application data in a volume
     - Avoid storing persistent data inside the container.
     - Use Docker volumes to store databases, logs, uploaded files

Docker: sizing containers

- By default, containers have no resource constraints
  - Can use as much CPU, memory, and I/O as the host's kernel scheduler allows

- Control resources by setting runtime configuration flags of `docker run`
  - Docker uses cgroups to manage resource limits

https://docs.docker.com/engine/containers/resource_constraints

Docker: sizing containers - memory

- Avoid running out of memory (OOM)
  - Containers may be killed
  - Docker daemon has lower OOM score, so less risk than containers
- Enforce hard or soft memory limits
  - Hard limit: container cannot use more than the specified limit; use `--memory` flag
  - Soft limit: container can use more memory if needed, unless certain conditions are met (e.g., kernel detects contention or low memory on host machine)
  - Example: hard limit (500 MB) and soft limit (300 MB)

```
$ docker run –it --memory-reservation="300m" \
  --memory="500m" ubuntu /bin/bash
```

Docker: sizing containers - CPU

- Options to limit CPU usage

  `--cpus=<value>`: limit container to a specific number of CPUs (hard limit)

  `--cpu-quota=<value>:` set Completely Fair Scheduler (CFS) CPU quota on container

  `--cpuset-cpus`: restrict container to specific CPUs/cores, example `--cpuset-cpus="0,1"` (use only CPU 0 and 1)

  `--cpu-shares`: set relative CPU weight (soft limit)

- Example: limit container to use at most 50% of CPU every second

```
$ docker run -it --cpus=".5" ubuntu /bin/bash
```

Alternatively,

```
$ docker run -it --cpu-period=100000 \
            --cpu-quota=50000 ubuntu /bin/bash
```

Resizing containers

- Containers can be resized and migrated, just like VMs

- Resizing allows changing CPU, memory, and I/O limits dynamically
  - Note: on Docker, dynamic resizing is not supported on Windows

```
$ docker update [OPTIONS] CONTAINER [CONTAINER...]
```

  - Examples

```
$ docker update --cpu-shares 512 containerID
$ docker update --cpu-shares 512 -m 300M containerID
```

il resizing non è disponibile su Windows


Container live migration

- As for VM migration, we need to:
  - Save state
  - Transfer state
  - Restore state
- State saving, transferring and restoring happen with frozen app: migration downtime
  - Use memory pre-copy or memory post-copy
- No native support in container engines, additional tools required la live migration non è supportata nativamente dal docker engine
- We also need to migrate container image, volumes, and network connections

Container live migration


- CRIU (Checkpoint/Restore in Userspace) tool for live migration through checkpointing and restoration (Docker and other engines) https://criu.org
  - Checkpoint: freeze running container on source host and collects information about its CPU state, memory content, and process tree
  - Transfer and restore: transfer collected information to destination host, restore container's state and resume execution https://docs.docker.com/reference/cli/docker/checkpoint

la figura mostra il pre-copy



Container security

- Where attacks come from in containerized environment?



- Attack origins
  - Vulnerabilities in containerized apps
  - Container runtime/kernel flaws

Container security

- Types of attacks
  - Container escape
    - Exploitation of container vulnerabilities to break isolation and access the host system
  - Privilege escalation
    - Once on the host, attackers can escalate privileges to:
      - Access other containers
      - Run malicious code on host system

podman non consente di eseguire in maniera privilegiata il container a differenza di docker

- Consequences
  - Compromised host system
  - Cross-container attacks


Docker: useful tools

- To manage images
  - Reduce image size: Slim https://slimtoolkit.org
  - Explore image layers: Dive https://github.com/wagoodman/dive
  - Automate image builds: Packer https://www.packer.io
- To monitor containers
  - cAdvisor https://github.com/google/cadvisor
- To check fo vulnerabilities
  - Docker Scout https://docs.docker.com/scout
  - Trivy https://trivy.dev
  - Static analysis: Clair https://github.com/quay/clair
- Many other tools: https://github.com/veggiemonk/awesome-docker

Container orchestration

- Sw platforms for managing multi-container apps
- Functionalities: configure, provision, deploy, monitor, and dynamically control containerized apps
  - Designed to integrate and manage containers in large-scale environments across multiple hosts
  - Can include autoscaling, load balancing, networking, monitoring and logging, fault tolerance and self-healing mechanisms
- Examples per applicazioni multi-host
  - Docker Swarm
  - **Kubernetes** che aiuta a scalare le repliche, il carico di lavoro e gestire politiche di rete oltre ad altre funzioni come ad esempio il self healing
  - Nomad https://developer.hashicorp.com/nomad
- Also available as fully managed Cloud services
- For single-host deployment of small-scale apps
  - **Docker Compose**

Docker Compose



- Tool for defining and running multi-container Docker applications https://docs.docker.com/compose
  - Included with Docker Desktop https://docs.docker.com/compose/install
- How it works invece di fare tutto manualmente con diversi dockerfile e configurazione di rete
  - Configuration-as-code
  - Define services: users specify the containers (services) to be instantiated, their configuration and relationships in a YAML file compose.yaml
- Single host, multiple containers o meglio li chiameremo servizi
  - Orchestrates multiple containers on a single host (single Docker engine) definendo magari dipendenze per l'avvio
- Network setup
  - Compose automatically creates a network and attaches all containers to it, enabling easy communication between them

Docker Compose: how to use

- Define containers in a YAML file named `compose.yaml` (or `compose.yml`)
  - Specifies the containerized services
  - Defines how containers interact and their configurations
- Start Docker composition (background `-d`):

```
$ docker compose up -d
```

  - By default, Docker Compose looks for `compose.yaml` in working directory
    - Use `-f` flag to specify a different YAML file

```
$ docker compose -f composefile up -d
```

- Stop running containers:

```
$ docker compose stop
```

- Bring composition down, removing everything

```
$ docker compose down
```

Docker Compose: Compose file

container

- To configure Docker application's services, networks, volumes, and more
  - Different versions of Compose file format
  - Compose V2: implements format defined by Compose Specification https://compose-spec.io/ and includes support for legacy formats (2.x and 3.x)
- What is inside `compose.yaml`
  - `version`, `services`, `networks`, `volumes`, `configs`, `secrets`
  - Only `services` is required, others are optional

https://docs.docker.com/reference/compose-file

https://github.com/docker/awesome-compose

Docker Compose: Compose file

unica sezione obbligatoria

- Service: abstract representation of computing resources within app, that can be scaled, updated or replaced independently from other components
  - Defines a set of containers
  - Compose file must include the `services` top-level element
- Within each service
  - `build`: defines how to create service image (e.g., from Dockerfile)
  - `container_name`, startup and shutdown dependencies between services (`depends_on`), exposed containers `ports`, CPU and memory limits, `volumes` that are accessible to service containers
  - and other settings, see https://docs.docker.com/reference/compose-file/services/

Docker Compose: example

- Simple Python web app running on Docker Compose
  - 2 containers: Python web app and Redis
  - Use Flask framework and maintain a hit counter in Redis
  - Redis: in-memory, key-value data store

  See https://docs.docker.com/compose/gettingstarted

- Steps:
  1. Write Python app
  2. Define Python container



```
# syntax=docker/dockerfile:1
FROM python:3.10-alpine
WORKDIR /app
ENV FLASK_APP=app.py
ENV FLASK_RUN_HOST=0.0.0.0
RUN apk add --no-cache gcc musl-dev linux-headers
COPY requirements.txt requirements.txt
RUN pip install -r requirements.txt
EXPOSE 5000
COPY . .
CMD ["flask", "run", "--debug"]
```

Docker Compose: example

- Steps (cont'd):
  3. Define services in Compose file
     - 2 services: web (image built from Dockerfile) and redis (official image pulled from Docker Hub https://hub.docker.com/_/redis)

compose.yaml

```
services:
  web: è il primo container
    build: .
    ports:
      - "8000:5000"
  redis: è il secondo container
    image: "redis:alpine"
```

  4. Build and run app with Compose

     ```
     $ docker compose up -d
     ```

  5. Send HTTP requests using curl or browser (counter is increased)
  6. Stop Compose and bring everything down

     ```
     $ docker compose down
     ```

Docker Compose: example

- Specify restart policy for containers nella sezione service
  - Options: `on-failure[:max-retries]`, `always`, `unless-stopped` numero di tentativi per il restart; utile per sapere informazioni sul crash docker logs; occhio comunque ai crash delle applicazioni che rendono uno "zombie" il container che comunque rimane up & running, ma l'applicazione crashata NON riparte
- Start multiple replicas of same service using `deploy` specification
  - Scale out or in manually the number of replicas

```
$ docker compose -f compose_v2.yaml up --scale web=4 -d
$ docker ps
$ docker compose -f compose_v2.yaml up --scale web=1 -d
$ docker ps
```

4 repliche

✗ Docker Compose only supports manual scaling

- To experience autoscaling, learn Kubernetes

Docker Compose: full example

compose_v2.yaml

vedi anche compose_v3.yaml con load balancer nginx

```
services:
  web:
    build: .
    ports:
      - "5000"
    restart: always
    deploy:
      replicas: 3
    environment:
      - FLASK_APP=app.py
    depends_on:
      - redis
  redis:
    image: "redis:latest"
    container_name: redis
    restart: always
    volumes:
      - redis-data:/data

volumes:
  redis-data:
```

repliche di default se non specificate

volume per mantere persistente il valore del contatore

in questo caso lascio a docker la scelta del mapping della porta del host, in quanto con le repliche ognuna di essi avrà una porta host dedicata non esiste un meccanismo nativo per NON esporre la distribuzione delle repliche. dunque docker compose non supporta la trasparenza di distribuzione. sempre per le repliche non scelgo il nome del container per evitare conflitti.
questa soluzione dunque espone le repliche, dato che per utilizzare ognuno debbo ogni volta cambiare la porta del host nella connessione http. per evitare ciò posso creare un load balancer tramite nginx in un nuovo container che comunicherà con le repliche di flask attraverso il network. infine esporrò solo il load balancer per l'applicazione

Example of Dockerized distributed system

- Kafka cluster using Docker Compose 

- Multiple pre-configured options are available, e.g.,
  - https://bitnami.com/stack/kafka/containers includes both single container and Docker Compose setup with Zookeeper or Kraft mode
  - https://medium.com/@darshak.kachchhi/setting-up-a-kafka-cluster-using-docker-compose-a-step-by-step-guide-a1ee5972b122 cluster of 3 brokers (Kraft mode) and UI, Docker network for inter-broker communication, and persistent volume storage


Docker Compose: pros and cons

- ✓ Simplified control
- ✓ Efficient collaboration
- ✓ Rapid application development
- ✓ Reproducible environments
- ✓ Portability across environments (development, staging, production)

esponiamo le repliche senza load balancer

- ✗ Single host limitation
- ✗ Lack of elasticity
- ✗ Not production-grade orchestration almeno su larga e media scala
- ✗ Only basic security features


Docker Swarm



- Swarm mode: advanced feature of Docker to natively manage a cluster of Docker engines called a *swarm* https://docs.docker.com/engine/swarm/
- Swarm: multiple Docker engines running in swarm mode swarm è l'orchestratore multi-host di default di docker
  - Swarm mode helps you orchestrate containers across multiple machines sistema distribuito con pattern master-worker
- Composed of Manager nodes and Worker nodes
  - Manager nodes: control the swarm and handle the orchestration of services possone esserci più manager
  - Worker nodes: run containers (tasks) as assigned by manager nodes
  - Tasks: containers running in a service
    - Task: smallest unit of work, typically one container
  - Services: how tasks (containers) should run on the swarm; provide an abstraction for deploying and managing tasks

Docker Swarm: architecture

- Node: single instance of Docker engine in a swarm
  - Manager nodes: handles cluster management, including task scheduling
    - Multiple managers to improve fault tolerance
    - Raft as consensus algorithm to ensure consistency
  - Worker nodes execute tasks
    - Workers use a gossip protocol to exchange information about their state



Docker Swarm: features

- Cluster management integrated with Docker
- Decentralized: distributed decision-making
- Declarative service model
- State reconciliation
  - Swarm monitors cluster state and reconciles any differences wrt desired state (e.g., a node crashes)
- Scaling
  - Easily scale services but lacks auto-scaling
- Multi-host networking
  - Use overlay networks to enable communication between services across nodes
- Load balancing
  - Can expose service ports to an external load balancer
- Secure: TLS authentication, encryption, role-based AC
- Easy to use and lightweight

Container-as-a-Service (CaaS)

termine coniato recentemente dai cloud provider

- Cloud-based platform for managing and deploying containerized applications si possono racchiudere nei servizi PaaS
  - Combines containerization with cloud benefits
- Features
  - Container orchestration and management: container lifecycle, scheduling, load balancing, and fault tolerance
  - Configuration for resource optimization (e.g., auto-scaling)
  - Security and access control
  - Integration with other cloud services (e.g., monitoring)
- Examples
  - Amazon Elastic Container Service https://aws.amazon.com/ecs
  - Azure Container Instances https://azure.microsoft.com/products/container-instances
  - Google Cloud Run https://cloud.google.com/run

Virtualization and IaaS providers


- Which virtualization technology for IaaS providers?
  - ✓ Hypervisor-based virtualization: greater security and isolation, flexibility (different OSs on same PM)
  - ✓ Container-based virtualization: smaller deployment size and higher density, faster startup/shutdown
- Questions
  - Containers on top of bare metal or inside VMs?
    - Performance and density vs. isolation and security
  - Are containers replacing VMs?
    - Not entirely: lightweight vs. isolation and security

più propriamente nel host OS

docker engine ad esempio su Windows e MacOs usa una VM per eseguire i container

New lightweight virtualization approaches

- Deployment approaches examined
  - Plus nested virtualization: hypervisor inside VM on top of an hypervisor, or Docker in VM




New lightweight approaches to virtualization

- Microservices, serverless computing, cloud-edge continuum demand for
  - Low-overhead (or lightweight) virtualization techniques, even lighter than containers
  - Better security
  - Portability across OSs and architectures (e.g., Arm, Intel)
- Technologies enabling lightweight virtualization: **MicroVM**, **lightweight OSs**, **unikernels** and **WebAssembly**
- MicroVMs, lightweight OSs, and unikernels: reduce OS overhead and attack surface obiettivo condiviso dalle tecniche
  - OS overhead: many common OS services (shells, editors, core utils, package managers) are unnecessary
  - Attack surface: images contain only the essential code needed to run the app, reducing potential attack vectors

MicroVM runtimes

- Tiny, specialized VMM that run lightweight VMs (called microVMs)
- Goal: reduce memory footprint and improve security of virtualization layer
- Firecracker: minimalist VMM purpose-built by Amazon for secure, efficient and multi-tenant microVMs
  https://firecracker-microvm.github.io
  - Why? To enable AWS Lambda and AWS Fargate for serverless and containerized workloads
  - Based on KVM but with minimalist design (no unnecessary devices and guest functionality)
  - Open source, written in Rust
  - microVM: <125 ms startup time and <5 MB memory footprint
  - Scales to thousands of multi-tenant microVMs
  - Supported OS guests inside microVM: Linux and OSv

Google usa gVisor



OSv è un sistema operativo ad-hoc realizzato per le VM


Lightweight operating systems

- Minimal, special-purpose OSs to run containerized apps
- Fedora CoreOS https://fedoraproject.org/it/coreos/
  - Minimal, monolithic, and compact Linux distribution designed for running containers
    - Only components for container deployment, together with built-in tools for service discovery, container management, and configuration sharing
  - Designed for scale and security
  - Fast bootstrap and small memory footprint
  - Can be installed directly on hardware or on hypervisor
  - Includes Docker and podman
- Other products: Ubuntu Core, balenaOS
  - Designed for edge and IoT devices

Unikernels

- Specialized, single-purpose OS designed to run a single application with minimal overhead
  - Single application + OS into a single executable (aka library OS): monolithic process that runs entirely in kernel mode
  - Single address space: app and OS share the same memory space
  - Built by compiling high-level language directly into specialized machine image that runs on hypervisor
  - Goal: isolation benefits of hypervisor without overhead of guest OS

applicazione e kernel condividono lo stesso spazio di indirizzamento eliminando cosi tutti i context switch da user mode a kernel mode. si ha solo la kernel mode



Unikernels: pros and cons

- Pros (specialized → high performance)
  - ✓ Lightweight: less resource-intensive (memory and CPU)
  - ✓ Minimal footprint
  - ✓ Reduced attack surface
  - ✓ Fast execution (no context switching)
  - ✓ Fast boot (measured in ms)
  - ✓ Strong isolation
- Cons
  - ✗ Less flexible than VMs and containers
  - ✗ Limited ecosystem support, including debugging and monitoring tools che rende appunto debugging e monitoraggio difficile
  - ✗ Scalability is more challenging (e.g., multi-instance deployments or load balancing)
  - ✗ Unikernel orchestration is not as easy as container orchestration

Unikernels: frameworks


- Frameworks
  - MirageOS (Ocaml language) https://mirage.io
  - OSv https://github.com/cloudius-systems/osv
  - Nanos https://nanos.org/
  - Unikraft
- OSv
  - Cloud-native unikernel optimized for high performance and low overhead in virtualized environments
  - Linux ABI compatibility allows running Linux applications with minimal changes
  - Open-source and fast
    - Can boot in ~5 ms on Firecracker using 11 MB of memory

Unikernels: Unikraft

- Fast, secure, and open-source Unikernel Development Kit https://unikraft.org
  - Designed to simplify unikernel creation without requiring deep expertise
  - Build, run and package: similar to Docker
  - Modular: supports a wide range of components (e.g., networking, storage), allowing to create custom unikernels
  - Multi-language support (e.g., C, C++, Rust, Go)
  - Application compatibility
    - Can run complex apps (e.g., Redis, Nginx, Memcached)
    - POSIX compliant: compatibility with a broad range of Unix-like applications
  - Architecture compatibility
    - Works with multiple hypervisors (e.g., Xen, KVM) and supports various CPU architectures, allowing deployment on both virtualized and bare-metal environments
  - Active development


sistema di storage key-value alternativa a redis

Unikernels: Unikraft




Performance of virtualization approaches

- VM boot times grow linearly with VM size



- Difficulties in securing containers due to growth of Linux syscall API



My VM is lighter (and safer) than your container, SOSP 2017
https://dl.acm.org/doi/pdf/10.1145/3132747.3132763


Performance of virtualization approaches

- Performance comparisons of hypervisor vs. lightweight virtualization
- Key findings:
  - Overhead introduced by containers is almost negligible
  - Fast instantiation time of containers
  - Small per-instance memory footprint
  - High density
  - But security tradeoffs: containers offer less isolation

Virtualization	Boot time	Image size	Memory footprint	Programming language dependance	Live migration
VM	~5/10 sec	~1 GB	~100 MB	No	Yes
Container	~0.8/1 sec	~50 MB	~5 MB	No	Non-native
Unikernel	<10 msec	<20 MB	~10 MB	Partially	No

Performance of virtualization approaches

- Comparing lightweight virtualization approaches
- Overall result: no clearly superior solution, each one has its own strengths and weaknesses



A functional and performance benchmark of lightweight virtualization platforms for edge computing, EDGE 2022 https://ieeexplore.ieee.org/document/9860335

WebAssembly (Wasm)




- Safe, portable, binary code format designed for efficient execution and compact representation https://webassembly.org
  - Safe: runs in a sandboxed environment, preventing untrusted code from harming the host system
  - Portable: the same Wasm binary can run on any platform that supports the Wasm runtime (browsers, servers, embedded)
  - Binary format: designed to be compact and fast to load and execute
- Other features
  - Open standard https://www.w3.org/TR/wasm-core-2
  - Portable compilation target for many programming languages
    - Originally built to safely execute JavaScript code in browsers
  - Memory-safe, sandboxed execution
  - Computational model based on stack VM come la JVM

WebAssembly: features

- Wasm code is validated and executed in a memory-safe, sandboxed environment → strong isolation and protection from unsafe operations
  - Wasm interacts with the host system through WebAssembly System Interface (WASI), which provides a standardized set of capability-based APIs
  - A Wasm module cannot directly perform OS systems calls, instead imports host-provided WASI functions
- Development workflow: write code in one of many supported languages, compile it to Wasm, and run it inside a Wasm runtime

nel caso della virtualizzazione



a seconda del linguaggio le performance variano terribilmente, con python che risulta lento a differenza di C, Rust o Go

WebAssembly: features

- Wasm uses stack-based VM to execute instructions https://en.wikipedia.org/wiki/Stack_machine
  - Code is composed of sequences of instructions executed in order
  - The operand stack is used to store values for computation
  - Instructions:
    - Pop argument values from the stack and push back onto it
    - Each operation manipulates values on the stack
    - Example: `i64.add`
      - Takes two i64 values from the stack
      - Add them
      - Pushes the result back onto the stack
    - Control instructions alter control flow
- JVM is a famous example of stack-based VM

che appunto produce bytecode

WebAssembly: example

- Factorial function written in C and its corresponding Wasm code after compilation
  - In `.wat` text format (human-readable textual representation of Wasm)

```c
int factorial(int n) {
  if (n == 0)
    return 1;
  else
    return n * factorial(n-1);
}
```

```
(func (param i64) (result i64)
  local.get 0             # put arg[0] on stack
  i64.eqz                 # compare top of stack to zero
  if (result i64)         # if it is zero
      i64.const 1         # put 1 on stack
  else
      local.get 0         # put arg[0] on stack
      local.get 0         # put arg[0] on stack
      i64.const 1         # put 1 on stack
      i64.sub             # subtract the top 2 values in stack
      call 0              # Call function #0 (return value is on the stack)
      i64.mul             # Multiply
  end)'
```


WebAssembly: example

- Factorial function written in C and its corresponding Wasm code after compilation
  - In `.wasm` binary format

```c
int factorial(int n) {
  if (n == 0)
    return 1;
  else
    return n * factorial(n-1);
}
```

```
00 61 73 6D 01 00 00 00
01 06 01 60 01 7E 01 7E
03 02 01 00
0A 17 01
15 00
20 00
50
04 7E
42 01
05
20 00
20 00
42 01
7D
10 00
7E
0B
0B
```

WebAssembly: pros and cons

- ✓ Efficient: near-native execution speed
- ✓ Secure: memory-safe, sandboxed execution, which prevents data corruption and security breaches
- ✓ Language-, platform-, and hardware-independent
  - Does not favour any particular language
  - Can run as a standalone VM
  - Can be compiled for all modern architectures, including desktop, mobile devices, and embedded systems
- ✗ In development
- ✗ Support varies by language
- ✗ Multiple runtimes (e.g., Wasmtime, Wasmer, WasmEdge) with different features: choice is complex

Kubernetes oggi supporta il Wasm

non c'è uno standard! e i differenti runtime non sono completi


non è supportata nativamente la comunicazione tra due applicazioni di wasm!

WebAssembly

- How to try: Wasm applications with Linux containers in Docker (beta)
  https://docs.docker.com/desktop/features/wasm/
  - Enable it on Docker Desktop by checking *Enable Wasm* on the *Features in development* tab under *Settings* (requires containerd image store)

```
$ docker run \
  --runtime=io.containerd.wasmedge.v1 \
  --platform linux/arm64 \
  secondstate/rust-example-hello
```

The full scenario



FORMAT	PC	CLOUD	CONTAINER	K8S	WASM	COSMONIC
EXECUTION	*Image (Datacenter)*	*VM (Public Cloud)*	*Container (Docker)*	*Containers (K8s / Cloud)*	*WASM (Everywhere)*	*Distributed WASM (Everywhere)*
Dev Responsibility	Full	OS, App, Lib	App, Lib	App, Lib	Wasm	Business Logic
Abstraction	-	CPU	Linux Kernel	K8s	Secure Sandbox	Sandbox + Capabilities
Compatibility	All	Most	Most	Most	Most	Most
Size	Large	Med	Small	Small	Tiny	Minuscule
Portability	-	Low	Med (CPU, Linux)	Med (CPU, Linux)	High	Highest
Security	System	OS	Process Boundary	Process Boundary	Capability	Component
Location	On Prem & Co-location	Proprietary Cloud & Edge	Dev, Edge, Cloud, K8s	Dev, Edge, Cloud, K8s	Dev, App, Edge, Cloud, K8s, Browser, Devices	Dev, App, Edge, Cloud, K8s, Browser, Devices

Legend: **Developer Provided** **Service Provided** **Flexible**