Message-oriented communication

- RPC provides distribution transparency over socket programming
- But still coupling between interacting entities
  - Temporal: caller waits for a reply
  - Spatial: shared data
  - Functionality and communication are tightly coupled
- How to improve decoupling and flexibility?
- Message-oriented communication
  - Transient
    - Berkeley sockets, Message Passing Interface (MPI)
  - Persistent
    - **Message Oriented Middleware (MOM)**

RPC non garantisce alcun tipo di decoupling
Spatial: deve conoscere minimo i metodi
Temporal: può essere sincrono
Synchronization: se sincrono si blocca il caller


In particolare un message-queuing system o MOM fornisce un supporto esteso per comunicazioni persistenti asincrone, ovvero dove i messaggi rimangono sul disco e i due host non devono essere entrambi presenti al momento della comunicazione.

Message-oriented middleware

- Communication middleware that supports sending and receiving messages in a persistent way
  - Provides intermediate-term storage for messages
- Loose coupling among system/app components
  - Supports temporal and spatial decoupling
  - Can also support synchronization decoupling
- Goals: increase performance, scalability, and reliability
  - Commonly used in serverless and microservice architectures
- Communication patterns:
  - **Message queue** studieremo questi due pattern
  - **Publish-subscribe** (pub/sub)
- Related systems:
  - **Message queue system** (MQS) e questi due sistemi
  - **Pub/sub system**

Message queue pattern


- Messages sent to a queue are stored until retrieved by a consumer
- Multiple producers can send messages to the queue
- Multiple consumers can receive messages from the queue
- Communication is one-to-one: each message is delivered to a single consumer




- Use cases:
  - Task scheduling, load balancing, logging or tracing

Message queue pattern

A sends a message to B



B processes the message and sends a response back to A



pattern abbastanza "rudimentale", da notare come il processamento sia operazione bloccante

Message queue API


- Typical calls in MQS:
  - **put**: non-blocking send
    - Inserts a message into the queue immediately
  - **get**: blocking receive
    - Waits until the queue is non-empty and retrieve a message
    - Variant: can search for a specific message in the queue
  - **poll**: non-blocking receive
    - Checks the queue and retrieves a message if available
    - Never blocks
  - **notify**: non-blocking receive
    - Installs a callback handler that is automatically invoked when a message arrives in the queue

come elencati da Tanenbaum

il pattern odierno

Publish/subscribe pattern

- Producers (publishers) send asynchronous messages, such as event notifications
- Consumers (subscribers) express interest in specific topics by subscribing
- Decoupling in time and space: publishers and subscribers do not need to interact directly
- Supports one-to-many communication, unlike message queues



RECAP del pattern

Publish/subscribe pattern

- Multiple consumers can subscribe to a topic, with or without filters
- An *event dispatcher* collects subscriptions and route messages to all matching subscribers
  - For scalability, the dispatcher is typically distributed
- High degree of decoupling among components
  - Components can be easily added or removed: ideal for dynamic environments
- Use cases:
  - Event notification, multicasting
- Comparison with message queue


Feature	Message queue	Pub/sub
Delivery	One-to-one	One-to-many
Consumers	Single consumer per message	Multiple consumers per message

Publish/subscribe API

- Typical calls in a pub/sub system:
  - `publish(event)`: called by a publisher to publish an event
    - Events can be any data type and may include meta-data
  - `subscribe(filter_expr, notify_cb, expiry) → sub_handle`: called by a subscriber to subscribe to events
    - Inputs: filter expression, reference to a notification callback, and subscription expiry time
    - Returns a subscription handle
  - `notify_cb(sub_handle, event)`: called by pub/sub system to deliver to a matching event to subscribers
  - `unsubscribe(sub_handle)`: called by the subscriber to remove the subscription

MOM functionalities

- MOM simplifies distributed communication by handling:
  - Addressing: locating the recipient(s) for messages
  - Routing: delivering messages along appropriate paths
  - Availability of application components (or applications)
  - Message format transformations gestendo l'eterogeneità



https://www.cloudcomputingpatterns.org/message_oriented_middleware

MOM functionalities

- Let's analyze
  - Delivery semantics
  - Delivery model
  - Message routing
  - Message transformations

An important aspect of message-queuing systems is that a sender is generally given only the guarantees that its message will eventually be inserted in the recipient's queue. No guarantees are given about when, or even if the message will actually be read, which is completely determined by the behavior of the recipient. Dunque si utilizza il concetto di ack, per avvisare della lettura

ripassiamo perché non fa male

MOM delivery semantics

At-most-once delivery




- Each message is delivered no more than once
- Messages may be lost, but are never redelivered

At-least-once delivery



- Messages are never lost, but they may be delivered multiple times
  - Since messages can be duplicated, the consumer-side application must be able to handle duplicate processing (or be sure that re-processing the same message does not cause errors)
- Mechanism:
  - Consumer sends ack for each message; MOM resends message if ack is missing




MOM delivery semantics

Exactly-once delivery



- Message is delivered exactly once to consumer
- Mechanisms
  - Deduplication logic: MOM filters message duplicates
    - Each message has a unique ID
  - Idempotent consumers: can safely process the same message multiple times
  - Messages survive MOM failures

ricorda idempotent è una richiesta che può essere fatta più volte perché senza effetti sullo stato dell'oggetto




MOM delivery semantics

Transaction-based delivery



- Guarantees messages are deleted from the queue only after they have been successfully received and processed by the consumer
- Mechanism
  - MOM and consumer participate in a transaction: read and delete operations are part of the transaction, ensuring ACID properties
    - Commit: if successful, the message is permanently deleted
    - Rollback: if the transaction fails, the message remains in the



MOM delivery semantics


Timeout-based delivery



- Ensures messages are delivered at least once while preventing duplicate consumption
- Mechanism


un messaggio appena letto diventa invisibile e se non cancellato torna visibile dopo che finisce il visibility timeout

  - Message is not deleted immediately from the queue, but marked as invisible until *visibility timeout* expires
  - Invisible message cannot be read by another consumer
  - After consumer's ack of message receipt, message is deleted from queue




MOM delivery model

- How messages are retrieved by subscribers or consumers
- Options: push vs. pull delivery
- Push: MOM actively notifies the receiver(s) when a message is available
- Pull: receiver(s) periodically polls MOM for new messages



Push delivery




Pull delivery

Message routing in MOM

- Queues are managed by queue managers (QMs)
  - Applications can only put messages into a local queue
  - Applications can only retrieve a message from a local queue
- QMs are responsible for routing messages between local queues and remote queues
  - Act as message-queuing relays, communicating with distributed applications and other QMs
  - Form an overlay network
  - Some QMs may operate only as routers, without storing messages


un po' ricorda RPC con gli stub



Un QM si deve occupare di instradare il messaggio, quindi possedere un contact address che indica il protocollo hostname e porta. Poi siccome due QMs possono collaborare un QM deve sapere i contact address gestiti dagli altri, dunque come soluzione per la scalabilità alcuni QMs possono opearre come router che instradano i messaggi, realizzando così una rete overlay

Message routing: overlay network


- Overlay network for message routing
  - Each QM maintains a routing table to map queue names to their location
- Overlay network maintenance
  - Static overlays: routing tables are set up and managed manually
    - Easier to configure but less flexible
  - Dynamic overlays: routing tables are updated at runtime
    - More complex but supports scalable and adaptive routing



ovviamente la soluzione migliore è quella dinamica

Application heterogeneity: message broker

- Problem: new and existing apps rarely share a common data format, how to integrate them into a single, coherent system?
- Solution: ***message broker***
  - Handles application heterogeneity in MOM
- Responsibilities
  - Message transformation: uses a repository of conversion rules to transform message types
  - Content-based routing: routes messages based on content or type
- Scalability and reliability: usually implemented in a distributed manner



18

Un message broker può comportarsi sia come un convertitore di messaggi, sia come un application-level gateway in a message-queuing system. Il suo scopo principale è convertire i messaggi in arrivo così che la destinazione li capisca.Come mostra la figura un message broker è software in più

MOM frameworks

- Main MOM systems and libraries
  - Apache ActiveMQ https://activemq.apache.org
  - **Apache Kafka**
  - Apache Pulsar https://pulsar.apache.org
  - IBM MQ https://www.ibm.com/products/mq
  - NATS https://nats.io
  - **RabbitMQ**
  - Redis https://redis.io/
  - ZeroMQ https://zeromq.org
- Note: distinction between queue-based and pub/sub patterns is sometimes blurred
  - Some frameworks support both patterns, e.g., NATS, Pulsar and Kafka (with specific configurations)
  - Others only one, e.g., Redis is pub/sub only, ZeroMQ is queue only


MOM frameworks

- Cloud-based MOM services
  - **Amazon Simple Queue Service (SQS)**
  - Amazon Simple Notification Service (SNS)
  - CloudAMQP: RabbitMQ as a Service
  - Google Cloud Pub/Sub
  - Microsoft Azure Service Bus
- Note
  - Cloud MOMs abstract infrastructure management, allowing developers to focus on messaging patterns
  - Many support both queue and pub/sub patterns

Amazon Simple Queue Service (SQS)




- Reliable, scalable cloud-based message queue service
  - Designed to decouple application components, allowing them to run independently and asynchronously
  - Supports integration across different languages and technologies
- Architecture
  - Message queues fully managed by AWS
  - Queues are distributed across multiple SQS servers
  - Replication within a region: messages stored on multiple servers for high availability
  - Pull delivery model: consumers poll the queue to retrieve messages



Amazon SQS: Message handling

- Consumer must delete message after processing
  - Queue = temporary holding location, not permanent storage
  - Message retention period: configurable (max 14 days)
- Implements timeout-based delivery
  - When a consumer retrieves a message, it remains in the queue but becomes invisible to others (visibility timeout)
  - If processing succeeds, the consumer deletes the message
  - If processing fails, the timeout expires and the message becomes visible again



Amazon SQS: Polling and queue types

- Consumers poll the queue to receive messages
  - *Short* polling: queries only a subset of SQS servers (may return empty)
  - *Long* polling: queries all servers, wait for messages (reduces empty responses)
- Queue types: standard or FIFO
- Standard queue (default)
  - Best-effort ordering: messages may arrive out-of-order
  - Duplicates possible



- FIFO queue
  - Guarantees in-order delivery (sent=processed order)
  - No duplicates
  - ✗ Lower throughput



Amazon SQS: API

- `CreateQueue`, `ListQueues`, `DeleteQueue`
  - Create a new queue, list all queues, delete an existing queue
- `SendMessage`
  - Add a message to queue (message size up to 256 KB)
  - For larger payloads: store on S3 and send an S3 reference instead
- `ReceiveMessage`
  - Retrieve one or more messages
  - Retrieve up to 10 messages: can specify the maximum number of messages to fetch (from 1 to 10)
  - No filtering before delivery
  - Post-delivery filtering
    - If a consumer wants to filter messages, it must inspect message body or attributes after receiving the messages and decide whether to process or discard them


https://docs.aws.amazon.com/AWSSimpleQueueService/latest/APIReference/Welcome.html

Amazon SQS: API

- `DeleteMessage`
  - Remove a specified message from the queue after processing
- `ChangeMessageVisibility`
  - Change the visibility timeout of a specific message in the queue
  - A message remains in the queue until explicitly deleted by the consumer
  - Default visibility timeout: 30 sec.
- `SetQueueAttributes`, `GetQueueAttributes`
  - Modify queue attributes (e.g., message retention), retrieve current queue settings


Amazon SQS: example

- Photo processing service using SQS
  - Goal: use SQS to decouple the front-end and back-end components, ensuring load balancing and fault tolerance
  - Front-end uploads a photo to S3 and sends to back-end an SQS message containing the S3 link
  - A pool of EC2 instances (back-end) retrieves messages from the queue
    - Each instances gets a photo, processes it (e.g., resize) and delete the message after processing
    - If processing fails, the message becomes visible again after the visibility timeout, allowing another instance to retry
    - The back-end pool can be scaled horizontally based on the number of messages in the queue




Apache Kafka

- Open-source, distributed event streaming platform https://kafka.apache.org/
- Designed to
  - Publish and subscribe to streams of events
  - Store event streams durably and reliably
  - Process event streams
- Started by LinkedIn in 2010, now Apache project
- Used at scale by LinkedIn, Netflix, Uber, and many others
- Written in Java and Scala
- Horizontally scalable and fault-tolerant
- High-throughput ingestion
  - Billions of events




Kafka at a glance



- **Kafka topics**: Kafka stores streams of events (aka *messages* or *records*) in categories known as topics
- **Kafka cluster**: composed of servers called brokers, which can span multiple data centers or cloud regions
  - Brokers receive and store events
- **Producers**: publish (write) events to a Kafka topic
- **Consumers**: subscribe to Kafka topics, read published events and process them
  - A topic can have 0, 1, or many subscribing consumers


Kafka: topics and partitions

- Topic: category to which events are published
- For each topic, Kafka cluster maintains a **partitioned log**
- Log (data structure): *append-only*, *totally ordered* sequence of events
- Partitioned log: each topic is split into a pre-defined number of partitions
  - Partition: the unit of parallelism for a topic



Kafka: partitions and parallelism

- Parallelism and scalability come from having multiple partitions per topic IMPORTANTE
- Producers publish events to topic partitions
- Consumers read events from the topic
- Each partition is:
  - A numbered, ordered, immutable sequence of records
  - Appended to, never modified (immutable records)
  - Similar to a commit log
- Every record has a monotonically increasing **offset**
  - Uniquely identifies each record within a partition




DA NOTARE COME UN CONSUMER LEGGE UN OFFSET DIVERSO

Kafka: partitions and design choices


- Improve scalability: topic partitions are distributed across multiple brokers
  - ✓ I/O throughput increases through parallel reads and writes
    - Multiple producers can write concurrently to different partitions
    - Multiple consumers can read concurrently from different partitions

un topic viene partizionato e ogni partizione finisce sotto broker diversi per incrementare il throughput




Kafka: partitions and design choices

- Improve fault tolerance: partitions can be *replicated* across brokers
  - Each partition has:
    - 1 leader: handles all writes and reads
    - 0 or more followers: replicate the leader data i follower fanno pull al leader
- *Replication-factor* = total number of replicas (including leader)
  - Replication-factor = *N* → up to *N*-1 brokers can fail without losing data




Kafka: partitions and design choices

- Simplify data consistency management: only leader handles all reads and writes
  - Producers write to the leader, consumers read from the leader
  - Followers replicate the leader and serve as backups
  - Followers can be:
    - in-sync: fully updated with the leader
    - out-of-sync: lagging behind the leader



Kafka: partitions and design choices

- Share responsibility and balance load: each broker acts as leader for some partitions and follower for others
- Coordination across brokers is managed by Apache Zookeeper or KRaft
  - Handles leader election
  - Maintains cluster metadata




Kafka: producers

- Producers = data sources
- Publish events to topics of their choice
  - Send events directly to the broker that is leader for the target partition (no routing tier)
- Responsible for assigning events to partitions using:
  - Key-based partitioning
    - Event contains a partition key (e.g., order ID, user ID)
    - Partition is chosen by hashing the key
    - Example: if `key=user_id`, all events for the same user go to the same partition
  - Round-robin partitioning
    - Default if no key is specified
  - Custom partitioning
    - A partitioner can be provided to implement a custom partitioning logic
- Multiple producers can write concurrently to the same partition

Kafka: consumers

- Kafka uses a pull-based delivery model for consumers
  https://kafka.apache.org/documentation.html#design_pull
- A consumer track its progress using offset
  - Offset identifies which events have been consumed
- Multiple consumers can be read the same partition, each reading at different offsets



Kafka: consumers

- Why pull?
- Push model
  - Broker actively pushes events to consumers
  - ✗ Broker must manage
    - Different consumers with their needs and capabilities
    - Transmission rate control
    - Timing decisions: whether to send a message immediately or accumulate more data to send later
- Pull model
  - Consumers control event retrieval from broker
  - Consumers maintain an offset to identify the next event to read
  - ✓ More scalable and flexible
    - Less burden on brokers
    - Consumers can pull events when ready, adjusting the rate
  - ✗ If no events are available, consumers may end up busy waiting for events to arrive

Kafka: consumers

- How can consumers read in a fault-tolerant way?
  - After a consumer reads events, it stores its committed offset in a special Kafka topic called `__consumer_offsets`
  - In case of crash, the consumer can recover by reading events from the committed offset
  - By default, `auto-commit` is enabled

gli offset sono mantenuti in un topic speciale
e ciascun consumer accede al topic tramite
un file chiamato: __consumer_offset-xx
dove xx è il numero del offset

Kafka: message retention and storage

- Kafka brokers store messages reliably on disk
- Messages are stored in log segments (files on disk)
- Unlike other message queue and pub/sub systems, Kafka does not delete messages after delivery, but retains messages based on size or time

A DIFFERENZA DI RABBITMQ

- Issue: how to free up disk space?
  - Topics are configured with retention time (how long events should be stored)
  - Upon expiry, events are marked for deletion importante
  - Alternatively, retention can be specified in bytes
- On each broker, messages are flushed from the broker's in-memory buffer to the disk
  - A log flush policy controls when messages are written to disk (time interval and number of messages)

Hands-on Kafka

- Preliminary steps
  - Download and install Kafka
    https://kafka.apache.org/downloads
    - Configure Kafka properties in `server.properties`
      - E.g., `listeners` which are network interfaces on Kafka broker: `listeners=PLAINTEXT://localhost:9092`
      - E.g., log flush policy
  - Start Kafka environment
    - Kafka can use KRaft or ZooKeeper (we will use KRaft)
      - Alternatively, start ZooKeeper first
    - Start Kafka broker (default port: 9092)

```
$ bin/kafka-server-start config/kafka.properties
```


Hands-on Kafka

- Let's use Kafka CLI to create a topic, publish and consume events to/from topic, and delete it
- Create a topic named test with 1 partition and no replication (`replication-factor=1`)

```
$ kafka-topics --create --bootstrap-server localhost:9092
  --replication-factor 1 --partitions 1 --topic test
```

  - Bootstrap server: an initial broker used by the producer to connect to the Kafka cluster
  - It provides the producer with metadata about the cluster, including a list of all the brokers
  - Multiple bootstrap servers for fault tolerance and load balancing
  - Once the producer discovers the partition leader, it can start sending messages

Hands-on Kafka

- Produce messages into the topic

```
$ kafka-console-producer --bootstrap-server localhost:9092 \
  --topic test
>msg 1
>msg 2
```

- Consume messages from the beginning of the topic

```
$ kafka-console-consumer --bootstrap-server localhost:9092 \
  --topic test --from-beginning
```

- Consume messages from a given offset (e.g., 2) of a specific partition (e.g., partition 0) of the topic

```
$ kafka-console-consumer --bootstrap-server localhost:9092 \
  --topic test --offset 2 --partition 0
```

- Produce messages with key

```
$ kafka-console-producer --bootstrap-server localhost:9092 \
  --topic test --property parse.key=true --property key.separator=:
>course:sdcc
>university:Tor Vergata
```

in /tmp trovo una cartella contenente i file legati a kafka
tra cui test-0, test-1, test-2 che sono le partizioni del topic test

Hands-on Kafka

- List available topics

```
$ kafka-topics --list --bootstrap-server localhost:9092
```

- Delete a topic

```
$ kafka-topics --delete --bootstrap-server localhost:9092 \
  --topic test
```

- Stop Kafka


```
$ kafka-server-stop
```

  - If Zookeper: `$ zookeeper-server-stop`

kafka-topics --bootstrap-server localhost:porta --describe da più informazioni su i topic in uso come ad esempio Replicas, Elr che indica il numero di leader elegibili (vedi file)


Kafka: consumer group

- Consumer Group: set of consumers that cooperate to consume data from a topic and share a group ID
  - A Consumer Group represents a *logical* subscriber
  - Topic partitions are divided among consumers in the group
    - Reassigned when consumers join/leave the group
  - Each event is delivered to *only one* consumer within the group
  - Each group maintains its own offset per topic partition




Kafka: consumer group

- How can many consumers read the same events?
  - By using different group IDs: consumers in different groups can independently read the same events from the same topic
- Example: microservices communicating through Kafka



- When we scale microservices
  - Each microservice has its own consumer group



Hands-on Kafka: consumer group


- Launch a consumer in a consumer group named `my-group`

```
$ kafka-console-consumer \
  --bootstrap-server localhost:9092 \
  --topic test \
  --group my-group
```

- Open two more terminal windows and run two additional consumers in `my-group`
  - Each consumer will be assigned to a different topic partition
- Produce messages in the topic and see how they are distributed among the consumers
  - Each consumer will read the messages from its assigned partition

Kafka: replication

- Topic partitions are replicates across brokers for fault tolerance
  - Leader-follower model: followers replicate the leader log
  - Replication is asynchronous: periodically, followers pull messages from the leader in order, using offsets
  - In-sync replicas (ISR): the leader and any followers that are updated with the leader's log
  - Durability (no message loss) is guaranteed as long as at least one in-sync replica is available
  - If the leader crashes, one in-sync replica is elected as new leader



Kafka: event ordering guarantees

- Events written by a producer to a topic partition are appended in the order they are sent

  message: m1 m2 m3 m4 m5
  offset: 10 11 12 13 15

- Consumer reads events in the same order they are stored in the partition

  m1 → m2 → m3 → m4 → m5

- Kafka provides ordering guarantees, but *only within a partition*
  - Total order of events within each partition (*per-partition ordering*)
- Kafka does not preserve order across partitions of the same topic
- In practice, per-partition ordering combined with key-based partitioning is sufficient for most applications

Kafka: write guarantees

- Controlled by `acks` and `min.insync.replicas`
- `acks` (producer setting): how many in-sync replicas must acknowledge a write before the producer considers it successful
  - `acks=0`: no ack (fire and forget)
  - `acks=1`: wait for leader only
  - `acks=all`: wait for all ISR replicas
- `min.insync.replicas` (topic/cluster setting): minimum number of ISR replicas that must acknowledge a write for it to succeed
- Strong durability: `acks=all + min.insync.replicas>=2`
  - Example: `replication-factor=3`
    - `min.insync.replicas=1`: only leader
    - `min.insync.replicas=2`: leader + 1 follower (recommended)
    - `min.insync.replicas=3`: leader + 2 followers (highest durability)

Kafka: read and visibility guarantees


- Message durability: depends on `acks` + ISR size/status
  - A write is kept only if enough in-sync replicas acknowledge it (as required by `acks` and `min.insync.replicas`)
- Message availability: consumers can read messages as soon as they are appended to the leader's log
  - Replication to followers is asynchronous
  - Exception: transactional consumers (`read_committed`)
- A write is successful only if:
  1. The leader appends the message, and
  2. The acknowledgment requirements (`acks` and `min.insync.replicas`) are satisfied
  - If reqs cannot be met, write is rejected (not visible to consumers)

è possibile che un consumer legga un dato che non ha raggiunto un numero di ack sufficiente per essere stabile. read_committed evita ciò

dunque se una delle repliche non è disponibile la write fallisce

Kafka: delivery semantics

- **At-most-once**: guarantees that events are never re-delivered but may be lost
  - Producer disables retries (i.e., `acks=0` on producer)



`acks=0`

  - Consumer commits its offset before processing event
    - What happens if the consumer crashes after committing but before processing?


If the consumer process crashes after saving its position, but before saving the output of its message processing, the consumer that takes over processing would start at the saved position and the messages prior to that position would not be processed. Quindi si perde il messaggio

https://kafka.apache.org/documentation/#semantics

https://docs.confluent.io/kafka/design/delivery-semantics.html

Kafka: delivery semantics

- **At-least-once** (default): guarantees no event loss, but events may be duplicated
  - Producer waits for ack only from the partition leader; if no ack, it retries
  - How? Set `acks=1` on producer
  - Consumer commits its offset after processing an event
    - What happens if the consumer crashes before committing?




`acks=1`

In this case, if the consumer process crashes after processing messages, but before saving its position, the new process that takes over may process some messages a second time. Va quindi implementato lato consumer un meccanismo di duplication filtering

Kafka: delivery semantics

- **Exactly-once**: guarantees no event loss, no duplicates, but at the cost of higher latency and lower throughput
  - Producer: `acks=all`
    - Waits for ack from all in-sync partition replicas
  - Idempotent producer: detect duplicates caused by retries
    - Producer ID and sequence number are added to each event
  - Durability: `min.insync.replicas >= 2`
  - Transactions enabled: atomic writes across partitions + transactional offset commits + `read_committed` consumers
  - Not fully exactly-once





`acks=all`

Kafka: delivery semantics

- Take-away message: choose delivery semantics that fit your application
  - At-most-once: prioritize speed (e.g., telemetry, if some data loss is acceptable)
  - At-least-once: prioritize reliability (e.g., email notifications)
  - Exactly-once: prioritize correctness (e.g., financial transactions)

In informatica teorica, il **teorema CAP**, noto anche come **teorema di Brewer**, afferma che è impossibile per un sistema informatico distribuito fornire simultaneamente tutte e tre le seguenti garanzie:[1][2]

- Coerenza (*copy-consistency*): tutti i nodi vedano gli stessi dati nello stesso momento
- Disponibilità (*availability*): la garanzia che ogni richiesta riceva una risposta su ciò che è riuscito o fallito
- Tolleranza di partizione (*partitioning*): il sistema continua a funzionare nonostante arbitrarie perdite di messaggi o malfunzionamenti

Secondo il teorema, un sistema distribuito è in grado di soddisfare al massimo due di queste garanzie allo stesso tempo, ma non tutte e tre.[3]




Diagramma di Venn del teorema CAP

Kafka è CA


Kafka: trade-offs

- Consistency vs. availability trade-off
  - Kafka ensures strong consistency per partition: all in-sync replicas are up-to-date with the leader
  - If the leader fails and no ISR follower is available, the partition becomes unavailable

- Latency vs. durability trade-off
  - Producers control durability via `acks`
    - `acks=all`: highest durability, higher latency (waits for all ISRs)
    - `acks=1`: lower latency, but messages may be lost if leader crashes
    - `acks=0`: lowest latency, highest risk of loss
  - Lower latency increases the chance of data loss in case of failure

Kafka: from ZooKeeper to KRaft


- Zookeeper: distributed coordination service used for managing distributed systems https://zookeeper.apache.org/
  - Provides locking, leader election, monitoring
- Role of ZooKeeper in Kafka
  - Metadata management: list of brokers, configuration for topics and partitions
  - Leader election: to determine partition leader
  - Cluster health monitoring



- Cons
  - ✗ Operational complexity: separate Zookeeper cluster
  - ✗ Scalability: as Kafka cluster grows, Zookeeper becomes bottleneck
  - ✗ Single point of failure for coordination: if Zookeeper is unavailable, Kafka brokers may be unable to manage metadata, elect new leader, and know broker status

Kafka: from ZooKeeper to KRaft


- Apache Kafka Raft (KRaft)
  - Kafka-native consensus protocol that replaces Zookeeper for metadata management and leader election
  - Kafka itself stores metadata and partition leader information
  - Raft protocol coordinates metadata updates
  - KRaft is used for leader election



- Pros
  - ✓ Simplified architecture
  - ✓ Improved scalability
  - ✓ Better fault tolerance: metadata replicated to all brokers, making failover faster

Kafka: APIs

- A set of APIs for interacting with Kafka
- Producer API: allows clients to publish data to Kafka topics
- Consumer API: allows clients to consume data from Kafka topics
- Connect API: integrates external systems (databases, file systems) as data sources and sinks
  - Pre-built connectors: AWS S3, Lambda, MySQL, Postgres, …
- Admin API: manages clusters and resources (topics, partitions, brokers, etc.)
- Streams API: for real-time processing of streaming data



https://kafka.apache.org/documentation/#api

Kafka: client libraries


- Kafka officially provides an SDK for Java
  - Fully featured (supports all APIs except Admin), actively maintained
- Community-driven Kafka client libraries for other languages, including
  - Go
    - Confluent https://github.com/confluentinc/confluent-kafka-go
    - Kafka-go https://github.com/segmentio/kafka-go
  - Python
    - Confluent https://github.com/confluentinc/confluent-kafka-python

Interacting with MOM: messaging protocols

- Application-layer open standard protocols for MOM interaction
  - **AMQP** (Advanced Message Queueing Protocol) unico che trattiamo
    - Binary protocol
  - MQTT (Message Queue Telemetry Transport) https://mqtt.org
    - Binary, lightweight protocol, for low-bandwidth and low-power devices, commonly used in IoT applications
  - STOMP (Simple Text Oriented Messaging Protocol) https://stomp.github.io/
    - Simple, text-based protocol, commonly used in web applications and real-time communication
- Goals:
  - Platform- and vendor-agnostic
  - Interoperability: facilitates communication between different MOMs

Messaging protocols and IoT

- Widely used in Internet of Things (IoT)
  - Messaging protocols enable data exchange between sensors and services that process data



- Advantages on MOM in IoT
  - Decoupling: separate data producers from consumers
  - Resiliency: MOM provides temporary message storage
  - Traffic spikes handling: MOM can persist data and process it eventually


AMQP: features

- Open standard messaging protocol, supported by industry
  - Version 1.0, approved in 2014 by ISO and IEC

  https://docs.oasis-open.org/amqp/core/v1.0/amqp-core-complete-v1.0.pdf
- Application-level, binary protocol molto efficiente essendo binario
  - Based on TCP with additional reliability mechanisms (delivery semantics)
- Programmable protocol
  - Entities and routing schemes are primarily defined by apps
- Designed to provide reliable, scalable and secure messaging
- Supports queue-based and pub/sub patterns
- Implementations noi studieremo RabbitMQ
  - Apache ActiveMQ, RabbitMQ, Azure Event Hubs, Pika (Python client library), …

AMQP: architecture

- 3 key actors: publishers, subscribers, and brokers
  - Brokers manage and route messages
- AMQP entities (within broker): queues, exchanges and bindings



schema interno del broker

  - Queues: storage units that hold messages
  - Exchanges: routing entities that determined how messages are distributed to queues tramite politiche specifiche
    - Like post offices or mailboxes
  - Bindings: rules that define how messages are distributed to queues sarebbero le frecce nell'immagine
  - Message delivery
    - Push delivery: brokers push messages to consumers subscribed to queues
    - Pull delivery: consumers pull messages from queues on demand

https://www.rabbitmq.com/tutorials/amqp-concepts


AMQP: routing

- Types of AMQP exchanges
  - Direct exchange: delivers messages to queues based on message routing key
    - Use case: routing to specific queues based on exact matching

la politica del exchange la sceglie il programmatore


poco flessibile

Direct exchange routing



  - Fanout exchange: delivers messages to all queues that are bound to the exchange
    - Use case: broadcasting to multiple queues

Fanout exchange routing



AMQP: routing

- Types of AMQP exchanges
  - Topic exchange: delivers messages to one or more queues based on topic matching più flessibile rispetto al direct exchange
    - Routing key can include wildcards
    - Use case: commonly used to implement pub/sub patterns
    - Enables multicast routing, e.g., targeted notifications to users in different regions
    - Example: a message with routing key `"location.northAmerica.newYork"` will be delivered to queues bound with patterns like `"location.northAmerica.#"`, `"location.#"`, `"*.newYork"`
  - Headers exchange: delivers messages based on message headers rispetto ai primi 3 tipi che si basano sul body del messaggio, questo si basa sul header
    - To route on multiple attributes that are expressed as message headers instead of routing key
    - Use case: complex multi-attribute matching





figura di approfondimento di AMQP dal libro di Tanenbaum

Figure 4.29: An overview of a single-server AMQP instance

AMQP: messages

- AMQP defines two message types:
  - Bare messages: raw messages supplied by sender immutabile!
  - Annotated messages: modified by intermediaries (e.g., brokers) during transit by adding headers and annotations
- Message header conveys delivery parameters
  - Including durability requirements, priority, time to live



RabbitMQ

- Open-source message broker https://www.rabbitmq.com/




- Multiple messaging protocols supported
  - AMQP, MQTT, and STOMP
- Push delivery model (can also support pull) pull che non vedremo. ricorda kafka usa pull
- FIFO ordering guarantee at queue level detttaglio importante
- Cross-platform
  - Can run on multiple operating systems and cloud environments
- Wide range of development tools (Java, Go, Python, …)

RabbitMQ: architecture

- Producers do not publish messages directly to queues
- Producer sends messages to an exchange, which routes messages to one or more queues with the help of bindings and routing keys
  - Binding: link between an exchange and a queue

Message flow in RabbitMQ



qui si nota la somiglianza con il protocollo AMQP

- RabbitMQ broker can be distributed, e.g., forming a cluster https://www.rabbitmq.com/distributed.html
  - Supports quorum queues: durable, replicated FIFO queues based on Raft consensus algorithm come per KRaft

RabbitMQ: delivery semantics

- At-most-once delivery by default
  - Consumer does not explicitly send acks (`autoAck = true` in the consumer settings); if the consumer fails before processing the message, the message will be lost
- At-least-once can be configured
  - Explicit message ack must be configured (`autoAck = false` in the consumer settings) and the consumer is required to send an explicit ack after successfully processing the message (esempio di seguito)


una volta mandato il messaggio, dopo la lettura viene cancellato. a differenza di Kafka che li mantiene persistenti

RabbitMQ: use cases

esempi in Go

1. Store and forward messages sent by a producer and received by a consumer (message queue)
2. Distribute tasks among multiple workers (work queue)
   quindi un load balancer
3. Deliver messages to many consumers (pub/sub) using a *message exchange*
4. Routing messages: producer sends messages to an *exchange,* that selects the queue based on binding rules and routing keys
5. Run a function on consumer and wait for result (RPC)

https://www.rabbitmq.com/tutorials



RabbitMQ and Go

- Let's use RabbitMQ, Go and AMQP (messaging protocol) for:

Ex. 1: Message queue


https://www.rabbitmq.com/tutorials/tutorial-one-go

i messaggi saranno distribuiti in maniera Round-robin



Ex. 2: Work queue

https://www.rabbitmq.com/tutorials/tutorial-two-go.html



Code on Teams/course website

RabbitMQ and Go

- Preliminary steps:

1. Install RabbitMQ and start RabbitMQ server on localhost (port 5672) https://www.rabbitmq.com/download.html

```
$ rabbitmq-server
```

   - RabbitMQ CLI tool: `rabbitmqctl`

```
$ rabbitmqctl stop
$ rabbitmqctl status
```

     Some useful commands for `rabbitmqctl`

```
list_channels
list_consumers
list_queues
reset
```

   - Also web UI for management and monitoring (port 15672)

2. Install Go AMQP client library


```
$ go get github.com/rabbitmq/amqp091-go
```

   Details on `ampq`: https://pkg.go.dev/github.com/rabbitmq/amqp091-go

RabbitMQ and Go: example 1

1. Message queue pattern

- Support single producer, single consumer or multiple producers, multiple consumers
- Note that:
  - Message is delivered to only one consumer
  - Delivery is push-based



RabbitMQ and Go: example 2

2. Work queue pattern


- Version 1 (new_task_v1.go and worker_v1.go):
  - Multiple consumers: tasks are distributed among consumers in a round-robin fashion
  - Message loss scenario: if consumer crashes after the message is delivered by RabbitMQ but before completing the task, the message is lost

    `auto-ack=true`: message is considered to be successfully delivered as soon as it is sent to consumer ("fire-and-forget")
- Version 2 (new_task_v1.go and worker_v2.go):
  - Set `auto-ack=false` in `Consume` and add explicit ack in consumer to tell RabbitMQ that message has been processed and RabbitMQ can safely discard it
  - What happens when RabbitMQ is restarted while there are pending messages?
  - Which delivery semantics with explicit acks? at-least-once

RabbitMQ and Go: example 2

2. Work queue pattern

- Version 3 (new_task_v3.go and worker_v3.go):
  - Use a durable queue so messages are persisted to disk and survives RabbitMQ crash and restart
  - Queue declared with `durable=true` in `QueueDeclare`
- Version 4 (new_task_v3.go and worker_v4.go):
  - Improve task distribution by preventing a worker from receiving a new message while it still has unacknowledged messages un load balancing più soffisticato
  - Achieved using channel prefetch (`Qos`) setting



Multicast communication

- **Multicast communication**: a group communication pattern where data is sent to *multiple* receivers (but not all) at once
  - Can be one-to-many or many-to-many
  - One-to-many multicast apps: video/audio resource distribution, file distribution
  - Many-to-many multicast apps: conferencing tools, multiplayer games, interactive distributed simulations
  - Broadcast: special case of multicast, where data is sent to *all* receivers
- Cannot be implemented via unicast replication (source sends indivudual copies to each receiver): lack of scalability
  - Solution: replicate data only when needed

Types of multicast

- How to realize multicast
  - **Network**-level multicast (IP-level)
    - Packet replication and routing managed by network routers
    - Uses IP Multicast
    - ✗ Limited in usage due to the need for specific router support and network infrastructure
  - **Application**-level multicast
    - Replication and routing managed by the hosts

Application-level multicast

- Basic idea:
  - Organize nodes into an overlay network
  - Use the overlay network to disseminate data
  - Can be structured or unstructured
- Structured application-level multicast
  - Explicit communication paths
  - How to build a structured overlay network?
    - Tree: one path between each pair of nodes (e.g., tree building based on Chord)
    - Mesh: multiple paths between each pair of nodes
- Unstructured application-level multicast che studieremo con il gossiping
  - No predefined communication paths, typically relying on random connections between nodes

Con un albero c'è solo un unico percorso tra ogni coppia di nodi. In una mesh ogni nodo possiede multipli vicini e quindi, multipli percorsi tra ogni coppia di nodi.La differenza principale tra le due reti è che la mesh è generalmente più robusta, in qunato se una connessione salta, c'è sempre un altro percorso per disseminare le informazioni senza dover riorganizzare l'intera rete.

Unstructured application-level multicast

- How to realize unstructured application-level multicast
  - ✓ Flooding
    - Node *P* sends the multicast message *m* to all its neighbors
    - Each neighbor forwards *m* to all its neighbors (except to *P)* if it has not seen *m* before
  - ✓ Random walk
    - Node *P* sends multicast message *m* to a randomly chosen neighbor
    - The chosen neighbor forwards *m* to another randomly chosen neighbor
  - 👉**Gossiping**

Gossip-based protocols

- Gossip-based protocols (or algorithms) are probabilistic (aka *epidemic* algorithms)
  - Gossiping effect: information spreads within a group just as it would be in real-life social interactions
  - Strongly related to epidemics, by which a disease is spread by infecting members of a group, which in turn can infect others
- Allow information dissemination in large-scale networks through random choice of successive receivers among those known to sender
  - Each node sends the message to a randomly chosen subset of nodes in the network
  - Each receiving node will forward the message to another randomly chosen subset, and so on

Origin of gossip-based protocols

- Proposed in 1987 by Demers et al. as a solution for data consistency in replicated databases with hundreds of servers
  - Assumption: no write conflicts (i.e., independent updates)
  - Updates are initially performed at one replica server
  - Each replica shares its updated state with only a few selected neighbors
  - Update propagation is *lazy*, i.e., not immediate
  - Eventually, each update should reach every replica

Demers et al., Epidemic Algorithms for Replicated Database Maintenance, PODC 1987 https://dl.acm.org/doi/pdf/10.1145/41840.41841

Why gossiping in large-scale DSs?

- Several attractive properties of gossip-based information dissemination for large-scale distributed systems
  - Simplicity of gossiping algorithms
  - No centralized control or management (and related bottleneck)
  - Scalability: each node sends only a limited number of messages, independently from system size
  - Reliability and robustness: thanks to message redundancy

Who uses gossiping? Examples

- AWS S3 uses a gossip protocol to rapidly disseminate information throughout its system. This allows S3 to quickly route around failed or unreachable servers, among other things
- Amazon's Dynamo uses gossiping for node failure detection
- BitTorrent uses a gossip-based information exchange
- Cassandra uses gossiping for group membership and node failure detection
- Gossip dissemination pattern
  https://martinfowler.com/articles/patterns-of-distributed-systems/gossip-dissemination.html

Strategies to spread updates


- Let's consider the two principal operations

1. Anti-entropy: each node periodically selects another node randomly and exchanges updates (i.e., state differences), with the goal of having identical states on both node afterwards

2. Rumor spreading: a node that has a new update (i.e., has been contaminated) periodically selects *F* (*F* >= 1) peers and sends them the update (contaminating them); a node that has received an update can stop further distributing it


Anti-entropy


- Goal: increase node state similarity, thus decreasing "disorder" (the reason for the name!)
- Node *P* selects node *Q* randomly: how does P update *Q*?
- Different update strategies:
  1. Push: *P* only pushes its own updates to *Q*
  2. Pull: *P* only pulls new updates from *Q*
  3. Push-pull: *P* and *Q* send updates to each other, i.e., *P* and *Q* exchange updates



Anti-entropy: performance

- Push-pull
  - Fast and message-saving strategy: takes O(ln *N*) rounds to disseminate updates to *N* nodes, using O(*N* ln ln *N*) messages
  - *Round* (or *gossip cycle*): time interval in which every node initiates an exchange






Rumor spreading

- Node *P*, having an update to report, contacts a randomly chosen node *Q* and forwards the update
- If *Q* has already been updated, *P* may lose interest in spreading the update further; with probability p_{stop} *P* stops contacting other nodes
- Fraction *s* of oblivious nodes (nodes that have not yet been updated) is equal to

$$s = e^{-(1/p_{stop}+1)(1-s)}$$

p_{stop} probabilità che il nodo non è stato raggiunto dall'informazione



Consider 10,000 nodes		
$1/p_{stop}$	s	N_s
1	0.203188	2032
2	0.059520	595
3	0.019827	198
4	0.006977	70
5	0.002516	25
6	0.000918	9
7	0.000336	3

- To improve information dissemination (especially when p_{stop} is high), combine rumor spreading with anti-entropy

Sia anti-entropy che rumor spreading sono strategie periodiche ma il periodo non è lo stesso.

Framework for gossiping protocols

- Two nodes *P* and *Q*, where *P* selects *Q* to exchange information with
  - *P* runs at each round (Δ time units)

Active thread (node P):		Passive thread (node Q):
selectPeer(&Q)		
selectToSend(&buf)		
sendTo(Q, buf)	----->	receiveFromAny(&P, &req)
		selectToSend(&buf)
receiveFrom(Q, &resp)	<-----	sendTo(P, buf)
selectToKeep(view, resp)		selectToKeep(view, req)
processData(view)		processData(view)

selectPeer: randomly select a node to send the gossip message to
selectToSend: select some entries from node's local view to send
selectToKeep: select which received entries to store in node's local view; remove duplicate entries

Kermarrec and van Steen, Gossiping in distributed systems, *SIGOPS Oper. Syst. Rev.*, 2007 https://www.distributed-systems.net/my-data/papers/2007.osr.pdf


Framework for gossiping protocols

- Simple? Not quite
- Several crucial aspects
  - Node selection to gossip: many alternatives including
    - Uniformly selecting from the set of currently available (alive) nodes
    - Selecting the peer that has been least contacted (e.g., used by CoachroachDB)
  - Data exchanged
    - What is exchanged is highly application-dependent
    - Choice of update strategy
  - Data processing
    - Again, highly application-dependent

Insomma i dettagli implementativi, non saranno dimostrati nel corso ma diamo almeno un ragionamento superficiale

Gossiping vs flooding: example

- Information dissemination is the classic and most popular application of gossiping protocols in DSs
  - Gossiping is generally more efficient than flooding
- Flooding-based information dissemination
  - Each node that receives a message forwards it to all its neighbors (including the sender)
  - Message is eventually discarded when TTL reaches 0




Sent messages: 18
Reached nodes: 8 out of 9_{90}

Gossiping vs flooding: example

- Use an example of rumor spreading algorithm
  - The node sends the message to each of its neighbors with probability *p*

```
for each msg m
    if random(0,1) < p then send m
```



Sent messages: 11
Reached nodes: 7 out 9

Dunque a parità di round il gossiping occupa meno la rete ma raggiunge meno nodi, mentre il carico con flooding è maggiore e si coprono più nodi.

Gossiping vs flooding

- Gossiping key features
  - Probabilistic
  - Localized decision, yet leads to a global state
  - Lightweight
  - Fault-tolerant
- Flooding pros and cons
  - ✓ Universal coverage and minimal state information needed
  - ✗ Can flood the network with redundant messages
- Gossiping goals
  - Reduce redundant transmissions compared to flooding while attempting to retain its advantages
  - However, due to its probabilistic nature, it cannot guarantee that all the peers are reached and it generally takes longer to complete than flooding

Other application domains of gossiping

- Besides information dissemination…
- Group membership
  - To know the list of nodes in DS (who is part of the system)
- Peer sampling
  - To select nodes from a larger set of available nodes to interact with
- Resource management in large-scale DS
  - Including monitoring and failure detection
- Distributed computations for data aggregation in large-scale DS (e.g., sensor network)
  - Computation of aggregates, e.g., sum, average, maximum, minimum
  - Example: computing average
    - Let $v_{t,i}$ and $v_{t,j}$ be the values at time t stored at nodes i and j
    - During a gossip exchange, i and j exchange their current local value v_i and v_j and adjust it to

$$v_{t+1,i},\ v_{t+1,j} \leftarrow (v_{t,i} + v_{t,j})/2$$

Gossiping case studies

1. Blind counter rumor mongering: example of gossip-based disseminatio protocol

2. Bimodal multicast: builds on gossiping to provide reliable multicast

Blind counter rumor mongering

- Why this name?
  - *Rumor mongering* (def.: "the act of spreading rumors", also known as gossip): a node with a "hot rumor" periodically infects other nodes
  - *Blind*: the node loses interest regardless of who the recipient is (*why*)
  - *Counter*: the node loses interest after a fixed number of contacts (*when*)
- Two parameters to control gossiping
  - *B*: max number of neighbors a message is forwarded to
  - *F*: number of times a node forwards the same message to its neighbors

un nodo che possiede hot rumor periodicamente diffonde il rumor. a tale nodo non importa a chi diffonde il rumor ma arrivato ad un counter smette di fare gossip

Portman and Seneviratne, The cost of application-level broadcast in a fully decentralized peer-to-peer network, ISCC 2002

Blind counter rumor mongering

- Gossiping protocol

```
A node n initiates a broadcast by sending message m to B
   of its neighbors, chosen at random
When node p receives a message m from node q
  If p has received m no more than F times
    p sends m to B neighbors, chosen uniformly at random,
    among those that p believes have not yet seen m
```

  - Note that *p* knows whether its neighbor *r* has already seen *m* only if *p* has previously sent *m* to *r*, or if *p* has received *m* from *r*


- Performance (*B*=*F*=2) compared to flooding
  - Lower number of messages: ~50%
  - Incomplete coverage: ~90%
  - Slower dissemination: ~2x

Bimodal multicast

- Aka pbcast (probabilistic broadcast)
- 2-phase protocol:
  1. **Message distribution**: a process sends a multicast message with no particular reliability guarantees
  2. **Gossip repair**: after receiving a message, a process begins to gossip about it to a set of peers
     - Gossip occurs at regular intervals, giving processes a chance to compare their states and fill gaps in their message sequence
- Used by Fastly CDN for cache invalidation
  https://www.fastly.com/blog/building-fast-and-reliable-purging-system


Birman et al., Bimodal multicast, *ACM Trans. Comput. Syst.,* 1999

Bimodal multicast: message distribution




- Start with *unreliable* multicast to rapidly distribute messages
- Partial distribution may occur:
  - Some message may not reach all nodes
  - Some process may be faulty

Bimodal multicast: gossip repair




- Periodically (e.g., every 100 ms), each process sends a *digest* describing its state to a *randomly* selected process
- The digest only identifies messages, without including them

Bimodal multicast: gossip repair



- The recipient checks the gossip digest against its own message history and *requests* copies of any missing messages from the process that sent the gossip

Bimodal multicast: gossip repair




- Processes reply to solicitations received during a gossip round by retransmitting the requested messages
- Some optimizations exist (not examined)

Bimodal multicast: why “bimodal”?

- Are there two phases?
- No; dual “modes” of result


1. Bimodal delivery pattern: pbcast is almost always delivered to most or to few processes, and almost never to some processes

   Atomicity = almost all or almost none



2. Bimodal delivery latencies: one distribution of very low latencies (messages arriving without loss in the initial phase) and a second distribution with higher latencies (messages that had to be repaired afterward)

Pub-sub event matching



- Subscriber specifies which events it is interested in (subscription *S*)
- Publisher publishes event *N*: does *N* match *S*?
- Challenge: efficiently implement event matching

Event matching: centralized architecture

- Naive solution: centralized architecture
  - Single server handles all subscriptions and notifications
- Server responsibilities:
  - Handles subscriptions from subscribers
  - Receives events from publishers
  - Checks events against subscriptions
  - Notifies matching subscribers

✓ Simple to realize, feasible for small-scale deployments

✗ Scalability

✗ SPOF

Event matching: distributed architecture

- Achieve matching scalability
- Simple solution: partition subscriptions

1. Hierarchical architecture: master distributes matching across multiple workers
   - Each worker stores and handles a subset of subscriptions
   - Master receives events and distribute them to workers for matching
   - Partitioning strategy
     - Topic-based pub/sub: hash topic names to map subscriptions and events to workers

   ✗ Single master
2. Flat architecture: no single master, matching is spread across distributed servers
   - Partitioning strategy
     - Topic-based pub/sub: hash topic names to select server

Event matching: distributed architecture

- Other solutions: decentralized servers (overlay network)
- Challenge: how to route notifications to subscribers?

1. Unstructured overlay: use flooding or gossiping to disseminate event notifications
   - Store a subscription at only one server, but disseminate notifications to all servers: matching is distributed across servers
   - Selective routing: install filters to ignore paths toward nodes that are not interested, reducing unnecessary messages
2. Structured overlay: use a DHT to disseminate event notifications