TOR VERGATA
UNIVERSITÀ DEGLI STUDI DI ROMA
Macroarea di Ingegneria
Dipartimento di Ingegneria Civile e Ingegneria Informatica

Communication in Distributed Systems: RPC

Corso di Sistemi Distribuiti e Cloud Computing

A.A. 2025/26

Valeria Cardellini


Laurea Magistrale in Ingegneria Informatica

Communication in distributed systems

- Message passing: the basics
- Communication is based on sending and receiving messages
- To make this work, parties must agree on many low-level communication details, such as:
  - How many volts represent a 0 or 1 bit?
  - How many bits represent an integer?
  - How does the receiver know when the message ends?
  - How can the receiver detect message corruption and what to do then?
- The good news: we don't care about these low-level details ☺

Basic networking model and its adaptation

- We already know the solution: divide network communication in layers
  - The well-known ISO/OSI reference model
  - For distributed systems we don't deal with low-level details: we focus on higher-level abstractions built over the network layer
- Adapted layering scheme in distributed systems



Middleware layer

- **Middleware** provides common services and protocols that support different distributed applications and systems
  - General-purpose
  - Application-independent
- Common middleware services
  - Communication: remote procedures calls, message queues, multicasting
  - Naming: identifies and enables sharing of resources
  - Security: ensures secure communication among distributed nodes
  - Distributed consensus: coordinates agreement across multiple distributed nodes
  - Distributed locking: prevents concurrent access to shared resources (e.g., multiple clients editing a file)
  - Data consistency: maintains data consistency across distributed nodes

Communication types in DS

- Let's distinguish communication types by 3 key aspects:

1. Persistency
   - Transient vs. persistent communication
2. Synchronization
   - Synchronous vs. asynchronous communication
3. Time dependence
   - Discrete vs. streaming communication


Persistent vs. transient communication

- Persistent communication
  - Message is stored by middleware until it can be delivered
  - Sender can continue execution after submitting the message
  - Receiver does not need to be active at the time of submission

- Transient communication
  - Message is kept only while sender and receiver are both active
  - If delivery is not possible, message is discarded
  - Requires both parties to be executing at the time of communication
  - Transport-layer example: routers store and forward messages, but discard them if forwarding fails

Synchronous communication…

- Once a message is submitted, the sender is blocked until the operation completes
- Send and receive are *blocking* operations
- Synchronization can occur:
  1. At request submission
  2. At request delivery
  3. After request processing



… vs asynchronous communication

- *Non-blocking send*
  - Once the message is submitted, the sender continues processing
  - The message is temporarily stored by middleware until it is transmitted
- *Receive* can be *blocking or non-blocking*
  - Non-blocking receive: immediately returns, either with data (if available) or with an indication that there is nothing to receive yet
- Benefits: decouples sender and receiver, enabling higher concurrency and responsiveness

Discrete vs. streaming communication


- Discrete communication
  - Each message forms a complete unit of information

- Streaming communication
  - Involves sending multiple messages, in temporal relationship or related to each other by sending order, which is needed to reconstruct complete information
  - E.g., audio, video

Combining persistence and synchronization


a) Persistent asynchronous communication
  - Message is stored until receiver is ready, sender does not wait for receiver
  - E.g., email, Teams chat, message-oriented middleware

b) Persistent synchronous communication
  - Sender is blocked until message is delivered to receiver
  - Message is stored until delivery is confirmed



Combining persistence and synchronization

c) Transient asynchronous communication
- Sender does not wait
- Message is not stored
- If the receiver is offline or unreachable, message is lost (e.g., UDP)




(c)Asynchronous communication


Combining persistence and synchronization

- Message is not stored
- Sender is blocked until a specific condition is met, which alternatives?
  - d) Receipt-based synchronous: sender is blocked until message reaches the receiver buffer (e.g., asynchronous RPC)
  - e) Delivery-based synchronous: sender is blocked until message is actually delivered to receiver

(d) Receipt-based synchronous communication




(e) Delivery-based synchronous communication




Combining persistence and synchronization

f) Response-based synchronous: sender is blocked until it receives a reply from receiver (e.g., synchronous RPC)



(f) Response-based synchronous communication

What happens when a client calls a RPC




- Which failures can happen?

Communication failures

- Different communication failures between sender (client) and receiver (server): what can go wrong?

1. Message loss or delay
   - Request or reply is lost or delayed
   - Connection is reset
   - Pitfall: *Network is reliable*
2. Server crashes
   a) Before performing the service
   b) After performing the service
   - Client can't distinguish between a) and b)
3. Client crashes after sending request



Failure semantics during communication

- In a DS, communication semantics define what guarantees the DS gives about message delivery in the presence of failures
  - **May-be** semantics
  - **At-least-once** semantics
  - **At-most-once** semantics
  - **Exactly-once** semantics

More guarantees, more complexity

- Failure semantics applies both to message delivery (e.g., MOM) and service processing (e.g., RPC)
- Let's focus on service processing
  - sender = client, receiver = server

Failure semantics in a nutshell

- Maybe: no guarantees that service has been executed or not by server
- At-least-once: service is executed at least once (i.e., >= 1)
  - If client does not receive the reply: service *might* have been executed or it might not, or it might have been executed mutiple times
- At-most-once: service is executed at most once (i.e., 0 or 1)
  - If client receives the reply, it has been processed by server *no more than once*
  - The service may not be executed at all
- Exactly-once: service is executed precisely once
  - Even in the face of retries, crashes, or delays
  - Ideal for critical operations, but complex and costly


Basic mechanisms for implementation

- 3 basic mechanisms to implement failure semantics

1. Client side: Request Retry (RR1)
   - Client keeps trying until it gets a reply or is confident about server failure after a certain number of failed retries
2. Server side: Duplicate Filtering (DF)
   - Server discards any duplicate request from same client
3. Server side: Result Retransmit (RR2)
   - Server keeps result (reply) so that it can be retransmitted without being computed again when server receives duplicate requests

May-be semantics


- No guarantee that service has been executed or not by server
- No action is taken to ensure reliable communication: no mechanism (among RR1, DF, RR2) is used
- E.g., best-effort in UDP
- Use cases: logging, sensor data (if occasional loss is tolerable)



At-least-once semantics

- Service, if executed, has been executed at least once
  - Perhaps more than once due to request duplicates caused by retransmissions
- Client uses RR1, server uses neither DF nor RR2
- Upon receiving the reply, client cannot know how many times its request has been processed by server
  - If server executes the service once or multiple times because the reply was lost or delayed
  - If server executed the service but crashed before replying and then recovered, and client retries the request after timeout; server processes the request again
- It works for idempotent services
  - **Idempotent** service: a service where applying it multiple times has the same effect as applying it once to the same input
    - E.g., `get(key)` or `put(key,value)` in KV data store


At-least-once semantics



At-most-once semantics

- Service, if executed, has been executed at most once
  - *If* client receives the reply, it knows that the service was executed *once*
  - In case of failure, client cannot determine whether the request never reached the server, or server executed the service but the reply was lost (at-most-once: at most once, but possibly not all)
- Mechanisms used: RR1, DF, and RR2
  - Client retransmits request when timeout expires
  - Server maintains some state to identify duplicate requests and avoid processing the same request more than once
- It works also for non-idempotent services
  - E.g., `increment(counter)` or `withdraw(amount)`
- No strict coordination between client and server
  - Client does not know if the service was executed (in case of no reply), server does not know if client received the reply

At-most-once semantics



At-most-once: implementation

- Server must:
  - Detect duplicate requests
  - Manage duplicate requests returning saved reply instead of re-running service `handler()`
  - Discard saved replies when it is safe

Server:

```
if seen[xid]
 reply = old[xid]
else
  reply = handler()
  old[xid] = reply
  seen[xid] = true
```

- How to detect duplicates
  - Client includes a unique ID (`xid`) with each request and uses same `xid` when retransmitting the request due to timeout
  - Server uses `xid` to detect duplicates
  - If server knows the request with that `xid`
    - If reply is saved, resend it
    - If original request is still executing, don't re-run service

At-most-once: implementation

- How to ensure unique `xid`?
  - Globally unique per client (and per server if needed)
  - Common pattern: `xid = client_id + sequence_number`
  - Sequence number: increments with every new request and wraps around only after large gaps
- How to handle duplicate requests during execution?
  - Server maintains also a status flag: `xid → {status, reply}`
  - Status is `pending` if service still executing
  - Status is `completed` if reply cached
  - If duplicate arrives while status is pending, server ignores it or queues it to wait for the original to finish
- Server must eventually discard cached replies: how?
  - Use sliding windows to track recent `xids`
  - Retain reply for a maximum lifetime

Idempotent Receiver pattern
https://martinfowler.com/articles/patterns-of-distributed-systems/idempotent-receiver.html

Exactly-once semantics

- Strongest and hardest guarantee to implement, especially in large-scale DS
- Requires full agreement on interaction between client and server
  - Service is run only once or not run at all: all-or-nothing semantics
    - If everything goes well: service runs only once, duplicates are found
    - If something goes wrong: client or server knows if service has run (once - all) or not (never - nothing)
- Semantics with concordant knowledge of each other's state and without constraint on maximum duration of interaction protocol between client and server
  - No constraint on maximum duration: barely practical in real systems!

Exactly-once semantics: more mechanisms

- Basic mechanisms (RR1, DF, RR2) are not enough
  - Do not protect against server failures
- Additional mechanisms for fault tolerance
  - Transparent server replication
    - Multiple servers replicate the same service
    - E.g., leader-follower or primary-backup
  - Write-ahead logging (WAL)
    - Before executing a service, the server logs the request to persistent storage
  - Recovery mechanisms
    - After failure, the server resumes processing from a safe state
    - *State checkpoint*: saves a local snapshot of server's state to persistent storage
      - Combined with WAL to reduce recovery time (only replay log entries after last checkpoint)
    - *Snapshot*: captures a consistent global state of replicated servers: more complex, requires coordination


Write-ahead logging pattern

- aka Commit log
- Goal
  - Ensure durability by persisting every state change so server can survive crashes and restarts.
  - Log is stored
- How
  - Each state change is stored as log entry in an append-only commit log file written on persistent storage (e.g., disk or SSD)
  - Entries are appended sequentially, ensuring fast write performance and crash-consistent ordering
  - On server restart, log is read and all entries are replayed in order to rebuild the in-memory state
  - No state is lost, as long as the log was flushed to disk before crash

WAL pattern
https://martinfowler.com/articles/patterns-of-distributed-systems/wal.html

Write-ahead logging pattern

- Why write-ahead?




```
public void put(String key, String value) {
    appendLog(key, value);
    kv.put(key, value);
}

private Long appendLog(String key, String value) {
    return wal.writeEntry(new SetValueCommand(key, value).serialize());
}
```


Summing up failure semantics

- In practice, at-least once and at-most once semantics are both feasible and widely used in DS
- Exactly-once is ideal, but often too complex, slow, or expensive to achieve in practice

- We often choose the lesser of two evils, i.e., at-least-once semantics
  - Easier to scale
    - Stateless retries
    - No need for coordination between sender and receiver
  - Works well with idempotent services
  - Can be combined with application-level deduplication if needed

Distributed systems are all about trade-offs!


Distributed application programming

- Explicit network programming
  - Operating system constructs based on socket API and explicit management of message exchange
  - Foundational for network applications (e.g. web browser, web server, chat app)
  - ✗ Distribution is not transparent and requires developer effort

- How to increase the abstraction level?
- Communication middleware between OS and applications
  - Provides a higher-level API for communication
  - Hides complexity of underlying hw and sw layers
  - Frees developers from automatable tasks
  - Improves software quality by providing reusable, correct, and efficient solutions to common DS challenges


Distributed application programming

- Implicit network programming
  - Language-level constructs simplify distributed programming by hiding network details from developers
  - Developers work with **remote procedure calls (RPC)** or **remote method invocations (RMI)** as if they were local calls
  - In reality, the caller (client) and callee (server) are located on separate machines



Remote Procedure Call (RPC)

- Core idea (Birrel and Nelson, 1984): use client/server model to call procedures executed on remote machines
  - Client on machine A calls a procedure on machine B
  - Calling process on A is suspended
  - Called procedure is execute on B
  - Input/output parameters are transported as messages
  - No message passing is visible to developer



Why RPC

- Widely used in many distributed systems, including cloud computing, microservice architectures
- Many languages and frameworks have they own implementation of RPC:
  - **C (Sun RCP)**
  - **Java (Java RMI)**
  - **Python (RPyC)**
  - **Go**
  - **gRPC**


  Our case studies
  - Distributed Ruby https://github.com/ruby/drb
  - Ice https://zeroc.com/ice
  - Microsoft .NET https://dotnet.microsoft.com/
  - JSON-RPC https://www.jsonrpc.org

Local procedure call

- Example of local procedure call:

```
newlist = append(data, dbList)
```


- Caller pushes to stack input parameters (`data`, `dbList`) and return address
- When callee returns, control is back to caller



How can RPC appear as close as possible to a local procedure call?

RPC: architecture

- Solution: proxies (aka **stubs**) to make RPC calls feel like local calls
- Client side: **client stub** exposes service's interface
  - Client calls client stub, which manages all communication details
- Server side: **server stub** receives request and dispatches it to the local procedure on the server
- Goal: distribution transparency
  - Automatic stub generation
  - Focus on application logic




RPC: basic steps

1. On client side, client calls a local procedure, the client stub
2. Client stub marshals parameters (converts them to a common format), packages them into a request message, and call local OS
3. Client OS sends request message to remote OS
4. On server side, remote OS delivers request message to server stub
5. Server stub unmarshals parameters and calls server as it were a local procedure
6. Server executes local call and returns result to server stub
7. Server stubs marshals return value(s) and calls OS
8. Server OS sends reply message to client OS
9. On client side, Client OS delivers reply message to client stub
10. Client stub unmarshals return value(s) and returns result to client

RPC: example

- RPC `doit(a,b)`



RPC: key requirements

- To make an RPC appear as local procedure call, the middleware must:
- Exchange messages between client and server
  - Identify request and reply messages, and remote procedure
  - Pass parameters and return values
- Manage data heterogeneity
  - Parameters, return value(s)
  - Marshaling vs. serialization:
    - ***Marshaling***: bundle parameters into a transferable form that can be unmarshaled (reconstructed) by another process
    - ***Serialization***: convert objects into a sequence of bytes for transmission; serialization is a subset of marshaling
- Handle failures
  - During communication (e.g., message loss, delay)
  - User errors (e.g., invalid input)

RPC: implementation challenges

1. Manage heterogeneity in data representation
   - In addition, client and server must agree on transport protocol for message passing: TPC, UDP, both?
2. Perform parameter passing by reference
   - Client and server run on different machines with separate address space
3. Define failure semantics
   - Local procedure call: exactly-once
   - Remote procedure call: typically at-least-once or at-most-once
4. Bind client to server
   - Locate server endpoint before performing the call

Data representation heterogeneity

- Client and server may use different data representations
  - E.g., byte ordering (little-endian vs big-endian), data size, padding, …
  - RPC must define how RPC messages are encoded on the wire

- Alternatives to handle data representation heterogeneity (*general*, not only RPC):
  1. Specify encoding within the message itself
  2. Sender converts data into receiver encoding
  3. Use a common encoding agreed by both parties
     - Sender converts from local to common format
     - Receiver converts from common to local format
  4. Use an intermediary to convert between different encodings

Data representation heterogeneity

- Comparing alternatives for data conversion, assuming *N* components
- #2: each component must know conversion functions for every other component
  - Number of conversion functions: *N**(*N*-1)
  - ✓ Faster conversion (direct)
  - ✗ Poor scalability
- #3: all components agree on common encoding, each component only needs to convert to and from local format
  - Number of conversion functions: 2*(*N*-1)
  - ✗ Slower conversion (2 steps)
  - ✓ Better scalability
- #3: standard choice in most RPC systems

Data representation heterogeneity: patterns

- Patterns to implement alternatives #3 and #4
- Proxy (aka stub)
  - Goal: support access and location transparency
  - Manage access to a remote object via a proxy
    - Proxy resides in local address space and exposes the same interface of remote object
- Broker
  - Goal: separate and encapsulate communication details from its functionality
  - Enable components to interact without handling remote concerns themselves
  - Handles tasks such as server location, message routing, and communication hiding
- Proxy: standard choice in RPC systems
  - Who automatically generates stubs?

Parameter passing methods

- Call by value
  - Parameter value is copied into local storage (usually stack)
  - Callee acts on copy; changes do not affect caller data
- Call by reference
  - Reference (pointer) to parameter is passed (copied into stack)
  - Callee acts directly on caller data
- Call by copy-restore
  - Special case of call by reference
  - Data is copied into callee stack; upon procedure return, updated data is copied back (restored) to caller
  - Supported in a few programming languages (e.g., Ada, Fortran)

RPC parameter passing

- A reference is a memory address
  - Valid only in its context (local machine)
  - We need a pointer-less representation

- Solution: simulate call by reference in RPC by using call by copy-restore
  - Client stub copies the pointed data into the request message
  - Server stub works on copy in its own address space
  - If modified, the updated copy is restored by client stub overwriting original data
  - Size of data to be copied must be known
  - What happens if data contains pointers?

RPC failure semantics

- Exactly-once semantics
  - Guarantees remote procedure is executed exactly once
  - Costly and complex to implement
- At-least-once semantics
  - If client receives a reply, the remote call has been executed at least once
  - Possible duplicate executions due to retransmissions
  - Suitable for idempotent operations
- At-most-once semantics
  - If client receives a reply, the remote call has been executed at most once
  - No duplicate executions, but call may not have been executed at all in failure scenarios
  - Requires duplicate request detection and state management on server

Binding: locating the server endpoint

- Binding: find the server endpoint, including address and specific process (e.g., port)
  - Types of binding: static or dynamic
- Static binding
  - Server endpoint known at design time (hard-coded)
  - ✓ Simple, no runtime overhead
  - ✗ Lacks transparency and flexibility
    - Changes require redeployment
- Dynamic binding
  - Server endpoint determined at run-time
  - ✓ Gains transparency and flexibility
    - Request redirection in case of server replication
  - ✗ Increased overhead: how to limit it?


Dynamic binding

- Two phases in client/server relationship

1. Naming: static phase *before* execution
   - Client specifies whom it wants to connect to, using a unique service name
   - Unique names correspond to operations or abstract interfaces
   - Binding is made to the specific service interface, not a concrete address
2. Addressing: dynamic phase *during* execution
   - Actual server endpoint are resolved when client invokes the service
   - Middleware may dynamically select among multiple replica servers

Dynamic binding


- Addressing can be explicit or implicit
  - Explicit addressing: client sends request using broadcast or multicast, waiting for the first reply
  - Implicit addressing: uses a name server (aka binder, directory service, registry service) that registers services and manages a binding table
    - Supports service lookup, registration, update, and deletion



- Addressing frequency
  - Each RPC requires addressing
  - To reduce overhead, binding results are cached and re-used


Other issues: Synchronous vs asynchronous RPC

- Synchronous RPC: strict request-reply behavior
  - RPC call blocks client that waits for server reply



Synchronous RPC

- Some RPC middleware supports asynchronous RPC
  - Client does not wait for server reply: continues execution
  - Server can send an ack upon receiving the request is received and execute procedure later



Asynchronous RPC

Other issues: transparency

- Is RPC truly transparent? Can RPCs be treated like local calls?
  - Performance, failures, concurrent requests, replication, migration, …
- Performance
  - RPC is much slower than local calls: why?
  - Local procedure call: ~10 cycles (~3 ns)
  - RPC on LAN: 0.1-1 ms => ~100000 times slower
    - Major overheads: context switching, data copying, communication
  - RPC over WAN: can be millions of times slower

Other issues: transparency

- Common failures in RPC
  - Client cannot locate server
  - Lost request messages during transmission
  - Server crashes during execution
  - Lost reply messages
  - Client crashes before or after request

Other issues: security

- Authentication
  - Does client send messages to genuine server or to impostor?
  - Is the client who it claims to be?
- Authorization and access control
  - Does server accept messages only from legitimate clients?
  - Can server identify users at client side?
- Messages confidentiality and integrity
  - Messages may be visible and sniffed on network
  - Can messages be encrypted?
  - Are messages protected against accidental corruption or truncation while on network?
- Replay attacks
  - Can a malicious host capture and retransmit a message later?

Programming with RPC


- Language-level support
  - Some languages (e.g., C, C++) lack built-in RPC support
  - Others (Java, Python, Go, Erlang, Haskell) provide direct support
    - Challenge: heterogeneous environments (e.g., Java service communicating with Python service)
- Common solution
  - Use an **Interface Definition Language (IDL)** to describe remote procedures
  - A dedicated IDL compiler automatically generates client and server stubs

Interface Definition Language (IDL)

- IDL allows developers to specify remote procedure interfaces (including *names, parameters, return values*) in a machine-independent way
- IDL compiler uses these interfaces to generate client and server stubs, containing:
  - Code to marshal
  - Code to unmarshal
  - Network transport code
- IDL definitions look similar to function prototypes
- Example: Thrift IDL

```
service KeyValueStore {
  i32 put(1: string key, 2: string value),
  string get(1: string key),
}
```


IDL and its compiler



RPC middleware: case studies

- Sun RPC
- Java RMI
- Python RPyC
- Go
- gRPC

RPC implementation: Sun RPC

- First-generation RPC
- Created by Sun Microsystems (now Oracle)
  - RFC 1831 (1995), RFC 5531 (2009)
  - Still used mainly for NFS (Network File System)
- Interfaces defined using XDR (eXternal Data Representation) as IDL
  - IDL compiler: `rpcgen`
  - Provides built-in conversion functions for:
    - Primitive types, e.g., `xdr_int()`
    - Structured types, e.g., `xdr_string()`
  - Binary format with *implicit typing*
    - Only values sent, no type or parameter metadata

Sun RPC: define RPC program using XDR

- Two main parts in a file `.x`
  1. Definition: procedure specifics to identify procedure names and parameters' data types
  2. XDR definitions: custom data definitions (if not built-in)

- Example: procedure to calculate the square of an integer

Sun RPC example: define remote procedure

`square.x`

```
struct square_in {       /* input (argument) */
  long arg1;
};
struct square_out {      /* output (result) */
  long res1;
};
program SQUARE_PROG {
  version SQUARE_VERS {
  square_out  SQUAREPROC(square_in) = 1; /* procedure number = 1 */
  } = 1;                 /* version number */
} = 0x31230000;          /* program number */
```

- Define remote procedure `SQUAREPROC`
  - Each procedure has only one input parameter and one output parameter
  - Identifiers are written in uppercase
  - Each procedure is associated with a unique procedure number within RPC program (e.g., 1)

Sun RPC: how to implement RPC program

- Developer responsibilities in RPC
- Client program: implements `main()` and logic needed to locate and bind remote procedure (`square_client.c`)
- Server program: implements remote procedures provided by RPC server (`square_server.c`)
  - Note: developer does not write server-side `main()`
  - Who calls the remote procedure on server side?

Example: local procedure

- Let's first consider the standard local procedure

`square_local.c`

```
#include <stdio.h>
#include <stdlib.h>

struct square_in {  /* input (argument) */
  long arg;
};
struct square_out {  /* output (result) */
  long res;
};
typedef struct square_in square_in;
typedef struct square_out square_out;

square_out *squareproc(square_in *inp) {
  static square_out out;

  out.res = inp->arg * inp->arg;
  return(&out);
}
```

Example: local procedure

- Local procedure *(continue)*

```
int main(int argc, char **argv) {
  square_in in;
  square_out *outp;

  if (argc != 2) {
    printf("usage: %s <integer-value>\n", argv[0]);
    exit(1);
  }
  in.arg = atol(argv[1]);

  outp = squareproc(&in);
  printf("result: %ld\n", outp->res);
  exit(0);
}
```

- Remote procedure: what changes?

Sun RPC example: remote procedure

- Remote vs. local: *similar*, not the same

server.c

```
#include <stdio.h>
#include <rpc/rpc.h>
#include "square.h"    /* generated by rpcgen */
square_out *squareproc_1_svc(square_in *inp, struct svc_req
   *rqstp) {
  static square_out out;

  out.res1 = inp->arg1 * inp->arg1;
  return(&out);
}
```

- Input and output parameters use pointers
- Output must point to a static variable so it persists after procedure returns
- Procedure naming convention: original RPC procedure name becomes `<procedure_name>_<version>_svc`, e.g., `squareproc_1_svc`, all lowercase)

Sun RPC example: client

- Run RPC client:

```
./square_client <server-hostname> <integer>
```

client.c

```
#include <stdio.h>
#include <rpc/rpc.h>
#include "square.h"   /* generated by rpcgen */
int main(int argc, char **argv) {
  CLIENT *clnt;
  char *host;
  square_in in;
  square_out *result;
   if (argc != 3) {
    printf("usage: client <hostname> <integer-value>\n");
    exit(1);
  }
  host = argv[1];
  clnt = clnt_create(host, SQUARE_PROG, SQUARE_VERS, "tcp");
```

```
CLIENT *clnt_create(char *host, unsigned long prog,
unsigned number vers, char *proto)
```


Sun RPC example: client


```
  if (clnt == NULL) {
    clnt_pcreateerror(host);
    exit(1);
  }
  in.arg1 = atol(argv[2]);
  if ((result = squareproc_1(&in, clnt)) == NULL) {
    printf("%s", clnt_sperror(clnt, argv[1]));
    exit(1);
  }
  printf("result: %ld\n", result->res1);
  exit(0);
}
```


Sun RPC example: client

- Creation of client transport manager: `clnt_create()`
  - Handles communication (TPC or UDP)
  - Default request timeout and retransmission
- Client must know:
  - Server hostname
  - Remote procedure info: program (`SQUARE_PROG`), version (`1`), procedure (`squareproc`)
- To call the remote procedure:
  - Procedure name: lowercase + _ + version (`squareproc_1`)
  - Input: actual parameter + client transport manager
  - Output: pointer to result
  - RPC failure: function returns `NULL`
- Error handling:
  - `clnt_pcreateerror()` and `clnt_perror()`

SUN RPC example: development process

1. Define service specification
   - Using XDR: `square.x`
2. Use `rpcgen` to generate stubs
   - Header: `square.h`
   - Client stub: `square_clnt.c`
   - Server stub: `square_svc.c`
   - XDR routines: `square_xdr.c`
3. Implement client and server procedures
   - Client program: `client.c`
   - Server program: `server.c`





Sun RPC: server binding

- Client stub needs to know port number: how?
- Server stub registers RPC program
  - Each procedure is identified by program number, procedure number, version number
- Information stored in *port map*
  - Dynamic table of RPC services on server host
  - Managed by *port mapper* (`rpcbind`), listening on port 111
  - Client stub contacts port mapper to discover the port number, then sends the request to server stub

Sun RPC: port mapper (rpcbind)

- List RPC programs


```
>$ rpcinfo -p
 program         vers     proto    port
   100000        4        tcp      111       rpcbind
   100000        4        udp      111       rpcbind
   824377344     1        udp      59528
   824377344     1        tcp      49311
```

Our RPC program `SQUAREPROC`

- 824377344 (= 0x31230000) is the program number in square.x
- Server supports both TCP and UDP: transport-protocol independent


What goes on: server side

- Server stub code (`square_svc.c`)
- In `main()`:
  - Creates a socket and binds it to any available local port
  - Calls `svc_register` (RPC library function)
    - Registers procedures with port mapper (port 111)
    - Associates the specified program and version number pair with the dispatch routine
  - Calls `svc_run` (RPC library function)
    - `svc_run` enters the server's main loop
    - Listens for RPC requests
    - Dispatches to correct service procedure based on program and procedure numbers
    - Sends RPC replies



What goes on: client side

- When client program starts, `clnt_create` contacts server's port mapper to get port for that RPC interface
  - Early binding: done once, not per call




- Client stub (`square_clnt.c`) manages communication
  - Handles request timeout
  - Marshals/unmarshals between local and XDR format

Sun RPC: summing up key features

- Remote procedures
  - RPC program can expose multiple procedures
  - Versioning support
  - One input and one output per procedure
  - Call by copy-restore
- Transport independent: TCP or UDP at run-time
- Synchronous, blocking calls
- Concurrency: default is no concurrency, mutual exclusion guaranteed
- Stub code: visible, auto-generated by `rpcgen`
- Failure semantics: at-least-once
  - Retransmission on timeout
- Server binding: port mapper
- Security: authentication added with Secure RPC


Java RMI

- Java RMI (Remote Method Invocation)
- Second-generation RPC
- RPC for Java, extended to distributed objects
  - Objects on one JVM can invoke methods on objects in another JVM
  - Goal: access transparency
  - Distribution transparency: not full




RMI: basics

- Physical separation possible due to logical separation
  - Java separation between definition (interface) and implementation (class)
- Remote interface: defines methods available for remote invocation
- Remote object: instance of class implementing remote interface
  - Important: internal state of remote object is not distributed



RMI: basics

- Remote method invocation: invoke methods of a remote interface on a remote object
  - Goal: keep same syntax as local method call
- Achieved via proxy pattern
  - Client-side **stub**: represents remote object locally
  - Server-side **skeleton**: dispatches calls to actual object




RMI: serialization/deserialization

- No external data representation needed
- Serialization/deserialization handled by Java
- Serialization: converts object passed as parameter to byte stream (`writeObject`)
- Deserialization: decodes byte stream to object (`readObject`)
- Stub and skeleton use this to exchange parameters and return values between JVMs
- Marshaling vs serialization
  - Marshaling: convert local data into network format for transmission
  - Serialization: convert object state into byte stream, reconstructs object at receiver
  - Note: Java distinguishes them (needs codebase), Python Pickle treats them as the same

RMI: call flow

- Client obtains object remote reference (stub) via **RMI registry**
  - Name server that relates objects with names
  - Server registers remote objects with registry
  - Client looks them up by name



- Client invokes remote method on stub
  - Syntax same as local call
- Stub serializes method ID and parameters and sends them to skeleton
- Skeleton receives message, deserializes data, invokes method, serializes return value, and sends it to stub
- Stub receives message, deserializes return value, and returns it to client

RMI example: echo remote interface

- Remote interface extends **`Remote`**
  - **`Remote`** identifies interfaces whose methods may be invoked from non-local JVMs
- Remote method
  - throws **`RemoteException`**
    - To handle failures (network, protocol, server)
    - Remote invocation is not fully transparent: failures are visible
  - passes parameters
    - by value: primitive types or objects implementing `Serializable`; stub serializes, skeleton deserializes
    - by reference: remote objects
      - Reference is a data structure containing {IP address, port, time, object ID, remote interface}, not a pointer

```
import java.rmi.Remote;
import java.rmi.RemoteException;

public interface EchoInterface
    extends Remote{
 String getEcho(String echo)
    throws RemoteException;
}
```


RMI example: echo server

- Class implements remote interface
  - Extend **`UnicastRemoteObject`**
  - Call class constructor **`UnicastRemoteObject`** which enables server to receive requests
  - Implement remote method, which throws remote exception

```
public class EchoRMIServer
 extends UnicastRemoteObject
 implements EchoInterface {

 // Constructor
 public EchoRMIServer()
  throws RemoteException {
    super();
 }

 // Implement remote method
 public String getEcho(String echo)
   throws RemoteException {
     return echo;
   }
```

RMI example: echo server

- Create instance of remote object
- Start RMI registry
- Register remote object with registry by name
  - Registry and server run on same host

```
public static void main(String[] args) {
  final int REGISTRYPORT = 1099;
  String registryHost = "localhost";
  String serviceName = "EchoService";
  try {
    // Create an instance of echo server
    EchoRMIServer serverRMI = new EchoRMIServer();
    // Bind remote object with RMI registry
    Registry registry =
      LocateRegistry.createRegistry(REGISTRYPORT);
    registry.bind(serviceName, serverRMI);
  }
  catch (Exception e) {
    System.err.println("EchoRMIServer exception: ");
    e.printStackTrace();
  }
 }
}
```


RMI example: echo client

- Lookup remote object in server's RMI registry by name
- Registry returns a remote reference (stub)
- Client invokes remote method
  - Synchronous, blocking

```
public class EchoRMIClient
{
  // Start RMI client
  public static void main(String[] args)
 {
   bufferedReader stdIn =
     new BufferedReader(
       new InputStreamReader(System.in));
  try
  {
    // Connect to remote RMI service
    EchoInterface serverRMI = (EchoInterface)
         Naming.lookup("EchoService");
    // Interact with user
    String message, echo;
    System.out.print("Message? ");
    message = stdIn.readLine();
    // Invoke remote service
    echo = serverRMI.getEcho(message);
    System.out.println("Echo: "+echo+"\n");
  }
  catch (Exception e)
  {e.printStackTrace(); System.exit(1); }
 }
}
```

RMI: key features

- Transparency: remote calls appear local
- Stub and skeleton auto-generated
- Synchronous, blocking calls
- Concurrency: multiple clients can invoke the same remote method
  - Thread-safety required (`synchronized`)
- Failure semantics: at-most-once
- Full support for object serialization/deserialization and dynamic class loading
- Server binding: RMI registry for object lookup
- Exception handling: `RemoteException`
- Security: optional security manager

Python RPC

- Various RPC implementations
  - Pyro https://pyro5.readthedocs.io/
  - RPyC
  - ZeroRPC https://www.zerorpc.io
- What helps Python achieve transparency
  - Runtime introspection: ability to examine objects during execution via `inspect` module https://docs.python.org/3/library/inspect.html
    - Inspect live objects, examine class contents, retrieve method source code, and extract function argument list
- General idea of RPC in Python:
  - Create connection using an RPC object
  - Invoke remote methods using that object
- Case study: RPyC (Remote Python Call) https://rpyc.readthedocs.io

RPyC: features

- Transparent RPC in Python
  - Transparent access to remote objects as if they were local
  - Proxy-based
  - Pass objects by value (immutable) or by reference (mutable, via `netref`)
  - Lightweight, pure Python: no interface definition file, IDL compiler, name server, transport service
- Symmetric operations
  - Client and server can call RPCs on each other (e.g., server can invoke callbacks on client)
- Synchronous and asynchronous calls
- Secure
  - Capability-based security model
  - Integrates with TLS/SSL, SSH

RPyC: server and client

- Server
  - Multiple implementations
    - `ThreadedServer`: thread for each connection
    - `OneShotServer`, `ThreadPoolServer`, `ForkingServer`: for different concurrency models
  - Binds to default port (18812, 18821 for SSL)
    - Developer can specify host IP and port
- Client
  - Connects to server
  - Uses `modules` property to access server module namespace
  - Transparent proxy forwards operations to remote objects

RPyC: passing data

- By value
  - Simple/immutable types (`int`, `string`, `tuple`)
  - Values are sent directly to remote side
  - Remote copy is independent
- By reference
  - Mutable or complex objects
  - Passed as reference via `netrefs`
  - Remote server contacts client to access attributes or call methods on the original object
    - Changes affect the original (local) object
  - Enables location-sensitive objects (files, OS resources, `sys.stdout`)
    - Remote process can print to local console by getting its `sys.stdout`

RPyC: stubs

- Transparent remote access
  - Client creates a local proxy object for remote modules/objects
  - Proxy acts like the actual object: all operations on proxy are automatically delivered to the remote side
  - Client is unaware that the object is remote
- Synchronous and asynchronous calls
  - Synchronous: client blocks and waits for return
  - Asynchronous: immediate return, notification when complete
  - Calls can be made asynchronous by wrapping the proxy with an *asynchronous wrapper* (`rpyc.async_`)

RPyC: services and security

- RPyC is built around services
  - Each connection exposes a service that defines the set of allowed (its policy)

- Service definition
  - Services are classes derived from `rpyc.core.service.Service`
  - Define methods that can be remotely accessed (exposed)
  - Methods can be called remotely when:
    - Their name begins with `exposed_` or are decorated with `@rpyc.exposed`
  - All exposed members of a service class are available to the remote side

RPyC example: calculator server

```
import rpyc

class CalculatorService(rpyc.Service):
    def exposed_add(self, a, b):
        return a + b
    def exposed_sub(self, a, b):
        return a - b
    def exposed_mul(self, a, b):
        return a * b
    def exposed_div(self, a, b):
        return a / b
    def exposed_fib(self,n):
        seq = []
        a, b = 0,1
        while a < n:
            seq.append(a)
            a, b = b, a+b
        return seq
    def foo(self):
        print("foo")

if __name__ == "__main__":
    from rpyc.utils.server import ThreadedServer
    t = ThreadedServer(CalculatorService, port=18861)
    print('Service started on port 18861')
    t.start()
```

RPyC example: calculator client

```
import rpyc

conn = rpyc.connect("localhost", 18861)
x = conn.root.add(4,7)
assert x == 11
print(conn.root.fib(1000))
# print(conn.root.div(1,0))
```

On the client, the remote service is exposed as the root object of the connection (`conn.root`).
This root object is a network reference (`netref`) to the service instance living in the server process
Any operation performed on `conn.root` is automatically forwarded to the server, making the remote service appear local.
This allows the client to transparently call exposed methods and access attributes of the server service.


RPyC: async operation

- Key feature of RPyC
  - Client starts remote call and continues without blocking
  - Returns `AsyncResult` object that will *eventually* hold the result
- Asynchronous behavior must be *explicitly* enabled: to make a call asynchronous, wrap it with `async_()`
- Then, client can
  - test `AsyncResult` object for completion using `ready()`
  - wait until completion using `wait()`
  - retrieve result using `value`
  - set timeout for result using `set_expiry()`
  - register a callback function to execute when result arrives using `add_callback()`
- No guaranteed order of execution for async requests

See https://rpyc.readthedocs.io/en/latest/docs/async.html

RPyC: async operation and events

- Events can be implemented as asynchronous callbacks
  - Server produces events, client consumes them asynchronously
- Example: FileMonitor
  - Server periodically monitors file on the client machine using `os.stat()`
  - On file change, server sends an event to client (using an async callback) and provides old and new `stat` results
  - At client side, incoming events are handled by a background thread



RPyC example: FileMonitor server

```
import rpyc
import os
import time
from threading import Thread

class FileMonitorService(rpyc.Service):
    class exposed_FileMonitor(object): # expose class
        def __init__(self, filename, callback, interval = 1):
            self.filename = filename
            self.interval = interval
            self.last_stat = None
            self.callback = rpyc.async_(callback) # create async callback
            self.active = True
            self.thread = Thread(target = self.work)
            self.thread.start()
        def exposed_stop(self): # this method has to be exposed too
            self.active = False
            self.thread.join()
        def work(self):
            while self.active:
                stat = os.stat(self.filename) # get status of monitored file
                if self.last_stat is not None and self.last_stat != stat:
                    self.callback(self.last_stat, stat) # notify client of change
                self.last_stat = stat
                time.sleep(self.interval) # monitor file status periodically

if __name__ == "__main__":
    from rpyc.utils.server import ThreadedServer
    # spawn a thread for each connection
    ThreadedServer(FileMonitorService, port = 18871).start()
```

RPyC example: FileMonitor client

```
import rpyc
import time
import os

# File to monitor
filename = "/tmp/floop.bloop"
if os.path.exists(filename):
    os.remove(filename)

# Open file to monitor
f = open(filename, "wb", buffering=0)

conn = rpyc.connect("localhost", 18871)

# Start background thread to process incoming events
bgsrv = rpyc.BgServingThread(conn)

# Callback function, obviously written on client side
def on_file_changed(oldstat, newstat):
    print("\nfile changed")
    print(f"    old stat: {oldstat}")
    print(f"    new stat: {newstat}")

# Create file monitor and pass filename and callback function as arguments
filemon = conn.root.FileMonitor(filename, on_file_changed)

# Wait for file monitor to have a look at file
time.sleep(2)
```


RPyC example: FileMonitor client

```
# Change file size and be notified by file monitor about change
print("change file size")
f.write(b"loop")

# Wait for file monitor to have a look at changed file
time.sleep(2)

# Change file size again
print("change size again")
f.write(b"groop")
time.sleep(2)

f.close()
filemon.stop()
bgsrv.stop()    # stop background thread
conn.close()
```

RPC in Go

- Let’s introduce the Go programming language
  http://www.ce.uniroma2.it/courses/sdcc2526/slides/Go.pdf

- What about RPC in Go?